



WELCOME TO BRADY [Register/Login](#)
 My Account **888-250-3082** [Contact Us](#)
[Find a Distributor](#)

MY CART
\$0.00 (0 Items)


[All Brady Products](#)
[Solutions by Regulation](#)
[Solutions by Industry](#)
[Professional Services](#)
[Customer & Product Support](#)

[Home](#) [Products](#) [Labels, Markers and Tapes](#) [Circuit Board and Component Identification](#) [Thermal Transfer Printable Labels](#)

[EMAIL PAGE](#)
[PRINT PAGE](#)


Thermal Transfer Printable Labels - # THT-2-423-10

SIZE: 0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)
MATERIAL: Permanent Polyester
QTY/UOM: 10,000/Roll
CATALOG #: THT-2-423-10
PRODUCT #: 30119

\$90.84 MSRP (\$US)

QTY:

QUESTIONS OR COMMENTS

Call our customer service at

1-888-250-3082



PRODUCT SUPPORT

[Portable Label Printers](#)

[Industrial Printers](#)

[Label Design Software](#)

[Printer Ribbons](#)

[JetTab Set Up Sheets](#)

[LaserTab Set Up Sheets](#)

[OVERVIEW](#) [SPECIFICATIONS](#)

Specification Of Thermal Transfer Printable Labels

Application(s): Circuit Board & Component ID, Through Hole - Top

Agency Approval (s)/Compliance: AGA Approved, CSA Approved, Halogen-Free (DIN VDE 0472/parts 815), UL Recognized

Size: 0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)

Printable Area: 0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)

Web Width: 3.350" (85.09 mm)

Label Type/Style: Label

Vertical Repeat: 0.350" (8.89 mm)

Horizontal Repeat: 1.125" (28.58 mm)

Color: White

Finish: Gloss

Qty Per Row: 3

Material Type: Polyester

Material Description: Permanent Polyester

Brady Material #: [B-423](#)

General ID Catalog: [pg. 88](#)

Recommended Ribbon Series: 6000

Suggested Ribbon Part#: R6002

Acceptable Ribbon Series: 4900, 6200

After Process: Yes, this material will work with this application

Printer Compatibility: BBP81, Brady 1244, Brady 1344, Brady 200MVP Plus, Brady 2461, Brady 300MVP Plus, Brady 300X-Plus II, Brady 3481, Brady 360X-Plus II, Brady 600X-Plus II, Brady 6441, IP300, IP600, Tagus T200, Tagus T300, Thermal Transfer Printers

Surface: Smooth

Surface Mount Technology: No, this material does not work with this application

Through Hole Technology: Top: Yes. In extreme high temperatures, testing of this material is recommended, Bottom: No

RoHS Compatibility: Compliant with RoHS Directive. NOTE: All statements concerning RoHS Directive compliance refer to 2005/618/EC MCV amendment to RoHS Directive 2002/95/EC. Product compliance is based upon information provided by suppliers of the raw materials used by Brady to manufacture these products, or by independent laboratory testing of these products. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

QTY/UOM: 10,000/Roll

LIVE CHAT

Customer & Tech Support

[Find a Distributor](#)
[Submit Product Feedback](#)
[Submit Website Feedback](#)
[Contact Us](#)
[Site Map](#)

Distribution Partners

[Bradyserve.com](#)
[BradyDistributor.com](#)
[Minimum Advertised Price Policy](#)

Corporate Info

[About Brady](#)
[Bradycorp.com](#)
[Privacy Policy](#)
[Legal Information](#)
[ISO Certified](#)
[Terms of Use](#)
[Terms and Conditions of Sale](#)

Brady International Sites

Canada	Brazil	Europe, Africa, Middle East
Canada (Français)	Asia	
Latin America	Australia	

Brady identifies and protects products, people, and premises with high performance labels, industrial label printers, software, safety & facility identification, spill control, Lockout Tagout solutions and more. Brady helps you create and maintain safer work environments and comply with regulatory standards. Our high-performance materials clearly identify products, components and other assets, even in the most extreme conditions.



©2012 Brady Worldwide, Inc.



Safe & Secure Online Shopping

LIVE CHAT

Brady B-423 is UL Recognized for Outdoor Use on glass, thermoset polyester plastic and polyvinyl fluoride plastic surfaces to support solar panel identification applications. Print Technology: Thermal transfer. Materials type: White polyester. Finish: Glossy. white. Adhesive: Permanent acrylic. Recommended Ribbons: Brady series R6000, Brady series R6000HF (low halogen), Brady series R4400 (colors - red, blue, green, white), Brady series R4900 and R6200 (alternates). Regulatory/Agency Approvals: UL: B-423 is a UL Recognized Component to UL969 Labeling and Marking Standard when printed with Brady Series R6000 and R6000HF ribbons.