



# EMC Test Data

Client: GE MDS LLC	Job Number: JD103878
Model: LN2	T-Log Number: T103940
	Project Manager: Christine Krebill
Contact: Dennis McCarthy	Project Coordinator: -
Standard: FCC Parts 80, 90 and 95, FCC Part 15B	Class: N/A

## Maximum Permissible Exposure / SAR Exclusion

### Test Specific Details

Objective: Evaluate the RF Exposure requirements per FCC 1.1310, 2.1091 and RSS-102.

Date of Test: 4/6/2017  
 Test Engineer: David Bare

### General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density ( $W/m^2$ ), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

### Summary of Results

Device complies with Power Density requirements at 20cm separation:	No
If not, required separation distance (in cm):	327

### Deviations From The Standard

No deviations were made from the requirements of the standard.



# EMC Test Data

Client: GE MDS LLC	Job Number: JD103878
Model: LN2	T-Log Number: T103940
	Project Manager: Christine Krebill
Contact: Dennis McCarthy	Project Coordinator: -
Standard: FCC Parts 80, 90 and 95, FCC Part 15B	Class: N/A

FCC MPE Calculation  
 Use: General  
 Antenna: 9.0 dBd Yagi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>
	dBm	mW*						
216	41.3	13489.6	0	11.1	41.3	173780.08	34.572	0.200
220	41.3	13489.6	0	11.1	41.3	173780.08	34.572	0.200
222	41.3	13489.6	0	11.1	41.3	173780.08	34.572	0.200

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>	Distance where S <= MPE Limit cm
216	34.572	0.200	263
220	34.572	0.200	263
222	34.572	0.200	263

Antenna: 5 dBd Omni

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>
	dBm	mW*						
216	41.3	13489.6	0	7.1	41.3	69183.10	13.764	0.200
220	41.3	13489.6	0	7.1	41.3	69183.10	13.764	0.200
222	41.3	13489.6	0	7.1	41.3	69183.10	13.764	0.200

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>	Distance where S <= MPE Limit cm
216	13.764	0.200	166
220	13.764	0.200	166
222	13.764	0.200	166