



EMC Test Data

Client:	GE MDS LLC	PR Number:	PR147289
Model:	LN400	T-Log Number:	TL147289-RA
Contact:	Christopher Hughes	Project Manager:	Christine Krebill
Standard:	FCC Part 90, ISEDC RSS-119	Project Engineer:	David Bare
		Class:	N/A

Maximum Permissible Exposure / SAR Exclusion

Specific Details

Objective: Evaluate the RF Exposure requirements per FCC 1.1310, 2.1091, 2.1093 and RSS-102.

Date of Test: 1/31/2022
Test Engineer: David Bare

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	No
If not, required separation distance (in cm):	507

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	GE MDS LLC	PR Number:	PR147289
Model:	LN400	T-Log Number:	TL147289-RA
Contact:	Christopher Hughes	Project Manager:	Christine Krebill
Standard:	FCC Part 90, ISEDC RSS-119	Project Engineer:	David Bare
		Class:	N/A

Run #1: FCC MPE Calculation for 300-1500 MHz single transmitters (General use)

Use: General

Antenna: 5 dBi, 10 dBi and 16 dBi

Run #1a: Antenna gain: 5 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	5	41.1	40738.03	8.105	0.271
430	41.1	12882.5	0	5	41.1	40738.03	8.105	0.287
470	41.1	12882.5	0	5	41.1	40738.03	8.105	0.313

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	8.105	0.271	109.4
430	8.105	0.287	106.3
470	8.105	0.313	101.7

Run #1b: Antenna gain: 10 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	10	41.1	128824.96	25.629	0.271
430	41.1	12882.5	0	10	41.1	128824.96	25.629	0.287
470	41.1	12882.5	0	10	41.1	128824.96	25.629	0.313

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	25.629	0.271	194.6
430	25.629	0.287	189.1
470	25.629	0.313	180.9

Note: These power values include margin for acceptable tolerance, refer to user's guide.



EMC Test Data

Client:	GE MDS LLC	PR Number:	PR147289
Model:	LN400	T-Log Number:	TL147289-RA
Contact:	Christopher Hughes	Project Manager:	Christine Krebill
Standard:	FCC Part 90, ISEDC RSS-119	Project Engineer:	David Bare
		Class:	N/A

Run #1c: Antenna gain: 16 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	16	41.1	512861.38	102.031	0.271
430	41.1	12882.5	0	16	41.1	512861.38	102.031	0.287
470	41.1	12882.5	0	16	41.1	512861.38	102.031	0.313

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	102.031	0.271	388.3
430	102.031	0.287	377.3
470	102.031	0.313	360.9

Note: These power values include margin for acceptable tolerance, refer to user's guide.



EMC Test Data

Client:	GE MDS LLC	PR Number:	PR147289
Model:	LN400	T-Log Number:	TL147289-RA
Contact:	Christopher Hughes	Project Manager:	Christine Krebill
Standard:	FCC Part 90, ISEDC RSS-119	Project Engineer:	David Bare
		Class:	N/A

Run #2: Industry Canada MPE Calculation for 300-6000 MHz single transmitters (General use)

Use: General
 Antenna: 5 dBi, 10 dBi and 16 dBi

Run #2a: Antenna gain: 5 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	5	41.1	40738.03	8.105	0.159
430	41.1	12882.5	0	5	41.1	40738.03	8.105	0.165
470	41.1	12882.5	0	5	41.1	40738.03	8.105	0.175

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	8.105	0.159	142.9
430	8.105	0.165	140.1
470	8.105	0.175	135.9

Run #2b: Antenna gain: 10 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	10	41.1	128824.96	25.629	0.159
430	41.1	12882.5	0	10	41.1	128824.96	25.629	0.165
470	41.1	12882.5	0	10	41.1	128824.96	25.629	0.175

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	25.629	0.159	254.1
430	25.629	0.165	249.2
470	25.629	0.175	241.7

Note: These power values include margin for acceptable tolerance, refer to user's guide.



EMC Test Data

Client:	GE MDS LLC	PR Number:	PR147289
Model:	LN400	T-Log Number:	TL147289-RA
Contact:	Christopher Hughes	Project Manager:	Christine Krebill
Standard:	FCC Part 90, ISEDC RSS-119	Project Engineer:	David Bare
		Class:	N/A

Run #2c: Antenna gain: 16 dBi

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
	dBm	mW*						
406.1	41.1	12882.5	0	16	41.1	512861.38	102.031	0.159
430	41.1	12882.5	0	16	41.1	512861.38	102.031	0.165
470	41.1	12882.5	0	16	41.1	512861.38	102.031	0.175

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²	Distance where S <= MPE Limit cm
406.1	102.031	0.159	506.9
430	102.031	0.165	497.1
470	102.031	0.175	482.2

Note: These power values include margin for acceptable tolerance, refer to user's guide.