

175 Science Parkway, Rochester, New York 14620 USA (585) 242-9600 Phone (585) 242-9620 Fax December 7, 2015

## To Whom It May Concern:

Subject: Manufacturer's Declaration for Limited Modular approval for FCC part 90 licensed

spectrum and IC RSS-119.

FCC ID: E5MDS-LN900, IC: 101D-LN900

**FCC KDB 996369** 

**Modular Approval Checklist:** 

Modular approval requirement	Yes	No (*)
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with Part 15 limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation.	YES, the RF circuitry is shielded on the PCB	
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	YES, the Data is buffered through communication drivers to the processors	
3. The modular transmitter must have its own power supply regulation. This is intended to ensure that the module will comply with Part 15 requirements regardless of the design of the power supplying circuitry in the device into which the module is installed.		No, we will control the host integration and DC regulation as described in Integrator's Guide.
4. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)).	Yes, the module was tested on the bench outside of the enclosure as a stand-alone device and complies with emission requirements for Parts 15, 90, and 101C	
5. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	Yes, there will be a FCC label on the module. The host device will be labeled with "Contains FCC ID: E5MDS-LN900"	
6. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	Yes, Instructions to the OEM installer regarding such requirements for use in host device(s) are included in this application.	

Modular approval requirement	Yes	No (*)
7. The modular transmitter must comply with any applicable RF exposure requirements. For	The module meets this	
example, RSS-102 and FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15,	requirement for a Fixed	
including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and	device that shall be used	
millimeter wave devices perform routine environmental evaluation for RF Exposure to	at separation distance of	
demonstrate compliance. In addition, spread spectrum transmitters operating under Section	more than 20cm from	
15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4).	the human body. The	
Modular transmitters approved under other Sections of Part 15, when necessary, may also need to	module complies with	
address certain RF Exposure concerns, typically by providing specific installation and operating	applicable RSS-102	
instructions for users, installers and other interested parties to ensure compliance.	exposure requirements,	
	in its intended	
	configuration/integration	
	in a host. Refer to the	
	MPE calculation and	
	Integrator's Guide.	

## IC RSP-100, 7.3 Modular Approval Checklist:

Modular approval requirement	Yes	No *
a) The radio elements shall have the radio frequency circuitry shielded. Physical / discrete and tuning capacitors may be located external to the shield, but must be on the module assembly.	YES, the RF circuitry is shielded on the PCB	
b) The module shall have buffered modulation/data input(s) (if such inputs are provided) to ensure that the module will comply with the requirements set out in the applicable RSS standard under conditions of excessive data rates or over-modulation.	YES, the Data is buffered through communication drivers to the processors	
c) The module shall have its own power supply regulation on the module. This is to ensure that the module will comply with the requirements set out in the applicable standard regardless of the design of the power supplying circuitry in the host device which houses the module.		No, we will control the host integration and DC regulation as described in Integrator's Guide.
d) The module shall comply with the provisions for external power amplifiers and antennas detailed in the applicable RSS standard. The equipment certification submission shall contain a detailed description of the configuration of all antennas that will be used with the module.		No, we use standard TNC antenna connector; As per all licensed devices, antenna and transmission system requirements must conform to the conditions of enduser's site license.
e) The module shall be tested for compliance with the applicable standard in a stand-alone configuration, i.e. the module must not be inside another device during testing.	Yes, the module was tested on the bench outside of the enclosure as a standalone device and complies with RSS-119 emission requirements.	user s site freelise.
f) The module shall comply with the Category I equipment labelling requirements.	Yes, there will be an IC label on the module. The host device will be labeled with "Contains IC: 101D-LN900"	

Modular approval requirement	Yes	No *
g) The module shall comply with applicable RSS-102 exposure requirements, which are based on the	Yes, The module	
intended use/configurations.	complies with RSS-	
	102 requirements.	
	Instructions to the	
	OEM installer	
	regarding such	
	requirements for use	
	in host device(s) are	
	included in this	
	application.	
h) Is the modular device for an Industry Canada licence-exempt service?		No. LN900 is a
		licensed device as
		indicated below.

\* This **Limited Modular Approval (LMA)** is applied with the understanding that we, the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by GE MDS, or when proper installation / integration is used as per the user manual instructions.

The LN900 is a wireless 900MHz module, compliant with FCC Parts 90 and 101C. The module is designed to be integrated into various enclosures designed by GE MDS. Alternatively the module can also be integrated by OEM as per the integration instructions provided in the user manual. All our products are Professional Installation only. These modules are not for sale to the general public. GE MDS has fully trained and qualified personnel.

Dated: 12/07/2015

By:

Signed: Olmi Law Law Name: Dennis McCarthy ......

(Signature) (Print Name)

Title: Agency Compliance Engineer On behalf of : GE MDS LLC Phone No.: 585 242-8440

Fax No.: 585 241-5590

Email: Dennis.McCarthy2@GE.com