

MERCURY 3650 MIMO SPREAD SPECTRUM XCVR

REV AA A JOB 123456 WA1 00 00 00 00 00  
PRIMARY POWER 10 - 55VDC 4A MAX WA2 00 00 00 00 00  
OPERATING TEMP - 40 to + 70 C TEMP CODE T3C



CONFID: H0R3M0001F30MNCVNS



WARNING: Substitution of components may void approval or warranty. Refer to instruction manual for installation procedure.



COMPLIANCE STATEMENT

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired operation.

WARNING - Do not disconnect while circuit is live unless area is known to be non-hazardous.





MDS Mercury 3650

www.gomds.com



MDS Mercury Remote

0  
PWR

0  
LAN

0  
COM1

0  
GPS

0  
LINK

MDS

Max Ant  
Gain 26 dB



USB



COM1



LAN 1

LAN 2



TX/RX1



TX/RX2



PWR



10-60VDC 4A max

WARNING - Do not disconnect while circuit is live unless are trained to be nonhazardous.

**MDS Mercury 3650**  
www.gemds.com



**MDS Mercury™ Remote**



PWR



LAN



COM1



GPS



LINK



USB



COM1



LAN 1

LAN 2

PWR

WARNING - Do not disconnect while circuit is live unless approved by the manufacturer.