

Serial number  
1824091

Fc 426.000 MHz PPM maximum  
Max drift of 169Hz is 0.39 ppm

Freq.	BANITEMP	VSUPPLY	FREQ	FREQ_ERROR
B	-40	13.8	426	69
B	-40	10	426	71
B	-40	16	426	77
B	-30	13.8	426	85
B	-30	10	426	74
B	-30	16	426	73
B	-20	13.8	426	78
B	-20	10	426	98
B	-20	16	426	122
B	-10	13.8	426	162
B	-10	10	426	169
B	-10	16	426	162
B	0	13.8	426	137
B	0	10	426	115
B	0	16	426	106
B	10	13.8	426	102
B	10	10	426	100
B	10	16	426	102
B	20	13.8	426	101
B	20	10	426	94
B	20	16	426	85
B	30	13.8	426	78
B	30	10	426	73
B	30	16	426	50
B	40	13.8	426	21
B	40	10	426	12
B	40	16	426	11
B	50	13.8	426	-3
B	50	10	426	9
B	50	16	426	8
B	60	13.8	426	11
B	60	10	426	4
B	60	16	426	-7
B	70	13.8	426	-41
B	70	10	426	-63
B	70	16	426	-85
B	25	13.8	426	-38
B	25	10	426	-60
B	25	16	426	-60

Serial number  
1824066

Fc 481.00C PPM maximum  
Max drift of -156Hz is 0.32 ppm

BAND	TEMP	VSUPPLY	FREQ	FREQ_ERROR
C	-40	13.8	481	-156
C	-40	10	481	-120
C	-40	16	481	-121
C	-30	13.8	481	-90
C	-30	10	481	-73
C	-30	16	481	-71
C	-20	13.8	481	-40
C	-20	10	481	-5
C	-20	16	481	12
C	-10	13.8	481	80
C	-10	10	481	76
C	-10	16	481	75
C	0	13.8	481	55
C	0	10	481	50
C	0	16	481	49
C	10	13.8	481	68
C	10	10	481	82
C	10	16	481	82
C	20	13.8	481	96
C	20	10	481	87
C	20	16	481	75
C	30	13.8	481	63
C	30	10	481	71
C	30	16	481	54
C	40	13.8	481	32
C	40	10	481	8
C	40	16	481	9
C	50	13.8	481	37
C	50	10	481	24
C	50	16	481	26
C	60	13.8	481	7
C	60	10	481	-17
C	60	16	481	-39
C	70	13.8	481	-103
C	70	10	481	-121
C	70	16	481	-129
C	25	13.8	481	-52
C	25	10	481	-67
C	25	16	481	-61