



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Wireless USB dongle

Model Number:

9039ARF III(RX), D300ARF(RX), 6310ARF III(RX),
6311ARF III(RX), 9039ARF III MM(RX), 6309ARF III(RX),
9089ARF III(RX), 3009ARF III(RX), M961AT III(RX)

Trade Name: BTC, EMPREX

Issued to

BEHAVIOR TECH COMPUTER CORP.
20F-B, No. 98, Sec. 1, Sintai 5th Rd., Sijhih City,
Taipei County 22102, Taiwan(R.O.C.)

Issued by



Compliance Certification Services Inc.
No. 11, Wu-Gong 6th Rd., Wugu Industrial Park,
Taipei Hsien 248, Taiwan (R.O.C.)
<http://www.ccsemc.com.tw>
service@ccsrf.com



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	6
3.5 DESCRIPTION OF TEST MODES	7
4. INSTRUMENT CALIBRATION.....	8
4.1 MEASURING INSTRUMENT CALIBRATION	8
4.2 MEASUREMENT EQUIPMENT USED	8
4.3 MEASUREMENT UNCERTAINTY	9
5. FACILITIES AND ACCREDITATIONS.....	10
5.1 FACILITIES	10
5.2 EQUIPMENT.....	10
5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....	11
6. SETUP OF EQUIPMENT UNDER TEST.....	12
6.1 SETUP CONFIGURATION OF EUT.....	12
6.2 SUPPORT EQUIPMENT	12
7. FCC PART 15.249 REQUIREMENTS.....	13
7.1 20 DB BANDWIDTH.....	13
7.2 BAND EDGES MEASUREMENT	16
7.3 SPURIOUS EMISSION	21
7.4 POWERLINE CONDUCTED EMISSIONS	28
APPENDIX I PHOTOGRAPHS OF TEST SETUP	31



1. TEST RESULT CERTIFICATION

Applicant: BEHAVIOR TECH COMPUTER CORP.
20F-B, No. 98, Sec. 1, Sintai 5th Rd., Sijhih City,
Taipei County 22102, Taiwan(R.O.C.)

Equipment Under Test: Wireless USB dongle

Trade Name: BTC, EMPREX

Model Number: 9039ARF III(RX), D300ARF(RX), 6310ARF III(RX),
6311ARF III(RX), 9039ARF III MM(RX), 6309ARF III(RX),
9089ARF III(RX), 3009ARF III(RX), M961AT III(RX)

Date of Test: July 7 ~ 20, 2009

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2003** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements emission limits of FCC Rules Part 15.207, 15.209 and 15.249.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

Reviewed by:

Rex Lai
Section Manager
Compliance Certification Services Inc.

Gina Lo
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Wireless USB dongle
Trade Name	BTC, EMPREX
Model Number	9039ARF III(RX), D300ARF(RX), 6310ARF III(RX), 6311ARF III(RX), 9039ARF III MM(RX), 6309ARF III(RX), 9089ARF III(RX), 3009ARF III(RX), M961AT III(RX)
Model Discrepancy	All the specification and layout are identical except they come with different model numbers for marketing purposes.
Power Supply	Powered by host device
Frequency Spacing	2405 ~ 2474 MHz
Frequency Number	70 Channel
Modulation Technique	GFSK
Antenna Gain	7.56 dBi
Antenna Designation	Printed Antenna

Remark:

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **E5XRX9039ARF3** filing to comply with Section 15.107, 15.109, 15.207, 15.209, 15.249 (FCC Part 15, Subpart C Rules.)



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003 and FCC CFR 47 Part 15.207, 15.209 and 15.249.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.249 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: 9039ARF III(RX)) had been tested under operating condition.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and powerline conducted emission below 30MHz, which worst case was in normal link mode.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

Channel Low(2405MHz), Channel Mid(2440MHz) and Channel High(2474MHz) were chosen for the final testing.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	09/10/2009
Test Receiver	Rohde&Schwarz	ESCI	100064	11/29/2009
Switch Controller	TRC	Switch Controller	SC94050010	05/02/2010
4 Port Switch	TRC	4 Port Switch	SC94050020	05/02/2010
Horn-Antenna	TRC	HA-0502	06	05/28/2010
Horn-Antenna	TRC	HA-0801	04	06/03/2010
Horn-Antenna	TRC	HA-1201A	01	06/17/2010
Horn-Antenna	TRC	HA-1301A	01	08/11/2009
Bilog- Antenna	Sunol Sciences	JB3	A030205	08/11/2009
Loop Antenna	EMCO	6502	8905/2356	03/27/2010
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC MRA: TW1039 IC: 2324G-1 / -2	10/17/2010 11/04/2010
Test S/W	LABVIEW (V 6.1)			

Powerline Conducted Emissions Test Site #3				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	845552/030	04/07/2010
LISN	R&S	ENV216	100074	12/02/2009
LISN	FCC	FCC-LISN-50/250-16 -2-07	06013	10/15/2009
ISN	FCC	FCC-TLISN-T2-02	20587	06/11/2010
ISN	FCC	FCC-TLISN-T8-02	20588	06/11/2010
Current Probe	FCC	F-35	506	06/18/2010
Telecom ISN	FCC	FCC-TLISN-T2-PLC	20491	12/21/2009
Test S/W	LabVIEW 6.1 (CCS Conduction Test SW Version_01)			



4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Powerline Conducted Emission # 3	+/- 1.7806
3M Semi Anechoic Chamber / 30MHz ~ 1GHz	+/-3.7046
3M Semi Anechoic Chamber / Above 1GHz	+/-3.0958

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☐ No. 199, Chunghsen Road, Hsintien City, Auerbach / Opf GERMANY

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☒ No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

☒ No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

Remark: The powerline conducted emissions test items was tested at Compliance Certification Services Inc. (Linkou Lab.) The test equipments were listed in page 8 and the test data, please refer page 29-30.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.




Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	 FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	 IC 2324G-1 IC 2324G-2

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No	Equipment	Model	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1.	PC	PL926AV	SGH528048P	FCC DoC	HP	N/A	Unshielded, 1.8m
2.	LCD Monitor	959NF	AQ19H2RT706126P	FCC DoC	SAMSUNG	Shielded, 1.8m with 2 cores	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
3.	Printer	B241A	FAPY150357	FCC DoC	EPSON	Shielded, 1.8m	Unshielded, 1.8m
4.	Modem	DM-1414	304012269	IFAXDM1414	ACEEX	Shielded, 1.8m	Unshielded, 1.8m
5.	Wireless Keyboard	9039ARF III	N/A	E5XKB9039ARF3	BTC, EMPREX	N/A	N/A
6.	USB Mouse	MO19UCA	20440964	FCC DoC	HP	Shielded, 1.8m	N/A
7.	Notebook PC	PP19L	GK102 A00	QDS-BRCM1021	DELL	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


7. FCC PART 15.249 REQUIREMENTS

7.1 20 DB BANDWIDTH

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=36kHz, VBW = 100kHz, Span = 10MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2405	2.70
Mid	2440	1.68
High	2474	2.18



Test Plot

CH Low

* Agilent 11:35:28 Jul 20, 2009

R T

 Δ Mkr2 2.70 MHz

0.63 dB

Ref -10 dBm

#Atten 0 dB

#Peak

Log

10

dB/

DI

-45.3

dBm

LgAv

V1 S2

Center 2.405 00 GHz

Span 10 MHz

#Res BW 36 kHz

#VBW 100 kHz

Sweep 7.44 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.405 00 GHz	-25.30 dBm
2R	(1)	Freq	2.404 87 GHz	-46.59 dBm
2Δ	(1)	Freq	2.70 MHz	0.63 dB

CH Mid

* Agilent 11:36:52 Jul 20, 2009

R T

 Δ Mkr2 1.68 MHz

0.57 dB

Ref -10 dBm

#Atten 0 dB

#Peak

Log

10

dB/

DI

-48.2

dBm

LgAv

V1 S2

Center 2.440 00 GHz

Span 10 MHz

#Res BW 36 kHz

#VBW 100 kHz

Sweep 7.44 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.440 02 GHz	-28.21 dBm
2R	(1)	Freq	2.439 92 GHz	-48.73 dBm
2Δ	(1)	Freq	1.68 MHz	0.57 dB



CH High

Agilent 11:38:11 Jul 20, 2009

R T

Δ Mkr2 2.18 MHz

2.23 dB

Ref -10 dBm

#Atten 0 dB

#Peak

Log

10

dB/

DI

-51.6

dBm

LgAv

V1 S2

Center 2.474 00 GHz

Span 10 MHz

#Res BW 36 kHz

#VBW 100 kHz

Sweep 7.44 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.474 02 GHz	-31.64 dBm
2R	(1)	Freq	2.473 88 GHz	-53.95 dBm
2Δ	(1)	Freq	2.18 MHz	2.23 dB

7.2 BAND EDGES MEASUREMENT


LIMIT

1. In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength ($\text{dB}\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

2. As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.


TEST RESULTS

Refer to attach spectrum analyzer data chart.

**Band Edges (CH Low)****Detector mode: Peak****Polarity: Vertical**


* Agilent

T

**Detector mode: Average****Polarity: Vertical**

* Agilent

T





Detector mode: Peak


Polarity: Horizontal

Agilent

R T

Mkr2 2.400 00 GHz
71.95 dB μ VRef 110 dB μ V

#Atten 10 dB



Start 2.310 00 GHz

Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.390 00 GHz	49.35 dB μ U
2	(1)	Freq	2.400 00 GHz	71.95 dB μ U

Detector mode: Average


Polarity: Horizontal

Agilent

R T

Mkr2 2.400 00 GHz
37.11 dB μ VRef 110 dB μ V

#Atten 10 dB



Start 2.310 00 GHz

^ Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 7.408 s (601 pts)


Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.390 00 GHz	36.98 dB μ U
2	(1)	Freq	2.400 00 GHz	37.11 dB μ U



Band Edges (CH High)


Detector mode: Peak

Polarity: Vertical



Detector mode: Average

Polarity: Vertical





Detector mode: Peak

Polarity: Horizontal

Agilent

T


Mkr1 2.483 50 GHz
60.19 dB μ V

Ref 110 dB μ V

#Atten 10 dB

Peak
Log
10
dB/
Offst
3
dB
DI
74.0
dB μ V
LgAv

M1 S2
S3 FC
A
£(f):
FTun
Swp



Start 2.470 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent

T


Mkr1 2.483 50 GHz
37.04 dB μ V

Ref 110 dB μ V

#Atten 10 dB

Peak
Log
10
dB/
Offst
3
dB
DI
54.0
dB μ V
LgAv

M1 S2
S3 FC
A
£(f):
FTun
Swp



Start 2.470 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 2.339 s (601 pts)



7.3 SPURIOUS EMISSION

LIMIT

1. In the section 15.249(a):

Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental Field Strength (mV/m)	Field Strength of Harmonics (μV/m)
902-928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

2. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

3. In the above emission table, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBμV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

**Below 1 GHz****Operation Mode:** Normal Link**Test Date:** July 7, 2009**Temperature:** 23°C**Tested by:** Mimic Yang**Humidity:** 53% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Detector Mode (PK/QP)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)
432.55	V	Peak	37.67	-5.84	31.83	46.00	-14.17
584.52	V	Peak	36.88	-2.63	34.25	46.00	-11.75
603.92	V	Peak	37.47	-2.51	34.96	46.00	-11.04
612.00	V	Peak	36.26	-2.48	33.78	46.00	-12.22
663.73	V	Peak	43.08	-2.22	40.86	46.00	-5.14
935.33	V	Peak	33.17	1.66	34.82	46.00	-11.18
432.55	H	Peak	38.67	-5.84	32.84	46.00	-13.16
493.98	H	Peak	37.83	-4.20	33.63	46.00	-12.37
584.52	H	Peak	38.53	-2.63	35.90	46.00	-10.10
665.35	H	Peak	40.51	-2.21	38.30	46.00	-7.70
927.25	H	Peak	35.89	1.42	37.31	46.00	-8.69
951.50	H	Peak	36.68	2.10	38.79	46.00	-7.21

Remark:

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

**Above 1 GHz****Operation Mode:** Tx / CH Low**Test Date:** July 7, 2009**Temperature:** 23°C**Tested by:** Mimic Yang**Humidity:** 53% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Result		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2406.67	V	100.56	60.93	-1.57	98.99	59.36	114.00	94.00	-34.64	AVG
1020.00	V	62.69	45.41	-7.92	54.77	37.49	74.00	54.00	-16.51	AVG
1280.00	V	58.02	---	-7.44	50.58	---	74.00	54.00	-3.42	Peak
1330.00	V	56.46	---	-7.35	49.12	---	74.00	54.00	-4.88	Peak
7216.67	V	58.46	42.80	4.08	62.54	46.88	74.00	54.00	-7.12	AVG
N/A										
2403.33	H	95.29	58.97	-1.58	93.71	57.39	114.00	94.00	-36.61	AVG
1333.33	H	55.70	---	-7.34	48.36	---	74.00	54.00	-5.64	Peak
4808.33	H	53.77	39.36	1.04	54.81	40.40	74.00	54.00	-13.60	AVG
7216.67	H	57.44	41.83	4.08	61.52	45.91	74.00	54.00	-8.09	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m). Peak detector mode and average detector mode of the emission shown in Result column.

**Operation Mode:** Tx / CH Mid**Test Date:** July 7, 2009**Temperature:** 23°C**Tested by:** Mimic Yang**Humidity:** 53% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Result		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2440.00	V	101.40	61.35	-1.52	99.88	59.83	114.00	94.00	-34.17	AVG
1026.67	V	57.51	---	-7.91	49.60	---	74.00	54.00	-4.40	Peak
1333.33	V	55.02	---	-7.34	47.68	---	74.00	54.00	-6.32	Peak
2653.33	V	55.35	38.87	-1.12	54.23	37.75	74.00	54.00	-16.25	AVG
4883.33	V	54.54	40.80	1.02	55.56	41.82	74.00	54.00	-12.18	AVG
7316.67	V	56.32	42.01	4.02	60.34	46.03	74.00	54.00	-7.97	AVG
N/A										
2440.00	H	94.68	58.76	-1.52	93.16	57.24	114.00	94.00	-36.76	AVG
1023.33	H	55.71	---	-7.92	47.79	---	74.00	54.00	-6.21	Peak
1333.33	H	56.09	---	-7.34	48.75	---	74.00	54.00	-5.25	Peak
4883.33	H	54.97	41.21	1.02	55.99	42.23	74.00	54.00	-11.77	AVG
7316.67	H	54.19	40.17	4.02	58.21	44.19	74.00	54.00	-9.81	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m). Peak detector mode and average detector mode of the emission shown in Result column.

**Operation Mode:** Tx / CH High**Test Date:** July 8, 2009**Temperature:** 23°C**Tested by:** Mimic Yang**Humidity:** 53% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Result		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2473.33	V	99.68	60.64	-1.46	98.22	59.18	114.00	94.00	-34.82	AVG
1043.33	V	57.33	---	-7.88	49.45	---	74.00	54.00	-4.55	Peak
1333.33	V	55.35	---	-7.34	48.01	---	74.00	54.00	-5.99	Peak
2653.33	V	55.17	38.49	-1.12	54.05	37.37	74.00	54.00	-16.63	AVG
4950.00	V	53.88	40.72	1.00	54.88	41.72	74.00	54.00	-12.28	AVG
7425.00	V	57.10	42.56	3.96	61.06	46.52	74.00	54.00	-7.48	AVG
N/A										
2473.33	H	93.44	58.28	-1.46	91.98	56.82	114.00	94.00	-37.18	AVG
1330.00	H	57.93	---	-7.35	50.58	---	74.00	54.00	-3.42	Peak
4950.00	H	55.94	42.29	1.00	56.94	43.29	74.00	54.00	-10.71	AVG
7425.00	H	53.62	40.26	3.96	57.58	44.22	74.00	54.00	-9.78	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m). Peak detector mode and average detector mode of the emission shown in Result column.



7.4 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link

Test Date: July 17, 2009

Temperature: 22°C

Tested by: Nan Tsai

Humidity: 45% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1850	47.00	39.50	0.10	47.10	39.60	64.26	54.26	-17.16	-14.66	L1
0.2750	26.22	24.62	0.08	26.30	24.70	60.97	50.97	-34.67	-26.27	L1
0.5550	23.54	22.54	0.06	23.60	22.60	56.00	46.00	-32.40	-23.40	L1
3.8850	16.44	15.34	0.06	16.50	15.40	56.00	46.00	-39.50	-30.60	L1
11.2850	17.93	11.53	0.17	18.10	11.70	60.00	50.00	-41.90	-38.30	L1
21.6450	21.34	11.64	0.46	21.80	12.10	60.00	50.00	-38.20	-37.90	L1
0.1850	43.89	38.19	0.11	44.00	38.30	64.26	54.26	-20.26	-15.96	L2
0.3267	24.81	17.01	0.09	24.90	17.10	59.53	49.53	-34.63	-32.43	L2
0.4600	26.62	15.72	0.08	26.70	15.80	56.69	46.69	-29.99	-30.89	L2
1.3800	22.22	20.52	0.08	22.30	20.60	56.00	46.00	-33.70	-25.40	L2
8.2150	23.98	23.08	0.12	24.10	23.20	60.00	50.00	-35.90	-26.80	L2
21.4250	22.20	12.90	0.20	22.40	13.10	60.00	50.00	-37.60	-36.90	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPN between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)
5. "-" means Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.



Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)

