

**FCC CFR47 PART 24 SUBPART E BROADBAND
CERTIFICATION REPORT**



FOR

1930-1990MHz W-CDMA MULTI-CARRIER POWER AMPLIFIER (45W)

MODEL: NTUM30DA

FCC ID: E675JS0067

REPORT NUMBER: 03U1998-1

ISSUE DATE: 06/06/03

Prepared for
**POWERWAVE TECHNOLOGIES, INC.
1117 WINDFIELD WAY, SUITE 100
EL DORADO HILLS, CA 95762**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES
561F Monterey Road
Morgan Hill, CA 95037
U.S.A.
TEL: (408) 463-0885
FAX: (408) 463-0888**

TABLE OF CONTENT

| | |
|---|-----------|
| 1. TEST RESULT CERTIFICATION | 3 |
| 2. EUT DESCRIPTION | 4 |
| 3. FACILITIES, LABORATORY AND ACCREDITATION | 4 |
| 3.1. FACILITIES | 4 |
| 3.2. LABORATORY ACCREDITATION | 4 |
| 3.3. LIST OF ACCREDITATIONS..... | 5 |
| 4. CALIBRATION, METHODOLOGY AND UNCERTAINTY | 6 |
| 4.1. EQUIPMENT CALIBRATION | 6 |
| 4.2. TEST METHODOLOGY | 6 |
| 4.3. MEASUREMENT UNCERTAINTY | 6 |
| 4.4 TEST AND MEASUREMENT EQUIPMENT | 7 |
| 5. APPLICABLE RULES | 7 |
| 5.1. RF POWER OUTPUT §2.1046 | 7 |
| 5.2. MODULATION CHARACTERISTICS §2.1047 | 7 |
| 5.3. OCCUPIED BANDWIDTH §2.1049 | 8 |
| 5.4. SPURIOUS EMISSIONS AT ANTENNA TERMINALS §2.1051..... | 8 |
| 5.5. FIELD STRENGTH OF SPURIOUS RADIATION §2.1053 | 8 |
| 5.6. FREQUENCY STABILITY §2.1055 | 8 |
| 5.7 FREQUENCY RANGE TO BE INVESTIGATED §2.1057..... | 9 |
| 5.8. RADIATED EMISSIONS, FCC PART 15, SECTIONS 209 & 205..... | 10 |
| 6. TEST SETUP, PROCEDURES, AND RESULTS | 11 |
| 6.1.1 RF CONDUCTED POWER OUTPUT | 11 |
| 6.1.2 RF RADIATED POWER OUTPUT | 12 |
| 6.2. OCCUPIED BANDWIDTH..... | 13 |
| 6.3. SPURIOUS EMISSIONS AT ANTENNA TERMINAL..... | 20 |
| 6.4 FIELD STRENGTH OF SPURIOUS RADIATION..... | 23 |
| 6.5. RADIATED EMISSIONS, FCC PART 15, SECTIONS 209 & 205..... | 27 |
| 7. ATTACHMENT | 30 |
| 7.1 EUT SETUP PHOTOS | 30 |
| 7.2 EUT PHOTOGRAPHS | 32 |
| 7.3 INSTALLATION AND SERVICE MANUAL..... | 32 |
| 7.4 SCHEMATIC, PART LISTS AND BLOCK DIAGRAM | 32 |
| 7.5 PROPOSED FCC ID LABEL FORMAT..... | 32 |

1. TEST RESULT CERTIFICATION

COMPANY NAME: POWERWAVE TECHNOLOGIES, INC.
1117 WINDFIELD WAY, SUITE 100
EL DORADO HILLS, CA 95762

EUT DESCRIPTION: 1930-1990MHz W-CDMA MULTI-CARRIER POWER
AMPLIFIER (45W)

MODEL NUMBER: NTUM30DA

DATE TESTED: MAY 20, 2003 – MAY 25, 2003

| | |
|-----------------------|--|
| EQUIPMENT TYPE | INTENTIONAL RADIATOR 1930-1990 MHz (part 24) |
| MEASUREMENT PROCEDURE | ANSI 63.4 / 2001, TIA/EIA 603 |
| PROCEDURE | CERTIFICATION |
| FCC RULE | CFR 47 PART 24 Subpart E |

Compliance Certification Services, Inc. tested the above equipment for compliance with the requirement set forth in CFR 47, PART 24 Subpart E-Broadband PCS. The equipment in the configuration described in this report, shows the measured emission levels emanating from the equipment do not exceed the specified limit. **Note:** This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Test By:

Released For CCS By:



VIEN TRAN
EMC TECHNICIAN
COMPLIANCE CERTIFICATION SERVICES

THU CHAN
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

2. EUT DESCRIPTION

The amplifier operates in the frequency range of 1930 – 1990 MHz. The linear amplifier is capable of handling W-CDMA modulation with a maximum power of 45 Watts.

3. FACILITIES, LABORATORY AND ACCREDITATION

3.1. FACILITIES








The open area test sites and conducted measurement facilities used to collect the radiated data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 16.

3.2. LABORATORY ACCREDITATION

The laboratory and associated test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200065-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT (1300B3) and 31040/SIT (1300F2)).

No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

3.3. LIST OF ACCREDITATIONS

| Country | Agency | Scope of Accreditation | Logo |
|---------|-----------------|---|--|
| USA | NVLAP* | FCC Part 15, CISPR 22, AS/NZS 3548, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, CNS 13438 |  200065-0 |
| USA | FCC | 3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements |  1300 |
| Japan | VCCI | CISPR 22 Two OATS and one conducted Site |  R-1014, R-619, C-640 |
| Norway | NEMKO | EN50081-1, EN50081-2, EN50082-1, EN50082-2, IEC61000-6-1, IEC61000-6-2, EN50083-2, EN50091-2, EN50130-4, EN55011, EN55013, EN55014-1, EN55104, EN55015, EN61547, EN55022, EN55024, EN61000-3-2, EN61000-3-3, EN60945, EN61326-1 |  ELA 117 |
| Norway | NEMKO | EN60601-1-2 and IEC 60601-1-2, the Collateral Standards for Electro-Medical Products. MDD, 93/42/EEC, AIMD 90/385/EEC |  ELA-171 |
| Taiwan | BSMI | CNS 13438 |  SL2-IN-E-1012 |
| Canada | Industry Canada | RSS210 Low Power Transmitter and Receiver |  IC2324 A,B,C, and F |

*No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

4. CALIBRATION, METHODOLOGY AND UNCERTAINTY

4.1. EQUIPMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2. TEST METHODOLOGY

Conducted and radiated testing were performed according to the procedures documented on chapter 13 of ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057.

Receiving equipment (i.e., receiver, analyzer, quasi-peak adapter, pre-selector) and LISNs conform to CISPR specifications for "Radio Interference Measuring Apparatus and Measurement Methods," Publication 16.

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Radiated Emission | |
|--------------------------------------|-------------|
| 30MHz – 200 MHz | +/- 3.3dB |
| 200MHz – 1000MHz | +4.5/-2.9dB |
| 1000MHz – 2000MHz | +4.6/-2.2dB |
| Power Line Conducted Emission | |
| 150kHz – 30MHz | +/-2.9 |

Any results falling within the above values are deemed to be marginal.

4.4 TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| TEST EQUIPMENT LIST | | | | |
|-----------------------------------|-------------------|------------|------------|-----------|
| Name of Equipment | Manufacturer | Model No. | Serial No. | Due Date |
| Spectrum Analyzer | HP | 8593EM | N/A | 6/11/2003 |
| Amplifier | MITEQ | NSP2600-44 | N/A | 4/25/2004 |
| Signal Generator, 10 MHz ~ 20 GHz | HP | 83732B | N/A | 4/4/2004 |
| Bicon Antenna | Eaton | 94455-1 | N/A | 3/6/2004 |
| LP Antenna | EMCO | 3146 | N/A | 3/6/2004 |
| Tune Dipole | Compliance Design | Robert | N/A | 5/15/2004 |
| Tx Horn Antenna | EMCO | 3115 | N/A | 2/4/2004 |
| Rx Horn Antenna | EMCO | 3115 | N/A | 2/4/2004 |
| HPF | MICROLAB | FH-1800H | N/A | N/A |
| HPF | MICROLAB | FH-2400H | N/A | N/A |
| 50 ohm terminator | SHX | TF-5 | N/A | N/A |

5. APPLICABLE RULES

5.1. RF POWER OUTPUT §2.1046

§ 24.232- POWER LIMIT

§24.232(a) Maximum Peak output power for base station transmitters should not exceed 100 Watts EIRP (equivalent isotropically radiated power).

§24.232(b) Mobile stations are limited to 2 Watts EIRP.

5.2. MODULATION CHARACTERISTICS §2.1047

Not applicable; EUT is an amplifier.

5.3. OCCUPIED BANDWIDTH §2.1049

§2.1049(i) Transmitters designed for other types of modulation – when modulated by an appropriate signal of sufficient amplitude to be representative of the type of service in which used. A description of the input signal should be supplied.

5.4. SPURIOUS EMISSIONS AT ANTENNA TERMINALS §2.1051

§ 24.238- EMISSION LIMITS

§24.238(a) The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under conditions specified in the instruction manual and/or alignment procedure, shall not be less than $43+10 \log$ (mean output power in watts) dBc below the mean power output outside a licensee's frequency block (-13dBm).

5.5. FIELD STRENGTH OF SPURIOUS RADIATION §2.1053

§ 24.238- EMISSION LIMITS

§24.238(a) The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under conditions specified in the instruction manual and/or alignment procedure, shall not be less than $43+10 \log$ (mean output power in watts) dBc below the mean power output outside a licensee's frequency block (-13dBm).

5.6. FREQUENCY STABILITY §2.1055

Not Applicable ; EUT is an amplifier.

5.7 FREQUENCY RANGE TO BE INVESTIGATED §2.1057

§2.1057(a) In all of the measurements set forth in §2.1051 and §2.1053, the spectrum shall be investigated from the lowest radio frequency signal generated in the equipment, without going below 9 kHz, up to at least the frequency shown below:

(1) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(2) If the equipment operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

(3) If the equipment operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower.

§2.1057(b) Particular attention should be paid to harmonics and sub-harmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.

§2.1057(c) The amplitude of spurious emissions, which are attenuated more than 20 dB below the permissible value, need not be reported.

§2.1057(d) Unless otherwise specified, measurements above 40 GHz shall be performed using a minimum resolution bandwidth of 1 MHz.

Spec limit: Frequency investigation range from 30 MHz to 20 GHz.

5.8. RADIATED EMISSIONS, FCC PART 15, SECTIONS 209 & 205

Radiated Emissions Limits:


| Radiated Emission Technical Requirements For Class B Device | | |
|--|--|---|
| Frequency (MHz) | FCC limits @ 3 meter Quasi-Peak/dBuV/m | CISPR 22 limits @10 meter Quasi-Peak/dBuV/m |
| 30-88 | 40.0 | 30.0 |
| 88-216 | 43.5 | 30.0 |
| 216-230 | 46.0 | 30.0 |
| 230-960 | 46.0 | 37.0 |
| 960-1000 | 54.0 | 37.0 |
| Above 1000 | 54.0 | Not Applicable |

Note: Power Line Conducted Emissions test is not applicable because the EUT is DC powered.

6. TEST SETUP, PROCEDURES, AND RESULTS

6.1.1 RF CONDUCTED POWER OUTPUT

TEST SETUP



TEST PROCEDURE

The EUT was connected to a signal generator, an output signal was injected to make sure the amplifier was operated at rated power, the reading at the power meter was confirmed to be 46.53 dBm.

RESULT

No non-compliance noted, see table below.

| Channel | Frequency | Conducted Output Power (dBm) | Limit (dBm) | Margin (dB) |
|---------|-----------|------------------------------|-------------|-------------|
| Low | 1.930 | 46.53 | 50 | -3.47 |
| Middle | 1.960 | 46.53 | 50 | -3.47 |
| High | 1.990 | 46.53 | 50 | -3.47 |

6.1.2 RF RADIATED POWER OUTPUT

TEST PROCEDURE:


- 1). On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 1m from the EUT to correspond to the frequency of the transmitter.
- 3). The output of the test antenna shall be connected to the measuring receiver and either a peak or average detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on, if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- 6). The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- 8). The maximum signal level detected by the measuring receiver shall be noted, use 1MHz setting for RBW and VBW.
- 9). The transmitter shall be replaced by a substitution antenna.
- 10). The substitution antenna shall be oriented for vertical polarization.
- 11). The substitution antenna shall be connected to a calibrated signal generator.
- 12). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- 13). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- 14). The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- 15). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- 16). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.
- 17). The measure of the effective radiated power is the larger of the two levels recorded, at the input to the substitution antenna, corrected for the gain of the substitution antenna if necessary.

RESULT

This test is not applicable as the EUT is an RF Amplifier and does not include an antenna.

6.2. OCCUPIED BANDWIDTH

TEST SETUP



TEST PROCEDURE


The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RES BW was set to about 1% of emission BW, -26 dBc display line was placed on the screen, the occupied BW is the delta frequency between the two points where the display line intersects the signal trace. 26dB BW was measured for low, middle and high channels on both RF input and output ports of the EUT.

RESULT


Reporting requirement only.

| Channel | Frequency (MHz) | Input -26dBc BW (MHz) | Output -26dBc BW (MHz) |
|---------|-----------------|-----------------------|------------------------|
| Low | 1930 | 4.587 | 4.614 |
| Middle | 1960 | 4.550 | 4.557 |
| High | 1990 | 4.424 | 4.612 |


Low Channel, RF Input




Mid Channel, RF Input




High Channel, RF Input




Low Channel, RF Output



Mid Channel, RF Output




High Channel, RF Output




6.3. SPURIOUS EMISSIONS AT ANTENNA TERMINAL

TEST SETUP

Antenna Port



Intermodulation Test



TEST PROCEDURE

1) RF signal or three balanced signals (intermodulation measurement) were applied to the RF input. One set as close as possible to the bottom of the block edge and one set as close as possible to the top of the block edge. Set the RES BW to 1% of the emission bandwidth to show compliance with the -13dBm limit, in the 1 MHz bands immediately outside and adjacent to the top and bottom edges of the frequency block.

2) EUT's RF output connector is connected to the spectrum analyzer with a short cable, RBW was set to 1MHz and VBW to 1MHz, the spectrum of 30MHz to 20GHz was investigated for any spurious emissions, a close up investigation for band edges for the low and high channels was also investigated with RBW setting of 1% of emission BW, and VBW setting of 3 times RBW.

RESULT

No non-compliance noted. Please see attached plots refer to the "Measurement Result Plots" below.

Measurement Result Plots

1900 MHz BANDS A – F (1930 – 1990)

| Plot # | Describe of Inter-modulation | Frequency Range (MHz) |
|---------------|--|------------------------------|
| 1 | Block-A Bottom Band Edge Within 1MHz Band | 1927.5 – 1937.5 |
| 2 | Block-A Upper Band Edge Within 1MHz Band | 1927.5 – 1937.5 |
| 3 | Block-A Bottom Band Edge Outside 1MHz Band | 1922.5 – 1942.5 |
| 4 | Block-A Upper Band Edge Outside 1MHz Band | 1922.5 – 1942.5 |
| 5 | Block-A Out-Of-Band #1 | 30 – 1000 |
| 6 | Block-A Out-Of-Band #2 | 1000 – 20000 |
| 7 | Block-B Bottom Band Edge Within 1MHz Band | 1947.5 – 1967.5 |
| 8 | Block-B Upper Band Edge Within 1MHz Band | 1947.5 – 1967.5 |
| 9 | Block-B Bottom Band Edge Outside 1MHz Band | 1942.5 – 1972.5 |
| 10 | Block-B Upper Band Edge Outside 1MHz Band | 1942.5 – 1972.5 |
| 11 | Block-B Out-Of-Band #1 | 30 – 1000 |
| 12 | Block-B Out-Of-Band #2 | 1000 – 20000 |
| 13 | Block-C Bottom Band Edge Within 1MHz Band | 1972.5 – 1992.5 |
| 14 | Block-C Upper Band Edge Within 1MHz Band | 1972.5 – 1992.5 |
| 15 | Block-C Bottom Band Edge Outside 1MHz Band | 1967.5 – 1997.5 |
| 16 | Block-C Upper Band Edge Outside 1MHz Band | 1967.5 – 1997.5 |
| 17 | Block-C Out-Of-Band #1 | 30 – 1000 |
| 18 | Block-C Out-Of-Band #2 | 1000 – 20000 |
| 19 | Block-D Bottom Band Edge Within 1MHz Band | 1937.5 – 1957.5 |
| 20 | Block-D Upper Band Edge Within 1MHz Band | 1937.5 – 1957.5 |
| 21 | Block-D Bottom Band Edge Outside 1MHz Band | 1942.5 – 1952.5 |
| 22 | Block-D Upper Band Edge Outside 1MHz Band | 1942.5 – 1952.5 |
| 23 | Block-D Bottom Band Edge Outside 1MHz Band (Narrow Band) | 1942.5 – 1952.5 |
| 24 | Block-D Upper Band Edge Outside 1MHz Band (Narrow Band) | 1942.5 – 1952.5 |
| 25 | Block-D Out-Of-Band #1 | 30 – 1000 |
| 26 | Block-D Out-Of-Band #2 | 1000 – 20000 |
| 27 | Block-E Bottom Band Edge Within 1MHz Band | 1957.5 – 1977.5 |
| 28 | Block-E Upper Band Edge Within 1MHz Band | 1957.5 – 1977.5 |
| 29 | Block-E Bottom Band Edge Outside 1MHz Band | 1962.5 – 1972.5 |
| 30 | Block-E Upper Band Edge Outside 1MHz Band | 1962.5 – 1972.5 |
| 31 | Block-E Bottom Band Edge Outside 1MHz Band (Narrow Band) | 1962.5 – 1972.5 |
| 32 | Block-E Upper Band Edge Outside 1MHz Band (Narrow Band) | 1962.5 – 1972.5 |
| 33 | Block-E Out-Of-Band #1 | 30 – 1000 |
| 34 | Block-E Out-Of-Band #2 | 1000 – 20000 |
| 35 | Block-F Bottom Band Edge Within 1MHz Band | 1962.5 – 1982.5 |
| 36 | Block-F Upper Band Edge Within 1MHz Band | 1962.5 – 1982.5 |
| 37 | Block-F Bottom Band Edge Outside 1MHz Band | 1967.5 – 1975.5 |
| 38 | Block-F Upper Band Edge Outside 1MHz Band | 1967.5 – 1975.5 |
| 39 | Block-F Bottom Band Edge Outside 1MHz Band (Narrow Band) | 1967.5 – 1975.5 |
| 40 | Block-F Upper Band Edge Outside 1MHz Band (Narrow Band) | 1967.5 – 1975.5 |
| 41 | Block-F Out-Of-Band #1 | 30 – 1000 |
| 42 | Block-F Out-Of-Band #2 | 1000 – 20000 |

6.4 FIELD STRENGTH OF SPURIOUS RADIATION

Detector Function Setting of Test Receiver

| Frequency Range (MHz) | Detector Function | Resolution Bandwidth | Video Bandwidth |
|-----------------------|--|---|---|
| Above 1000 | <input checked="" type="checkbox"/> Peak <input type="checkbox"/> Average | <input checked="" type="checkbox"/> 1 MHz <input type="checkbox"/> 1 MHz | <input checked="" type="checkbox"/> 1 MHz <input type="checkbox"/> 10 Hz |

TEST SETUP




Fig 1: Radiated Emission Measurement




Fig 2: Radiated Emission – Substitution Method set-up

TEST PROCEDURE

- 1). On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 1m from the EUT to correspond to the frequency of the transmitter.
- 3). The output of the test antenna shall be connected to the measuring receiver and either a peak or average detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on, if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- 6). The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- 8). The maximum signal level detected by the measuring receiver shall be noted, set RBW and VBW to 1MHz.
- 9). The transmitter shall be replaced by a substitution antenna.
- 10). The substitution antenna shall be oriented for vertical polarization.
- 11). The substitution antenna shall be connected to a calibrated signal generator.
- 12). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.

- 13). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- 14). The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- 15). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- 16). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.
- 17). The measure of the effective radiated power is the larger of the two levels recorded, at the input to the substitution antenna, corrected for the gain of the substitution antenna if necessary.

RESULT

No non-compliance noted:

05/21/03 **High Frequency Substitution Measurement**
Compliance Certification Services, Morgan Hill Open Field Site

Test Engr: VIEN TRAN
 Project #: 03U1998-1
 Company: POWERWAVE TECHNOLOGIES
 EUT Descr.: 1930-1990MHz W-CDMA, Multicarrier Power Amplifier (45W)
 EUT M/N: NTUM30DA
 Test Target: FCC PART 24
 Mode Oper: Tx at Low, Mid, Hi Channels

Test Equipment:

| | | | | |
|--|---|---|--------------|-----------------|
| EMCO Horn 1-18GHz T73: S/N: 6717 @ 3n | Pre-amplifier 1-26GHz T86 Miteo 924341 | Spectrum Analyzer HP 8593EM Analyzer | Horn > 18GHz | Limit FCC 24 |
|--|---|---|--------------|-----------------|


Hi Frequency Cables
 (2 ft) (2 ~ 3 ft) (4 ~ 6 ft) (12 ft)

Peak Measurements:
 Bandedge: Spurious
 RBW=>1% Emissions BW RBW=1MHz
 VBW=> 3*RBW VBW=1MHz

| f GHz | SA reading (dBuV) | SG reading (dBm) | CL (dB) | Gain (dBi) | Gain (dBd) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Notes |
|--|-------------------|------------------|---------|------------|------------|------------|-------------|-------------|----------------|
| Low Channel: | | | | | | | | | |
| 3.865 | 62.2 | -50.3 | 3.0 | 9.7 | 7.5 | -43.6 | -13.0 | -30.6 | H |
| 5.798 | 75.7 | -36.8 | 3.8 | 11.3 | 9.2 | -29.4 | -13.0 | -16.4 | H |
| 7.730 | 77.8 | -31.7 | 4.6 | 11.4 | 9.3 | -24.8 | -13.0 | -11.8 | H |
| 9.663 | 61.5 | -44.1 | 5.2 | 11.3 | 9.2 | -38.0 | -13.0 | -25.0 | H |
| 11.595 | 52.3 | -53.1 | 5.8 | 12.7 | 10.5 | -46.3 | -13.0 | -33.3 | H, NOISE FLOOR |
| 3.865 | 66.7 | -45.7 | 3.0 | 9.7 | 7.5 | -39.1 | -13.0 | -26.1 | V |
| 5.798 | 78.0 | -34.6 | 3.8 | 11.3 | 9.2 | -27.1 | -13.0 | -14.1 | V |
| 7.730 | 79.3 | -30.2 | 4.6 | 11.4 | 9.3 | -23.3 | -13.0 | -10.3 | V |
| 9.663 | 63.7 | -41.8 | 5.2 | 11.3 | 9.2 | -35.7 | -13.0 | -22.7 | V |
| 11.595 | 50.1 | -55.3 | 5.8 | 12.7 | 10.5 | -48.5 | -13.0 | -35.5 | V, NOISE FLOOR |
| Mid Channel: | | | | | | | | | |
| 3.920 | 63.5 | -48.2 | 3.0 | 9.7 | 7.5 | -41.5 | -13.0 | -28.5 | H |
| 5.880 | 80.2 | -31.9 | 3.9 | 11.4 | 9.2 | -24.4 | -13.0 | -11.4 | H |
| 7.840 | 79.6 | -28.6 | 4.6 | 11.4 | 9.2 | -21.8 | -13.0 | -8.8 | H |
| 9.800 | 59.7 | -43.4 | 5.3 | 11.6 | 9.5 | -37.0 | -13.0 | -24.0 | H |
| 11.760 | 58.0 | -47.4 | 5.9 | 12.6 | 10.5 | -40.6 | -13.0 | -27.6 | NOISE FLOOR |
| 3.920 | 63.1 | -48.2 | 3.0 | 9.7 | 7.5 | -41.5 | -13.0 | -28.5 | V |
| 5.880 | 80.0 | -32.3 | 3.9 | 11.4 | 9.2 | -24.8 | -13.0 | -11.8 | V |
| 7.840 | 73.1 | -36.8 | 4.6 | 11.4 | 9.2 | -30.0 | -13.0 | -17.0 | V |
| 9.800 | 62.4 | -41.8 | 5.3 | 11.6 | 9.5 | -35.4 | -13.0 | -22.4 | V |
| 11.760 | 58.8 | -47.2 | 5.9 | 12.6 | 10.5 | -40.5 | -13.0 | -27.5 | NOISE FLOOR |
| High Channel: | | | | | | | | | |
| 3.975 | 63.8 | -48.5 | 3.0 | 9.7 | 7.6 | -41.8 | -13.0 | -28.8 | H |
| 5.963 | 72.7 | -39.8 | 3.9 | 11.4 | 9.3 | -32.3 | -13.0 | -19.3 | H |
| 7.950 | 75.3 | -33.6 | 4.7 | 11.3 | 9.2 | -26.9 | -13.0 | -13.9 | H |
| 9.930 | 74.0 | -31.9 | 5.3 | 11.9 | 9.7 | -25.3 | -13.0 | -12.3 | H |
| 11.925 | 59.1 | -46.2 | 5.9 | 12.6 | 10.5 | -39.5 | -13.0 | -26.5 | H, NOISE FLOOR |
| 3.975 | 67.9 | -44.4 | 3.0 | 9.7 | 7.6 | -37.7 | -13.0 | -24.7 | V |
| 5.963 | 81.1 | -31.3 | 3.9 | 11.4 | 9.3 | -23.8 | -13.0 | -10.8 | V |
| 7.950 | 74.9 | -34.0 | 4.7 | 11.3 | 9.2 | -27.3 | -13.0 | -14.3 | V |
| 9.930 | 56.9 | -48.9 | 5.3 | 11.9 | 9.7 | -42.4 | -13.0 | -29.4 | V |
| 11.925 | 58.4 | -47.0 | 5.9 | 12.6 | 10.5 | -40.3 | -13.0 | -27.3 | NOISE FLOOR |
| No other emissions were found up to 20GHz. | | | | | | | | | |

6.5. RADIATED EMISSIONS, FCC PART 15, SECTIONS 209 & 205

TEST SETUP



Test Procedures

The EUT was placed on a wooden table 80 cm above the ground screen. The antenna to EUT distance was 3 meters from the leading edge of the turntable to the antenna for the frequency range of 30-1000 MHz, and 1m from the center of the EUT to the horn antenna for the frequency range of 1-20 GHz. During the test, the table was rotated 360 degrees to maximize emissions and the antenna was positioned from 1 to 4 meters above the ground screen to further maximize emissions. Measurements were made with the antenna polarized in both the vertical and the horizontal positions.

The EUT test configuration was according to Section 8 of ANSI C63.4.

The following procedure was used to make the measurements: The frequency range of interest was monitored at a fixed antenna height and EUT azimuth. The Frequency span was set small enough to easily differentiate between broadcast stations, intermittent ambient signals and EUT emissions. The EUT was rotated through 360 degrees to maximize emissions received. During the rotation if emission increased by more than 1 dB, or if another emission appeared that was greater by 1 dB, the EUT was returned to the azimuth where the maximum occurred, and additional cable manipulation was performed to further maximize received emissions.

The antenna was moved up and down to further maximize the suspected highest amplitude signal. If the emission increased by 1 dB or more, or if another emission appeared that was greater by 1dB or more, the antenna was returned to the height where maximum signal was observed, and, cables were manipulated to produce highest emissions, noting frequency and amplitude.

RESULT

No non-compliance noted:



FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

561F MONTEREY ROAD, SAN JOSE, CA 95037-9001
PHONE: (408) 463-0885 FAX: (408) 463-0888

Project #: 03U1998-2
Report #: 03U1998-2 SITE B
Date & Time: 05/22/03 9:36 AM
Test Engr: VIEN TRAN

Company: POWERWAVE TECHNOLOGIES
EUT Description: 1930-1990MHz W-CDMA Multi-carrier Power Amplifier (45W)
Test Configuration : EUT/SIGNAL GENERATOR
Type of Test: FCC CLASS B
Mode of Operation: Tx AT MID CHANNEL EUT M/N: NTUM30DA


A-Site
 B-Site
 C-Site
 F-Site
 6 Worst Data
 Descending

| Freq. (MHz) | Reading (dBuV) | AF (dB) | Closs (dB) | Pre-amp (dB) | Level (dBuV/m) | Limit FCC B | Margin (dB) | Pol (H/V) | Az (Deg) | Height (Meter) | Mark (P/Q/A) |
|--------------------------|-------------------|------------|---------------|-----------------|-------------------|----------------|----------------|--------------|-------------|-------------------|-----------------|
| 135.03 | 47.53 | 11.76 | 2.81 | 28.33 | 33.77 | 43.50 | -9.73 | 3mH | 0.00 | 1.00 | P |
| 180.47 | 50.50 | 9.04 | 3.31 | 28.21 | 34.63 | 43.50 | -8.87 | 3mH | 0.00 | 1.50 | P |
| 165.04 | 44.62 | 9.69 | 3.09 | 28.25 | 29.15 | 43.50 | -14.35 | 3mH | 0.00 | 1.00 | P |
| 240.55 | 45.89 | 11.55 | 3.78 | 27.98 | 33.23 | 46.00 | -12.77 | 3mH | 0.00 | 1.00 | P |
| 270.63 | 38.00 | 12.61 | 4.00 | 27.94 | 26.67 | 46.00 | -19.33 | 3mH | 0.00 | 1.00 | P |
| 300.07 | 40.00 | 12.74 | 4.21 | 27.90 | 29.05 | 46.00 | -16.95 | 3mH | 0.00 | 1.00 | P |
| 330.08 | 42.15 | 13.55 | 4.44 | 28.09 | 32.04 | 46.00 | -13.96 | 3mH | 0.00 | 1.00 | P |
| 360.11 | 49.04 | 14.35 | 4.66 | 28.28 | 39.77 | 46.00 | -6.23 | 3mH | 0.00 | 1.00 | P |
| 390.10 | 47.30 | 15.15 | 4.89 | 28.47 | 38.87 | 46.00 | -7.13 | 3mH | 0.00 | 1.00 | P |
| 420.10 | 46.50 | 15.89 | 5.09 | 28.59 | 38.90 | 46.00 | -7.10 | 3mH | 0.00 | 1.00 | P |
| 690.18 | 42.00 | 18.76 | 6.75 | 29.01 | 38.50 | 46.00 | -7.50 | 3mH | 0.00 | 1.00 | P |
| 360.11 | 48.80 | 14.35 | 4.66 | 28.28 | 39.53 | 46.00 | -6.47 | 3mV | 0.00 | 1.00 | P |
| 390.11 | 47.90 | 15.15 | 4.89 | 28.47 | 39.47 | 46.00 | -6.53 | 3mV | 0.00 | 1.00 | P |
| 420.10 | 47.10 | 15.89 | 5.09 | 28.59 | 39.50 | 46.00 | -6.50 | 3mV | 0.00 | 1.00 | P |
| 130.03 | 48.80 | 12.14 | 2.78 | 28.35 | 35.37 | 43.50 | -8.13 | 3mV | 0.00 | 1.00 | P |
| 150.36 | 47.80 | 10.43 | 2.93 | 28.28 | 32.89 | 43.50 | -10.61 | 3mV | 0.00 | 1.00 | P |
| 180.47 | 49.20 | 9.04 | 3.31 | 28.21 | 33.33 | 43.50 | -10.17 | 3mV | 0.00 | 1.00 | P |
| Total data #: 17 V.2b | | | | | | | | | | | |


7. ATTACHMENT

7.1 EUT SETUP PHOTOS

CONDUCTED RF MEASUREMENTS



RADIATED EMISSIONS



- 7.2 MEASUREMENT RESULT PLOTS**
- 7.3 EUT PHOTOGRAPHS**
- 7.4 INSTALLATION AND SERVICE MANUAL**
- 7.5 SCHEMATIC, PART LISTS AND BLOCK DIAGRAM**
- 7.6 PROPOSED FCC ID LABEL FORMAT**

END OF REPORT