

RF EXPOSURE REPORT

 REPORT NO.:
 SA110927D11

 MODEL NO.:
 KT-1155

 FCC ID:
 E8HKT-1155

 RECEIVED:
 Sep. 27, 2011

 TESTED:
 Sep. 30 ~ Oct. 3, 2011

 ISSUED:
 Oct. 7, 2011

APPLICANT: Chicony Electronics Co., Ltd.

ADDRESS: No. 25, Wu-Gong 6th Rd., Wu Ku Industrial Park, Taipei Hsien, Taiwan, R.O.C.

ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.)
	Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEAS	SE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	CONCLUSION	5



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110927D11	Original release	Oct. 7, 2011



1. CERTIFICATION

PRODUCT:	Bluetooth Keyboard
BRAND NAME:	Chicony
MODEL NO.:	KT-1155
APPLICANT:	Chicony Electronics Co., Ltd.
TESTED:	Sep. 30 ~ Oct. 3, 2011
TEST ITEM:	ENGINEERING SAMPLE
STANDARDS:	FCC Part 2 (Section 2.1091)
	FCC OET Bulletin 65, Supplement C (01-01)
	IEEE C95.1

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

 PREPARED BY :
 Annie Chang / Senior Specialist)
 , DATE: Oct. 7. 2011

 APPROVED BY :
 Kan Lin , DATE: Oct. 7. 2011

(Ken Liu / Manager)



2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	24.50

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	-0.9	0.8
EIRP Power	-7.7	0.2

*Note: The antenna is Printed antenna with -6.79dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 0.8mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END----