

FCC MPE Evaluation (FCC ID: EF400209)

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	902 – 924 MHz
Limits for General Population/Uncontrolled Exposure in the band of:	300 - 1500 MHz,
Power Density Limit:	f/1500 mW/cm ²
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Prediction distance 20 cm

Radio	Frequency (MHz)	Max Conducted Output Power (dBm)	Antenna Gain (dBi)	Separation distance (cm)	Power Density (mW/ cm ²)	MPE Limit (mW/ cm ²)
900MHz radio	910.2 – 919.872	13.220	2	20	0.0066	0.6068

The above results show that the device complies with the MPE requirement.

Completed By: David Zhang

Vista Laboratories, Inc.

1261 Puerta Del Sol, San Clemente, CA 92673

Date: Dec 2nd, 2020