



<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	<b>CN21VC66 001</b>	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	<b>168289126</b>	Seite 1 von 22 Page 1 of 22	
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	<b>N/A</b>	<b>Auftragsdatum:</b> <i>Order date:</i>	<b>2020-11-04</b>		
<b>Auftraggeber:</b> <i>Client:</i>	Nortek Security&Control LLC 5919 Sea Otter Place,Suite 100,Carlsbad,California, United States				
<b>Prüfgegenstand:</b> <i>Test item:</i>	System Controller				
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	EL-SC-300 (Trademark: ELAN)				
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC & IC approval				
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 CFR47 FCC Part 2: Section 2.1091				
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2020-12-02	Please refer to Photo Document			
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A002957975-005~007				
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2020-12-03 – 2021-01-26				
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass				
<b>geprüft von:</b> <i>tested by:</i>		<b>genehmigt von:</b> <i>authorized by:</i>			
<b>Datum:</b> <i>Date:</i> 2021-01-29	Signed by: Jonathan Li	<b>Ausstellungsdatum:</b> <i>Issue date:</i> 2021-01-29	Signed by: Winnie Hou		
<b>Stellung / Position:</b>	Project Manager	<b>Stellung / Position:</b>	Technical Certifier		
<b>Sonstiges / Other:</b>	FCC ID: EF400211 IC: 1078A-00211 HVIN: EL-SC-300				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend 4 = sufficient	5 = mangelhaft N/T = nicht getestet 5 = poor
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

v05

## **Test Summary**

**5.1.1 ANTENNA REQUIREMENT***RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 CONDUCTED POWER SPECTRAL DENSITY***RESULT: Pass***5.1.4 6dB BANDWIDTH***RESULT: Pass***5.1.5 99% BANDWIDTH***RESULT: Pass***5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH***RESULT: Pass***5.1.7 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.8 RADIATED EMISSION***RESULT: Pass***5.1.9 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass*

## Contents

<b>1</b>	<b>GENERAL REMARKS.....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2</b>	<b>TEST SITES .....</b>	<b>4</b>
<b>2.1</b>	<b>TEST FACILITIES.....</b>	<b>4</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS .....</b>	<b>5</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>6</b>
<b>2.4</b>	<b>CALIBRATION.....</b>	<b>6</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>7</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING .....</b>	<b>7</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>8</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>8</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>8</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES.....</b>	<b>9</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS.....</b>	<b>9</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS .....</b>	<b>9</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES.....</b>	<b>10</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>10</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>10</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....</b>	<b>10</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE .....</b>	<b>10</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>11</b>
<b>5</b>	<b>TEST RESULTS.....</b>	<b>13</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>13</b>
<i>5.1.1</i>	<i>Antenna Requirement.....</i>	<i>13</i>
<i>5.1.2</i>	<i>Maximum Peak Conducted Output Power.....</i>	<i>14</i>
<i>5.1.3</i>	<i>Conducted Power Spectral Density.....</i>	<i>15</i>
<i>5.1.4</i>	<i>6dB Bandwidth.....</i>	<i>16</i>
<i>5.1.5</i>	<i>99% Bandwidth.....</i>	<i>17</i>
<i>5.1.6</i>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth .....</i>	<i>18</i>
<i>5.1.7</i>	<i>Radiated Spurious Emission .....</i>	<i>19</i>
<i>5.1.8</i>	<i>Radiated Emission.....</i>	<i>20</i>
<i>5.1.9</i>	<i>Conducted Emission on AC Mains .....</i>	<i>21</i>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>	<b>22</b>
<b>7</b>	<b>LIST OF TABLES .....</b>	<b>22</b>

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Wi-Fi 802.11 b/g/n and Conducted Emission on AC Mains

Appendix C: Test Results of FCC Part 15B and ICES-003

# 2 Test Sites

## 2.1 Test Facilities

**TÜV Rheinland (Shenzhen) Co., Ltd.**

No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069

## 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

<b>Radio Spectrum Testing (TS8997)</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
Signal Analyzer	R&S	FSV 40	101441	2021-08-10
OSP	R&S	OSP 150	101017	2021-12-10
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
Test Software	R&S	WMS32 (V11.00.00)	N/A	N/A
Power Meter	R&S	NRP2	107105	2021-12-10
Wideband Power Sensor	R&S	NRP-Z81	105677	2021-09-10
Shielding Room 8#	Albatross	SR8	APC17151-SR8	2021-07-23
<b>Unwanted Emission Testing (TS9975)</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
EMI Test Receiver	R&S	ESR 7	102021	2021-08-11
Signal Analyzer	R&S	FSV 40	101439	2021-08-10
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	2021-08-10
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2021-08-10
Amplifier	R&S	SCU-18F	180070	2021-08-10
Amplifier	R&S	SCU40A	100475	2021-09-10
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2022-08-08
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2022-08-08
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2022-08-08
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2022-09-13
Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18313	2021-09-02
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2021-07-06

<b>Conducted Emission</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
EMI Test Receiver	R&S	ESR3	102428	2021-08-16
Artificial Mains Network	R&S	ENV216	102333	2021-08-16
Impedance Stabilisation Network	R&S	ENY81-CA6	101810	2021-08-16
EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A
<b>Radiated Emission (3m chamber)</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
3m SAC	ETS	SAC3	CT001632-Q1362	2021-08-23
EMI Test Receiver	R&S	ESR7	102111	2021-12-16
Horn Antenna	R&S	HF907	102706	2022-08-07
Preamplifier	FIT	SCU-18F	180077	2021-08-16
Trilog-Broadband antenna	SCHWARZBECK	VULB9168	0945	2021-12-08
EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF Power (conducted)	$\pm 2.5$ dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	$\pm 6$ dB
Radiated Emission of Receiver, valid up to 26.5 GHz	$\pm 6$ dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	$\pm 3.70$ dB / $\pm 3.30$ dB
Radiated Emission (3m SAC), 30MHz to 1000MHz	$\pm 4.52$ dB
Radiated Emission (3m SAC), above 1000MHz	$\pm 4.37$ dB
Temperature	$\pm 1$ °C
Humidity	$\pm 5$ %
Voltage (DC)	$\pm 1$ %
Voltage (AC, <10kHz)	$\pm 2$ %

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

### 3 General Product Information

#### 3.1 Product Function and Intended Use

The EUT is a System Controller, which supports Wi-Fi 802.11 a/b/g/n/ac wireless technologies. The EUT supports the following functions: Wireless access in the 2.4GHz band or 5GHz band.

For details refer to the User Manual, Technical Description and Circuit Diagram.

#### 3.2 Ratings and System Details

**Table 2: Technical Specification of EUT**

General Information of EUT	Value
Kind of Equipment	System Controller
Type Designation	EL-SC-300
Trade Mark	ELAN
FCC ID	EF400211
IC	1078A-00211
HVIN	EL-SC-300
Operating Voltage	DC 12.0V @2.5A input via AC/DC adapter DC 48V @600mA via POE
Testing Voltage	AC 120V @60Hz
Antenna Type	Integral Antenna
Antenna Gain	3.0 dBi for 2.4G/5G Wi-Fi
Power Adapter	Model: SRB1202500P Input: AC 100-240V~50/60Hz, 1.0A Output: DC 12.0V @2.5A
<b>Technical Specification of Wi-Fi 802.11 b/g/n</b>	
Operating Frequency	2412 - 2472 MHz for 802.11b/g/n(HT20)
Type of Modulation	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM)
Data Rate	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 Mbps for 802.11n(HT20)
Channel Number	11 channels for 802.11b/g/n(HT20)
Channel Separation	5 MHz



Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n

RF Channel	802.11 b/g/n(HT20)
	Frequency (MHz)
<b>01</b>	<b>2412</b>
02	2417
<b>03</b>	<b>2422</b>
04	2427
05	2432
<b>06</b>	<b>2437</b>
07	2442
08	2447
<b>09</b>	<b>2452</b>
10	2457
<b>11</b>	<b>2462</b>

Test frequencies are lowest channel: 2412 MHz, middle channel: 2437 MHz and highest channel: 2462 MHz for 802.11b/g/n(HT20)

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wi-Fi 802.11 b/g/n wireless transmitting mode
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Wi-Fi 802.11 b/g/n connecting mode
- C. On, Normal work (Device communicating with PC via Lan port)
- D. Off

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

### 3.5 Submitted Documents

- FCC/IC Label and Location Info
- User Manual
- Schematics
- PCB Layout

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

According to clause 3.1, all tests were performed on model EL-SC-300 in this report.

### 4.3 Special Accessories and Auxiliary Equipment

Table 4: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	T480	PF-16A6N8	N/A
Portable Laptop	Lenovo	ThinkPad T480	10Q67059	N/A

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

RESULT:

Pass

**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203  
RSS-Gen Clause 6.8

According to the manufacturer declared, the EUT has an external antenna, the directional gain of antenna is 3.0 dBi and this device must be professionally installed, which does not permit use of any antenna with the transmitter; the permitted types of antenna must be specified, refer to user manual for the detail.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

**Prüfbericht - Nr.: CN21VC66 001**  
*Test Report No.*

 Seite 14 von 22  
 Page 14 of 22

### 5.1.2 Maximum Peak Conducted Output Power

**RESULT:**
**Pass**
**Test Specification**

Test standard : FCC Part 15.247(b)(3)  
 RSS-247 Clause 5.4(d)  
 Basic standard : ANSI C63.10: 2013  
 Limits : 1.0 Watts  
 Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2021-01-18  
 Input voltage : AC 120V@60Hz  
 Operation mode : A  
 Test channel : Low / Middle / High  
 Ambient temperature : 24.9 °C  
 Relative humidity : 51 %  
 Atmospheric pressure : 101 kPa

**Table 5: Test Result of Maximum Peak Conducted Output Power, Wi-Fi 802.11 b/g/n**

Test Mode	Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
			(dBm)	(W)	
802.11b	1 Mbps	2412	14.60	0.0288	< 1.0
		2437	16.20	0.0417	
		2462	14.50	0.0282	
802.11g	6 Mbps	2412	21.60	0.1445	
		2437	22.80	0.1905	
		2462	21.90	0.1549	
802.11n (HT20)	MCS0	2412	20.80	0.1202	
		2437	22.20	0.1660	
		2462	21.20	0.1318	
<b>Maximum Measured Value</b>			22.80	0.1905	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 3.0 dBi  
 e.i.r.p.= $P_{(\text{Peak power})} + G$ , which is far below the 4 W

### 5.1.3 Conducted Power Spectral Density

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(e) RSS-247 Clause 5.2(b)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 8 dBm / 3kHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	Refer to test result
Input voltage	:	AC 120V @60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.9 °C
Relative humidity	:	51 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix B.

### 5.1.4 6dB Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(a)(2) RSS-247 Clause 5.2(a)
Basic standard	:	ANSI C63.10: 2013
Limits	:	> 500 KHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2021-01-18
Input voltage	:	AC 120V@60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.9 °C
Relative humidity	:	51 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix B.



**Prüfbericht - Nr.: CN21VC66 001**  
Test Report No.Seite 17 von 22  
Page 17 of 22

### 5.1.5 99% Bandwidth

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.247(a)  
Basic standard : ANSI C63.10: 2013  
Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2021-01-18  
Input voltage : AC 120V@60Hz  
Operation mode : A  
Test channel : Low / Middle / High  
Ambient temperature : 24.9 °C  
Relative humidity : 51 %  
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: **CN21VC66 001**  
Test Report No.Seite 18 von 22  
Page 18 of 22

## 5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:

Pass

### Test Specification

Test standard	:	FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	:	Shielded Room

### Test Setup

Date of testing	:	Refer to test result
Input voltage	:	AC 120V @60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.9 °C
Relative humidity	:	51 %
Atmospheric pressure	:	101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

## 5.1.7 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 5
Kind of test site	:	3m Semi-anechoic Chamber

**Test Setup**

Date of testing	:	2021-01-20 ~ 2021-01-22
Input voltage	:	AC 120V @60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: **CN21VC66 001**  
Test Report No.Seite 20 von 22  
Page 20 of 22

## 5.1.8 Radiated Emission

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.109(a) ICES-003
Basic standard	:	ANSI C63.4:2014
Frequency range	:	Refer to FCC Part15.33
Classification	:	Class B
Limits	:	FCC Part 15.109(a) ICES-003 Table 5 & Table 7
Kind of test site	:	3m Semi-anechoic Chamber

**Test Setup**

Date of testing	:	2021-01-12
Input voltage	:	AC 120V@60Hz
Operation mode	:	B, C
Earthing	:	Not connected
Ambient temperature	:	23 °C
Relative humidity	:	50 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix C.

## 5.1.9 Conducted Emission on AC Mains

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.207(a) & FCC Part 15.107(a) RSS-Gen Clause 8.8 & ICES-003
Basic standard	: ANSI C63.10: 2013 & ANSI C63.4:2014
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a) & FCC Part 15.107(a) RSS-Gen Table 3 & ICES-003 Table 2
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2021-01-19
Input voltage	: AC 120V@60Hz
Operation mode	: B, C
Earthing	: Not connected
Ambient temperature	: 23.1 °C
Relative humidity	: 52 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B & C.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

## 7 List of Tables

Table 1: List of Test and Measurement Equipment .....	5
Table 2: Technical Specification of EUT .....	8
Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n .....	9
Table 4: Auxiliary Equipment Used during Test.....	10
Table 5: Test Result of Maximum Peak Conducted Output Power, Wi-Fi 802.11 b/g/n.....	14