



DEVICE: MDKP KEYPAD Alarm Transmitter

PHOTOGRAPH: Occupied Bandwidth

CONDITIONS: Transmitter Fundamental. A1D Modulation - Pulse Position Modulation. Fixed Duty Cycle. Surface Acoustic Wave (SAW) Frequency Determining Element.

SPECTRUM ANALYZER CONTROL SETTINGS

CENTER FREQUENCY: 318 MHz INPUT ATTENUATION: -10 dB

SCAN WIDTH: 2.0 KHz / Div. PREAMPLIFIER GAIN: 0 dB

SCAN TIME: 1.0 Sec / Div. LOG REF. LEVEL: -10 dBm

RF BANDWIDTH: 0.3 KHz

ANTENNA: 6" Whip Ant. at Analyzer Input TUNED TO: N/A

ANTENNA DISTANCE: 0.25 Meters ANTENNA HEIGHT: N/A

SYSTEM NOISE FLOOR: N/A

NOTES: Per 15.231(c), Occupied Bandwidth (20 dB down) is less than +/- 8 KHz. This is less than 0.010% of the center frequency. FCC Rules, 15.231(c) devices must be less than 0.25% of center frequency. This device therefore complies with 15.231(c).

LINEAR CORPORATION
FCC ID: EF4 ACP00878