



RF EXPOSURE REPORT

REPORT NO.: SA110707C20

MODEL NO.: INBT01

FCC ID: EHA-INBT01

RECEIVED: Jul. 7, 2011

TESTED: Sep. 5 ~ 8, 2011

ISSUED: Sep. 26, 2011

APPLICANT : Intermec Technologies Corporation

ADDRESS : 550 Second street SE Cedar Rapids Iowa 52401-2029
USA

ISSUED BY : Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien, 244 Taiwan

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. CONCLUSION	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110707C20	Original release	Sep. 26, 2011



1. CERTIFICATION

PRODUCT: BT board
BRAND NAME: Intermec
MODEL NO.: INBT01
APPLICANT: Intermec Technologies Corporation
TESTED: Sep. 5 ~ 8, 2011
TEST ITEM: ENGINEERING SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Jessica Cheng , DATE: Sep. 26, 2011
(Jessica Cheng / Specialist)

APPROVED BY : Ken Liu , DATE: Sep. 26, 2011
(Ken Liu / Manager)

2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	4.9	3.1
EIRP Power	6.2	4.2

***Note:** The antenna is Chip antenna with 1.34dBi gain

Threshold for no SAR evaluation is 24.58mW
 Transmitter power is 4.2mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---