



# FCC TEST REPORT

**REPORT NO.:** RF930729H04

**MODEL NO.:** WM600-AF

**RECEIVED:** Jul. 30, 2004

**TESTED:** Aug. 3 to Sep. 16, 2004

**APPLICANT:** Intermec Technologies Corporation

**ADDRESS:** 550 Second Street SE Cedar Rapids, IA 52401  
USA

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.

This test report consists of 77 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



0536  
ILAC MRA



No. 2177-01



## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS.....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT.....	6
3.2	DESCRIPTION OF TEST MODES.....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST .....	9
4	TEST TYPES AND RESULTS.....	10
4.1	CONDUCTED EMISSION MEASUREMENT .....	10
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	10
4.1.2	TEST INSTRUMENTS .....	10
4.1.3	TEST SETUP.....	11
4.1.4	EUT OPERATING CONDITIONS.....	12
4.1.5	TEST RESULTS.....	13
4.2	RADIATED EMISSION MEASUREMENT .....	15
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	15
4.2.2	TEST INSTRUMENTS .....	16
4.2.3	TEST PROCEDURES.....	17
4.2.4	TEST SETUP .....	18
4.2.5	EUT OPERATING CONDITIONS.....	18
4.2.6	TEST RESULTS.....	19
4.2.7	TEST RESULTS – Antenna 1, DSSS .....	21
4.2.8	TEST RESULTS – Antenna 2, DSSS .....	24
4.2.9	TEST RESULTS - Antenna 1, OFDM .....	27
4.2.10	TEST RESULTS - Antenna 2, OFDM .....	30
4.3	6dB BANDWIDTH MEASUREMENT .....	33
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	33
4.3.2	TEST INSTRUMENTS .....	33
4.3.3	TEST PROCEDURE .....	34
4.3.4	TEST SETUP .....	34
4.3.5	EUT OPERATING CONDITIONS.....	34
4.3.6	TEST RESULTS-DSSS.....	35
4.3.7	TEST RESULTS-OFDM .....	39
4.4	MAXIMUM PEAK OUTPUT POWER.....	43



4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	43
4.4.2	TEST INSTRUMENTS .....	43
4.4.3	TEST PROCEDURES .....	44
4.4.4	TEST SETUP .....	44
4.4.5	EUT OPERATING CONDITIONS .....	44
4.4.6	TEST RESULTS- DSSS .....	45
4.4.7	TEST RESULTS- OFDM .....	46
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	47
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	47
4.5.2	TEST INSTRUMENTS .....	47
4.5.3	TEST PROCEDURE .....	48
4.5.4	TEST SETUP .....	48
4.5.5	EUT OPERATING CONDITIONS .....	48
4.5.6	TEST RESULTS-DSSS .....	49
4.5.7	TEST RESULTS-OFDM .....	53
4.6	BAND EDGES MEASUREMENT .....	57
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	57
4.6.2	TEST INSTRUMENTS .....	57
4.6.3	TEST PROCEDURE .....	57
4.6.4	EUT OPERATING CONDITION .....	57
4.6.5	TEST RESULTS –Antenna 1, DSSS .....	58
4.6.6	TEST RESULTS –Antenna 2, DSSS .....	61
4.6.7	TEST RESULTS- Antenna 1, OFDM .....	64
4.6.8	TEST RESULTS- Antenna 2, OFDM .....	67
4.7	ANTENNA REQUIREMENT .....	70
4.7.1	STANDARD APPLICABLE .....	70
4.7.2	ANTENNA CONNECTED CONSTRUCTION .....	70
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	71
6	INFORMATION ON THE TESTING LABORATORIES .....	77



## 1 CERTIFICATION

**PRODUCT :** 11g Compact Flash Module  
**BRAND NAME :** Intermec  
**MODEL NO. :** WM600-AF  
**TESTED:** Aug. 3 to Sep. 16, 2004  
**APPLICANT :** Intermec Technologies Corporation  
**TEST ITEM:** MASS-PRODUCTION  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2001

The above equipment (Model: WM600-AF) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Midoli Peng , **DATE:** Sep. 21, 2004  
( Midoli Peng )

**TECHNICAL ACCEPTANCE :** Hank Chung , **DATE:** Sep. 21, 2004  
Responsible for RF ( Hank Chung )

**APPROVED BY :** Eric Lin , **DATE:** Sep. 21, 2004  
( Eric Lin, Manager )



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -17.35 dBuV at 0.154 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -0.9 dBuV at 2483.50MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	11g Compact Flash Module
<b>MODEL NO.</b>	WM600-AF
<b>POWER SUPPLY</b>	3.3Vdc from host equipment
<b>MODULATION TYPE</b>	CCK, OFDM, DBPSK, DQPSK
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	1/2/5.5/6/9/11/12/18/24/36/48/54Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	11b: 17.20dBm 11g: 14.60dBm
<b>ANTENNA TYPE</b>	Please see note 3
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.
2. This product can be also programmed to operate in the frequency range allowed in France.
3. There are three antennas provided to this EUT, please refer to the following table:

No.	Gain (dBi)	Antenna Type	Antenna Connector	Notes
1	-4.0 dBi	PCB antenna	miniature coaxial plugs	RX
	0 dBi	PIFA antenna	miniature coaxial plugs	TX / RX
2	1.4dBi	PCB Antenna	miniature coaxial plugs	TX / RX

4. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate, 11Mbps with CCK technique and 6Mbps with OFDM technique, the worst case, were chosen for final test.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 11g Compact Flash Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**47 CFR Part 15, Subpart C. (15.247)**  
**ANSI C63.4-2001**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	Compaq	N800C	470048-515	DoC
2	PRINTER	HP	C2642A	MY79F1C3MZ	B94C2642X

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8 m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core

**NOTE:** All power cords of the above support units are non-shielded (1.8m).

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST



**NOTE:** 1. Please refer to the photos of test configuration in Item 5 also.



## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Dec. 04, 2004
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 04, 2004
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 23, 2005
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 02, 2005
Terminator(for KYORITSU)	50	3	May 10, 2005
Software	Cond-V2e	NA	NA


**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. \* = These equipment are used for the final measurement.
5. The measurement uncertainty is 2.53 dB, which is calculated as per the document CISPR 16-4

## 2. TEST PROCEDURES

- The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT/HOST were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

### 4.1.3 TEST SETUP



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.4 EUT OPERATING CONDITIONS

- a. Plug the EUT into the support unit 1 (Notebook computer) which placed on a testing table.
- b. The support unit 1 (Notebook computer) ran a test program "RFET.exe" to enable EUT under transmission condition continuously at specific channel frequency.
- c. Notebook computer sends "H" messages to printer, and the printer prints them on paper.




4.1.5 TEST RESULTS

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 70%RH, 964 hPa	<b>TESTED BY</b>	Sky Liao

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.21	48.23	-	48.44	-	65.79	55.79	-17.35	-
2	0.283	0.26	42.90	-	43.16	-	60.73	50.73	-17.57	-
3	0.841	0.27	34.07	-	34.34	-	56.00	46.00	-21.66	-
4	4.258	0.42	28.24	-	28.66	-	56.00	46.00	-27.34	-
5	6.965	0.60	31.08	-	31.68	-	60.00	50.00	-28.32	-
6	18.719	1.35	38.26	-	39.61	-	60.00	50.00	-20.39	-

- NOTES:** (1) "": Undetectable  
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.  
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.  
 (4) The emission levels of other frequencies were very low against the limit.  
 (5) Correction Factor = Insertion loss + Cable loss  
 (6) Margin value = Emission level - Limit value






<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 70%RH, 964 hPa	<b>TESTED BY</b>	Sky Liao

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.28	45.59	-	45.87	-	64.08	54.08	-18.21	-
2	0.259	0.27	38.44	-	38.71	-	61.45	51.45	-22.74	-
3	0.409	0.20	29.97	-	30.17	-	57.68	47.68	-27.51	-
4	4.391	0.42	29.33	-	29.75	-	56.00	46.00	-26.25	-
5	7.059	0.55	30.71	-	31.26	-	60.00	50.00	-28.74	-
6	18.688	1.17	37.76	-	38.93	-	60.00	50.00	-21.07	-

- NOTES:** (1) "\*\*": Undetectable  
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.  
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.  
 (4) The emission levels of other frequencies were very low against the limit.  
 (5) Correction Factor = Insertion loss + Cable loss  
 (6) Margin value = Emission level - Limit value





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*HP Spectrum Analyzer	8594ER	3829U04676	Sep. 01, 2005
*ADVANTEST Spectrum Analyzer	R3271A	85060311	Jun. 16, 2005
*CHASE RF Pre_Amplifier	CPA9232	1057	May 10, 2005
*HP Pre_Amplifier	8449B	3008A01922	Oct. 13, 2004
*ROHDE & SCHWARZ Test Receiver	ESVS 10	849231 /019	Sep. 30, 2004
*CHASE Broadband Antenna	VULB9168	138	May 22, 2005
*Schwarzbeck Horn_Antenna	3115	5619	Jun. 16, 2005
*SCHWARZBECK Tunable Dipole Antenna	UHAP	897	Mar. 07, 2005
*R&S Loop Antenna	HFH2-Z2	881058/15	Mar. 07, 2005
*SCHWARZBECK Tunable Dipole Antenna	VHAP	880	Mar. 07, 2005
*RF Switches (ARNITSU)	CS-201	1565157	Dec. 01, 2004
*RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Feb. 09. 2005
*RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1 GHz-021	Dec. 01, 2004
*Software	AS60P8	NA	NA
*CHANCE MOST Antenna Tower	AT-100	0203	NA
*CHANCE MOST Turn Table	TT-100	0203	NA

**Note:** 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Dipole Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. \* = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. C.
5. The FCC Site Registration No. is 656396.
6. The VCCI Site Registration No. is R-1626.
7. The CANADA Site Registration No. is IC 4824-3.
8. The measurement uncertainty is 3.56 dB, which is calculated as per the document CISPR 16-4




### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.5 EUT OPERATING CONDITIONS

Same as. 4.1.4



## 4.2.6 TEST RESULTS

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Antenna 1, Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Quasi-Peak, 120kHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 72%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	120.00	26.70 QP	43.50	-16.80	2.64 H	2	14.60	12.10
2	199.92	42.20 QP	43.50	-1.30	1.72 H	18	32.60	9.60
3	239.99	32.90 QP	46.00	-13.10	1.25 H	213	20.10	12.80
4	319.99	22.10 QP	46.00	-23.90	1.98 H	173	6.30	15.80
5	359.99	30.80 QP	46.00	-15.20	1.04 H	143	13.70	17.10
6	440.01	27.20 QP	46.00	-18.80	1.02 H	127	7.90	19.30
7	479.99	23.20 QP	46.00	-22.80	1.00 H	120	3.00	20.20

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	160.00	19.10 QP	43.50	-24.40	1.00 V	344	7.70	11.40
2	200.00	32.30 QP	43.50	-11.20	1.03 V	354	22.70	9.60
3	239.99	28.10 QP	46.00	-17.90	1.03 V	204	15.40	12.80
4	319.99	24.30 QP	46.00	-21.70	1.12 V	298	8.50	15.80
5	359.99	26.00 QP	46.00	-20.00	1.05 V	130	8.90	17.10
6	479.99	22.50 QP	46.00	-23.50	1.01 V	132	2.30	20.20

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Antenna 2, Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Quasi-Peak, 120kHz
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 76%RH, 964 hPa	<b>TESTED BY</b>	Sky Liao

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	119.98	25.10 QP	43.50	-18.40	1.94 H	6	13.00	12.10
2	200.25	28.80 QP	43.50	-14.70	1.34 H	199	19.20	9.60
3	240.01	27.50 QP	46.00	-18.50	1.30 H	254	14.70	12.80
4	359.96	38.30 QP	46.00	-7.70	1.05 H	206	21.20	17.10
5	400.02	38.60 QP	46.00	-7.40	1.00 H	192	20.20	18.40
6	479.99	38.80 QP	46.00	-7.20	1.81 H	197	18.60	20.20
7	679.73	28.40 QP	46.00	-17.60	1.07 H	175	4.70	23.70

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.00	30.80 QP	40.00	-9.20	1.41 V	337	22.90	8.00
2	199.99	26.10 QP	43.50	-17.40	1.72 V	25	16.50	9.60
3	240.00	23.30 QP	46.00	-22.70	1.94 V	0	10.50	12.80
4	359.99	31.80 QP	46.00	-14.20	1.70 V	22	14.70	17.10
5	479.99	31.70 QP	46.00	-14.30	1.27 V	6	11.40	20.20
6	719.95	21.00 QP	46.00	-25.00	1.08 V	58	-3.80	24.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



## 4.2.7 TEST RESULTS – Antenna 1, DSSS

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	59.30 PK	74.00	-14.70	1.23 H	152	26.70	32.60
1	2386.00	48.40 AV	54.00	-5.60	1.23 H	152	15.90	32.60
2	2390.00	59.30 PK	74.00	-14.70	1.20 H	170	25.50	33.80
2	2390.00	49.50 AV	54.00	-4.50	1.20 H	170	15.70	33.80
3	*2412.00	107.20 PK			1.20 H	170	77.30	29.90
3	*2412.00	99.80 AV			1.20 H	170	69.90	29.90
4	4824.00	55.40 PK	74.00	-18.60	1.48 H	91	19.20	36.20
4	4824.00	42.80 AV	54.00	-11.20	1.48 H	91	6.60	36.20
5	7236.00	51.90 PK	74.00	-22.10	1.47 H	112	10.30	41.70
5	7236.00	37.90 AV	54.00	-16.10	1.47 H	112	-3.80	41.70
6	9648.00	56.60 PK	74.00	-17.40	1.13 H	79	11.70	44.90
6	9648.00	47.80 AV	54.00	-6.20	1.13 H	79	2.90	44.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	62.50 PK	74.00	-11.50	1.23 V	154	29.90	32.60
1	2386.00	51.90 AV	54.00	-2.10	1.23 V	154	19.30	32.60
2	2390.00	62.30 PK	74.00	-11.70	1.00 V	6	28.50	33.80
2	2390.00	52.60 AV	54.00	-1.40	1.00 V	6	18.80	33.80
3	*2412.00	110.20 PK			1.00 V	6	80.30	29.90
3	*2412.00	102.90 AV			1.00 V	6	73.00	29.90
4	4824.00	54.30 PK	74.00	-19.70	1.04 V	270	18.00	36.20
4	4824.00	40.70 AV	54.00	-13.30	1.04 V	270	4.40	36.20
5	7236.00	51.00 PK	74.00	-23.00	1.25 V	237	9.40	41.70
5	7236.00	37.90 AV	54.00	-16.10	1.25 V	237	-3.80	41.70
6	9648.00	56.10 PK	74.00	-17.90	1.51 V	80	11.20	44.90
6	9648.00	46.80 AV	54.00	-7.20	1.51 V	80	1.90	44.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* ” : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.00 PK			1.27 H	124	78.00	30.00
1	*2437.00	100.40 AV			1.27 H	124	70.40	30.00
2	4874.00	57.30 PK	74.00	-16.70	1.57 H	96	20.90	36.50
2	4874.00	44.30 AV	54.00	-9.70	1.57 H	96	7.90	36.50
3	7311.00	50.50 PK	74.00	-23.50	1.59 H	104	8.80	41.80
4	9748.00	57.50 PK	74.00	-16.50	1.58 H	100	12.90	44.60
4	9748.00	50.60 AV	54.00	-3.40	1.58 H	100	6.00	44.60

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	112.70 PK			1.18 V	67	82.70	30.00
1	*2437.00	105.40 AV			1.18 V	67	75.40	30.00
2	4874.00	55.30 PK	74.00	-18.70	1.02 V	69	18.90	36.50
2	4874.00	41.80 AV	54.00	-12.20	1.02 V	69	5.30	36.50
3	7311.00	50.80 PK	74.00	-23.20	1.38 V	72	9.00	41.80
4	9748.00	57.70 PK	74.00	-16.30	1.54 V	77	13.10	44.60
4	9748.00	49.20 AV	54.00	-4.80	1.54 V	77	4.60	44.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.50 PK			1.22 H	171	77.40	30.10
1	*2462.00	100.10 AV			1.22 H	171	70.00	30.10
2	2483.50	58.20 PK	74.00	-15.80	1.22 H	171	28.00	30.10
2	2483.50	48.10 AV	54.00	-5.90	1.22 H	171	18.00	30.10
3	2489.00	56.20 PK	74.00	-17.80	1.27 H	351	26.00	30.20
3	2489.00	42.30 AV	54.00	-11.70	1.27 H	351	12.10	30.20
4	4924.00	52.00 PK	74.00	-22.00	1.47 H	91	15.30	36.70
4	4924.00	42.90 AV	54.00	-11.10	1.47 H	91	6.20	36.70
5	7386.00	50.90 PK	74.00	-23.10	1.31 H	77	9.00	41.80
6	9848.00	57.70 PK	74.00	-16.30	1.44 H	79	13.40	44.40
6	9848.00	49.90 AV	54.00	-4.10	1.44 H	79	5.50	44.40

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.30 PK			1.17 V	38	82.20	30.10
1	*2462.00	105.10 AV			1.17 V	38	75.00	30.10
2	2483.50	63.20 PK	74.00	-10.80	1.17 V	38	33.10	30.10
<b>2</b>	<b>2483.50</b>	<b>53.10 AV</b>	<b>54.00</b>	<b>-0.90</b>	<b>1.17 V</b>	<b>38</b>	<b>23.00</b>	<b>30.10</b>
3	2489.00	57.50 PK	74.00	-16.50	1.20 V	360	27.30	30.20
3	2489.00	44.20 AV	54.00	-9.80	1.20 V	360	14.00	30.20
4	4924.00	47.10 PK	74.00	-26.90	1.28 V	278	10.40	36.70
5	7386.00	49.90 PK	74.00	-24.10	1.14 V	236	8.00	41.80
6	9848.00	58.10 PK	74.00	-15.90	1.20 V	33	13.70	44.40
6	9848.00	48.80 AV	54.00	-5.20	1.20 V	33	4.40	44.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



## 4.2.8 TEST RESULTS – Antenna 2, DSSS

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	46.90 PK	74.00	-27.10	1.10 H	349	13.10	33.80
2	*2412.00	97.20 PK			1.10 H	349	67.30	29.90
2	*2412.00	90.60 AV			1.10 H	349	60.70	29.90
3	4824.00	45.50 PK	74.00	-28.50	1.08 H	0	9.30	36.20
4	7236.00	47.90 PK	74.00	-26.10	1.16 H	294	6.20	41.70
5	9648.00	51.90 PK	74.00	-22.10	1.13 H	18	7.00	44.90
5	9648.00	41.40 AV	54.00	-12.60	1.13 H	18	-3.50	44.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.80 PK	74.00	-19.20	1.08 V	20	21.00	33.80
1	2390.00	48.90 AV	54.00	-5.10	1.08 V	20	15.10	33.80
2	*2412.00	105.10 PK			1.08 V	20	75.20	29.90
2	*2412.00	99.20 AV			1.08 V	20	69.30	29.90
3	4824.00	53.00 PK	74.00	-21.00	1.47 V	237	16.80	36.20
3	4824.00	41.60 AV	54.00	-12.40	1.47 V	237	5.40	36.20
4	7236.00	48.30 PK	74.00	-25.70	1.46 V	236	6.60	41.70
5	9648.00	52.90 PK	74.00	-21.10	1.59 V	45	8.00	44.90
5	9648.00	43.10 AV	54.00	-10.90	1.59 V	45	-1.80	44.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	97.40 PK			1.40 H	330	67.40	30.00
1	*2437.00	91.50 AV			1.40 H	330	61.50	30.00
2	4874.00	46.00 PK	74.00	-28.00	1.40 H	181	9.60	36.50
3	7311.00	48.90 PK	74.00	-25.10	1.11 H	285	7.20	41.80
4	9748.00	50.80 PK	74.00	-23.20	1.28 H	13	6.20	44.60

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.80 PK			1.64 V	198	76.80	30.00
1	*2437.00	100.00 AV			1.64 V	198	70.00	30.00
2	4874.00	51.90 PK	74.00	-22.10	1.48 V	194	15.40	36.50
2	4874.00	40.10 AV	54.00	-13.90	1.48 V	194	3.60	36.50
3	7311.00	48.80 PK	74.00	-25.20	1.44 V	233	7.00	41.80
4	9748.00	52.10 PK	74.00	-21.90	1.41 V	38	7.50	44.60
4	9748.00	43.40 AV	54.00	-10.60	1.41 V	38	-1.20	44.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.50 PK			1.64 H	262	68.40	30.10
1	*2462.00	91.60 AV			1.64 H	262	61.60	30.10
2	2483.50	46.60 PK	74.00	-27.40	1.64 H	262	16.40	30.10
3	4924.00	44.50 PK	74.00	-29.50	1.21 H	174	7.80	36.70
4	7386.00	49.10 PK	74.00	-24.90	1.10 H	288	7.20	41.80
5	9848.00	52.40 PK	74.00	-21.60	1.36 H	40	8.00	44.40
5	9848.00	44.30 AV	54.00	-9.70	1.36 H	40	0.00	44.40

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.30 PK			1.64 V	204	76.20	30.10
1	*2462.00	99.60 AV			1.64 V	204	69.60	30.10
2	2483.50	54.30 PK	74.00	-19.70	1.64 V	204	24.20	30.10
2	2483.50	47.70 AV	54.00	-6.30	1.64 V	204	17.60	30.10
3	4924.00	49.70 PK	74.00	-24.30	1.33 V	192	13.00	36.70
4	7386.00	48.90 PK	74.00	-25.10	1.44 V	233	7.10	41.80
5	9848.00	53.10 PK	74.00	-20.90	1.37 V	258	8.70	44.40
5	9848.00	45.00 AV	54.00	-9.00	1.37 V	258	0.60	44.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



## 4.2.9 TEST RESULTS - Antenna 1, OFDM

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.30 PK	74.00	-15.70	1.24 H	124	24.50	33.80
1	2390.00	48.50 AV	54.00	-5.50	1.24 H	124	14.70	33.80
2	*2412.00	101.80 PK			1.14 H	344	71.90	29.90
2	*2412.00	91.90 AV			1.14 H	344	62.00	29.90
3	4824.00	51.60 PK	74.00	-22.40	1.00 H	90	15.40	36.20
3	4824.00	38.40 AV	54.00	-15.60	1.00 H	90	2.20	36.20
4	7236.00	50.50 PK	74.00	-23.50	1.30 H	124	8.90	41.70
5	9648.00	56.40 PK	74.00	-17.60	1.42 H	64	11.50	44.90
5	9648.00	47.50 AV	54.00	-6.50	1.42 H	64	2.60	44.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.30 PK	74.00	-11.70	1.24 V	24	28.50	33.80
1	2390.00	52.80 AV	54.00	-1.20	1.24 V	24	19.00	33.80
2	*2412.00	106.20 PK			1.20 V	68	76.30	29.90
2	*2412.00	96.20 AV			1.20 V	68	66.30	29.90
3	4824.00	48.20 PK	74.00	-25.80	1.07 V	131	12.00	36.20
4	7236.00	51.30 PK	74.00	-22.70	1.43 V	140	9.60	41.70
4	7236.00	37.90 AV	54.00	-16.10	1.43 V	140	-3.70	41.70
5	9648.00	56.20 PK	74.00	-17.80	1.54 V	75	11.30	44.90
5	9648.00	47.90 AV	54.00	-6.10	1.54 V	75	3.00	44.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.20 PK			1.61 H	349	71.20	30.00
1	*2437.00	91.60 AV			1.61 H	349	61.70	30.00
2	4874.00	51.60 PK	74.00	-22.40	1.51 H	86	15.10	36.50
2	4874.00	38.50 AV	54.00	-15.50	1.51 H	86	2.10	36.50
3	7311.00	51.00 PK	74.00	-23.00	1.62 H	129	9.20	41.80
3	7311.00	38.00 AV	54.00	-16.00	1.62 H	129	-3.80	41.80
4	9748.00	58.30 PK	74.00	-15.70	1.58 H	102	13.70	44.60
4	9748.00	51.80 AV	54.00	-2.20	1.58 H	102	7.10	44.60

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	105.50 PK			1.21 V	27	75.50	30.00
1	*2437.00	96.10 AV			1.21 V	27	66.10	30.00
2	4874.00	48.10 PK	74.00	-25.90	1.09 V	138	11.60	36.50
3	7311.00	51.70 PK	74.00	-22.30	1.21 V	154	9.90	41.80
3	7311.00	38.00 AV	54.00	-16.00	1.21 V	154	-3.80	41.80
4	9748.00	59.10 PK	74.00	-14.90	1.55 V	75	14.50	44.60
4	9748.00	50.20 AV	54.00	-3.80	1.55 V	75	5.50	44.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 57%RH, 964 hPa	<b>TESTED BY</b>	Tony Chen

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	102.00 PK			1.64 H	354	71.90	30.10
1	*2462.00	91.30 AV			1.64 H	354	61.20	30.10
2	2483.50	53.20 PK	74.00	-20.80	1.64 H	354	23.10	30.10
2	2483.50	43.60 AV	54.00	-10.40	1.64 H	354	13.50	30.10
3	4924.00	50.50 PK	74.00	-23.50	1.58 H	90	13.80	36.70
4	7386.00	51.60 PK	74.00	-22.40	1.39 H	146	9.80	41.80
4	7386.00	38.00 AV	54.00	-16.00	1.39 H	146	-3.90	41.80
5	9848.00	58.40 PK	74.00	-15.60	1.54 H	96	14.00	44.40
5	9848.00	51.90 AV	54.00	-2.10	1.54 H	96	7.50	44.40

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.80 PK			1.45 V	40	77.80	30.10
1	*2462.00	97.70 AV			1.45 V	40	67.70	30.10
2	2483.50	61.40 PK	74.00	-12.60	1.47 V	40	31.20	30.10
2	2483.50	50.00 AV	54.00	-4.00	1.47 V	40	19.90	30.10
3	4924.00	48.00 PK	74.00	-26.00	1.03 V	119	11.30	36.70
4	7386.00	51.10 PK	74.00	-22.90	1.35 V	141	9.20	41.80
4	7386.00	38.00 AV	54.00	-16.00	1.35 V	141	-3.80	41.80
5	9848.00	57.70 PK	74.00	-16.30	1.55 V	81	13.30	44.40
5	9848.00	51.10 AV	54.00	-2.90	1.55 V	81	6.70	44.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency



## 4.2.10 TEST RESULTS - Antenna 2, OFDM

<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	50.30 PK	74.00	-23.70	1.53 H	151	16.50	33.80
2	*2412.00	93.70 PK			1.53 H	151	63.80	29.90
2	*2412.00	84.80 AV			1.53 H	151	54.90	29.90
3	4824.00	43.30 PK	74.00	-30.70	1.50 H	7	7.10	36.20
4	7236.00	48.50 PK	74.00	-25.50	1.12 H	289	6.80	41.70
5	9648.00	52.00 PK	74.00	-22.00	1.53 H	22	7.10	44.90
5	9648.00	42.00 AV	54.00	-12.00	1.53 H	22	-2.90	44.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.30 PK	74.00	-17.70	1.54 V	247	22.50	33.80
1	2390.00	48.00 AV	54.00	-6.00	1.54 V	247	14.20	33.80
2	*2412.00	99.80 PK			1.54 V	247	69.90	29.90
2	*2412.00	91.50 AV			1.54 V	247	61.60	29.90
3	4824.00	49.60 PK	74.00	-24.40	1.49 V	243	13.40	36.20
4	7236.00	48.60 PK	74.00	-25.40	1.41 V	245	6.90	41.70
5	9648.00	52.00 PK	74.00	-22.00	1.57 V	29	7.10	44.90
5	9648.00	43.10 AV	54.00	-10.90	1.57 V	29	-1.90	44.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* ” : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	96.10 PK			1.58 H	247	66.10	30.00
1	*2437.00	86.70 AV			1.58 H	247	56.70	30.00
2	4874.00	42.30 PK	74.00	-31.70	1.61 H	325	5.80	36.50
3	7311.00	48.80 PK	74.00	-25.20	1.14 H	281	7.00	41.80
4	9748.00	53.20 PK	74.00	-20.80	1.42 H	162	8.60	44.60
4	9748.00	43.80 AV	54.00	-10.20	1.42 H	162	-0.90	44.60

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	102.00 PK			1.56 V	212	72.00	30.00
1	*2437.00	93.00 AV			1.56 V	212	63.00	30.00
2	4874.00	44.70 PK	74.00	-29.30	1.43 V	265	8.30	36.50
3	7311.00	48.80 PK	74.00	-25.20	1.45 V	231	7.00	41.80
4	9748.00	52.60 PK	74.00	-21.40	1.85 V	50	8.00	44.60
4	9748.00	44.60 AV	54.00	-9.40	1.85 V	50	0.00	44.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	11g Compact Flash Module	<b>MODEL</b>	WM600-AF
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 964 hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	94.10 PK			1.14 H	46	64.10	30.10
1	*2462.00	85.60 AV			1.14 H	46	55.60	30.10
2	2483.50	46.50 PK	74.00	-27.50	1.14 H	46	16.40	30.10
3	4924.00	42.60 PK	74.00	-31.40	1.66 H	322	5.90	36.70
4	7386.00	49.20 PK	74.00	-24.80	1.13 H	287	7.30	41.80
5	9848.00	53.70 PK	74.00	-20.30	1.40 H	163	9.40	44.40
5	9848.00	46.50 AV	54.00	-7.50	1.40 H	163	2.10	44.40

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	101.90 PK			1.12 V	40	71.80	30.10
1	*2462.00	92.90 AV			1.12 V	40	62.80	30.10
2	2483.50	54.20 PK	74.00	-19.80	1.12 V	40	24.10	30.10
2	2483.50	45.20 AV	54.00	-8.80	1.12 V	40	15.10	30.10
3	4924.00	45.10 PK	74.00	-28.90	1.43 V	244	8.40	36.70
4	7386.00	48.90 PK	74.00	-25.10	1.46 V	235	7.10	41.80
5	9848.00	52.60 PK	74.00	-21.40	1.57 V	59	8.20	44.40
5	9848.00	44.70 AV	54.00	-9.30	1.57 V	59	0.40	44.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100037	May. 06, 2005

**Note:**

1. The measurement uncertainty is 2.79dB, which is calculated as per the document ETSI TR 100 028
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.6 TEST RESULTS-DSSS

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Tony Chen

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	12.65	0.5	PASS
6	2437	12.70	0.5	PASS
11	2462	12.65	0.5	PASS




CH1






CH6





CH11






## 4.3.7 TEST RESULTS-OFDM

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Tony Chen

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.65	0.5	PASS
6	2437	16.65	0.5	PASS
11	2462	16.60	0.5	PASS




CH1






CH6





CH11





#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100037	May 06, 2005
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2005
TEKTRONIX OSCILLOSCOPE	TDS 220	B027241	Jun. 29, 2005
NARDA DETECTOR	4503A	FSCM99899	NA


**Note:**

1. The measurement uncertainty is 1.25dB, which is calculated as per the document ETSI TR 100 028.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

#### 4.4.4 TEST SETUP



#### 4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5



## 4.4.6 TEST RESULTS- DSSS

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Sky Liao

## Antenna 1 ( Gain 0dBi)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.10	30	PASS
6	2437	17.20	30	PASS
11	2462	17.00	30	PASS

## Antenna 2 ( Gain 1.4dBi)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.10	30	PASS
6	2437	17.20	30	PASS
11	2462	17.00	30	PASS



## 4.4.7 TEST RESULTS- OFDM

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Sky Liao

## Antenna 1 ( Gain 0dBi)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	14.60	30	PASS
6	2437	14.10	30	PASS
11	2462	14.40	30	PASS

## Antenna 2 ( Gain 1.4dBi)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	14.60	30	PASS
6	2437	14.10	30	PASS
11	2462	14.40	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100037	May. 06, 2005


**Note:**

1. The measurement uncertainty is 1.02dB, which is calculated as per the document ETSI TR 100 028.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 TEST SETUP



#### 4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5




## 4.5.6 TEST RESULTS-DSSS

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Tony Chen

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-9.74	8	PASS
6	2437	-8.25	8	PASS
11	2462	-8.88	8	PASS




CH1






CH6





CH11






## 4.5.7 TEST RESULTS-OFDM

<b>EUT</b>	11g Compact Flash Module		
<b>MODEL</b>	WM600-AF	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 59%RH, 964 hPa
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TESTED BY</b>	Tony Chen

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-14.82	8	PASS
6	2437	-15.55	8	PASS
11	2462	-14.77	8	PASS




CH1






CH6





CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 1 MHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100037	May. 06, 2005

**Note:**

1. The measurement uncertainty is 2.79dB, which is calculated as per the document ETSI TR 100 028
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW spectrum analyzer to 1 MHz and set VBW spectrum analyzer to 10 Hz with suitable frequency span including 1 MHz bandwidth from band edge. The band edges was measured and recorded.

### 4.6.4 EUT OPERATING CONDITION

Same as Item 4.3.5




#### 4.6.5 TEST RESULTS –Antenna 1, DSSS

The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).


Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (1):** The band edge emission plot on the following first page shows 50.31dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 102.9dBuV/m, so the maximum field strength in restrict band is  $102.9-50.31=52.59$ dBuV/m which is under 54 dBuV/m limit.

**NOTE (2):** The band edge emission plot on the following second page shows 51.95dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2. is 105.10dBuV/m, so the maximum field strength in restrict band is  $105.10-51.95=53.15$ dBuV/m which is under 54 dBuV/m limit.



1 PK VIEW






#### 4.6.6 TEST RESULTS –Antenna 2, DSSS


The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (1):** The band edge emission plot on the following first page shows 50.31dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 99.20dBuV/m, so the maximum field strength in restrict band is  $99.20 - 50.31 = 48.89$ dBuV/m which is under 54 dBuV/m limit.

**NOTE (2):** The band edge emission plot on the following second page shows 51.95dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2. is 99.6dBuV/m, so the maximum field strength in restrict band is  $99.6 - 51.95 = 47.65$ dBuV/m which is under 54 dBuV/m limit.








#### 4.6.7 TEST RESULTS- Antenna 1, OFDM


The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (1):** The band edge emission plot on the following first page shows 43.44dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2. is 96.2dBuV/m, so the maximum field strength in restrict band is  $96.2-43.44=52.76$ dBuV/m which is under 54 dBuV/m limit.

**NOTE (2):** The band edge emission plot on the following second page shows 47.67dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2. is 97.7dBuV/m, so the maximum field strength in restrict band is  $97.7-47.67=50.03$ dBuV/m which is under 54 dBuV/m limit.








#### 4.6.8 TEST RESULTS- Antenna 2, OFDM


The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (1):** The band edge emission plot on the following first page shows 43.44dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2. is 91.50dBuV/m, so the maximum field strength in restrict band is  $91.50 - 43.44 = 48.06$ dBuV/m which is under 54 dBuV/m limit.

**NOTE (2):** The band edge emission plot on the following second page shows 47.67dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2. is 92.90dBuV/m, so the maximum field strength in restrict band is  $92.90 - 47.67 = 45.23$ dBuV/m which is under 54 dBuV/m limit.







## 4.7 ANTENNA REQUIREMENT

### 4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antennas used in this product are PCB antenna (RX), PIFA antenna (TX / RX) with miniature coaxial plugs connector and PCB antenna (TX / RX) with miniature coaxial plugs connector.

No.	Gain (dBi)	Antenna Type	Antenna Connector	Notes
1	-4.0 dBi	PCB antenna	miniature coaxial plugs	RX
	0 dBi	PIFA antenna	miniature coaxial plugs	TX / RX
2	1.4dBi	PCB Antenna	miniature coaxial plugs	TX / RX

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST (Antenna 1)





CONDUCTED EMISSION TEST (Antenna 2)





### RADIATED EMISSION TEST(Antenna 1)



### RADIATED EMISSION TEST(Antenna 2)





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB , GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**  
Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**  
Tel: 886-3-3183232  
Fax: 886-3-3185050

**Linko RF Lab.**  
Tel: 886-3-3270910  
Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)  
**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.

Report Format Version 1.3