

## **RF Exposure Report**

Report No.: MFBDGE-WTW-P22050591

FCC ID: EHTPERS2

Test Model: 6930w

Received Date: 2022/5/18

Test Date: 2022/5/31 ~ 2022/6/23

**Issued Date:** Jul. 08, 2022

**Applicant:** Mitel Networks Corporation

Address: 4000 Innovation Drive Ottawa, Ontario Canada K2K 3K1

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN

FCC Registration / 788550 / TW0003

**Designation Number:** 





This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Report No.: MFBDGE-WTW-P22050591 Page No. 1 / 5 Report Format Version: 6.1.1



# Table of Contents Release Control Record 3 1 Certificate of Conformity 4 2 RF Exposure 5 2.1 Limits for Maximum Permissible Exposure (MPE) 5 2.2 MPE Calculation Formula 5 2.3 Classification 5

3



### **Release Control Record**

Issue No.	Description	Date Issued
MFBDGE-WTW-P22050591	Original release.	Jul. 08, 2022



# 1 Certificate of Conformity

Product: IP Phone

Brand: Mitel

Test Model: 6930w

Sample Status: Engineering sample

**Applicant:** Mitel Networks

**Test Date:** 2022/5/31 ~ 2022/6/23

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Gina Liu / Specialist , Date: Jul. 08, 2022

Jeremy Lin / Project Engineer



### 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)			
Limits For General Population / Uncontrolled Exposure							
0.3-1.34	614	1.63	(100)*	30			
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

f = Frequency in MHz; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max. AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN 2412~2462	19.48	2.63	20	0.032	1
WLAN 5180~5240	16.12	2.63	20	0.015	1
WLAN 5260~5320	16.11	2.73	20	0.015	1
WLAN 5500~5700	11.99	3.42	20	0.007	1
WLAN 5745~5825	11.91	3.82	20	0.007	1
BT EDR 2402~2480	4.32	2.63	20	0.001	1
BT LE 2402~2480	2.49	2.63	20	0.001	1

<sup>\*</sup>The EUT is not capable of simultaneous transmission.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

---END---

<sup>\*2.4</sup>GHz & 5GHz & BT technology cannot transmit at same time.