



**EMC Technologies Pty Ltd**  
ABN 82 057 105 549  
57 Assembly Drive  
Tullamarine Victoria Australia 3043  
  
Ph: + 613 9335 3333  
Fax: + 613 9338 9260  
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

**FCC ID:** EJE-WB0026  
**Industry Canada ID:** 337J-WB0026

**Test Sample:** Stylistic ST Series  
**Model:** ST5030D

**Radio Modules:** Bluetooth, Model: UGXZ5-102A &  
Mini-PCI WLAN (Atheros 11a+b/g), Model: WLL4070

**Report Number** M050508\_Cert\_BT\_WLL4070\_11abg

**Tested for:** Fujitsu Australia Ltd.

**Issue Date:** 17<sup>th</sup> June 2005

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full.

**NATA Accredited Laboratory**  
Number: 5292

**EMI TEST REPORT FOR CERTIFICATION**  
to  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**  
**EMC Technologies Report No. M050508\_Cert\_BT\_WLL4070\_11abg**  
**Issue Date: 17<sup>th</sup> June 2005**

**CONTENTS**

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

**RESULTS – Bluetooth, UGXZ5-102A**

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY**
- 7.0 RADIO FREQUENCY EXPOSURE**
- 8.0 ANTENNA REQUIREMENT**
- 9.0 COMPLIANCE STATEMENT**

**RESULTS – WLAN, WLL4070 (Atheros 11a+b/g):**

Refer to Report No: M050508\_Cert\_WLL4070\_11abg\_DTS\_BT (802.11b/g and 802.11a (DTS))

Refer to Report No: M050508\_Cert\_WLL4070\_11abg\_NII\_BT (802.11a (NII))

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA DETAILS**
- APPENDIX G: SPECIFICATIONS**
- APPENDIX H: FCC LABELLING DETAILS**
- APPENDIX I: USER MANUAL**
- APPENDIX J: CHANNEL BANDWIDTH PLOTS**
- APPENDIX K: HARMONICS PLOTS**
- APPENDIX L: BANDEDGE PLOTS**
- APPENDIX M: PEAK POWER OUTPUT PLOTS**
- APPENDIX N: BLUETOOTH CHANNEL OCCUPANCY PLOTS**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for Stylistic ST Series**

**Attachment 3: FCC Part 15B Test Report (Report: FG05-050EAL)**



**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

**Report Number:** M050508\_Cert\_BT\_WLL4070\_11abg

**Test Sample:** Stylistic ST Series  
**Model:** ST5030D  
**Radio Modules:** Bluetooth, Model: UGXZ5-102A (Fujitsu Ltd)  
Mini-PCI WLAN, Model: WLL4070 (Askey Computer Corp.)


**FCC ID:** EJE-WB0026  
**Industry Canada ID:** 337J-WB0026  
**Equipment Type:** Intentional Radiator (Transceiver)

**Manufacturer (LifeBook):** Fujitsu Ltd  
**Address:** 1405, Ohamaru, Inagi-shi, Tokyo 206-8503, Japan  
**Contact:** Mr. Tsuyoshi Uchihara


**Tested for:** Fujitsu Australia Ltd

**Test Standards:** FCC Part 15, Subpart C – Intentional Radiators  
FCC Part 15.247, 2400 – 2483.5 MHz Operation Band  
ANSI C63.4 – 2003  
OET Bulletin No. 65  
  
RSS-210 Issue 5 Low Power Licence-Exempt RadioCommunication  
Devices: 6.2.2 (o) 2400 – 2483.5 MHz Spread Spectrum  
  
RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and  
Portable Radio Transmitters with respect to Health Canada's Safety  
Code 6 for Exposure of Humans to Radio Frequency Fields

**Test Dates:** 12<sup>th</sup> May to 16<sup>th</sup> June 2005

**Test Officers:**   
**Chieu Huynh - B.Eng (Hons) Electronics**  
**Jorge Lara**

**Attestation:** *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

**Authorised Signatory:**   
**Chris Zombolas**  
**Technical Director**  
**EMC Technologies Pty Ltd**



**EMI TEST REPORT FOR CERTIFICATION**  
to  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

## 1.0 INTRODUCTION

EMI testing was performed on test sample Stylistic ST Series, Model: ST5030D with Mini-PCI Wireless LAN Module (Atheros 11a+b/g), Model WLL4070 & Bluetooth, Model UGXZ5-102A.

The WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE 802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations and also on the Bluetooth.

The results for the Bluetooth are reported in this test report.

The results for the WLAN Atheros module are reported separately.

Refer to EMC Technologies' test reports: M050508\_Cert\_WLL4070\_11abg\_DTS\_BT (DTS) and M050508\_Cert\_WLL4070\_11abg\_NII\_BT (U-NII).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) and the RF exposure requirements of RSS-102.

## 1.1 Summary of Results

### 1.1.1 Bluetooth - FCC PART 15 Subpart C (Section 15.247)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>*Complies with SAR requirements</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>



**1.1.2 WLAN, Atheros: 802.11b, 802.11g and 802.11a (DTS) - FCC Subpart C, Section 15.247**

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	<b>Complies</b>
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>*Complies with SAR requirements</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	<b>Complies</b>

Refer to EMC Technologies Report No: M050508\_Cert\_WLL4070\_11abg\_DTS\_BT

**1.1.3 WLAN, Atheros: 802.11a (U-NII) - FCC Subpart E, Section 15.407**

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.407 (a)(4)	6.2.2(q1)	Peak Transmit Power	<b>Complies</b>
15.407 (a)(5)	6.2.2(q1)	Peak Power Spectral Density	<b>Complies</b>
15.407 (a)(6)		Peak Excursion	<b>Complies</b>
15.407 (b)	6.2.2(q1)	Undesirable Emission	<b>Complies</b>
15.407 (f)		Radio Frequency Hazard	<b>*Complies with SAR requirements</b>
15.407 (g)	6.4	Frequency Stability	<b>Complies</b>

Refer to EMC Technologies Report No: M050508\_Cert\_WLL4070\_11abg\_NII\_BT

\*Refer to EMC Technologies' report M050509\_Cert\_WLL4070\_SAR\_2.4 and M050509\_Cert\_WLL4070\_SAR\_5.2

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

**1.2 Modifications by EMC Technologies**

No modifications were required.



## 2.0 GENERAL INFORMATION

(Information supplied by the Client)

### 2.1 Product Details

<b>Test Sample (Host Notebook):</b>	Stylistic ST Series
<b>Model Number:</b>	ST5030D
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	Fujitsu Ltd
<hr/>	
<b>CPU Type and Speed:</b>	Pentium M 1.2 GHz ULV
<hr/>	
<b>Wired LAN:</b>	Broadcom BCM5751M : 10 Base-T/100 Base-TX/1000 Base-T
<b>Modem:</b>	Agere MDC 1.5, Model: AM2
<b>Port Replicator Model:</b>	FPCPR43 / FPCPR44
<hr/>	
<b>AC Adapter Model:</b>	SEC80N2-16.0 / UJ88
<b>Voltage:</b>	16 V
<b>Current Specs:</b>	3.75A
<b>Watts:</b>	60 W
<hr/>	
<b>Radio Modules:</b>	Bluetooth and WLAN (Atheros 11a+b/g)
<b>Bluetooth Model Number:</b>	UGXZ5-102A
<b>Bluetooth Manufacturer:</b>	Fujitsu Ltd
<hr/>	
<b>WLAN Model Number:</b>	WLL4070
<b>WLAN Manufacturer:</b>	Askey Computer Corp.
<b>Interface Type:</b>	Mini-PCI Wireless LAN Module
<hr/>	
<b>FCC ID:</b>	EJE-WB0026
<b>Industry Canada ID:</b>	337J-WB0026
<b>Equipment Type:</b>	Intentional Radiator (Transceiver)



## 2.2 Technical Specifications

### 2.2.1 Bluetooth Transmitter Specifications

<b>Transmitter:</b>	Bluetooth
<b>Model Number:</b>	UGXZ5-102A
<b>Manufacturer:</b>	Fujitsu Ltd.
<b>Network Standard:</b>	Bluetooth™ RF Test Specification
<b>Modulation Type:</b>	Frequency Hopping Spread Spectrum (FHSS)
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Number of Channels:</b>	79
<b>Carrier Spacing:</b>	1.0 MHz
<b>Antenna Types:</b>	Yokowo Monopole Antenna – Model: YCE-5008
<b>Antenna gain:</b>	0.69 dBi
<b>Max. Output Power:</b>	12 dBm
<b>Reference Oscillator:</b>	16 MHz (Built-in)
<b>Power Supply:</b>	3.3 VDC from host.

**Frequency allocation:**

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
<b>1*</b>	<b>2402</b>	Power (Ext, Int) = 180, 50
2	2403	
3	2404	
.	.	
.	.	
.	.	
39	2440	
<b>40*</b>	<b>2441</b>	
41	2442	
.	.	
.	.	
.	.	
77	2478	
78	2479	
<b>79*</b>	<b>2480</b>	

\*Channels tested and reported in this report



**2.2.2 WLAN Transmitter Specifications**

**Transmitter:** Mini-PCI Wireless LAN Module  
**Wireless Module:** Atheros  
**Model Number:** WLL4070 (11a+b/g module)  
**Manufacturer:** Askey Computer Corp.

**Modulation Type:** Direct Sequence Spread Spectrum (DSSS for 802.11b)  
 Orthogonal Frequency Division Multiplexing (OFDM for 802.11g)  
 Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)

**802.11a**  
 BPSK – 6Mbps, 9Mbps  
 QPSK – 12Mbps, 18Mbps  
 16QAM – 24Mbps, 36Mbps  
 64QAM – 48Mbps, 54Mbps

**802.11g**  
 BPSK – 6Mbps, 9Mbps  
 QPSK – 12Mbps, 18Mbps  
 16QAM – 24Mbps, 36Mbps  
 64QAM – 48Mbps, 54Mbps

**802.11b**  
 DBPSK – 1Mbps  
 DQPSK – 2Mbps  
 CCK – 5.5Mbps, 11Mbps

**Maximum Data Rate:** 802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps  
**Frequency Range:** 2.4 –2483.5 GHz for 11b/g  
 5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 11a

**Antenna Types:** Yokowo Monopole Antenna – Model: YCE-5008  
**Antenna gain:** 802.11b/g = 0.69 dBi  
 802.11a (5.15 – 5.35 GHz) = 1.51 dBi  
 802.11a (5.725 – 5.825 GHz) = 4.91 dBi

**Power Supply:** 3.3 VDC from PCI bus  
**Chipset Used:** Atheros AR5414, AR5413

**Turbo Mode:** For 802.11g & 802.11a only  
**Data rate (Turbo):** 12 Mbps to 108 Mbps

**Frequency allocation and maximum output power setting for 802.11b/g:**

Channel Number	Frequency (MHz)	EUT Power level setting dBm	
		802.11b	802.11g
1	2412*	18	17
2	2417	18	17
3	2422	18	17
4	2427	18	17
5	2432	18	17
6	2437*	18	17
<b>6 Turbo (802.11g only)</b>	<b>2437*</b>	-	<b>15</b>
7	2442	18	17
8	2447	18	17
9	2452	18	17
10	2457	18	17
11	2462*	18	17

\*Channels tested and reported in the DTS submission (M050508\_Cert\_WLL4070\_11abg\_DTS\_BT)





**Frequency allocation and maximum output power setting for 802.11a:**

<b>Channel Number</b>	<b>Frequency (MHz)</b>	<b>Power level setting dBm</b>
*Channels tested and reported in the DTS submission (M050508_Cert_WLL4070_11abg_DTS_BT)		
<b>149</b>	<b>5745*</b>	<b>16</b>
<b>152</b>	<b>*5760 Turbo</b>	<b>17</b>
153	5765	16
<b>157</b>	<b>5785*</b>	<b>16</b>
<b>160</b>	<b>*5800 Turbo</b>	<b>17</b>
161	5805	16
<b>165</b>	<b>5825*</b>	<b>16</b>
*Channels tested and reported in the U-NII submission (M050508_Cert_WLL4070_11abg_NII_BT)		
<b>36</b>	<b>5180*</b>	<b>14</b>
40	5200	14
<b>42</b>	<b>*5210 Turbo</b>	<b>13</b>
44	5220	14
48	5240	14
<b>50</b>	<b>*5250 Turbo</b>	<b>13</b>
<b>52</b>	<b>5260*</b>	<b>17</b>
56	5280	17
<b>58</b>	<b>*5290 Turbo</b>	<b>17</b>
60	5300	17
<b>64</b>	<b>5320*</b>	<b>17</b>



## 2.3 Operational Description

The EUT is a Stylistic ST Series, Model: ST5030D installed with a Mini-PCI Wireless LAN (WLAN) Module (Atheros 11a+b/g, Model WLL4070) & Bluetooth, Model UGXZ5-102A.

The same WLAN radio module and Bluetooth combination has been previously certified by Fujitsu under FCC ID: EJE-WB0032 and IC: 337J-WB0032 in a different host.

The intention of this application is to re-certify this WLAN and Bluetooth with a different antenna combination in host – Stylistic ST Series, Model: ST5030D.

## 2.4 Test Configuration

The Askey software and the BlueSuiteCasira software were used to set-up the WLAN module and Bluetooth devices respectively to continuously transmit during the tests. The LCD screen was observed for the transmitter status shown for the respective software.

### Antenna

The Atheros (11a+b/g) WLAN, Model WLL4070, and ALPS Bluetooth device are configured with Yokowo Monopole Antenna – Model: YCE-5008. The installation of the OEM WLAN module, Bluetooth Device and the Antenna in Fujitsu Stylistic ST Series, Model: ST5030D is in a controlled environment. The installation is performed during the production/assembly process at the Fujitsu factory.

Refer to Appendix F – Antenna Information.

Refer to photos in Appendix B3 for BT Antenna location.

### AC Adapter

The AC adapter SEC80N2-16.0 was used for all the tests. Details of the AC adapter are supplied in section 2.1 of this report.

## 2.5 Block Diagram

Refer to Appendix D - Block Diagram



## 2.6 Support Equipment

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-050EAL)

## 2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 and 1 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

## 2.8 Test Facility

### 2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted emission measurements were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional).

**Industry Canada File Number IC 4161.**

### 2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)

It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).



## 2.9 Units of Measurements

### 2.9.1 Conducted Emissions

Measurements are reported in units of dB relative to one microvolt. (dB $\mu$ V).

### 2.9.2 Radiated Emissions

Measurements are reported in units of dB relative to one microvolt per metre (dB $\mu$ V/m).

## 2.10 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

## 2.11 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



## RESULTS

### Bluetooth Module, Model UGXZ5-102A

#### 3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207  
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-050EAL)

#### 4.0 SPURIOUS EMISSION MEASUREMENTS

##### 4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(c).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115 and EMCO 3116 Horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-050EAL).

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

##### 4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

- E** = Radiated Field Strength in dB $\mu$ V/m.
- V** = EMI Receiver Voltage in dB $\mu$ V. (measured value)
- AF** = Antenna Factor in dB(m<sup>-1</sup>). (stored as a data array)
- G** = Preamplifier Gain in dB. (stored as a data array)
- L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB $\mu$ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz)  $\pm$  4.1 dB



### 4.3 Radiated Emissions (Spurious and Harmonics)

#### 4.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB $\mu$ V/m limit at 3 metres has been converted to 64 dB $\mu$ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Testing was performed while both the Bluetooth transmitter and WLAN transmitter continuously operated. Harmonics related to the Bluetooth transmitter are reported below. For harmonics related to the WLAN transmitter, Refer to EMC Technologies' test reports: M050508\_Cert\_WLL4070\_11abg\_DTS\_BT and M050508\_Cert\_WLL4070\_11abg\_NII\_BT.

Measurements for the WLAN were made on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2480 MHz), was 50.9 dB $\mu$ V/m peak & 39.6 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2402 MHz), was 69.1 dB $\mu$ V/m peak & 50.4 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

#### Channel 1 - 2402 MHz

Frequency MHz	Level dB $\mu$ V/m		Antenna Polarization	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector				
2402	Transmitter	Fundamental		-	-	
4804	50	37	Vert/Hort	74.0	54.0	Pass
7206	54	41	Vert/Hort	-	-	Pass
9608	56	43	Vert/Hort	-	-	Pass
12010	57	44	Vert/Hort	74.0	54.0	Pass
14412	61	47	Vert/Hort	-	-	Pass
16814	64	50	Vert/Hort	-	-	Pass
19216	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21618	67	54	Vert/Hort	-	-	Pass
24020	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



**Channel 40 - 2441 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2441	Transmitter	Fundamental		-	-	
4882	50	37	Vert/Hort	74.0	54.0	Pass
7323	54	41	Vert/Hort	74.0	54.0	Pass
9764	56	43	Vert/Hort	-	-	Pass
12205	57	44	Vert/Hort	74.0	54.0	Pass
14646	61	47	Vert/Hort	-	-	Pass
17087	64	50	Vert/Hort	-	-	Pass
19528	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21969	67	54	Vert/Hort	-	-	Pass
24410	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Channel 79 - 2480 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2480	Transmitter	Fundamental		-	-	
4960	50	37	Vert/Hort	74.0	54.0	Pass
7440	54	41	Vert/Hort	74.0	54.0	Pass
9920	56	43	Vert/Hort	-	-	Pass
12400	57	44	Vert/Hort	74.0	54.0	Pass
14880	61	47	Vert/Hort	-	-	Pass
17360	64	50	Vert/Hort	-	-	Pass
19840	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22320	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24800	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Result:** No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**4.3.2 Spurious Emissions Generated When Both (WLAN and BT) Transmitters Transmitting**

**Result:** No spurious emissions were recorded within the restricted bands of up to 40 GHz. Spurious emissions were confirmed low with both RBW and VBW reduced. Emissions were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**4.3.3 Frequency Band: 30 - 1000 MHz**

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-050EAL).



**4.3.4 RF Conducted Measurements at the antenna terminal**

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Measurements for the WLAN were made on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

Refer to Appendix K for Harmonics plots

**Result:** Complies.

**4.3.5 Band Edge Measurements**

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Testing was performed while the WLAN transmitter continuously transmitted on a low (2402 MHz) and high frequency (2480 MHz) channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

Refer to Appendix L for Band Edge plots

*NB:* D1 line indicates the 20 dB limit below the highest level of the transmitter

**Result:** Complies.

**5.0 PEAK OUTPUT POWER - Section 15.247 (b)(1) & (3)**

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the Bluetooth transmitter continuously transmitted.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 1 MHz and the video bandwidth of 3 MHz were utilised.

Testing was performed while the transmitter continuously transmitted on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

Variation by +/- 15% of the supply voltage, in accordance with section 15.31(e), to the computer power supply power did not cause any variations to the RF output power.

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Power Plots
2402	10.6	30	11.5	1000	Appendix M
2441	10.8	30	12.0	1000	Appendix M
2480	10.5	30	11.2	1000	Appendix M

**Result:** Complies.





## 6.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY

Testing was carried out in accordance with the requirements of FCC Part 15.247(a)(1)(i)&(iii)

The EUT was a Frequency Hopping Spread Spectrum transmitter and operated as described in section 2 of this report.

### 6.1 Channel Bandwidth

In the band 2400 - 2483.5 MHz the hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

The transmitter output was connected to the spectrum analyser in peak hold mode.

A resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised.

Testing was performed while the transmitter continuously transmitted on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

Frequency MHz	Bandwidth kHz	Result	20 dB Bandwidth Plots
2402	739	Complies	Appendix J
2441	745	Complies	Appendix J
2480	733	Complies	Appendix J

### 6.2 Channel Occupancy

79 channels were observed operating between 2400 – 2483.5 MHz. Refer to Appendix N for number of channel plot.

The channel separation of 1 MHz was recorded. Refer to Appendix N for number of channel separation plot.

The device was observed to have a dwell time of 410.8 uS. This measurement was made on a channel using a spectrum analyser with a 0 Hz span and a sweep time of 5 mS. Refer to Appendix N for dwell time plot.

The specification allows for a dwell time not exceeding 0.4 seconds.

The maximum period is 79 channels x 0.4 seconds = 31.6 seconds

During the test the transmitter was observed to activate on average 315 times in 31.6 seconds.

The transmitter therefore occupies in one channel for  $315 \times 410.8\mu\text{S} = 0.129$  seconds

**Result:** Complies.



## 7.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(5)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1 (WLAN): The antenna is located on the right hand side (near the WLAN module) and projected distance of less than 20cm from user.

Transmitter # 2 (Bluetooth): The antenna is located on the top of LCD screen (away from the battery) and projected distance of less than 20cm from user.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters. Testing was performed with both WLAN and BT transmitters transmitting continuously.

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies M050509\_Cert\_WLL4070\_SAR\_2.4 and M050509\_Cert\_WLL4070\_SAR\_5.2. The highest SAR value was 1.04 mW/g which complies with the FCC human exposure requirements of 47 CFR 2.1093 (d).

Refer to EMC Technologies' report - M050509\_Cert\_WLL4070\_SAR\_2.4 and M050509\_Cert\_WLL4070\_SAR\_5.2 for details of SAR compliance.

**Results:       Complies**



## 8.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 9.0 COMPLIANCE STATEMENT

The Stylistic ST Series, Model: ST5030D with Mini-PCI Wireless LAN Module (Atheros 11a+b/g), Model WLL4070 & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **comply** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 -Operation in the frequency band 2400 - 2483.5 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

### Bluetooth - FCC PART 15 Subpart C (Section 15.247)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>*Complies with SAR requirements</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>

\*Refer to EMC Technologies' report M050509\_Cert\_WLL4070\_SAR\_2.4 and M050509\_Cert\_WLL4070\_SAR\_5.2

**The results for the WLAN Atheros module are reported separately.**

Refer to EMC Technologies' test reports: M050508\_Cert\_WLL4070\_11abg\_DTS\_BT (DTS) and M050508\_Cert\_WLL4070\_11abg\_NII\_BT (U-NII).



## TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**  
**APPENDIX B: REPORT PHOTOGRAPHS**  
**APPENDIX C: FUNCTIONAL DESCRIPTION**  
**APPENDIX D: BLOCK DIAGRAM**  
**APPENDIX E: SCHEMATICS**  
**APPENDIX F: ANTENNA DETAILS**  
**APPENDIX G: SPECIFICATIONS**  
**APPENDIX H: FCC LABELLING DETAILS**  
**APPENDIX I: USER MANUAL**  
**APPENDIX J: CHANNEL BANDWIDTH PLOTS**  
**APPENDIX K: HARMONICS PLOTS**  
**APPENDIX L: BANDEDGE PLOTS**  
**APPENDIX M: PEAK POWER OUTPUT PLOTS**  
**APPENDIX N: BLUETOOTH CHANNEL OCCUPANCY PLOTS**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for Stylistic ST Series**

**Attachment 3: FCC Part 15B Test Report (Report: FG05-050EAL)**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.