



EMC Technologies Pty Ltd
ABN 82 057 105 549
57 Assembly Drive
Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333
Fax: + 613 9338 9260
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WB0034
Industry Canada ID: 337J-WB0034

Test Sample: LifeBook P Series
Model: P7120D

Radio Modules: WLL4070 Mini-PCI WLAN (Atheros 11a+b/g) &
UGXZ5-102A Bluetooth

Report Number: M050750_Cert_WLL4070_DTS_BT

Tested for: Fujitsu Australia Ltd.

Issue Date: 30th August 2005

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



NATA Accredited
Laboratory Number: 5292

The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
EMC Technologies Report No. M050750_Cert_WLL4070_DTS_BT
Issue Date: 30th August 2005

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

RESULTS – WLAN, WLL4070 (802.11b, 802.11g and *802.11a)

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 PEAK POWER SPECTRAL DENSITY**
- 8.0 RADIO FREQUENCY EXPOSURE**
- 9.0 ANTENNA REQUIREMENT**
- 10.0 COMPLIANCE STATEMENT**

***RESULTS of 802.11a (5.15 – 5.35 GHz Band)**

Refer to Report No: M050750_Cert_WLL4070_NII_BT

RESULTS – Bluetooth, UGXZ5-102A

Refer to Report No: M050750_Cert_BT_WLL4070

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA DETAILS**
- APPENDIX G: SPECIFICATIONS**
- APPENDIX H: FCC LABELLING DETAILS**
- APPENDIX I: USER MANUAL**
- APPENDIX J: CHANNEL BANDWIDTH PLOTS**
- APPENDIX K: HARMONICS PLOTS**
- APPENDIX L: BANDEDGE PLOTS**
- APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS**

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook P Series

Attachment 3: FCC Part 15B Test Report (Report: FG05-073EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210

Report Number: M050750_Cert_WLL4070_DTS_BT

Test Sample: LifeBook P Series
Model: P7120D
Radio Modules: Mini-PCI WLAN, Model: WLL4070 (Askey Computer Corp.)
Bluetooth, Model: UGXZ5-102A (Fujitsu Ltd)

FCC ID: EJE-WB0034
Industry Canada ID: 337J-WB0034
Equipment Type: Intentional Radiator (Transceiver)

LifeBook Manufacturer: Fujitsu Ltd
Address: 1405, Ohamaru, Inagi-shi, Tokyo 206-8503, Japan
Contact: Mr. Tsuyoshi Uchihara

Tested for: Fujitsu Australia Ltd

Test Standards: FCC Part 15, Subpart C – Intentional Radiators
FCC Part 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Band
ANSI C63.4 – 2003
OET Bulletin No. 65

RSS-210 Issue 5 Low Power Licence-Exempt RadioCommunication Devices:
6.2.2 (o) 2400 – 2483.5 MHz & 5725 – 5850 MHz Spread Spectrum

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable
Radio Transmitters with respect to Health Canada's Safety Code 6 for
Exposure of Humans to Radio Frequency Fields

Test Dates: 4th to 19th August 2005

Test Officers:




Chieu Huynh - B.Eng (Hons) Electronics
Jorge Lara

Attestation:

I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.

Authorised Signatory:



Chris Zombolas
Technical Director
EMC Technologies Pty Ltd



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION to FCC PART 15 Subpart C (Section 15.247) & RSS-210

1.0 INTRODUCTION

EMI testing was performed on test sample LifeBook P Series, Model: P7120D with Mini-PCI Wireless LAN Module (Atheros 11a+b/g), Model WLL4070 & Bluetooth, Model UGXZ5-102A.

The WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE 802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations and also on the Bluetooth.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE 802.11a (DTS: 5725 – 5850 MHz) are reported in this test report.

The results for IEEE 802.11a (U-NII) and Bluetooth are reported separately.
Refer to EMC Technologies' test report: M050750_Cert_WLL4070_NII_BT (U-NII: 5150 – 5350 MHz) and M050750_Cert_BT_WLL4070 (Bluetooth).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) and the RF exposure requirements of RSS-102.

1.1 Summary of Results

1.1.1 WLAN, Atheros: 802.11b, 802.11g and 802.11a (DTS) - FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (i)		Radio Frequency Hazard	*Complies with SAR requirements
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

1.1.2 WLAN, Atheros: 802.11a (U-NII) - FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	6.2.2(q1)	Peak Transmit Power	Complies
15.407 (a)(5)	6.2.2(q1)	Peak Power Spectral Density	Complies
15.407 (a)(6)		Peak Excursion	Complies
15.407 (b)	6.2.2(q1)	Undesirable Emission	Complies
15.407 (f)		Radio Frequency Hazard	*Complies with SAR requirements
15.407 (g)	6.4	Frequency Stability	Complies

Refer to EMC Technologies Report No: M050750_Cert_WLL4070_NII_BT

1.1.3 Bluetooth - FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(1)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	Complies
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (i)		Radio Frequency Hazard	*Complies with SAR requirements
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies

Refer to EMC Technologies Report No: M050750_Cert_BT_WLL4070

*Refer to EMC Technologies' report M050751_Cert_WLL4070_SAR_2.4 and M050751_Cert_WLL4070_SAR_5.2

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 Product Details

Test Sample (LifeBook):	LifeBook P Series
Model Number:	P7120D
Serial Number:	Pre-production Sample
Manufacturer:	Fujitsu Ltd
CPU Type and Speed:	Pentium-M 1.2 GHz ULV Celeron-M 1.0 GHz ULV
LCD:	10.6" WXGA
Wired LAN:	Realtech RTL8100C : 10 Base-T/100 Base-TX
Modem:	Agere MDC 1.5, Model: AM2
Port Replicator Model:	FPCPR62
AC Adapter Model:	SEC80N2-16.0 (Sanken) / US25 (Eastern)
Voltage:	16 V
Current Specs:	3.75A
Watts:	60 W
Radio Modules:	WLAN (Atheros 11a+b/g) and Bluetooth
WLAN Model Number:	WLL4070
WLAN Manufacturer:	Askey Computer Corp.
Interface Type:	Mini-PCI Wireless LAN Module
Bluetooth Model Number:	UGXZ5-102A (ALPS)
Bluetooth Manufacturer:	Fujitsu Ltd.
FCC ID:	EJE-WB0034
Industry Canada ID:	337J-WB0034
Equipment Type:	Intentional Radiator (Transceiver)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.2 Technical Specifications

2.2.1 WLAN Transmitter Specifications

Transmitter:	Mini-PCI Wireless LAN Module
Wireless Module:	Atheros
Model Number:	WLL4070 (11a+b/g module)
Manufacturer:	Askey Computer Corp.
Modulation Type:	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
802.11a	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
802.11g	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
802.11b	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
Maximum Data Rate:	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps
Frequency Range:	2.4 – 2483.5 GHz for 802.11b/g 5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 802.11a
Antenna Types:	Nissei Electric Inverted-F
Models:	CP254654 (left) and CP254655 (right) Located on top edge of LCD screen
Antenna gain:	802.11b/g = 1.9 dBi 802.11a (5.15 – 5.35 GHz) = 1.23 dBi 802.11a (5.725 – 5.825 GHz) = 1.94 dBi
Power Supply:	3.3 VDC from PCI bus
Chipset Used:	Atheros AR5414, AR5413
Turbo Mode:	For 802.11g & 802.11a only
Data rate (Turbo):	12 Mbps to 108 Mbps



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Frequency allocation and maximum output power setting for 802.11b/g:

Channel Number	Frequency (MHz)	EUT Power level setting dBm	
		802.11b	802.11g
1	2412*	18	17
2	2417	18	17
3	2422	18	17
4	2427	18	17
5	2432	18	17
6	2437*	18	17
6 Turbo (802.11g only)	2437*	-	15
7	2442	18	17
8	2447	18	17
9	2452	18	17
10	2457	18	17
11	2462*	18	17

*Channels tested and reported in this report

Frequency allocation and maximum output power setting for 802.11a:

Channel Number	Frequency (MHz)	Power level setting dBm
*Channels tested and reported in this report (DTS)		
149	5745*	16
152	*5760 Turbo	17
153	5765	16
157	5785*	16
160	*5800 Turbo	17
161	5805	16
165	5825*	16
*Channels tested and reported in the U-NII submission (M050750_Cert_WLL4070_NII_BT)		
36	5180*	14
40	5200	14
42	*5210 Turbo	13
44	5220	14
48	5240	14
50	*5250 Turbo	13
52	5260*	17
56	5280	17
58	*5290 Turbo	17
60	5300	17
64	5320*	17



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.2.2 Bluetooth Transmitter Specifications

Transmitter:	Bluetooth
Model Number:	UGXZ5-102A
Manufacturer:	Fujitsu Ltd.
Network Standard:	Bluetooth™ RF Test Specification
Modulation Type:	Frequency Hopping Spread Spectrum (FHSS)
Frequency Range:	2402 MHz to 2480 MHz
Number of Channels:	79
Carrier Spacing:	1.0 MHz
Antenna Types:	Yokowo Monopole Chip Antenna
Model:	YCE-5250
Location:	Right palm rest area
Antenna gain:	2.78 dBi
Max. Output Power:	12 dBm
Reference Oscillator:	16 MHz (Built-in)
Power Supply:	3.3 VDC from host.

Frequency allocation:

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
1*	2402	Power (Ext, Int) = 180, 45
2	2403	
3	2404	
.	.	
.	.	
.	.	
39	2440	
40*	2441	
41	2442	
.	.	
.	.	
.	.	
77	2478	
78	2479	
79*	2480	

*Channels tested and reported in the Bluetooth submission (M050750_Cert_BT_WLL4070)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.3 Operational Description

The EUT is a LifeBook P Series, Model: P7120D installed with a Mini-PCI Wireless LAN (WLAN) Module (Atheros 11a+b/g, Model WLL4070) & Bluetooth, Model UGXZ5-102A.

The same WLAN radio module and Bluetooth combination has been previously certified by Fujitsu under FCC ID: EJE-WB0029 and IC: 337J-WB0029 in a different host.

The intention of this application is to re-certify this WLAN and Bluetooth with a different antenna combination in host – LifeBook P Series, Model: P7120D.

2.4 Test Configuration

The Askey software and the BlueSuiteCasira software were used to set-up the WLAN module and Bluetooth devices respectively to continuously transmit during the tests. The LCD screen was observed for the transmitter status shown for the respective software.

Antenna

The Atheros (11a+b/g) WLAN, Model WLL4070 is configured with Nissei Electric Inverted-F Antenna, Models: CP254654 and CP254655. The ALPS Bluetooth device is configured with Yokowo Monopole Antenna, Model: YCE-5250. The installation of the OEM WLAN module, Bluetooth Device and the Antennas in Fujitsu LifeBook P Series, Model: P7120D is in a controlled environment. The installation is performed during the production/assembly process at the Fujitsu factory.

Refer to Appendix F – Antenna Information.

There are three antennas: WLAN antennas (x2) are located on the right hand side and left hand side on the top edge of the LCD screen. Bluetooth antenna is located on the right palm rest area.

Refer to photos in Appendix B3 for WLAN Antenna locations.

AC Adapter

The AC adapter SEC80N2-16.0 was used for all the tests. Details of the AC adapter are supplied in section 2.1 of this report.

2.5 Block Diagram

Refer to Appendix D - Block Diagram

2.6 Support Equipment

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-073EAL)

2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.8 Test Facility

2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional).

Industry Canada File Number IC 4161.

2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.9 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

2.10 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

RESULTS

WLAN Module - WLL4070 (802.11b, 802.11g and 802.11a (DTS))

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-073EAL)

4.0 SPURIOUS EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-073EAL)

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

- E** = Radiated Field Strength in dBμV/m.
- V** = EMI Receiver Voltage in dBμV. (measured value)
- AF** = Antenna Factor in dB(m⁻¹). (stored as a data array)
- G** = Preamplifier Gain in dB. (stored as a data array)
- L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

• Example Field Strength Calculation

Assuming a receiver reading of 34.0 dBμV is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz) ± 4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3 Radiated Emissions (Spurious and Harmonics)

4.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB μ V/m limit at 3 metres has been converted to 64 dB μ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Harmonics related to the WLAN transmitter (2.4 – 2.4835 GHz and 5725 – 5850 GHz) are reported below. Harmonics in the frequency band (5.15 – 5.35 GHz), refer to M050750_Cert_WLL4070_NII_BT. Harmonics related to the Bluetooth transmitter, refer to M050750_Cert_BT_WLL4070.

4.3.1.1 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 11 Mbps (CCK).

When the EUT was operating at its highest channel (2462 MHz), the field strength at 2483.5 MHz was 57.1 dB μ V/m peak and 40.4 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

When the EUT was operating at its lowest channel (2412 MHz), the field strength at 2400 MHz was 69.9 dB μ V/m peak and 63.6 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 1 - 2412 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	50.6	44.8	Vert/Hort	74.0	54.0	Pass
7236	46	37	Vert/Hort	-	-	Pass
9648	48	39	Vert/Hort	-	-	Pass
12060	51	41	Vert/Hort	74.0	54.0	Pass
14472	55	46	Vert/Hort	74.0	54.0	Pass
16884	56	49	Vert/Hort	-	-	Pass
19296	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	67	54	Vert/Hort	-	-	Pass
24120	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Channel 6 - 2437 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	51.3	46.7	Vert/Hort	74.0	54.0	Pass
7311	46	37	Vert/Hort	74.0	54.0	Pass
9748	48	39	Vert/Hort	-	-	Pass
12185	51	41	Vert/Hort	74.0	54.0	Pass
14622	55	46	Vert/Hort	-	-	Pass
17059	56	49	Vert/Hort	-	-	Pass
19496	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	67	54	Vert/Hort	-	-	Pass
24370	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 11 - 2462 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	50.8	44.5	Vert/Hort	74.0	54.0	Pass
7386	46	37	Vert/Hort	74.0	54.0	Pass
9848	48	39	Vert/Hort	-	-	Pass
12310	51	41	Vert/Hort	74.0	54.0	Pass
14772	55	46	Vert/Hort	-	-	Pass
17234	56	49	Vert/Hort	-	-	Pass
19696	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: 2nd harmonic was recorded within the restricted bands of up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 7.3 dB. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3.1.2 Configuration 802.11g - Normal Operating Mode

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

When the EUT was operating at its highest channel (2462 MHz), the field strength at 2483.5 MHz was 74.4 dB μ V/m peak and 57.2 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

When the EUT was operating at its lowest channel (2412 MHz), the field strength at 2400 MHz was 90.4 dB μ V/m peak and 71.3 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 1 - 2412 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	47	37	Vert/Hort	74.0	54.0	Pass
7236	46	37	Vert/Hort	-	-	Pass
9648	48	39	Vert/Hort	-	-	Pass
12060	51	41	Vert/Hort	74.0	54.0	Pass
14472	55	46	Vert/Hort	74.0	54.0	Pass
16884	56	49	Vert/Hort	-	-	Pass
19296	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	67	54	Vert/Hort	-	-	Pass
24120	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 6 - 2437 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	47	37	Vert/Hort	74.0	54.0	Pass
7311	46	37	Vert/Hort	74.0	54.0	Pass
9748	48	39	Vert/Hort	-	-	Pass
12185	51	41	Vert/Hort	74.0	54.0	Pass
14622	55	46	Vert/Hort	-	-	Pass
17059	56	49	Vert/Hort	-	-	Pass
19496	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	67	54	Vert/Hort	-	-	Pass
24370	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Channel 11 - 2462 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	47	37	Vert/Hort	74.0	54.0	Pass
7386	46	37	Vert/Hort	74.0	54.0	Pass
9848	48	39	Vert/Hort	-	-	Pass
12310	51	41	Vert/Hort	74.0	54.0	Pass
14772	55	46	Vert/Hort	-	-	Pass
17234	56	49	Vert/Hort	-	-	Pass
19696	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.1.3 Configuration 802.11g - Turbo Mode

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 108 Mbps (64QAM).

Channel 6 - 2437 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	47	37	Vert/Hort	74.0	54.0	Pass
7311	46	37	Vert/Hort	74.0	54.0	Pass
9748	48	39	Vert/Hort	-	-	Pass
12185	51	41	Vert/Hort	74.0	54.0	Pass
14622	55	46	Vert/Hort	-	-	Pass
17059	56	49	Vert/Hort	-	-	Pass
19496	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	67	54	Vert/Hort	-	-	Pass
24370	68	55	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3.1.4 Configuration 802.11a (5.725 – 5.850 MHz) Normal Operating Mode

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

When the EUT was operating at its highest channel (5825 MHz), the field strength at 5850 MHz was 70.7 dB μ V/m peak & 51.9 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

When the EUT was operating at its lowest channel (5745 MHz), the field strength at 5725 MHz was 75.8 dB μ V/m peak & 54.4 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 149 – 5745 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5745	Transmitter	Fundamental				
11490	52	43	Vert/Hort	74.0	54.0	Pass
17235	55	46	Vert/Hort	-	-	Pass
22980	66	51	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
28725	70	56	Vert/Hort	-	-	Pass
34470	79	65	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 157 – 5785 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5785	Transmitter	Fundamental				
11570	52	43	Vert/Hort	74.0	54.0	Pass
17355	55	46	Vert/Hort	-	-	Pass
23140	66	51	Vert/Hort	-	-	Pass
28925	70	56	Vert/Hort	-	-	Pass
34710	79	65	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 161 – 5825 MHz

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
5825	Transmitter	Fundamental				
11650	52	43	Vert/Hort	74.0	54.0	Pass
17475	55	46	Vert/Hort	-	-	Pass
23300	66	51	Vert/Hort	-	-	Pass
29125	70	56	Vert/Hort	-	-	Pass
34950	79	65	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Result: No harmonics were recorded within the restricted bands of up to 40 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.1.5 Configuration 802.11a (5.725 – 5.850 MHz) Turbo Mode

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 108 Mbps (64QAM).

When the EUT was operating at its highest channel (5800 MHz), the field strength at 5850 MHz was 68.9 dB μ V/m peak & 51.0 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

When the EUT was operating at its lowest channel (5760 MHz), the field strength at 5725 MHz was 70.9 dB μ V/m peak & 52.1 dB μ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

Channel 152 – 5760 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
5760	Transmitter	Fundamental				
11520	52	43	Vert/Hort	74.0	54.0	Pass
17280	55	46	Vert/Hort	-	-	Pass
23040	66	51	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
28800	70	56	Vert/Hort	-	-	Pass
34560	79	65	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Channel 160 – 5800 MHz

Frequency MHz	Level dB μ V/m		Antenna Polarization	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
	Peak Detector	Average Detector				
5800	Transmitter	Fundamental				
11560	52	43	Vert/Hort	74.0	54.0	Pass
17360	55	46	Vert/Hort	-	-	Pass
23160	66	51	Vert/Hort	-	-	Pass
28960	70	56	Vert/Hort	-	-	Pass
34760	79	65	Vert/Hort	-	-	Pass

*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

Result: No harmonics were recorded within the restricted bands of up to 40 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

4.3.2 Frequency Band: 30 - 1000 MHz

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-073EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.3.3 RF Conducted Measurements at the Antenna Terminal

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

D1 line indicates the 20 dB limit below the highest level of the transmitter

Results: Complies.

Configuration 802.11a (5.725 – 5.850 GHz)

Refer to Appendix K1 for Harmonics plots

Configuration 802.11b

Refer to Appendix K2 for Harmonics plots

Configuration 802.11g

Refer to Appendix K3 for Harmonics plots

4.3.4 Band Edge Measurements

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

D1 line indicates the 20 dB limit below the highest level of the transmitter

Results: Complies.

Configuration 802.11a (5.725 – 5.850 GHz)

Refer to Appendix L1 for Band Edge plots

Configuration 802.11b

Refer to Appendix L2 for Band Edge plots

Configuration 802.11g

Refer to Appendix L3 for Band Edge plots



5.0 PEAK OUTPUT POWER - Section 15.247 (b)(3)

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the WLAN transmitter continuously transmitted.

The peak output power measurement was performed using the integration method as per test method # 3 of DA 02-2138. The resolution bandwidth of 1 MHz was used. The video bandwidth of 30 kHz was used ($VBW \geq 1/T$, where T (worst case) = 360 μ S for normal operating mode and 180 μ S for turbo mode).

Variation by +/- 15% of the supply voltage, in accordance with Section 15.31(e), to the computer power supply did not vary the output power observed.

5.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Peak output power with 64QAM modulation was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Power dBm	Limit dBm	Power mW	Limit mW	Result
5745	Normal	15.8	30	38.0	1000	Complies
5760	Turbo	16.7	30	46.8	1000	Complies
5785	Normal	15.9	30	38.9	1000	Complies
5800	Turbo	16.8	30	47.9	1000	Complies
5825	Normal	15.7	30	37.2	1000	Complies

5.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Peak output power with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Operating Mode	Power dBm	Limit dBm	Power mW	Limit mW	Result
2412	Normal	17.5	30	56.2	1000	Complies
2437	Normal	17.3	30	53.7	1000	Complies
2462	Normal	17.2	30	52.5	1000	Complies

5.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Peak output power with 64QAM modulation was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Power dBm	Limit dBm	Power mW	Limit mW	Result
2412	Normal	16.2	30	41.7	1000	Complies
2437	Normal	16.5	30	44.7	1000	Complies
2437	Turbo	14.8	30	30.2	1000	Complies
2462	Normal	16.4	30	43.7	1000	Complies



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

6.0 CHANNEL BANDWIDTH

Testing was performed in accordance with the requirements of FCC Part 15.247(a)(2)

In the band 2400 - 2483.5 MHz and 5725 – 5850 MHz the minimum 6 dB bandwidth was at least 500 kHz. The 6 dB bandwidth was measured while the transmitter continuously transmitted.

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised

The minimum 6 dB bandwidth is at least 500 kHz

6.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Bandwidth MHz	Result	6 dB Bandwidth Plots
5745	Normal	16.6	Complies	Appendix J1
5760	Turbo	33.0	Complies	Appendix J1
5785	Normal	16.6	Complies	Appendix J1
5800	Turbo	33.1	Complies	Appendix J1
5825	Normal	16.6	Complies	Appendix J1

6.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Operating Mode	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	Normal	11.4	Complies	Appendix J2
2437.0	Normal	11.5	Complies	Appendix J2
2462.0	Normal	11.4	Complies	Appendix J2

6.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412	Normal	16.5	Complies	Appendix J3
2437	Normal	16.5	Complies	Appendix J3
2437	Turbo	33.0	Complies	Appendix J3
2462	Normal	16.6	Complies	Appendix J3



7.0 PEAK POWER SPECTRAL DENSITY - Section 15.247(e)

Testing was performed accordance with the requirements of FCC Part 15.247(e)

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 3 kHz and the video bandwidth of 30 kHz were utilised

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

7.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Level dBm	Limit dBm	Result	Spectral Density plots
5745	Normal	-12.3	8.0	Complies	Appendix M1
5760	Turbo	-12.0	8.0	Complies	Appendix M1
5785	Normal	-11.3	8.0	Complies	Appendix M1
5800	Turbo	-12.4	8.0	Complies	Appendix M1
5825	Normal	-12.0	8.0	Complies	Appendix M1

7.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Operating Mode	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	Normal	-4.5	8.0	Complies	Appendix M2
2437.0	Normal	-6.5	8.0	Complies	Appendix M2
2462.0	Normal	-8.7	8.0	Complies	Appendix M2

7.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps and 108 Mbps (64QAM).

Frequency MHz	Operating Mode	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	Normal	-10.5	8.0	Complies	Appendix M3
2437.0	Normal	-9.9	8.0	Complies	Appendix M3
2437.0	Turbo	-15.5	8.0	Complies	Appendix M3
2462.0	Normal	-10.1	8.0	Complies	Appendix M3



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

8.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1 (WLAN): The antennas are located on the top edge of LCD screen (left and right hand side) and projected distance of less than 20cm from user.

Transmitter # 2 (Bluetooth): The antenna is located on the right palm rest area and projected distance of less than 20cm from user.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies M050751_Cert_WLL4070_SAR_2.4 and M050751_Cert_WLL4070_SAR_5.2. The highest SAR value was less than 0.01mW/g which complies with the FCC human exposure requirements of 47 CFR 2.1093 (d).

Refer to EMC Technologies' report - M050751_Cert_WLL4070_SAR_2.4 and M050751_Cert_WLL4070_SAR_5.2 for details of SAR compliance.

Results: Complies



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

9.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.0 COMPLIANCE STATEMENT

The LifeBook P Series, Model: P7120D with Mini-PCI Wireless LAN Module (Atheros 11a+b/g), Model WLL4070 & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **complies** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 -Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz and 5725 – 5850 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

WLAN Module - 802.11b, 802.11g and 802.11a (DTS: 5725 – 5850 MHz)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (i)		Radio Frequency Hazard	*Complies with SAR requirements
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies

*Refer to EMC Technologies' report M050751_Cert_WLL4070_SAR_2.4 and M050751_Cert_WLL4070_SAR_5.2

The results for IEEE 802.11a (U-NII) and Bluetooth are reported separately.

Refer to EMC Technologies' test report: M050750_Cert_WLL4070_NII_BT (U-NII: 5150 – 5350 MHz) and M050750_Cert_BT_WLL4070 (Bluetooth).



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

TEST REPORT APPENDICES

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS
APPENDIX B: REPORT PHOTOGRAPHS
APPENDIX C: FUNCTIONAL DESCRIPTION
APPENDIX D: BLOCK DIAGRAM
APPENDIX E: SCHEMATICS
APPENDIX F: ANTENNA DETAILS
APPENDIX G: SPECIFICATIONS
APPENDIX H: FCC LABELLING DETAILS
APPENDIX I: USER MANUAL
APPENDIX J: CHANNEL BANDWIDTH PLOTS
APPENDIX K: HARMONICS PLOTS
APPENDIX L: BANDEDGE PLOTS
APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook P Series

Attachment 3: FCC Part 15B Test Report (Report: FG05-073EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.