



**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
176 Harrick Road  
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000  
Fax: + 613 9331 7455  
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WB0055  
Industry Canada ID: 337J-WB0055

Test Sample: LifeBook P Series  
Model: P1620

Radio Modules: EYTF3CSFT Bluetooth Module &  
4965AG Kedron INTEL Mini-PCI WLAN Module

Report Number: M071119\_Cert\_EYTF3CSFT\_WLAN

Issue Date: 9<sup>th</sup> January 2008

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements (FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz) which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

NATA Accredited Laboratory  
Number: 5292

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**  
**EMC Technologies Report No. M071119\_Cert\_EYTF3CSFT\_WLAN**  
**Issue Date: 9<sup>th</sup> January 2008**

**CONTENTS**

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

- FCC 15.247 (DSS) RESULTS - Bluetooth**
- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY**
- 7.0 RADIO FREQUENCY EXPOSURE**
- 8.0 ANTENNA REQUIREMENT**
- 9.0 COMPLIANCE STATEMENT**
- 10.0 TEST REPORT APPENDICES**

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: OPERATIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA DETAILS**
- APPENDIX G: SPECIFICATIONS**
- APPENDIX H: FCC LABELLING DETAILS**
- APPENDIX I: USER MANUAL**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook P Series**

**Attachment 3: FCC Part 15B Test Report (Report: FG07-172EAL)**

**Attachment 4: EMCT 15.247 Test Report (Report: M060756\_Cert\_EYTF3CSFT\_WLAN)**

**FCC 15.407 (U-NII) RESULTS - WLAN**

**Refer to Report No: M071119\_Cert\_4965AG\_NII\_BT**

**FCC 15.247 (DTS) RESULTS – WLAN**

**Refer to Report No: M071119\_Cert\_4965AG\_DTS\_BT**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

**Report No. M071119\_Cert\_EYTF3CSFT\_WLAN**

**Test Sample:** LifeBook P Series  
**Model:** P1620  
**Radio Modules:** Kedron INTEL Mini-PCI WLAN Module, Model: 4965AG (Intel Corp.)  
Bluetooth Module, Model: EYTF3CSFT (TAIYO YUDEN)

**FCC ID:** EJE-WB0055  
**Industry Canada ID:** 337J-WB0055  
**Equipment Type:** Intentional Radiator (Transceiver)


**LifeBook Manufacturer:** Fujitsu Ltd - Mobile Computing Division  
**Address:** 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan  
**Contact:** Mr. Tsuyoshi Uchihara

**Test Standards:** FCC Part 15 – Radio Frequency Devices (May 2007)  
FCC Part 15 Subpart C - Intentional Radiators  
Section 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Bands  
ANSI C63.4 – 2003  
OET Bulletin No. 65  
  
RSS-210 Issue 7 Low Power Licence-Exempt RadioCommunication  
Devices Annex 8: 2400–2483.5 MHz & 5725–5850 MHz Operation Bands  
  
RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and  
Portable Radio Transmitters with respect to Health Canada's Safety  
Code 6 for Exposure of Humans to Radio Frequency Fields

**Test Dates:** 2<sup>nd</sup> December 2007 to 6<sup>th</sup> January 2008

**Senior Test Engineer:**   
**Chieu Huynh - B.Eng (Hons) Electronics**  
**Lee Hopkins**

**Attestation:** *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

**Authorised Signatory:**   
**Chris Zombolas**  
**Technical Director**  
**EMC Technologies Pty Ltd**



**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

## 1.0 INTRODUCTION

EMI testing was performed on the Fujitsu notebook PC, Model: P1620 with INTEL Mini-PCI Wireless LAN Module (Kedron 802.11a/b/g), Model: 4965AG & TAIYO YUDEN Bluetooth Module, Model: EYTF3CSFT.

The Bluetooth module was originally certified by TAIYO YUDEN as a modular approval under FCC ID: RYYEYTF3CSFT (Canada ID: 4389AEYTF3CSFT). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The Kedron WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD94965AGN (Canada ID: 1000M-4965AGN). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The Kedron WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE 802.11a (DTS & U-NII) configurations. Tests were performed in all configurations and also on the Bluetooth.

DSS results for the Bluetooth are reported in this test report.

The U-NII and DTS (WLAN) results are reported separately.  
Refer to EMC Technologies' test report: M071119\_Cert\_4965AG\_NII\_BT and M071119\_Cert\_4965AG\_DTS\_BT.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 8 and the RF exposure requirements of RSS-102.

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 1.1 Summary of Results

### 1.1.1 FCC Subpart C, Section 15.247 - Bluetooth

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Issue 7 and RSS-Gen Clauses	Test Performed	Result
15.203	RSS-Gen (7.1.4)	Antenna Requirement	<b>Complies</b>
15.205	2.2 (Table 1)	Operation in Restricted Band	<b>Complies</b>
15.207	RSS-Gen (7.2.2)	Conducted Emissions	<b>Complies</b>
15.209	RSS-Gen (6)	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)	A8.1 (b) (d)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	A8.4	Peak Output Power	<b>Complies</b>
15.247 (c)	RSS-Gen (7.1.4)	Antenna Gain > 6 dBi	<b>Not Applicable.</b> Antenna gain < 6 dBi
15.247 (d)	A8.5	Out of Band Emissions	<b>Complies</b>
15.247 (e)	A8.2 (b)	Peak Power Spectral Density	<b>Not Applicable.</b> EUT is not digital modulated system
15.247 (f)	A8.3	*Hybrid Systems	<b>Not Applicable.</b> EUT does not employ a hybrid system
15.247 (g)	A8.1	Frequency Hopping	<b>Complies</b>
15.247 (h)	A8.1	Frequency Hopping	<b>Complies</b>
15.247 (i)	RSS-Gen (5.5)	Radio Frequency Hazard	<b>Complies</b>

\*Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

### 1.1.2 FCC Subpart E, Section 15.407 - WLAN

Refer to EMC Technologies Report No: M071119\_Cert\_4965AG\_NII\_BT

### 1.1.3 FCC Subpart C, Section 15.247 – WLAN

Refer to EMC Technologies Report No: M071119\_Cert\_4965AG\_DTS\_BT

## 1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**2.0 GENERAL INFORMATION**  
(Information supplied by the Client)

**2.1 EUT (Bluetooth) Details**

**Transmitter:** Bluetooth  
**Model Number:** EYTF3CSFT  
**Manufacturer:** TAIYO YUDEN  
**Network Standard:** Bluetooth™ RF Test Specification  
**Modulation Type:** Frequency Hopping Spread Spectrum (FHSS)  
**Frequency Range:** 2402 MHz to 2480 MHz  
**Number of Channels:** 79  
**Carrier Spacing:** 1.0 MHz  
**Antenna Types:** Yokowo Inverted F Antenna, Model: YCE-5250  
 Location: Right palm rest area  
**Antenna gain:** Max antenna gain is less than 6 dBi.  
 Refer antenna data provided separately  
**Max. Output Power:** 4 dBm  
**Reference Oscillator:** 16 MHz (Built-in)  
**Power Supply:** 3.3 VDC from host.

**Frequency allocation:**

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
<b>1*</b>	<b>2402</b>	Power (Ext, Int) = 0, 96
2	2403	
3	2404	
.	.	
.	.	
.	.	
39	2440	
<b>40*</b>	<b>2441</b>	
41	2442	
.	.	
.	.	
.	.	
77	2478	
78	2479	
<b>79*</b>	<b>2480</b>	

\*Channels tested and reported in this report.



## 2.2 EUT (WLAN) Details

<b>Transmitter:</b>	Mini-Card Wireless LAN Module
<b>Wireless Module:</b>	Kedron (802.11a/b/g)
<b>Model Number:</b>	4965AG
<b>Manufacturer:</b>	Intel Corporation
<b>Modulation Type:</b>	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
<b>2.4 GHz (802.11b/g/n):</b>	DBPSK, DQPSK, CCK, 16QAM and 64QAM
<b>5 GHz (802.11a/n):</b>	BPSK, QPSK, 16QAM and 64QAM
<b>Maximum Data Rate:</b>	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps
<b>Frequency Ranges:</b>	2.412 –2.462 GHz for 11b/g 5.18 - 5.32 GHz and 5.745 - 5.825 GHz for 11a
<b>Number of Channels:</b>	11 channels for 11b/g 13 channels for 11a
<b>Antenna Types:</b>	Nissei Electric Inverted F Antenna Model: CP115455 (Main: Right), CP115456 (Aux: Left) Location: Top edge of LCD screen
<b>Antenna gain:</b>	Max antenna gain is less than 6 dBi. Refer antenna data provided separately
<b>Power Supply:</b>	3.3 VDC from PCI bus

### Channels Tested and Output power setting:

Channel and Mode	Frequency MHz	Average Output Power dBm
<b>802.11b/g mode</b>		
*Channels 1, 6 and 11	2412, 2437 and 2462	15.5
<b>802.11a mode</b>		
**Channels 36	5180	16.5
**Channels 48	5240	16.5
**Channels 52	5260	16.5
**Channels 64	5320	16.5
*Channels 149	5745	17.5
*Channels 157	5785	17.5
*Channels 165	5825	17.5

\*Channels tested and reported in the DTS submission (M071119\_Cert\_4965AG\_DTS\_BT)

\*\*Channels tested and reported in the U-NII submission ((M071119\_Cert\_4965AG\_NII\_BT)



## 2.3 EUT (Notebook PC) Details

<b>EUT:</b>	LifeBook P series
<b>Model Name:</b>	P1620
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Core2 Duo U7700 1.3GHz
<b>LCD</b>	8.9"WXGA
<b>Wired LAN:</b>	Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	Agere MDC1.5 modem Model: D40
<b>Port Replicator Model:</b>	FPCPR56
<b>AC Adapter Model:</b>	60W:SED80N2-16.0(Sanken) 40W: SEB55N2-16.0 (Sanken)
<b>Voltage:</b>	16 V
<b>Current Specs:</b>	3.75A / 2.5A
<b>Watts:</b>	60W / 40W

## 2.4 Operational Description

The Bluetooth test software "BlueTest" was used to transmit continuously during the tests.

## 2.5 Test Configuration

Conducted tests were performed at the Bluetooth Antenna ports.

Radiated tests were performed for measuring the harmonics and spurious from the transmitters.

## 2.6 Support Equipment

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG07-172EAL)

## 2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003.

Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.





## 2.8 Test Facility

### 2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderberg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number IC 4161**.

### 2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)  
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).

## 2.9 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

## 2.10 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



## FCC 15.247 (DTS) RESULTS

### 3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207  
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG07-172EAL)

### 4.0 SPURIOUS EMISSION MEASUREMENTS

#### 4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The test frequency range was subdivided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG07-172EAL).

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

#### 4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

**E** = Radiated Field Strength in dB $\mu$ V/m.

**V** = EMI Receiver Voltage in dB $\mu$ V. (measured value)

**AF** = Antenna Factor in dB(m<sup>-1</sup>). (stored as a data array)

**G** = Preamplifier Gain in dB. (stored as a data array)

**L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB $\mu$ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz)  $\pm$  4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

### 4.3 Radiated Emissions (Spurious and Harmonics)

#### 4.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 74 dB $\mu$ V/m @ 3m and 54 dB $\mu$ V/m @ 3m limits are applied for emissions fall in the restricted bands. The limits for emission outside the restricted band are 20 dB below the fundamental field strength.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Harmonics related to the Bluetooth transmitter are reported below. Harmonics related to the WLAN transmitter refer to M071119\_Cert\_4965AG\_NII\_BT. and M071119\_Cert\_4965AG\_DTS\_BT.

##### Channel 1 - 2402 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2402	94.1	64.2	-	-	-
4804	50.7	35.5	74.0	54.0	Complies
2390	34.9	23.8	74.0	54.0	Complies

##### Channel 40 - 2441 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2441	96.0	64.3	-	-	-
4882	50.5	35.1	74.0	54.0	Complies

##### Channel 79 - 2480 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2480	96.3	64.0	-	-	-
4960	49.1	34.6	74.0	54.0	Complies
2483.5	46.5	29.7	74.0	54.0	Complies

**Result:** Harmonic emission was recorded up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. Emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of 18.5 dB. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

#### 4.3.2 Frequency Band: 30 - 1000 MHz

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

Results: Complied - refer to Attachment 3 – FCC Part 15B Test Report (Report: FG07-172EAL).



#### **4.3.3 RF Conducted Measurements at the antenna terminal**

Testing was performed by EMC Technologies, Melbourne Australia, NATA accredited Laboratory Number: 5292.

Results: Complied – refer to attachment 4, EMCT test report: M060756\_Cert\_EYTF3CSFT\_WLAN (section 4.3.4) with FCC ID: EJE-WB0041.

#### **4.3.4 Band Edge Measurements**

Complied (refer to section 4.3 – radiated emissions).

### **5.0 PEAK OUTPUT POWER - Section 15.247 (b)(1)**

Testing was performed by EMC Technologies, Melbourne Australia, NATA accredited Laboratory Number: 5292.

Results: Complied – refer to attachment 4, EMCT test report: M060756\_Cert\_EYTF3CSFT\_WLAN (section 5.0) with FCC ID: EJE-WB0041.

### **6.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY**

Testing was performed by EMC Technologies, Melbourne Australia, NATA accredited Laboratory Number: 5292.

Results: Complied – refer to attachment 4, EMCT test report: M060756\_Cert\_EYTF3CSFT\_WLAN (section 6.0) with FCC ID: EJE-WB0041.

### **7.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION**

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M071143\_Cert\_4965AG\_SAR\_2.4 and M071143\_Cert\_4965AG\_SAR\_5.6. Highest SAR value measured 0.842 mW/g, which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

### **8.0 ANTENNA REQUIREMENT**

This intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



## 9.0 COMPLIANCE STATEMENT

The Fujitsu notebook PC, Model: P1620 with INTEL Mini-PCI Wireless LAN Module ((Kedron 802.11a/b/g), Model: 4965AG and Bluetooth Module, Model: EYTF3CSFT, **complied** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 8 and the RF exposure requirements of RSS-102.

**Results were as follows:**

### FCC Subpart C, Section 15.247 - Bluetooth

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Issue 7 and RSS-Gen Clauses	Test Performed	Result
15.203	RSS-Gen (7.1.4)	Antenna Requirement	<b>Complies</b>
15.205	2.2 (Table 1)	Operation in Restricted Band	<b>Complies</b>
15.207	RSS-Gen (7.2.2)	Conducted Emissions	<b>Complies</b>
15.209	RSS-Gen (6)	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)	A8.1 (b) (d)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	A8.4	Peak Output Power	<b>Complies</b>
15.247 (c)	RSS-Gen (7.1.4)	Antenna Gain > 6 dBi	<b>Not Applicable.</b> Antenna gain < 6 dBi
15.247 (d)	A8.5	Out of Band Emissions	<b>Complies</b>
15.247 (e)	A8.2 (b)	Peak Power Spectral Density	<b>Not Applicable.</b> EUT is not digital modulated system
15.247 (f)	A8.3	*Hybrid Systems	<b>Not Applicable.</b> EUT does not employ a hybrid system
15.247 (g)	A8.1	Frequency Hopping	<b>Complies</b>
15.247 (h)	A8.1	Frequency Hopping	<b>Complies</b>
15.247 (i)	RSS-Gen (5.5)	Radio Frequency Hazard	<b>Complies</b>

\*Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

### FCC Subpart E, Section 15.407 - WLAN

Refer to EMC Technologies Report No: M071119\_Cert\_4965AG\_NII\_BT

### FCC Subpart C, Section 15.247 – WLAN

Refer to EMC Technologies Report No: M071119\_Cert\_4965AG\_DTS\_BT



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 10.0 TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**

**APPENDIX B: REPORT PHOTOGRAPHS**

**APPENDIX C: OPERATIONAL DESCRIPTION**

**APPENDIX D: BLOCK DIAGRAM**

**APPENDIX E: SCHEMATICS**

**APPENDIX F: ANTENNA DETAILS**

**APPENDIX G: SPECIFICATIONS**

**APPENDIX H: FCC LABELLING DETAILS**

**APPENDIX I: USER MANUAL**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook P Series**

**Attachment 3: FCC Part 15B Test Report (Report: FG07-172EAL)**

**Attachment 4: EMCT 15.247 Test Report (Report: M060756\_Cert\_EYTF3CSFT\_WLAN)**



---

This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.