

**Attachment 1**

**RF EXPOSURE INFORMATION**

**RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION**

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

Testing was performed in accordance with the requirements of FCC Part 15.247(i)  
Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Testing was performed in accordance with the requirements of FCC Part 15.407(f)  
Spread spectrum transmitters operating in the 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M080506\_Cert\_512AN\_HMW\_SAR\_2.4 (2.4 GHz) and M080506\_Cert\_512AN\_HMW\_SAR\_5.6 (5.18 – 5.825 GHz). SAR value of 0.108 mW/g is measured which complies with the FCC human exposure requirements of 47 CFR 2.1093 (d).