

Attachment 1 **RF EXPOSURE INFORMATION**

RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

Intel 533AN-HMW WLAN - SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M090733_Cert_533AN_HMW_SAR_2.4 (2.4 GHz) and M090733_Cert_533AN_HMW_SAR_5.6 (5.18 – 5.825 GHz). SAR values of 0.963 mW/g (DTS) and 1.54 mW/g (NII) were measured which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

CSR BSMAN3 Bluetooth - SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies report M090733_Cert_BSMAN3_SAR_BT. SAR value was low (noise floor measured) which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).