



Global Product Certification  
EMC-EMF Safety Approvals

**EMC Technologies Pty Ltd**  
ABN 82 057 105 549  
176 Harrick Road  
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000  
Fax: + 613 9331 7455  
email: melb@emctech.com.au

## EMI TEST REPORT FOR CERTIFICATION to FCC PART 15 Subpart E (Section 15.407) & RSS-210

FCC ID: EJE-WB0077  
Industry Canada ID: 337J-WB0077

Test Sample: LifeBook T Series  
Model: T4310

Radio Modules: 512AN\_HMW INTEL Shirley Peak 1x2 Half Mini-PCI  
WLAN Module & BSMAN3 Bluetooth Module

Report Number M090737\_Cert\_512AN\_HMW\_NII\_BT

Issue Date: 10<sup>th</sup> September 2009

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

**This document shall not be reproduced except in full.**

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

**EMC Technologies Report No. M090737\_Cert\_512AN\_HMW\_NII\_BT**

**Issue Date: 10<sup>th</sup> September 2009**

**CONTENTS**

**1.0 INTRODUCTION  
2.0 GENERAL INFORMATION**

**FCC 15.407 (U-NII) RESULTS**

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 RADIATED EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 PEAK POWER SPECTRAL DENSITY**
- 8.0 PEAK EXCURSION**
- 9.0 FREQUENCY STABILITY**
- 10.0 DYNAMIC FREQUENCY SELECTION**
- 11.0 DISCONTINUE TRANSMISSION**
- 12.0 RADIO FREQUENCY EXPOSURE**
- 13.0 ANTENNA REQUIREMENT**
- 14.0 COMPLIANCE STATEMENT**
- 15.0 MEASUREMENT UNCERTAINTIES**
- 16.0 TEST REPORT APPENDICES**

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**

**APPENDIX B: PHOTOGRAPHS**

**APPENDIX C: OPERATIONAL DESCRIPTION**

**APPENDIX D: BLOCK DIAGRAM**

**APPENDIX E: ANTENNA INFORMATION**

**APPENDIX F: SCHEMATIC**

**APPENDIX G: FCC LABELLING DETAILS**

**APPENDIX H: USER MANUAL**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook T Series**

**Attachment 3: Intel FCC Part 15.407 Test Report**

**Attachment 4: Intel FCC Part 15.407 DFS Test Report**



Accreditation No. 5292

This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart E (Section 15.407) & RSS-210**

**Report No. M090737\_Cert\_512AN\_HMW\_NII\_BT**

**Test Sample:** LifeBook T Series  
**Model:** T4310  
**Radio Modules:** Shirley Peak 1x2 Half Mini-PCI WLAN Module, Model: 512AN\_HMW (Intel Corp.)  
Bluetooth Module, Model: BSMAN3 (CSR)

**FCC ID:** EJE-WB0077  
**Industry Canada ID:** 337J-WB0077  
**Equipment Type:** Intentional Radiator (Transceiver)


**Manufacturer (LifeBook):** Fujitsu Ltd  
**Address:** 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan  
**Contact:** Mr. Tsuyoshi Uchihara, Mobile Computing Division

**Test Standards:** FCC Part 15 – Radio Frequency Devices (July 2008)  
FCC Part 15, Subpart E – Unlicensed National Information, Infrastructure Devices  
FCC Part 15.407, General Technical Requirements  
ANSI C63.4 – 2003

RSS-210 Issue 7 Low Power Licence-Exempt RadioCommunication Devices  
Annex 9: Local Area Network Devices

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

**Test Dates:** 16<sup>th</sup> to 27<sup>th</sup> August 2009

**Senior Engineer:**   
**Chieu Huynh - B.Eng (Hons) Electronics**  
**Lee Hopkins**

**Attestation:** *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*



**Authorised Signatory:**   
**Chieu Huynh**  
**Senior EMC Engineer**  
**EMC Technologies Pty Ltd**



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

Accreditation No. 5292

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart E (Section 15.407) & RSS-210**

## 1.0 INTRODUCTION

EMI testing was performed on the Fujitsu notebook PC, Model: T4310 with INTEL Mini-PCI Wireless LAN Module (Shirley Peak 802.11a/b/g/n 1x2), Model: 512AN\_HMW & CSR Bluetooth Module, Model: BSMAN3.

The Shirley Peak 1x2 WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The Bluetooth module was originally certified by CSR as a modular approval under FCC ID: PIWBSMAN (Canada ID: 5255A-BSMAN). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The intention of this application is to FCC certify Intel Mini-PCI Wireless LAN Module (11a+b/g/n), Model: 512AN\_HMW & CSR Bluetooth Module, Model: BSMAN3 installed in Fujitsu LifeBook T Series, Model: T4310

The 512AN\_HMW 1x2 WLAN supports IEEE 802.11b, IEEE 802.11g, IEEE 802.11a and IEEE 802.11n (DTS & U-NII) configurations.

NII results for configurations IEEE 802.11a and IEEE 802.11n are reported in this test report.

The DTS (WLAN) and DSS (Bluetooth) are submitted separately under DTS and DSS submissions.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart E:	Unlicensed National Information Infrastructure Devices (U-NII) operating in the 5.15-5.35 GHz, 5.47-5.725 GHz and 5.725-5.825 GHz frequency bands
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.407:	General Technical Requirements

The results and technical details of the test sample are detailed in this report. The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart E - Section 15.407.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 and the RF exposure requirements of RSS-102.

The measurement procedure used was in accordance with ANSI C63.4-2003. The instrumentation conformed to the requirements of ANSI C63.2-1996.



## 1.1 Summary of Results

### FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
<b>15.203</b>	5.5	Antenna Requirement	<b>Complies</b>
<b>15.205</b>	6.3	Operation in Restricted Band	<b>Complies</b>
<b>15.207</b>	6.6	Conducted Emissions	<b>Note 1</b>
<b>15.209</b>	6.3	Radiated Emissions	<b>Complies</b>
<b>15.407 (a)(1) (a)(2)</b>	Annex A9.2	Peak Transmit Power	<b>Note 2</b>
<b>15.407 (a)(5)</b>	Annex A9.2	Peak Power Spectral Density	<b>Note 2</b>
<b>15.407 (a)(6)</b>		Peak Excursion	<b>Note 2</b>
<b>15.407 (b)</b>	Annex A9.3	Undesirable Emission	<b>Complies</b>
<b>15.407 (c)</b>	Annex A9.5(4)	Discontinue Transmission	<b>Complies</b>
<b>15.407 (d)</b>		Reserved	-
<b>15.407 (e)</b>	2.2 (Table 1)	Restricted to Indoor Operations	<b>Complies</b>
<b>15.407 (f)</b>	RSS-Gen (5.5)	Radio Frequency Hazard	<b>Complies</b>
<b>15.407 (g)</b>	Annex A9.5(5)	Frequency Stability	<b>Note 2</b>
<b>15.407 (h)</b>		Transmit Power Control	<b>Not Applicable</b> E.I.R.P < 500 mW
<b>15.407 (h)</b>	Annex A9.4	Dynamic Frequency Selection	<b>Note 3</b>

**Note 1:** Refer to Attachment 2, FCC DOC for LifeBook T Series

**Note 2:** Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH)

**Note 3:** Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH)

## 1.2 Modifications by EMC Technologies

No modifications were required.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

Accreditation No. 5292

## 2.0 GENERAL INFORMATION

(Information supplied by the Client)

### 2.1 EUT (WLAN) Details

<b>Transmitter:</b>	Half Mini-Card Wireless LAN Module
<b>Wireless Module:</b>	Shirley Peak 1x2 (11a/b/g/n)
<b>Model Number:</b>	512AN_HMW
<b>Manufacturer:</b>	Intel Corporation
<b>Modulation Type:</b>	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a/g/n)
<b>2.4 GHz (802.11b/g/n):</b>	DBPSK, DQPSK, CCK, 16QAM and 64QAM
<b>5 GHz (802.11a/n):</b>	BPSK, QPSK, 16QAM and 64QAM
<b>Maximum Data Rate:</b>	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps 802.11n = 450 Mbps
<b>Frequency Ranges:</b>	2.412 –2.462 GHz for 11b/g/n 5.18 - 5.32 GHz, 5.5 – 5.7 GHz and 5.745 - 5.825 GHz for 11a/n
<b>Number of Channels:</b>	11 channels for 11b/g/n 24 channels for 11a/n with 20 MHz bandwidth 18 channels for 11n with 40 MHz bandwidth
<b>Antenna Types:</b>	Nissei Inverted F (1 <sup>st</sup> , 2 <sup>nd</sup> ) Locations: Left Top edge of LCD screen(1 <sup>st</sup> ) Right lower edge of LCD screen(2 <sup>nd</sup> )
<b>Antenna gain:</b>	Max antenna gain is less than 6 dBi.
<b>Power Supply:</b>	Refer antenna data provided separately 3.3 VDC from PCI bus



**Channels and Output Power Settings:**

Modes	Channels	Frequency MHz	Average Output Power (dBm)
802.11b	1	2412	16.5
	6	2437	18.2
	11	2462	16.5
802.11g	1	2412	13.9
	6	2437	17.8
	11	2462	15.4
802.11a	36	5180	14.7
	40	5200	17.5
	48	5240	17.4
	52	5260	17.0
	56	5280	17.3
	64	5320	14.6
	100	5500	17.5
	120	5600	17.8
	140	5700	17.2
	149	5745	17.5
	157	5785	17.8
	165	5825	17.3
	1	2412	14.0
	6	2437	16.5
	11	2462	14.3
802.11n 20MHz Bandwidth	36	5180	14.5
	40	5200	17.5
	48	5240	17.4
	52	5260	16.5
	56	5280	17.5
	64	5320	14.5
	100	5500	17.5
	120	5600	16.5
	140	5700	16.5
	149, 157 and 165	5745, 5785 and 5825	16.5
	1	2412	14.0
	6	2437	16.5
	11	2462	14.3
802.11n 40MHz Bandwidth	36	5180	14.5
	40	5200	17.5
	48	5240	17.4
	52	5260	16.5
	56	5280	17.5
	64	5320	14.5
	100	5500	17.5
	120	5600	16.5
	140	5700	16.5
	149, 157 and 165	5745, 5785 and 5825	16.5
	1	2412	14.0
	6	2437	16.5



## 2.2 EUT (Notebook PC) Details

<b>Host:</b>	LifeBook T series
<b>Model Name:</b>	T4310
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Core2 Duo T9600 2.8GHz
<b>LCD:</b>	12.1"WXGA
<b>Wired LAN:</b>	Broadcom BCM57780 : 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	None
<b>Port Replicator Model:</b>	FPCPR94
<b>AC Adapter Model:</b>	80W: SEE100P2-19.0 (Sanken), ADP-80NB A(Delta)
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	4.22A
<b>Watts:</b>	80W

## 2.3 Test Configuration

The Intel WLAN test software "CRTU" was used to transmit continuously during the tests.

Conducted tests were performed at the WLAN Antenna ports.

Radiated harmonics and spurious emissions were performed while the transmitter transmits continuously.

## 2.4 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT.

## 2.5 Test Facility

### 2.5.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (DoC) and Certification under Parts 15 & 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional) - **Industry Canada OATS number - IC 3569B-1**.

Radiated Emission measurements were performed at EMC Technologies Open Area Test Site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia.

Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.



## 2.5.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)  
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).

## 2.6 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by EMC Technologies. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

## 2.7 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



---

This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

## FCC 15.407 (U-NII) RESULTS

### 3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

### 4.0 RADIATED EMISSION MEASUREMENTS

#### 4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.407(b).

Radiated emission measurements were performed to the limits as per section 15.209 and 15.407. The measurements were made at the open area test site. All measurements above 1 GHz were made over a distance of 3 and 1 metres.

Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

#### 4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

**E** = Radiated Field Strength in dB $\mu$ V/m.

**V** = EMI Receiver Voltage in dB $\mu$ V. (measured value)

**AF** = Antenna Factor in dB(m<sup>-1</sup>). (stored as a data array)

**G** = Preamplifier Gain in dB. (stored as a data array)

**L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB $\mu$ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$



#### 4.3 Results - Out of Band Emissions (Spurious and Harmonics)

This transmitter module was originally tested and certified by the manufacturer as a stand-alone module outside a laptop (host) with higher gain antennas. Refer to manufacturer's original test report (Attachment 3) for full results showing compliance with the spurious and harmonics limits. However, to ensure the transmitter module install in T4310 LifeBook is still in compliance, verification tests were performed at the worst case (frequencies with higher average output power) or selected frequencies for harmonics and spurious emissions.

##### 4.3.1 Frequency Band: 1 – 40 GHz

The peak limits for undesirable emission outside of the restricted bands are –27 dBm (68.3 dB $\mu$ V/m @ 3m). The 74 dB $\mu$ V/m @ 3m and 54 dB $\mu$ V/m @ 3m limits are applied for emissions fall in the restricted bands.

Testing was performed while the WLAN transmitter continuously operated. Harmonics related to the WLAN transmitter operated in the frequency bands 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are reported below. Harmonics in the frequency bands 2.4 – 2.4835 GHz and 5.725 – 5.850 GHz, refer to M090737\_Cert\_512AN\_HMW\_DTS\_BT.

##### Configuration 802.11a and 802.11n

Initial investigations were performed with all data rates: (6 Mbps to 54 Mbps and MCS0 to MCS7). Final testing was performed while the transmitter continuously operated in the worst case condition.

Harmonics were measured for channels where the RF output power was highest.

##### 802.11a - Channel 52 - 5260 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB $\mu$ V/m	Average Detector dB $\mu$ V/m	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
802.11a	6 Mbps	5260	106.7	96.3	Transmitter Fundamental Level		
		10520	64.7	51.0	68.3	-	Complied

##### 802.11a - Channel 120 - 5600 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB $\mu$ V/m	Average Detector dB $\mu$ V/m	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
802.11a	6 Mbps	5600	107.0	96.8	Transmitter Fundamental Level		
		11200	68.6	54.0	74.0	54.0	Complied

##### 802.11n - Tx BW = 20 MHz, Channel 48 - 5240 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB $\mu$ V/m	Average Detector dB $\mu$ V/m	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
802.11n	MCS0	5240	107.9	97.1	Transmitter Fundamental Level		
		10480	65.6	50.8	68.3	-	Complied

##### 802.11n - Tx BW = 20 MHz, Channel 100 - 5500 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB $\mu$ V/m	Average Detector dB $\mu$ V/m	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
802.11n	MCS0	5500	107.6	96.8	Transmitter Fundamental Level		
		11000	65.5	50.8	74.0	54.0	Complied



**802.11n - Tx BW = 40 MHz, Channel 118 - 5590 MHz**

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
802.11n	MCS0	5590	104.4	93.2	Transmitter Fundamental Level		
		11180	64.6	51.4	74.0	54.0	Complied

**Result:** Harmonics and spurious emissions were recorded up to 40 GHz. Harmonics were low and confirmed with both RBW and VBW reduced. Emissions complied with the FCC limits of sections 15.209 and 15.407 by a margin of 0 dB.

**4.3.2 Frequency Band: 30 - 1000 MHz**

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

**4.3.3 RF Conducted Measurements at the antenna terminal (including Band Edge)**

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

Accreditation No. 5292

## 5.0 PEAK OUTPUT POWER - Section 15.407(a)

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)

## 6.0 CHANNEL BANDWIDTH

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)

## 7.0 PEAK POWER SPECTRAL DENSITY

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)

## 8.0 PEAK EXCURSION

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)

## 9.0 FREQUENCY STABILITY

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

Accreditation No. 5292

## 10.0 DYNAMIC FREQUENCY SELECTION

The EUT is a Client Device without Radar Interference Detection Function.

Ad-hoc operation (not under control of a Master Device) is supported in the 2.4 GHz & 5.15 - 5.25 GHz bands only. This Ad-hoc capability is limited in hardware via factory programmed EEPROM settings that cannot be accessed or changed by end users. The Ad-hoc supported channels of operation cannot be modified – regardless of which client utility or operating system control is used.

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Testing was performed by Elliott Laboratories Inc CA, USA accredited by A2LA (Certificate Number: 2016-01)

## 11.0 DISCONTINUE TRANSMISSION

Data Transmission is always initiated by software, which is then passed down through the MAC, through the digital and analog baseband, finally to the RF chip. Several special packets (ACKs, CTS, PSPoll, etc) are initiated by the MAC. These are the only ways the digital baseband portion will turn on the RF transmitter, which then turns off at the end of the packet. Therefore, the transmitter will be ON only while one of the four mentioned packets is being transmitted.

## 12.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M090734\_Cert\_512AN\_HMW\_SAR\_2.4 (2.4 GHz) and M090734\_Cert\_512AN\_HMW\_SAR\_5.6 (5.18 – 5.825 GHz). SAR values of 1.06 mW/g (DTS) and 1.49 mW/g (NII) were measured which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

## 13.0 ANTENNA REQUIREMENT

This intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.  
[www.emctech.com.au](http://www.emctech.com.au)

Accreditation No. 5292

## 14.0 COMPLIANCE STATEMENT

The Fujitsu notebook PC, Model: T4310 with INTEL Mini-PCI Wireless LAN Module (Shirley Peak 802.11a/b/g/n 1x2), Model: 512AN\_HMW & CSR Bluetooth Module, Model: BSMAN3, **complied** with the requirements of 47 CFR, Part 15 Subpart E -Section 15.407 (5.15-5.35 GHz and 5.47 – 5.725 GHz bands).

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 Local Area Network Devices requirements and the RF exposure requirements of RSS-102.

**Results were as follows:**

### FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
<b>15.203</b>	5.5	Antenna Requirement	<b>Complies</b>
<b>15.205</b>	6.3	Operation in Restricted Band	<b>Complies</b>
<b>15.207</b>	6.6	Conducted Emissions	<b>Note 1</b>
<b>15.209</b>	6.3	Radiated Emissions	<b>Complies</b>
<b>15.407 (a)(1) (a)(2)</b>	Annex A9.2	Peak Transmit Power	<b>Note 2</b>
<b>15.407 (a)(5)</b>	Annex A9.2	Peak Power Spectral Density	<b>Note 2</b>
<b>15.407 (a)(6)</b>		Peak Excursion	<b>Note 2</b>
<b>15.407 (b)</b>	Annex A9.3	Undesirable Emission	<b>Complies</b>
<b>15.407 (c)</b>	Annex A9.5(4)	Discontinue Transmission	<b>Complies</b>
<b>15.407 (d)</b>		Reserved	-
<b>15.407 (e)</b>	2.2 (Table 1)	Restricted to Indoor Operations	<b>Complies</b>
<b>15.407 (f)</b>	RSS-Gen (5.5)	Radio Frequency Hazard	<b>Complies</b>
<b>15.407 (g)</b>	Annex A9.5(5)	Frequency Stability	<b>Note 2</b>
<b>15.407 (h)</b>		Transmit Power Control	<b>Not Applicable</b> E.I.R.P < 500 mW
<b>15.407 (h)</b>	Annex A9.4	Dynamic Frequency Selection	<b>Note 3</b>

**Note 1:** Refer to Attachment 2, FCC DOC for LifeBook T Series

**Note 2:** Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH)

**Note 3:** Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH)



## 15.0 MEASUREMENT UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

<b>Conducted Emissions:</b>	9 kHz to 30 MHz	±3.2 dB
<b>Radiated Emissions:</b>	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB
	1 GHz to 18 GHz	±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

## 16.0 TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**

**APPENDIX B: PHOTOGRAPHS**

**APPENDIX C: OPERATIONAL DESCRIPTION**

**APPENDIX D: BLOCK DIAGRAM**

**APPENDIX E: ANTENNA INFORMATION**

**APPENDIX F: SCHEMATIC**

**APPENDIX G: FCC LABELLING DETAILS**

**APPENDIX H: USER MANUAL**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook T Series**

**Attachment 3: Intel FCC Part 15.407 Test Report**

**Attachment 4: Intel FCC Part 15.407 DFS Test Report**



Accreditation No. 5292

---

This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.

[www.emctech.com.au](http://www.emctech.com.au)