

## **Attachment 1 RF EXPOSURE INFORMATION**

### **RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION**

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

**Intel 622ANHMW WLAN** - SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M091069\_Cert\_622ANHMW\_SAR\_2.4\_BT (2.4 GHz) and M091069\_Cert\_622ANHMW\_SAR\_5.6\_BT (5.18 – 5.825 GHz). SAR values of 0.182 mW/g (DTS) and 0.068 mW/g (NII) were measured which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

**Taiyo Yuden EYSMJCS Bluetooth (FCC ID: RYYEYSMJCS)** - SAR measurements were not required because the Bluetooth transmit power is very low and Bluetooth antenna is located at more than 5cm away from the other transmitting antennas.