

APPENDIX B PLOTS OF THE SAR MEASUREMENTS

Plots of the measured SAR distributions inside the phantom are given in this Appendix for all tested configurations.



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5200 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5199.7$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 49.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;
 Sensor-Surface: 2 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 40 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.674 W/kg

Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 40 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 3.828 V/m; **Power Drift = 0.03 dB**

Averaged SAR: SAR(1g) = 0.197 W/kg; SAR(10g) = 0.054 W/kg

Maximum value of SAR (interpolated) = 0.702 W/kg




SAR Measurement Plot 1



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5240 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5239.3$ MHz; $\sigma = 5.45$ S/m; $\epsilon_r = 49.1$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 48 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.659 W/kg

Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 48 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.917 V/m; **Power Drift = 0.04 dB**


Averaged SAR: SAR(1g) = 0.271 W/kg; SAR(10g) = 0.075 W/kg

Maximum value of SAR (interpolated) = 0.942 W/kg



0 dB = 0.659 W/kg = -1.81 dBW/kg

SAR Measurement Plot 2



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5260 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5260.75$ MHz; $\sigma = 5.50$ S/m; $\epsilon_r = 49.1$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 52 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.628 W/kg**Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 52 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 6.085 V/m; **Power Drift = 0.05 dB****Averaged SAR: SAR(1g) = 0.287 W/kg; SAR(10g) = 0.080 W/kg**

Maximum value of SAR (interpolated) = 1.010 W/kg



0 dB = 0.628 W/kg = -2.02 dBW/kg

SAR Measurement Plot 3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5300 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5300.35$ MHz; $\sigma = 5.58$ S/m; $\epsilon_r = 48.9$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 60 Test/Area Scan (91x121x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.516 W/kg**Edge 2 OFDM 5200 MHz Antenna A (1) 24-10-14/Channel 60 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 4.267 V/m; **Power Drift = -0.21 dB****Averaged SAR: SAR(1g) = 0.188 W/kg; SAR(10g) = 0.051 W/kg**

Maximum value of SAR (interpolated) = 0.699 W/kg



0 dB = 0.516 W/kg = -2.87 dBW/kg

SAR Measurement Plot 4



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5200 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5199.7$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 49.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 40 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.477 W/kg

Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 40 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.537 V/m; **Power Drift = -0.04 dB**


Averaged SAR: SAR(1g) = 0.248 W/kg; SAR(10g) = 0.077 W/kg

Maximum value of SAR (interpolated) = 1.400 W/kg



0 dB = 0.477 W/kg = -3.21 dBW/kg

SAR Measurement Plot 5



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5240 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5239.3$ MHz; $\sigma = 5.45$ S/m; $\epsilon_r = 49.1$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;
 Sensor-Surface: 2 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 48 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.409 W/kg

Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 48 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.092 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 0.209 W/kg; SAR(10g) = 0.065 W/kg

Maximum value of SAR (interpolated) = 0.792 W/kg




0 dB = 0.409 W/kg = -3.88 dBW/kg

SAR Measurement Plot 6



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5260 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5260.75$ MHz; $\sigma = 5.50$ S/m; $\epsilon_r = 49.1$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 52 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.376 W/kg**Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 52 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.917 V/m; **Power Drift = -0.08 dB****Averaged SAR: SAR(1g) = 0.195 W/kg; SAR(10g) = 0.060 W/kg**

Maximum value of SAR (interpolated) = 0.739 W/kg



0 dB = 0.376 W/kg = -4.25 dBW/kg

SAR Measurement Plot 7



Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5300 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5300.35$ MHz; $\sigma = 5.58$ S/m; $\epsilon_r = 48.9$; $\rho = 1000.0$ g/cm³

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 60 Test/Area Scan (91x121x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.479 W/kg**Edge 2 OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 60 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 5.624 V/m; **Power Drift = 0.02 dB****Averaged SAR: SAR(1g) = 0.229 W/kg; SAR(10g) = 0.068 W/kg**

Maximum value of SAR (interpolated) = 1.570 W/kg



0 dB = 0.479 W/kg = -3.20 dBW/kg

SAR Measurement Plot 8



Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:8

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Lap Held OFDM 5200 MHz Antenna B (2) 24-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.2 GHz Band; Frequency: 5260 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5260.75$ MHz; $\sigma = 5.50$ S/m; $\epsilon_r = 49.1$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 52 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.197 W/kg**Lap Held OFDM 5200 MHz Antenna B (2) 24-10-14/Channel 52 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 2.291 V/m; **Power Drift = -0.19 dB****Averaged SAR: SAR(1g) = 0.043 W/kg; SAR(10g) = 0.012 W/kg**

Maximum value of SAR (interpolated) = 0.493 W/kg




0 dB = 0.197 W/kg = -7.06 dBW/kg

SAR Measurement Plot 9



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5200 MHz WLAN 11a.da52:9

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008**Configuration: System Performance Check with D5GHzV2 Dipole (uniform grid) 24-10-14**

Communication System: 0 - CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5200 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5199.7$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 49.2$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.75,3.75,3.75); Calibrated: 17/12/2013;

Sensor-Surface: 1.4 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (uniform grid) 24-10-14/d=10mm, Pin=100mW, f=5200 MHz/Area Scan (91x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 20.000 W/kg**System Performance Check with D5GHzV2 Dipole (uniform grid) 24-10-14/d=10mm, Pin=100mW, f=5200 MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0:** Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 68.388 V/m; **Power Drift = -0.11 dB****Averaged SAR: SAR(1g) = 7.970 W/kg; SAR(10g) = 2.240 W/kg**

Maximum value of SAR (interpolated) = 30.500 W/kg




SAR Measurement Plot 10



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5520 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5519.8$ MHz; $\sigma = 5.77$ S/m; $\epsilon_r = 48.0$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;
 Sensor-Surface: 2 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 104 Test/Area Scan (91x121x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.676 W/kg

Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 104 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 5.928 V/m; **Power Drift = -0.05 dB**

Averaged SAR: SAR(1g) = 0.303 W/kg; SAR(10g) = 0.085 W/kg

Maximum value of SAR (interpolated) = 1.060 W/kg




SAR Measurement Plot 11



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5580 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5579.2$ MHz; $\sigma = 5.87$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 116 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.808 W/kg

Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 116 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.863 V/m; **Power Drift = 0.16 dB**

Averaged SAR: SAR(1g) = 0.331 W/kg; SAR(10g) = 0.095 W/kg

Maximum value of SAR (interpolated) = 1.280 W/kg




0 dB = 0.808 W/kg = -0.93 dBW/kg

SAR Measurement Plot 12



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5680 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5679.85$ MHz; $\sigma = 6.05$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 136 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.732 W/kg**Edge 2 OFDM 5600 MHz Antenna A (1) 22-10-14/Channel 136 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.786 V/m; **Power Drift = 0.10 dB****Averaged SAR: SAR(1g) = 0.304 W/kg; SAR(10g) = 0.085 W/kg**

Maximum value of SAR (interpolated) = 1.120 W/kg



0 dB = 0.732 W/kg = -1.35 dBW/kg

SAR Measurement Plot 13



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5520 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5519.8$ MHz; $\sigma = 5.77$ S/m; $\epsilon_r = 48.0$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;
 Sensor-Surface: 2 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 104 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.748 W/kg

Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 104 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 7.440 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 0.373 W/kg; SAR(10g) = 0.113 W/kg

Maximum value of SAR (interpolated) = 1.430 W/kg




0 dB = 0.748 W/kg = -1.26 dBW/kg

SAR Measurement Plot 14



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5580 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5579.2$ MHz; $\sigma = 5.87$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 116 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.515 W/kg

Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 116 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.989 V/m; **Power Drift = -0.14 dB**


Averaged SAR: SAR(1g) = 0.251 W/kg; SAR(10g) = 0.074 W/kg

Maximum value of SAR (interpolated) = 1.540 W/kg



0 dB = 0.515 W/kg = -2.88 dBW/kg

SAR Measurement Plot 15



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5680 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5679.85$ MHz; $\sigma = 6.05$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 136 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.784 W/kg**Edge 2 OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 136 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 7.525 V/m; **Power Drift = -0.15 dB****Averaged SAR: SAR(1g) = 0.398 W/kg; SAR(10g) = 0.131 W/kg**

Maximum value of SAR (interpolated) = 1.590 W/kg



0 dB = 0.784 W/kg = -1.06 dBW/kg

SAR Measurement Plot 16



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:8

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Lap Held OFDM 5600 MHz Antenna B (2) 22-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.5 GHz Band; Frequency: 5580 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5579.2$ MHz; $\sigma = 5.87$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 116 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.199 W/kg

Lap Held OFDM 5600 MHz Antenna B (2) 22-10-14/Channel 116 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 2.847 V/m; **Power Drift = -0.15 dB**


Averaged SAR: SAR(1g) = 0.062 W/kg; SAR(10g) = 0.019 W/kg

Maximum value of SAR (interpolated) = 0.289 W/kg



0 dB = 0.199 W/kg = -7.01 dBW/kg

SAR Measurement Plot 17



Test Lab: EMCTech

Test File: M141024 Tablet 5600 MHz WLAN 11a.da52:9

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008**Configuration: System Performance Check with D5GHzV2 Dipole (uniform grid) 22-10-14**

Communication System: 0 - CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5500 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5500$ MHz; $\sigma = 5.74$ S/m; $\epsilon_r = 48.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.06,3.06,3.06); Calibrated: 17/12/2013;

Sensor-Surface: 1.4 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI v4.0 (30deg probe tilt); Type: QDOVA001BB; Serial: TP:1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (uniform grid) 22-10-14/d=10mm, Pin=100mW, f=5500**MHz/Area Scan (91x91x1):** Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 21.700 W/kg**System Performance Check with D5GHzV2 Dipole (uniform grid) 22-10-14/d=10mm, Pin=100mW, f=5500****MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0:** Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 69.928 V/m; **Power Drift = 0.08 dB****Averaged SAR: SAR(1g) = 8.890 W/kg; SAR(10g) = 2.480 W/kg**

Maximum value of SAR (interpolated) = 34.000 W/kg




SAR Measurement Plot 18



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5745 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5744.2$ MHz; $\sigma = 5.88$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 149 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.686 W/kg

Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 149 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.907 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 0.318 W/kg; SAR(10g) = 0.090 W/kg

Maximum value of SAR (interpolated) = 1.160 W/kg




0 dB = 0.686 W/kg = -1.64 dBW/kg

SAR Measurement Plot 19



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5785 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5785.45$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 157 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.523 W/kg**Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 157 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.145 V/m; **Power Drift = -0.08 dB****Averaged SAR: SAR(1g) = 0.226 W/kg; SAR(10g) = 0.064 W/kg**

Maximum value of SAR (interpolated) = 0.853 W/kg



0 dB = 0.523 W/kg = -2.81 dBW/kg

SAR Measurement Plot 20



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5825 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5825.05$ MHz; $\sigma = 6.00$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 165 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.623 W/kg**Edge 2 OFDM 5800 MHz Antenna A (1) 21-10-14/Channel 165 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.808 V/m; **Power Drift = -0.02 dB****Averaged SAR: SAR(1g) = 0.278 W/kg; SAR(10g) = 0.081 W/kg**

Maximum value of SAR (interpolated) = 1.100 W/kg




0 dB = 0.623 W/kg = -2.06 dBW/kg

SAR Measurement Plot 21



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5745 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5744.2$ MHz; $\sigma = 5.88$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;
Sensor-Surface: 2 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 149 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.426 W/kg

Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 149 Test/Zoom Scan (31x31x61)/Cube 0:

Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.983 V/m; **Power Drift = 0.14 dB**


Averaged SAR: SAR(1g) = 0.201 W/kg; SAR(10g) = 0.067 W/kg

Maximum value of SAR (interpolated) = 0.820 W/kg



0 dB = 0.426 W/kg = -3.71 dBW/kg

SAR Measurement Plot 22



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5785 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5785.45$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 157 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.374 W/kg**Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 157 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 4.914 V/m; **Power Drift = -0.21 dB****Averaged SAR: SAR(1g) = 0.139 W/kg; SAR(10g) = 0.042 W/kg**

Maximum value of SAR (interpolated) = 0.554 W/kg



0 dB = 0.374 W/kg = -4.27 dBW/kg

SAR Measurement Plot 23



Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:5

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5825 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5825.05$ MHz; $\sigma = 6.00$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 165 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.495 W/kg**Edge 2 OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 165 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 5.229 V/m; **Power Drift = -0.06 dB****Averaged SAR: SAR(1g) = 0.238 W/kg; SAR(10g) = 0.078 W/kg**

Maximum value of SAR (interpolated) = 0.964 W/kg



0 dB = 0.495 W/kg = -3.05 dBW/kg

SAR Measurement Plot 24



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:8

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Lap Held OFDM 5800 MHz Antenna B (2) 21-10-14**

Communication System: 0 - OFDM 5 GHz 6 Mbs (0); Communication System Band: 5.8 GHz Band; Frequency: 5785 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5785.45$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 2 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 157 Test/Area Scan (91x121x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.216 W/kg**Lap Held OFDM 5800 MHz Antenna B (2) 21-10-14/Channel 157 Test/Zoom Scan (31x31x61)/Cube 0:**Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 1.901 V/m; **Power Drift = 0.09 dB****Averaged SAR: SAR(1g) = 0.040 W/kg; SAR(10g) = 0.013 W/kg**

Maximum value of SAR (interpolated) = 0.408 W/kg




SAR Measurement Plot 25



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

Test Lab: EMCTech

Test File: M141024 Tablet 5800 MHz WLAN 11a.da52:9

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008**Configuration: System Performance Check with D5GHzV2 Dipole (uniform grid) 21-10-14**

Communication System: 0 - CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5800 MHz; Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=5800.3$ MHz; $\sigma = 5.98$ S/m; $\epsilon_r = 47.0$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN3657; ConvF: (3.31,3.31,3.31); Calibrated: 17/12/2013;

Sensor-Surface: 1.4 mm (Mechanical Surface Detection)


Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI v4.0 (30deg probe tilt); Type: QDOVA001BB; Serial: TP:1101

DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole (uniform grid) 21-10-14/d=10mm, Pin=100mW, f=5800 MHz/Area Scan (91x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 19.800 W/kg**System Performance Check with D5GHzV2 Dipole (uniform grid) 21-10-14/d=10mm, Pin=100mW, f=5800 MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0:** Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 62.605 V/m; **Power Drift = 0.09 dB****Averaged SAR: SAR(1g) = 8.350 W/kg; SAR(10g) = 2.320 W/kg**

Maximum value of SAR (interpolated) = 31.900 W/kg



SAR Measurement Plot 26



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

