

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:4

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 2 04-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5530 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5530.93$ MHz; $\sigma = 5.83$ S/m; $\epsilon_r = 47.7$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 2 04-11-16/Channel 106 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.430 W/kg

Edge 1 OFDM Antenna 2 04-11-16/Channel 106 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 11.582 V/m; **Power Drift = 0.04 dB**

Averaged SAR: SAR(1g) = 0.334 W/kg; SAR(10g) = 0.098 W/kg

Maximum value of SAR (interpolated) = 1.290 W/kg




0 dB = 0.430 W/kg = -3.67 dBW/kg

SAR Measurement Plot 31



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:4

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 2 04-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5610 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5609.93$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 2 04-11-16/Channel 122 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.514 W/kg

Edge 1 OFDM Antenna 2 04-11-16/Channel 122 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 11.145 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 0.426 W/kg; SAR(10g) = 0.127 W/kg

Maximum value of SAR (interpolated) = 1.690 W/kg




0 dB = 0.514 W/kg = -2.89 dBW/kg

SAR Measurement Plot 32



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:4

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 2 04-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5690 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5690.9$ MHz; $\sigma = 6.07$ S/m; $\epsilon_r = 47.3$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 2 04-11-16/Channel 138 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.422 W/kg

Edge 1 OFDM Antenna 2 04-11-16/Channel 138 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 9.521 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 0.391 W/kg; SAR(10g) = 0.119 W/kg

Maximum value of SAR (interpolated) = 1.660 W/kg




SAR Measurement Plot 33



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5510 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5509.2$ MHz; $\sigma = 5.82$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 102 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 1.260 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 102 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 24.940 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 1.020 W/kg; SAR(10g) = 0.259 W/kg

Maximum value of SAR (interpolated) = 4.380 W/kg




0 dB = 1.26 W/kg = 1.00 dBW/kg

SAR Measurement Plot 34



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
Frequency: 5510 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5509.2$ MHz; $\sigma = 5.82$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 102 Variability/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.370 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 102 Variability/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 26.106 V/m; **Power Drift = -0.04 dB**

Averaged SAR: SAR(1g) = 1.140 W/kg; SAR(10g) = 0.282 W/kg

Maximum value of SAR (interpolated) = 4.960 W/kg




0 dB = 1.37 W/kg = 1.37 dBW/kg

SAR Measurement Plot 35



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5550 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5550.68$ MHz; $\sigma = 5.89$ S/m; $\epsilon_r = 47.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 110 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.380 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 110 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 25.712 V/m; **Power Drift = -0.07 dB**

Averaged SAR: SAR(1g) = 1.110 W/kg; SAR(10g) = 0.273 W/kg

Maximum value of SAR (interpolated) = 4.940 W/kg




0 dB = 1.38 W/kg = 1.40 dBW/kg

SAR Measurement Plot 36



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5550 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5550.68$ MHz; $\sigma = 5.89$ S/m; $\epsilon_r = 47.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 110 Variability/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.170 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 110 Variability/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 24.089 V/m; **Power Drift = -0.16 dB**

Averaged SAR: SAR(1g) = 0.973 W/kg; SAR(10g) = 0.250 W/kg

Maximum value of SAR (interpolated) = 4.250 W/kg




0 dB = 1.17 W/kg = 0.68 dBW/kg

SAR Measurement Plot 37



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
Frequency: 5610 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5609.93$ MHz; $\sigma = 6.01$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 122 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.340 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 122 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 25.796 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 1.150 W/kg; SAR(10g) = 0.290 W/kg

Maximum value of SAR (interpolated) = 5.100 W/kg




0 dB = 1.34 W/kg = 1.27 dBW/kg

SAR Measurement Plot 38



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5610 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5609.93$ MHz; $\sigma = 6.01$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 122 Variability/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.370 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 122 Variability/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 25.799 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 1.150 W/kg; SAR(10g) = 0.291 W/kg

Maximum value of SAR (interpolated) = 4.940 W/kg




0 dB = 1.37 W/kg = 1.37 dBW/kg

SAR Measurement Plot 39



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
Frequency: 5690 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5690.9$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 138 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 1.240 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 138 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 25.175 V/m; **Power Drift = -0.13 dB**

Averaged SAR: SAR(1g) = 1.090 W/kg; SAR(10g) = 0.288 W/kg

Maximum value of SAR (interpolated) = 4.810 W/kg




0 dB = 1.24 W/kg = 0.93 dBW/kg

SAR Measurement Plot 40



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5690 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5690.9$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 07-11-16/Channel 138 Variability/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.260 W/kg

Edge 1 OFDM Antenna 1 07-11-16/Channel 138 Variability/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 25.192 V/m; **Power Drift = -0.16 dB**

Averaged SAR: SAR(1g) = 1.100 W/kg; SAR(10g) = 0.287 W/kg

Maximum value of SAR (interpolated) = 4.740 W/kg




0 dB = 1.26 W/kg = 1.00 dBW/kg

SAR Measurement Plot 41



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:6

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 2 OFDM Antenna 2 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5530 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5530.93$ MHz; $\sigma = 5.85$ S/m; $\epsilon_r = 47.7$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 OFDM Antenna 2 07-11-16/Channel 106 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.175 W/kg

Edge 2 OFDM Antenna 2 07-11-16/Channel 106 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 6.046 V/m; **Power Drift = -0.15 dB**

Averaged SAR: SAR(1g) = 0.063 W/kg; SAR(10g) = 0.022 W/kg

Maximum value of SAR (interpolated) = 0.497 W/kg




0 dB = 0.175 W/kg = -7.57 dBW/kg

SAR Measurement Plot 42



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:6

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 2 OFDM Antenna 2 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5610 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5609.93$ MHz; $\sigma = 6.01$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 OFDM Antenna 2 07-11-16/Channel 122 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.339 W/kg

Edge 2 OFDM Antenna 2 07-11-16/Channel 122 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 6.006 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 0.188 W/kg; SAR(10g) = 0.043 W/kg

Maximum value of SAR (interpolated) = 1.150 W/kg




0 dB = 0.339 W/kg = -4.70 dBW/kg

SAR Measurement Plot 43



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:6

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 2 OFDM Antenna 2 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5690 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5690.9$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0\text{g}/\text{cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 OFDM Antenna 2 07-11-16/Channel 138 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.121 W/kg

Edge 2 OFDM Antenna 2 07-11-16/Channel 138 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 8.886 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 0.134 W/kg; SAR(10g) = 0.032 W/kg

Maximum value of SAR (interpolated) = 0.720 W/kg




0 dB = 0.121 W/kg = -9.17 dBW/kg

SAR Measurement Plot 44



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:7

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 4 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
Frequency: 5510 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5509.2$ MHz; $\sigma = 5.82$ S/m; $\epsilon_r = 47.8$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 4 OFDM Antenna 1 07-11-16/Channel 102 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.309 W/kg

Edge 4 OFDM Antenna 1 07-11-16/Channel 102 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 15.995 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 0.333 W/kg; SAR(10g) = 0.077 W/kg

Maximum value of SAR (interpolated) = 1.890 W/kg




SAR Measurement Plot 45



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:7

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 4 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (40 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5550 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5550.68$ MHz; $\sigma = 5.89$ S/m; $\epsilon_r = 47.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 4 OFDM Antenna 1 07-11-16/Channel 110 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.361 W/kg

Edge 4 OFDM Antenna 1 07-11-16/Channel 110 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 17.842 V/m; **Power Drift = -0.03 dB**

Averaged SAR: SAR(1g) = 0.422 W/kg; SAR(10g) = 0.104 W/kg

Maximum value of SAR (interpolated) = 2.570 W/kg




0 dB = 0.361 W/kg = -4.42 dBW/kg

SAR Measurement Plot 46



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:7

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 4 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
 Frequency: 5610 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5609.93$ MHz; $\sigma = 6.01$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 4 OFDM Antenna 1 07-11-16/Channel 122 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.298 W/kg

Edge 4 OFDM Antenna 1 07-11-16/Channel 122 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 16.253 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 0.365 W/kg; SAR(10g) = 0.088 W/kg

Maximum value of SAR (interpolated) = 2.190 W/kg




SAR Measurement Plot 47



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:7

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 4 OFDM Antenna 1 07-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.6 GHz Band;
Frequency: 5690 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5690.9$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 47.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 4 OFDM Antenna 1 07-11-16/Channel 138 Test/Area Scan (61x91x1): Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm; Maximum value of SAR (interpolated) = 0.311 W/kg

Edge 4 OFDM Antenna 1 07-11-16/Channel 138 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: $dx=0.8$ mm, $dy=0.8$ mm, $dz=0.4$ mm; Reference Value = 16.505 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 0.370 W/kg; SAR(10g) = 0.087 W/kg

Maximum value of SAR (interpolated) = 2.340 W/kg




SAR Measurement Plot 48



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:8

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008


Configuration: System Performance Check with D5GHzV2 Dipole 04-11-16

Communication System: 0 - System Check (0); Communication System Band: 5600 MHz; Frequency: 5600 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: f=5600.05 MHz; $\sigma = 5.93$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 1.4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole 04-11-16/d=10mm, Pin=100mW, f=5600 MHz/Area Scan (91x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 22.000 W/kg
System Performance Check with D5GHzV2 Dipole 04-11-16/d=10mm, Pin=100mW, f=5600 MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 67.534 V/m; **Power Drift = -0.04 dB**
Averaged SAR: SAR(1g) = 8.510 W/kg; SAR(10g) = 2.360 W/kg
 Maximum value of SAR (interpolated) = 34.900 W/kg




0 dB = 22.0 W/kg = 13.42 dBW/kg

SAR Measurement Plot 49



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5600 MHz WLAN FCC.da52:9

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008


Configuration: System Performance Check with D5GHzV2 Dipole 07-11-16

Communication System: 0 - System Check (0); Communication System Band: 5600 MHz; Frequency: 5600 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: f=5600.05 MHz; $\sigma = 5.99$ S/m; $\epsilon_r = 47.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN7358; ConvF: (3.75,3.75,3.75); Calibrated: 11/12/2015;
 Sensor-Surface: 1.4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole 07-11-16/d=10mm, Pin=100mW, f=5600 MHz/Area Scan (91x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 22.800 W/kg
System Performance Check with D5GHzV2 Dipole 07-11-16/d=10mm, Pin=100mW, f=5600 MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 67.800 V/m; **Power Drift = 0.11 dB**
Averaged SAR: SAR(1g) = 8.660 W/kg; SAR(10g) = 2.390 W/kg
 Maximum value of SAR (interpolated) = 35.500 W/kg




0 dB = 22.8 W/kg = 13.58 dBW/kg

SAR Measurement Plot 50



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:0

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Bystander 25mm Spacing OFDM Antenna 2 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing OFDM Antenna 2 08-11-16/Channel 155 Test/Area Scan (61x121x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.054 W/kg

Bystander 25mm Spacing OFDM Antenna 2 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 3.587 V/m; Power Drift = -0.00 dB

Averaged SAR: SAR(1g) = 0.038 W/kg; SAR(10g) = 0.009 W/kg

Maximum value of SAR (interpolated) = 0.478 W/kg




SAR Measurement Plot 51



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:1

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Bystander 25mm Spacing OFDM Antenna 1 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing OFDM Antenna 1 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid:
dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.046 W/kg

Bystander 25mm Spacing OFDM Antenna 1 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0:
Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 3.404 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 0.018 W/kg; SAR(10g) = 0.006 W/kg

Maximum value of SAR (interpolated) = 0.289 W/kg




0 dB = 0.0455 W/kg = -13.42 dBW/kg

SAR Measurement Plot 52



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:2

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Lap Held OFDM Antenna 2 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held OFDM Antenna 2 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.051 W/kg

Lap Held OFDM Antenna 2 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 4.728 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 0.044 W/kg; SAR(10g) = 0.014 W/kg

Maximum value of SAR (interpolated) = 0.248 W/kg




0 dB = 0.0510 W/kg = -12.92 dBW/kg

SAR Measurement Plot 53



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:3

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Lap Held OFDM Antenna 1 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held OFDM Antenna 1 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.088 W/kg

Lap Held OFDM Antenna 1 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 5.264 V/m; **Power Drift = -0.09 dB**

Averaged SAR: SAR(1g) = 0.046 W/kg; SAR(10g) = 0.017 W/kg

Maximum value of SAR (interpolated) = 0.198 W/kg




0 dB = 0.0878 W/kg = -10.57 dBW/kg

SAR Measurement Plot 54



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:4

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 2 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 2 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.463 W/kg

Edge 1 OFDM Antenna 2 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 11.621 V/m; **Power Drift = -0.01 dB**

Averaged SAR: SAR(1g) = 0.391 W/kg; SAR(10g) = 0.114 W/kg

Maximum value of SAR (interpolated) = 1.750 W/kg




0 dB = 0.463 W/kg = -3.34 dBW/kg

SAR Measurement Plot 55



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
 Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.370 W/kg

Edge 1 OFDM Antenna 1 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 24.706 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 1.150 W/kg; SAR(10g) = 0.294 W/kg

Maximum value of SAR (interpolated) = 5.050 W/kg




0 dB = 1.37 W/kg = 1.37 dBW/kg

SAR Measurement Plot 56



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:5

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 1 OFDM Antenna 1 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
 Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 OFDM Antenna 1 08-11-16/Channel 155 Test Variability/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 1.280 W/kg

Edge 1 OFDM Antenna 1 08-11-16/Channel 155 Test Variability/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 21.768 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 1.110 W/kg; SAR(10g) = 0.288 W/kg

Maximum value of SAR (interpolated) = 4.630 W/kg




0 dB = 1.28 W/kg = 1.07 dBW/kg

SAR Measurement Plot 57



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:6

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 2 OFDM Antenna 2 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 7/12/2015
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 OFDM Antenna 2 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.096 W/kg

Edge 2 OFDM Antenna 2 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 6.085 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 0.095 W/kg; SAR(10g) = 0.019 W/kg

Maximum value of SAR (interpolated) = 0.534 W/kg




0 dB = 0.0963 W/kg = -10.16 dBW/kg

SAR Measurement Plot 58



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:7

DUT Name: Fujitsu Tablet with 11 abgn/ac WLAN, Type: 8265NGW, Serial: WFM: 0028F800E556

Configuration: Edge 4 OFDM Antenna 1 08-11-16

Communication System: 0 - OFDM 5 GHz HT0 (80 MHz); Communication System Band: 5.8 GHz Band;
 Frequency: 5775 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5775.82$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 4 OFDM Antenna 1 08-11-16/Channel 155 Test/Area Scan (61x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 0.243 W/kg

Edge 4 OFDM Antenna 1 08-11-16/Channel 155 Test/Zoom Scan (31x31x61)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 13.994 V/m; **Power Drift = -0.11 dB**

Averaged SAR: SAR(1g) = 0.261 W/kg; SAR(10g) = 0.068 W/kg

Maximum value of SAR (interpolated) = 1.470 W/kg




0 dB = 0.243 W/kg = -6.14 dBW/kg

SAR Measurement Plot 59



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M161026 Tablet 5800 MHz WLAN FCC.da52:8

DUT Name: Dipole 5200_5800 MHz, Type: D5GHzV2, Serial: 1008


Configuration: System Performance Check with D5GHzV2 Dipole 08-11-16

Communication System: 0 - CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5800 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=5799.52$ MHz; $\sigma = 6.17$ S/m; $\epsilon_r = 46.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: EX3DV4 - SN7358; ConvF: (3.85,3.85,3.85); Calibrated: 11/12/2015;
 Sensor-Surface: 1.4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 7/12/2015
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Performance Check with D5GHzV2 Dipole 08-11-16/d=10mm, Pin=100mW, f=5800 MHz/Area Scan (91x91x1): Interpolated grid: dx=1.0 mm, dy=1.0 mm; Maximum value of SAR (interpolated) = 21.000 W/kg
System Performance Check with D5GHzV2 Dipole 08-11-16/d=10mm, Pin=100mW, f=5800 MHz/Zoom Scan (4x4x2mm, uniform), dist=1.4mm (36x36x66)/Cube 0: Interpolated grid: dx=0.8 mm, dy=0.8 mm, dz=0.4 mm; Reference Value = 70.831 V/m; **Power Drift = -0.13 dB**
Averaged SAR: SAR(1g) = 8.080 W/kg; SAR(10g) = 2.240 W/kg
 Maximum value of SAR (interpolated) = 33.000 W/kg




0 dB = 21.0 W/kg = 13.22 dBW/kg

SAR Measurement Plot 60



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.