

**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
176 Harrick Road  
Keilor Park  
Victoria Australia 3042

Ph: + 613 9365 1000  
Fax: + 613 9331 7455  
email: melb@emctech.com.au

## SAR Test Report

Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_5.6

Test Sample: Portable P SERIES LIFEBOOK  
Computer  
Host PC Model Number: P727  
Radio Modules: WLAN & Bluetooth module 8265NGW  
FCC ID: EJE-WB0100  
IC ID: 337J-WB0100  
Date of Issue: 28<sup>th</sup> November 2016

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table of Revisions				
Report Number	Revision Number	Description	Pages affected	Date
M161026F_FCC_8265NGW_SAR_5.6	1	Original	N/A	25th November 2016
M161026FR1_FCC_8265NGW_SAR_5.6	2	Original	All	28th November 2016



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## CONTENTS

<b>1.0 GENERAL INFORMATION.....</b>	<b>4</b>
<b>2.0 INTRODUCTION.....</b>	<b>5</b>
<b>3.0 TEST SAMPLE TECHNICAL INFORMATION.....</b>	<b>6</b>
3.1 Radio Module (WLAN+BT) Details.....	6
3.2 DUT (Notebook PC) Details.....	11
3.3 Test sample Accessories.....	11
3.3.1 Battery Types.....	11
<b>4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER.....</b>	<b>12</b>
4.1 Battery Status.....	12
<b>5.0 DETAILS OF TEST LABORATORY.....</b>	<b>13</b>
5.1 Location.....	13
5.2 Accreditations.....	13
5.3 Environmental Factors.....	13
<b>6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA.....</b>	<b>14</b>
6.1 System verification.....	14
6.1.1 System verification Results @ 5GHz.....	14
6.1.2 Liquid Temperature and Humidity.....	15
<b>7.0 SAR MEASUREMENT PROCEDURE USING DASY5.....</b>	<b>15</b>
<b>8.0 MEASUREMENT UNCERTAINTY.....</b>	<b>16</b>
<b>9.0 EQUIPMENT LIST AND CALIBRATION DETAILS.....</b>	<b>19</b>
<b>10.0 TEST METHODOLOGY.....</b>	<b>20</b>
10.1 Position.....	20
10.1.1 "Lap Held" Position Definition (0mm spacing).....	20
10.1.2 "Edge On" Position (Portrait or Landscape).....	20
10.1.3 "Bystander" Position (25mm spacing).....	20
10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes).....	21
<b>11.0 SAR MEASUREMENT RESULTS.....</b>	<b>22</b>
11.1 5GHz Band SAR Results.....	22
<b>12.0 COMPLIANCE STATEMENT.....</b>	<b>30</b>
<b>13.0 MULTIBAND EVALUATION CONSIDERATIONS.....</b>	<b>31</b>
<b>APPENDIX A1 TEST SAMPLE PHOTOGRAPHS.....</b>	<b>34</b>
<b>APPENDIX A2 TEST SAMPLE PHOTOGRAPHS.....</b>	<b>35</b>
<b>APPENDIX A3 TEST SAMPLE PHOTOGRAPHS.....</b>	<b>36</b>
<b>APPENDIX A4 TEST SETUP PHOTOGRAPHS.....</b>	<b>37</b>
<b>APPENDIX A5 TEST SETUP PHOTOGRAPHS.....</b>	<b>38</b>
<b>APPENDIX A6 TEST SETUP PHOTOGRAPHS.....</b>	<b>39</b>
<b>APPENDIX A7 TEST SETUP PHOTOGRAPHS.....</b>	<b>40</b>
<b>APPENDIX A8 TEST SETUP PHOTOGRAPHS.....</b>	<b>41</b>
<b>APPENDIX B PLOTS OF THE SAR MEASUREMENTS.....</b>	<b>42</b>
<b>APPENDIX C DESCRIPTION OF SAR MEASUREMENT SYSTEM.....</b>	<b>163</b>
<b>APPENDIX D CALIBRATION DOCUMENTS.....</b>	<b>165</b>



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**SAR TEST REPORT**

**Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_5.6**  
**FCC ID: EJE-WB0100IC ID: 337J-WB0100**

**1.0 GENERAL INFORMATION**

**Test Sample:** Portable P Series LIFEBOOK Convertible Computer  
**Model Name:** P727  
**Radio Modules:** WLAN & Bluetooth 8265NGW  
**Interface Type:** M.2 Wireless LAN Module  
**Device Category:** Portable Transmitter  
**Test Device:** Pre-Production Unit  
**FCC ID:** EJE-WB0100  
**IC ID:** 337J-WB0100  
**RF exposure Category:** General Population/Uncontrolled

**Manufacturer:** Fujitsu Limited

**FCC KDB Procedures:** 1\*. 248227 D01 802.11 Wi-Fi SAR v02r02  
447498 D01 General RF Exposure Guidance v06  
616217 D04 SAR for laptop and tablets v01r02  
865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04  
865664 D02 RF Exposure Reporting v01r02

**Test Standard/s:** 2\*. Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), RSS-102  
3. **EN 62209-2:2010**  
Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices. Human models, instrumentation, and procedures.  
**Part 2:** Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)  
4. **IEEE 1528: 2013**  
Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

**Statement Of Compliance:** The Fujitsu P Series LIFEBOOK Convertible Computer P727 with Wireless LAN and Bluetooth model 8265NGW complied\* with the FCC General public/uncontrolled RF exposure limits of 1.6mW/g per requirements of 47CFR2.1093(d). It also complied with ISED RSS-102 requirements.


**Highest Reported SAR:** 5 GHz WLAN Band - **1.198 mW/g**

**Test Dates:** 2<sup>nd</sup> to 8<sup>th</sup> November 2016

**Test Officer:**   


---

**Peter Jakubiec**

**Authorised Signature:**   


---

**Chris Zombolas**  
**Technical Director**

\*Not within the current scope of NATA accreditation



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**SAR TEST REPORT**  
**Portable P SERIES LIFEBOOK Computer**  
**Model: P727**  
**Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_5.6**

**2.0 INTRODUCTION**

Testing was performed on the Fujitsu P Series LIFEBOOK Convertible PC, Model: P727 with M.2 integrated Wireless LAN & Bluetooth Module (Windstorm Peak 802.11a/b/g/n/ac), Model: 8265NGW. The 8265NGW WLAN module was originally certified by INTEL Corporation as a modular approval under FCC ID: PD98265NG IC ID: 1000M-8265NG. The Intel Windstorm Peak module is an OEM product, it was tested in the dedicated host – LIFEBOOK P SERIES, Model P727. The system tested will be referred to as the DUT throughout this report.

The Wireless LAN Module incorporates Bluetooth Transmitter, which can only transmit via Antenna B (2), the Bluetooth maximum power was 11.5 dBm (including tune-up) therefore it requires SAR testing as a stand-alone transmitter.

The measurement test results mentioned hereon only apply to the 5GHz frequency band; an additional report titled "M161026FR1\_FCC\_8265NGW\_SAR\_2.4" applies to the 2450MHz frequency range.

**Table 1**

Applicable Head Configurations	: None
Applicable Body Configurations	: Lap Held Position
	: Edge On Position
	: Bystander Position




---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 3.0 TEST SAMPLE TECHNICAL INFORMATION

(Information supplied by the client)

#### 3.1 Radio Module (WLAN+BT) Details

<b>Transmitter:</b>	M.2 Wireless LAN Module (WLAN parts)
<b>Wireless Module:</b>	Intel Dual Band Wireless-AC 8265 (Windstorm Peak) (11ac/abgn)
<b>Model Number:</b>	8265NGW
<b>Manufacturer:</b>	Intel Corporation
<b>Wi-Fi standard</b>	802.11ac 2x2
<b>Wi-Fi TX/RX chains</b>	2x2 chains
<b>Supported Bands</b>	2.4GHz, 5GHz
<b>Antenna Allocation</b>	Main: Wi-Fi only, Aux: Shared Wi-Fi, BT
<b>Wi-Fi TX/RX Throughput</b>	660 Mbps
<b>Bluetooth Core</b>	Bluetooth 4.1
<b>Antenna Types:</b>	Nissei Inverted F antenna Model: refer to WLAN antenna data Location: refer to Antenna location file For BT: use Aux(right side connect on module)
<b>Antenna gain:</b>	Please refer antenna data provided separately
<b>Power Supply:</b>	3.3 VDC from PCI bus



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 2 WLAN Channels and Output power setting**

**2.4 GHz (802.11b, 802.11g and 802.11n/ac)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B	
<b>802.11b 2.4 GHz</b>	1	2412	CCK 1	20MHz 99%DC	15.0	15.0	-	-	-	-	
	6	2437					-	-	-	-	
	7	2442					15.00	15.50	14.78	14.75	
	11	2462					-	-	-	-	
	12	2467					14.0	-	-	-	
	13	2472					8.0	8.0	-	-	
<b>802.11g 2.4 GHz</b>	1	2412	OFDM 6	20MHz 99%DC	15.0	15.0	-	-	-	-	
	2	2417					-	-	-	-	
	6	2437					-	-	-	-	
	10	2457					-	-	-	-	
	11	2462					15.25	15.125	14.80	14.75	
	12	2467					12.0	13.0	-	-	
	13	2472					-4.0	-4.0	-	-	
<b>802.11n 2.4 GHz</b>	3F	2422	CCK HT0	40 98%DC	15.0	15.0	15.125	15.25	14.80	14.76	
	4F	2427					-	-	-	-	
	5F	2432					-	-	-	-	
	6F	2437					15.00	15.25	14.84	14.81	
	7F	2442					15.00	15.375	14.98	14.83	
	8F	2447					-	-	-	-	
	9F	2452					-	-	-	-	
	10F	2457					14.0	15.125	15.375	14.86	14.89
	11F	2462					8.0	8.0	-	-	
	3F	2422	OFDM HT0	40 98%DC	15.0	15.0	13.0	-	-	-	-
	4F	2427					-	-	-	-	
	5F	2432					-	-	-	-	
	6F	2437					-	-	-	-	
	7F	2442					-	-	-	-	
	8F	2447					-	-	-	-	
9F	2452	-					-	-	-		
10F	2457	12.0					12.0	-	-		
11F	2462	-5.0					-5.0	-	-		



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

5 GHz (802.11a)

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B	
802.11a	<b>5.2 GHz</b>		OFDM 6	20 99%DC	13.5	13.5	-	-	-	-	
	36	5180					-	-	-	-	
	40	5200					-	-	-	-	
	44	5220					-	-	-	-	
	48	5240			-	-	-	-			
	<b>5.3 GHz</b>				13.5	13.5	-	-	-	-	
	52	5260					-	-	-	-	
	56	5280					-	-	-	-	
	60	5300					-	-	-	-	
	64	5320			-	-	-	-			
	<b>5.6 GHz</b>				13.5	13.5	-	-	-	-	
	100	5500					-	-	-	-	
	104	5520					-	-	-	-	
	108	5540					-	-	-	-	
	112	5560					-	-	-	-	
	116	5580					-	-	-	-	
	120	5600					-	-	-	-	
	124	5620					-	-	-	-	
	128	5640			-	-	-	-			
	5.65 to 5.835 GHz	132			5660	-	-	-	-		
		136			5680	-	-	-	-		
		140			5700	-	-	-	-		
		<b>5.8 GHz</b>			13.5	13.5	-	-	-	-	
		149					5745	-	-	-	-
153	5765	-	-	-			-				
157	5785	-	-	-			-				
161	5805	-	-	-	-						
165	5825	-	-	-	-						



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



5 GHz (802.11n)

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)																													
					Ch A	Ch B	Power Control Tx A (Main-1)	Power Control Tx B (Aux -2)	Tx A	Tx B																												
802.11n	<b>5.2 GHz</b>		OFDM HT0	20 99%DC	13.5	13.5	-	-	-	-																												
	36	5180					-	-	-	-																												
	40	5200					-	-	-	-																												
	44	5220					-	-	-	-																												
	48	5240					-	-	-	-																												
	<b>5.3 GHz</b>						OFDM HT0	20 99%DC	13.5	13.5	-	-	-	-																								
	52	5260									-	-	-	-																								
	56	5280									-	-	-	-																								
	60	5300									-	-	-	-																								
	64	5320									-	-	-	-																								
	<b>5.6 GHz</b>										OFDM HT0	20 99%DC	13.5	13.5	-	-	-	-																				
	100	5500													-	-	-	-																				
	104	5520													-	-	-	-																				
	108	5540													-	-	-	-																				
	112	5560													-	-	-	-																				
	116	5580													-	-	-	-																				
	120	5600													-	-	-	-																				
	124	5620													-	-	-	-																				
	128	5640													-	-	-	-																				
	5.65 to 5.835 GHz	132													5660	-	-	-	-																			
		136													5680	-	-	-	-																			
		140													5700	-	-	-	-																			
		<b>5.8 GHz</b>													OFDM HT0	20 99%DC	13.5	13.5	-	-	-	-																
		149																	5745	-	-	-	-															
		153																	5765	-	-	-	-															
	157	5785																	-	-	-	-																
	161	5805																	-	-	-	-																
	165	5825																	-	-	-	-																
	<b>5.2 GHz</b>																		OFDM HT0	40 98%DC	13.5	13.5	12.75	13.125	13.37	13.40												
	38	5190																					12.875	13.375	13.41	13.39												
	46	5230																					-	-	-	-												
	<b>5.3 GHz</b>																						OFDM HT0	40 98%DC	13.5	13.5	12.75	13.00	13.43	13.40								
	54	5270																									12.75	13.00	13.47	13.43								
	62	5310																									-	-	-	-								
	<b>5.6 GHz</b>																										OFDM HT0	40 98%DC	13.5	13.5	13.50	-	13.37	-				
	102	5510																													13.375	-	13.42	-				
	110	5550																													-	-	-	-				
	118	5590																													-	-	-	-				
	126	5630																													-	-	-	-				
	5.65 to 5.835 GHz	134																													5670	-	-	-	-			
		142																													5710	-	-	-	-			
		<b>5.8 GHz</b>																													OFDM HT0	40 98%DC	13.5	13.5	-	-	-	-
	151	5755																																	-	-	-	-
	159	5795																																	-	-	-	-



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**5 GHz (802.11ac)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B	
802.11 ac	<b>5.2 GHz</b>		VHT0	80 96%DC							
	42	5210			13.0	13.0	-	-	-	-	
	<b>5.3 GHz</b>										
	58	5290			11.0	12.0	-	-	-	-	
	<b>5.6 GHz</b>										
	106	5530			13.0	13.5	-	13.50	-	13.33	
	122	5610			13.5	13.5	13.50	14.125	13.49	13.34	
	5.65 to 5.835 GHz	138			5690	13.5	13.5	13.750	13.35	13.37	13.56
		<b>5.8 GHz</b>									
		155			5775			13.5	13.5	13.50	14.0

**Table 3 Bluetooth Ant Aux (2)(B) Channels and Output power setting**

Channel Number	Frequency (MHz)	Average Power Measured (dBm)	Tune-up Power (dBm)	Bluetooth Utility power setting
0	2402	10.36	11.5	BR/EDR in DH5 mode (77% DC) Out Pwr. 12dBm Fine Power + 16
40	2441	10.46	11.5	
79	2480	10.90	11.5	



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 3.2 DUT (Notebook PC) Details

Table 4

<b>Host notebook :</b>	LIFEBOOK P series
<b>Model Name:</b>	P727
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Core i7 2.8GHz
<b>LCD</b>	12.5" FHD : LGD: LP125WF4-SPH1 12.5" HD: BOE: NT125WHM-N43
<b>Graphics chip</b>	Non
<b>Wired LAN:</b>	Intel 219LM: 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	Non
<b>Port Replicator Model:</b>	NPR44
<b>AC Adapter Model:</b>	90W: A13-090P1A(Chicony), A13-090P2A (Chicony) ADP-90BE D(Delta), ADP-90BE C(Delta) 80W: ADP-80SB A(Delta), ADP-80SB B(Delta) 65W:PC only ADP-65MD B(Delta), ADP-65MD C(Delta) A13-065N2A(Chicony), A13-065N3A(Chicony)
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	4.74A / 4.22A / 3.42A
<b>Watts:</b>	90W / 80W / 65W
<b>Battery type</b>	Li-ion
<b>Brand</b>	FUJITSU
<b>Manufacturer</b>	Tocad
<b>Rating</b>	4170mAh, 10.8Vdc, 45Wh

### 3.3 Test sample Accessories

#### 3.3.1 Battery Types

One type of Fujitsu Lithium Ion battery is used to power the DUT.

Table 5 Battery Details

Model	CP721833-01
V/Wh	18.8V/46Wh



## 4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER

INTEL's DRTU test tool was used to configure the WLAN for testing. The DUT Wireless LAN operates in 2 modes, OFDM and DSSS. For the SAR measurements, the device was operating in continuous transmit mode using programming codes supplied by Fujitsu.

It is possible for the Bluetooth (Antenna 2) to operate simultaneously with the WLAN (Antenna 1) (co-transmission). Also the DUT is capable of using two antennas in WLAN mode transmitting simultaneously.

The test results mentioned in this report only apply to the 5.6 GHz frequency range. An additional report titled "M161026FR1\_FCC\_8265NGW\_SAR\_2.4" is specific to the 2450MHz range.

At the beginning of the SAR tests, the conducted power of the device was measured after temporary modification of antenna connector inside the device's TX RX compartment. Measurements were performed with a calibrated Power Meter and the result of the measurements includes the tune up tolerance of 1 dB for WLAN and 2 dB for Bluetooth. WLAN and Bluetooth SAR results were scaled up to the maximum tune-up RF power levels and to 100% Duty Cycle.

### 4.1 Battery Status

The DUT battery was fully charged prior to commencement of measurement. The battery condition was monitored by measuring the RF field at a defined position inside the phantom before the commencement of each test and again after the completion of the test. It was not possible to perform conducted power measurements at the output of the DUT, at the beginning and end of each scan due to lack of a suitable antenna port. The uncertainty associated with the power drift was less than 5% and was assessed in the uncertainty budget.



## 5.0 DETAILS OF TEST LABORATORY

### 5.1 Location

EMC Technologies Pty Ltd  
176 Harrick Road  
Keilor Park, (Melbourne) Victoria  
Australia 3042

**Telephone:** +61 3 9365 1000  
**Facsimile:** +61 3 9331 7455  
**email:** [melb@emctech.com.au](mailto:melb@emctech.com.au)  
**website:** [www.emctech.com.au](http://www.emctech.com.au)

### 5.2 Accreditations

EMC Technologies Pty. Ltd. is accredited by the National Association of Testing Authorities, Australia (NATA).

**NATA Accredited Laboratory Number: 5292**

Last assessed in May 2014, next scheduled assessment in December 2017

EMC Technologies Pty Ltd is NATA accredited for the following standards:

<b>AS/NZS 2772.2 2011:</b>	RF and microwave radiation hazard measurement
<b>ACMA:</b>	Radio communications (Electromagnetic Radiation - Human Exposure) Standard 2003
<b>EN 50360: 2001</b>	Product standard to demonstrate the compliance of Mobile Phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
<b>EN 62209-1:2006</b>	Human exposure to radio frequency fields from hand-held and body-mounted devices-Human models, instrumentation and procedures. <b>Part 1:</b> Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range 300 MHz to 3 GHz)
<b>EN 62209-2:2010</b>	Human Exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models instrumentation and procedures <b>Part 2:</b> Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)
<b>IEEE 1528: 2013</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

Refer to NATA website [www.nata.asn.au](http://www.nata.asn.au) for the full scope of accreditation.

### 5.3 Environmental Factors

The measurements were performed in a shielded room with no background RF signals. The temperature in the laboratory was controlled to within  $20 \pm 1^\circ\text{C}$ , the humidity was in the range 36% to 48%. The liquid parameters are measured daily prior to the commencement of each test. Tests were performed to check that reflections within the environment did not influence the SAR measurements. DASY5 SAR measurement system using the EX3DV4 E-field probe is less than  $5\mu\text{V}$  in both air and liquid mediums.




---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA

### 6.1 System verification

#### 6.1.1 System verification Results @ 5GHz

The following table lists the results of the System Verification. The forward power into the reference dipole for SAR System Verification was adjusted to 100 mW.

The SPEAG calibration reference SAR value is the SAR system verification result obtained in a specific dielectric liquid using the validation dipole (D5GHZV2) during calibration. The measured one-gram SAR should be within 10% of the expected target reference values shown in below.

**Table 6 Deviation from reference system verification values in 5.6 GHz band**

Frequency and Date	Measured SAR 1g (mW/g)	Measured SAR 1g (Normalized to 1W)	SPEAG Calibration reference SAR Value 1g (mW/g)	Deviation From SPEAG Reference 1g (%)	Last Validation Date
5200MHz 2 <sup>nd</sup> Nov. 16	7.44	74.40	75.1	-0.93	9/08/16
5200MHz 3 <sup>rd</sup> Nov. 16	7.62	76.20	75.1	1.46	9/08/16
5600MHz 4 <sup>th</sup> Nov. 16	8.51	85.10	81.3	4.67	16/08/16
5600MHz 7 <sup>th</sup> Nov. 16	8.66	86.60	81.3	6.52	16/08/16
5800MHz 8 <sup>th</sup> Nov. 16	8.08	80.80	76.7	5.35	18/08/16

NOTE: All reference system verification values are referenced to 1W input power.

**Table 7 Linearity Check**

Freq. ( MHz)	Mode	Measured 10mW/g SAR 1g (input power = 125mW)	Measured SAR 1g (Normalized to 1W)	Measured 2mW/g SAR 1g (input power = 25mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.4mW/g SAR 1g (input power = 15mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.08mW/g SAR 1g (input power = 1mW)	Measured SAR 1g (Normalized to 1W)	Date
5200	CW	10.2	81.60	1.94	77.60	1.18	78.67	0.0801	80.10	9/08/16
5600	CW	10.6	84.80	2.02	80.80	1.22	81.33	0.07	70.00	16/08/16
5800	CW	9.69	77.52	1.92	76.80	1.14	76.00	0.0792	79.20	18/08/16
Freq. ( MHz)	Mode	Measured 10mW/g SAR 1g (input power = 125mW)	Measured SAR 1g (Normalized to 1W)	Measured 2mW/g SAR 1g (input power = 25mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.4mW/g SAR 1g (input power = 15mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.08mW/g SAR 1g (input power = 3mW)	Measured SAR 1g (Normalized to 1W)	Date
5200	OFDM 5Mbps 20MHz	10	80.00	1.91	76.40	1.08	72.00	0.257	85.67	15/08/16
5600	OFDM 5Mbps 20MHz	10.5	84.00	2.09	83.60	1.22	81.33	0.258	86.00	17/08/16
5800	OFDM 5Mbps 20MHz	10.3	82.40	1.99	79.60	1.15	76.67	0.249	83.00	19/08/16



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 6.1.2 Liquid Temperature and Humidity

The humidity and dielectric/ambient temperatures were recorded during the assessment of the tissue material dielectric parameters. The difference between the ambient temperature of the liquid during the dielectric measurement and the temperature during tests was less than  $|2|^\circ\text{C}$ .

**Table 8 Temperature and Humidity recorded for each day**

Date	Ambient Temperature ( $^\circ\text{C}$ )	Liquid Temperature ( $^\circ\text{C}$ )	Humidity (%)
2 <sup>nd</sup> November 2016	19.8	19.6	42
3 <sup>rd</sup> November 2016	20.5	20.1	41
4 <sup>th</sup> November 2016	19.8	19.5	47
7 <sup>th</sup> November 2016	19.5	19.3	48
8 <sup>th</sup> November 2016	19.6	19.3	47

## 7.0 SAR MEASUREMENT PROCEDURE USING DASY5

The SAR evaluation was performed with the SPEAG DASY5 system. A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the DUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 2.0 mm from the inner surface of the shell. The area covers the entire dimension of the DUT and the horizontal grid spacing is 10 mm x 10 mm. The actual Area Scan has dimensions of 60mm x 90mm surrounding the test device. Based on this data, the area of the maximum absorption is determined by Spline interpolation.
- c) Around this point, a volume of 24 mm x 24 mm x 22 mm is assessed by measuring 7 x 7 x 12 points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:
  - (i) The data at the surface are extrapolated, since the centre of the dipoles is 1.0 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 2.0 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axis. This polynomial is then used to evaluate the points between the surface and the probe tip.
  - (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
  - (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
  - (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.



## 8.0 MEASUREMENT UNCERTAINTY

The uncertainty analysis is based on the template listed in the IEEE Std 1528-2013 for both device SAR tests and Validation uncertainty. The measurement uncertainty of a specific device is evaluated independently.

**Table 9 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 5GHz**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1.00	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	2.4	R	1.73	1	1	1.39	1.39	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Device Holder Uncertainty	3.6	N	1.00	1	1	3.60	3.60	5
Output Power Variation – SAR Drift Measurement	4.72	R	1.73	1	1	2.73	2.73	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.64	0.71	1.60	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.6	0.26	1.50	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u <sub>c</sub> )						<b>12.71</b>	<b>12.54</b>	
Expanded Uncertainty (95% CONFIDENCE LEVEL)				<b>k= 2</b>		<b>25.41</b>	<b>25.08</b>	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 12.71\%$ . The expanded uncertainty ( $K = 2$ ) was assessed to be  $\pm 25.41\%$  based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



**Table 10 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 5GHz****IEC 62209-2 UNCERTAINTY FOR RSS-102**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1.00	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	2.4	R	1.73	1	1	1.39	1.39	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Device Holder Uncertainty	3.6	N	1.00	1	1	3.60	3.60	∞
Output Power Variation – SAR Drift Measurement	4.72	R	1.73	1	1	2.73	2.73	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.6	0.49	1.50	1.23	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.05	0.06	∞
Combined standard Uncertainty (u <sub>c</sub> )						<b>12.82</b>	<b>12.64</b>	
Expanded Uncertainty (95% CONFIDENCE LEVEL)				<b>k= 2</b>		<b>25.65</b>	<b>25.28</b>	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 12.82\%$ . The expanded uncertainty ( $K = 2$ ) was assessed to be  $\pm 25.65\%$  based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 11 Uncertainty Budget for DASY5 Version 52 – System verification 5GHz**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1.00	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	1	1	2.71	2.71	∞
Hemispherical Isotropy	9.6	R	1.73	0	0	0.00	0.00	∞
Boundary Effects	1	R	1.73	1	1	0.58	0.58	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	0	R	1.73	1	1	0.00	0.00	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0	R	1.73	1	1	0.00	0.00	∞
Integration Time	0	R	1.73	1	1	0.00	0.00	∞
RF Ambient Noise	1	R	1.73	1	1	0.58	0.58	∞
RF Ambient Reflections	1	R	1.73	1	1	0.58	0.58	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	2	R	1.73	1	1	1.15	1.15	∞
<b>Dipole Related</b>								
Deviation of exp. dipole	5.5	R	1.73	1	1	3.18	3.18	##
Dipole Axis to Liquid Dist.	2	R	1.73	1	1	1.15	1.15	##
Input power & SAR drift	3.40	R	1.73	1	1	1.96	1.96	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	4	R	1.73	1	1	2.31	2.31	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.26	0.26	0.65	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u <sub>c</sub> )						10.36	10.19	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			20.73	20.37	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 10.36\%$ . The expanded uncertainty ( $K = 2$ ) was assessed to be  $\pm 20.73\%$  based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 9.0 EQUIPMENT LIST AND CALIBRATION DETAILS

Table 12 SPEAG DASY5 Version 52

Equipment Type	Manufacturer	Model Number	Serial Number	Calibration Due	Used For this Test?
Robot - Six Axes	Staubli	RX90BL	N/A	Not applicable	✓
Robot Remote Control	SPEAG	CS7MB	RX90B	Not applicable	✓
SAM Phantom	SPEAG	N/A	1260	Not applicable	
SAM Phantom	SPEAG	N/A	1060	Not applicable	
Flat Phantom	AndreT	10.1	P 10.1	Not Applicable	
Flat Phantom	AndreT	9.1	P 9.1	Not Applicable	
Flat Phantom	SPEAG	ELI 4.0	1101	Not Applicable	✓
Data Acquisition Electronics	SPEAG	DAE3 V1	359	11-Jan-2017	
Data Acquisition Electronics	SPEAG	DAE3 V1	442	07-Dec-2016	✓
Probe E-Field - Dummy	SPEAG	DP1	N/A	Not applicable	
Probe E-Field	SPEAG	ET3DV6	1380	10-Dec-2016	
Probe E-Field	SPEAG	ET3DV6	1377	11-June-2016	
Probe E-Field	SPEAG	ES3DV6	3029	Not Used	
Probe E-Field	SPEAG	EX3DV4	3956	15-June-2016	
Probe E-Field	SPEAG	EX3DV4	7358	11-Dec-2016	✓
Validation Source 150 MHz	SPEAG	CLA150	4003	3-Dec-2016	
Antenna Dipole 300 MHz	SPEAG	D300V3	1012	09-Dec-2018	
Antenna Dipole 450 MHz	SPEAG	D450V3	1074	09-Dec-2018	
Antenna Dipole 600 MHz	SPEAG	D600V3	1008	16-Oct-2018	
Antenna Dipole 750 MHz	SPEAG	D750V2	1051	13-Dec-2016	
Antenna Dipole 900 MHz	SPEAG	D900V2	047	09-Dec-2017	
Antenna Dipole 1640 MHz	SPEAG	D1640V2	314	05-Dec-2017	
Antenna Dipole 1800 MHz	SPEAG	D1800V2	242	05-Dec-2017	
Antenna Dipole 1950 MHz	SPEAG	D1950V3	1113	09-Dec-2018	
Antenna Dipole 2300 MHz	SPEAG	D2300V2	1032	10-Dec-2018	
Antenna Dipole 2450 MHz	SPEAG	D2450V2	724	10-Dec-2018	
Antenna Dipole 2600 MHz	SPEAG	D2600V2	1044	13-Dec-2016	
Antenna Dipole 3500 MHz	SPEAG	D3500V2	1002	13-July-2013	
Antenna Dipole 5600 MHz	SPEAG	D5GHzV2	1008	16-Dec-2016	✓
RF Amplifier	EIN	603L	N/A	*In test	
RF Amplifier	Mini-Circuits	ZHL-42	N/A	*In test	
RF Amplifier	Mini-Circuits	ZVE-8G	N/A	*In test	✓
Synthesized signal generator	Hewlett Packard	86630A	3250A00328	*In test	✓
RF Power Meter	Hewlett Packard	437B	3125012786	*In test	✓
RF Power Sensor 0.01 - 18 GHz	Hewlett Packard	8481H	1545A01634	18-Oct-2017	✓
RF Power Meter	Rohde & Schwarz	NRP	101415	16-Oct-2016	
RF Power Sensor	Rohde & Schwarz	NRP - Z81	100174	19-Oct-2017	
RF Power Meter Dual	Hewlett Packard	435A	1733A05847	*In test	✓
RF Power Sensor	Hewlett Packard	8482A	2349A10114	*In test	✓
Network Analyser	Hewlett Packard	8714B	GB3510035	03-Oct-2016	
Network Analyser	Hewlett Packard	8753ES	JP39240130	03-Dec-2016	
Network Analyser	Hewlett Packard	8753D	3410A04122	04-Feb-2017	✓
Dual Directional Coupler	Hewlett Packard	778D	1144 04700	*In test	
Dual Directional Coupler	NARDA	3022	75453	*In test	✓
Thermometer	Digitech	QM7217	T-103	31-Aug-2017	✓
Thermometer	Digitech	QM7217	T-104	15-Jan-2017	

\* Calibrated during the test for the relevant parameters.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 10.0 TEST METHODOLOGY

Notebooks should be evaluated in normal use positions, typical for lap-held bottom-face only. However, the number of positions will depend on the number of configurations the laptop can be operated in. The “LIFEBOOK P SERIES” can be used in either a conventional laptop position (see Appendix A) or a Tablet configuration. The antenna location in the “LIFEBOOK P SERIES” is closest to the top of the screen when used in a conventional laptop configuration and due to the separation distances involved between the phantom and the laptop antenna, testing is not required in this position.

### 10.1 Position

#### 10.1.1 “Lap Held” Position Definition (0mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Lap Held” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of the DUT was touching the phantom. This device orientation simulates the PC’s normal use – being held on the lap of the user. A spacing of 0mm ensures that the SAR results are conservative and represent a worst-case position.

#### 10.1.2 “Edge On” Position (Portrait or Landscape)

The DUT was tested in the (2.00 mm) flat section of the ELI4 Flat phantom for the “Edge On” position. The Antenna edge of the Transceiver was placed underneath the flat section of the phantom and suspended until the edge touched the phantom. *Refer to Appendix A for photos of measurement positions.*

#### 10.1.3 “Bystander” Position (25mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Bystander” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of its LCD screen was parallel to phantom and at 25mm distance. This orientation simulates use of the device in a way that allows occasional RF exposure of the nearby person (Bystander).




**10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes)**

The DUT has fixed antennas. Depending on the measured SAR level up to three test channels with the test sample operating at maximum power were recorded. The following table represents the matrix used to determine what testing was required. All relevant provisions of KDB 447498 are applied for SAR measurements of the host system.


**Table 13 Testing configurations**

Phantom Configuration	*Device Mode	Antenna	Test Configurations		
			Channel (Remining)	Channel (Highest)	Channel (Remining)
Lap Held	OFDM 5GHz All Bands	A		X	
		B		X	
Bystander	OFDM 5GHz All Bands	A		X	
		B		X	
Edge On	OFDM 5GHz All Bands	A		X	
		B		X	

**Legend**



Testing Required in this configuration



Testing required in this configuration only if SAR of middle channel is more than 3dB below the SAR limit or it is the worst case.

*NOTE: Throughout this report, Antenna A and B refer to Tx1 and Tx2 in the host respectively.*



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 11.0 SAR MEASUREMENT RESULTS

The SAR values averaged over 1g tissue masses were determined for the sample DUT for all test configurations listed in section 10.2.

### 11.1 5GHz Band SAR Results



---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 14 SAR MEASUREMENT RESULTS Lower Band – OFDM Mode**

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	$\epsilon_r$	$\sigma$	Reported (mW/g)	Tune-up Power (dBm)	Conducted Power (dBm)	PWR Scaling factor
Bystander 25mm Spacing OFDM Antenna 2 02-11-16	1.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.0384	-0.1	48.1	5.30	0.04	13.5	13.39	1.03
Bystander 25mm Spacing OFDM Antenna 2 02-11-16	2.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.0679	-0.09	47.9	5.43	0.07	13.5	13.43	1.02
Bystander 25mm Spacing OFDM Antenna 1 02-11-16	3.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.0166	0	48.1	5.30	0.02	13.5	13.41	1.02
Bystander 25mm Spacing OFDM Antenna 1 02-11-16	4.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.0424	-0.07	47.9	5.43	0.04	13.5	13.47	1.01
Lap Held OFDM Antenna 2 02-11-16	5.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.0426	-0.13	48.1	5.30	0.04	13.5	13.39	1.03
Lap Held OFDM Antenna 2 02-11-16	6.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.0483	0.14	47.9	5.43	0.05	13.5	13.43	1.02
Lap Held OFDM Antenna 1 02-11-16	7.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.0369	0.17	48.1	5.30	0.04	13.5	13.41	1.02
Lap Held OFDM Antenna 1 02-11-16	8.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.0504	0.1	47.9	5.43	0.05	13.5	13.47	1.01
Edge 1 OFDM Antenna 2 03-11-16	9.	OFDM 5 GHz HT0 (40 MHz)	38	5190	0.54	-0.09	48.6	5.36	0.55	13.5	13.4	1.02
Edge 1 OFDM Antenna 2 03-11-16	10.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.616	-0.05	48.5	5.42	0.63	13.5	13.39	1.03
Edge 1 OFDM Antenna 2 03-11-16	11.	OFDM 5 GHz HT0 (40 MHz)	54	5270	0.595	-0.12	48.4	5.51	0.61	13.5	13.4	1.02
Edge 1 OFDM Antenna 2 03-11-16	12.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.573	-0.13	48.3	5.58	0.58	13.5	13.43	1.02
Edge 1 OFDM Antenna 1 03-11-16	13.	OFDM 5 GHz HT0 (40 MHz)	38	5190	0.534	-0.2	48.6	5.36	0.54	13.5	13.37	1.03
Edge 1 OFDM Antenna 1 03-11-16	14.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.665	-0.05	48.5	5.42	0.68	13.5	13.41	1.02
Edge 1 OFDM Antenna 1 03-11-16	15.	OFDM 5 GHz HT0 (40 MHz)	54	5270	0.695	-0.15	48.4	5.51	0.71	13.5	13.43	1.02
Edge 1 OFDM Antenna 1 03-11-16	16.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.728	0	48.3	5.58	0.74	13.5	13.47	1.01
Edge 2 OFDM Antenna 2 03-11-16	17.	OFDM 5 GHz HT0	38	5190	0.199	-0.02	48.6	5.36	0.20	13.5	13.4	1.02



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

		(40 MHz)										
Edge 2 OFDM Antenna 2 03-11-16	18.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.174	0	48.5	5.42	0.18	13.5	13.39	1.03
Edge 2 OFDM Antenna 2 03-11-16	19.	OFDM 5 GHz HT0 (40 MHz)	54	5270	0.0601	-0.15	48.4	5.51	0.06	13.5	13.4	1.02
Edge 2 OFDM Antenna 2 03-11-16	20.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.0835	0.02	48.3	5.58	0.09	13.5	13.43	1.02
Edge 4 OFDM Antenna 1 03-11-16	21.	OFDM 5 GHz HT0 (40 MHz)	38	5190	0.191	-0.01	48.6	5.36	0.19	13.5	13.37	1.03
Edge 4 OFDM Antenna 1 03-11-16	22.	OFDM 5 GHz HT0 (40 MHz)	46	5230	0.179	-0.05	48.5	5.42	0.18	13.5	13.41	1.02
Edge 4 OFDM Antenna 1 03-11-16	23.	OFDM 5 GHz HT0 (40 MHz)	54	5270	0.237	-0.01	48.4	5.51	0.24	13.5	13.43	1.02
Edge 4 OFDM Antenna 1 03-11-16	24.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.302	0.08	48.3	5.58	0.31	13.5	13.47	1.01
System Performance Check with D5GHzV2 Dipole 02-11-16	25.	System Check	0	5200	7.44	-0.07	48.2	5.25	-	-	-	-
System Performance Check with D5GHzV2 Dipole 03-11-16	26.	System Check	0	5200	7.62	-0.02	48.6	5.38	-	-	-	-

NOTE: The measurement uncertainty of 25.41% for 5GHz testing is not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



**Table 15 Target Body Simulating Liquid Dielectric Values for 5200MHz range**

Frequency Band	$\epsilon_r$ (target)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
5190 MHz Body	49.0 ±5% (46.55 to 51.45)	5.3 ±5% (5.04 to 5.57)	1000
5230 MHz Body	48.9 ±5% (46.46 to 51.35)	5.4 ±5% (5.13 to 5.67)	1000
5270 MHz Body	48.9 ±5% (46.46 to 51.35)	5.4 ±5% (5.13 to 5.67)	1000
5310 MHz Body	49.0 ±5% (46.55 to 51.45)	5.3 ±5% (5.04 to 5.57)	1000



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 16 SAR MEASUREMENT RESULTS Middle Band – OFDM Mode**

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	$\epsilon_r$	$\sigma$	Reported (mW/g)	Tune-up Power (dBm)	Conducted Power (dBm)	PWR Scaling factor
Bystander 25mm Spacing OFDM Antenna 2 04-11-16	27.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.0474	0.15	47.5	5.95	0.05	13.5	13.34	1.04
Bystander 25mm Spacing OFDM Antenna 1 04-11-16	28.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.0327	0.18	47.5	5.95	0.03	13.5	13.49	1.00
Lap Held OFDM Antenna 2 04-11-16	29.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.0499	-0.21	47.5	5.95	0.05	13.5	13.34	1.04
Lap Held OFDM Antenna 1 04-11-16	30.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.0635	-0.03	47.5	5.95	0.07	13.5	13.49	1.00
Edge 1 OFDM Antenna 2 04-11-16	31.	OFDM 5 GHz HTO (80 MHz)	106	5530	0.334	0.04	47.7	5.83	0.36	13.5	13.33	1.04
Edge 1 OFDM Antenna 2 04-11-16	32.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.426	-0.02	47.5	5.95	0.46	13.5	13.34	1.04
Edge 1 OFDM Antenna 2 04-11-16	33.	OFDM 5 GHz HTO (80 MHz)	138	5690	0.391	-0.14	47.3	6.07	0.42	13.5	13.37	1.03
Edge 1 OFDM Antenna 1 07-11-16	34.	OFDM 5 GHz HTO (40 MHz)	102	5510	1.02	-0.02	47.8	5.82	1.07	13.5	13.37	1.03
Edge 1 OFDM Antenna 1 Variability 07-11-16	35.	OFDM 5 GHz HTO (40 MHz)	102	5510	1.14	-0.04	47.8	5.82	1.20	13.5	13.37	1.03
Edge 1 OFDM Antenna 1 07-11-16	36.	OFDM 5 GHz HTO (40 MHz)	110	5550	1.11	-0.07	47.6	5.89	1.13	13.5	13.52	1.00
Edge 1 OFDM Antenna 1 Variability 07-11-16	37.	OFDM 5 GHz HTO (40 MHz)	110	5550	0.973	-0.16	47.6	5.89	0.99	13.5	13.52	1.00
Edge 1 OFDM Antenna 1 07-11-16	38.	OFDM 5 GHz HTO (80 MHz)	122	5610	1.15	-0.19	47.5	6.01	1.20	13.5	13.49	1.00
Edge 1 OFDM Antenna 1 Variability 07-11-16	39.	OFDM 5 GHz HTO (80 MHz)	122	5610	1.15	-0.14	47.5	6.01	1.20	13.5	13.49	1.00
Edge 1 OFDM Antenna 1 07-11-16	40.	OFDM 5 GHz HTO (80 MHz)	138	5690	1.09	-0.13	47.2	6.12	1.18	13.5	13.35	1.04
Edge 1 OFDM Antenna 1 Variability 07-11-16	41.	OFDM 5 GHz HTO (80 MHz)	138	5690	1.1	-0.16	47.2	6.12	1.19	13.5	13.35	1.04
Edge 2 OFDM Antenna 2 07-11-16	42.	OFDM 5 GHz HTO	106	5530	0.0633	-0.15	47.7	5.85	0.07	13.5	13.33	1.04



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

		(80 MHz)										
Edge 2 OFDM Antenna 2 07-11-16	43.	OFDM 5 GHz HT0 (80 MHz)	122	5610	0.188	-0.14	47.5	6.01	0.20	13.5	13.34	1.04
Edge 2 OFDM Antenna 2 07-11-16	44.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.134	-0.02	47.2	6.12	0.14	13.5	13.37	1.03
Edge 4 OFDM Antenna 1 07-11-16	45.	OFDM 5 GHz HT0 (40 MHz)	102	5510	0.333	-0.11	47.8	5.82	0.35	13.5	13.37	1.03
Edge 4 OFDM Antenna 1 07-11-16	46.	OFDM 5 GHz HT0 (40 MHz)	110	5550	0.422	-0.03	47.6	5.89	0.43	13.5	13.52	1.00
Edge 4 OFDM Antenna 1 07-11-16	47.	OFDM 5 GHz HT0 (80 MHz)	122	5610	0.365	-0.08	47.5	6.01	0.38	13.5	13.49	1.00
Edge 4 OFDM Antenna 1 07-11-16	48.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.37	-0.11	47.2	6.12	0.40	13.5	13.37	1.03
System Performance Check with D5GHzV2 Dipole 04-11-16	49.	System Check	1	5600	8.51	-0.04	47.5	5.93	-	-	-	-
System Performance Check with D5GHzV2 Dipole 07-11-16	50.	System Check	1	5600	8.66	0.11	47.5	5.99	-	-	-	-

NOTE: The measurement uncertainty of 25.41% for 5GHz testing is not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 17 Target Body Simulating Liquid Dielectric Values for 5600MHz range**

Frequency Band	$\epsilon_r$ (target)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
5530 MHz Body	48.6 ±5% (46.17 to 51.03)	5.6 ±5% (5.32 to 5.88)	1000
5550 MHz Body	48.5 ±5% (46.08 to 50.93)	5.77 ±5% (5.48 to 6.06)	1000
5610 MHz Body	48.5 ±5% (46.08 to 50.93)	5.77 ±5% (5.48 to 6.06)	1000
5690 MHz Body	48.4 ±5% (45.98 to 50.82)	5.9 ±5% (5.61 to 6.20)	1000



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 18 SAR MEASUREMENT RESULTS Upper Band – OFDM Mode**

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	$\epsilon_r$	$\sigma$	Reported (mW/g)	Tune-up Power (dBm)	Conducted Power (dBm)	PWR Scaling factor
Bystander 25mm Spacing OFDM Antenna 2 08-11-16	51.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.0375	0	46.6	6.13	0.04	13.5	13.42	1.02
Bystander 25mm Spacing OFDM Antenna 1 08-11-16	52.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.0178	-0.19	46.6	6.13	0.02	13.5	13.49	1.00
Lap Held OFDM Antenna 2 08-11-16	53.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.0444	-0.2	46.6	6.13	0.05	13.5	13.42	1.02
Lap Held OFDM Antenna 1 08-11-16	54.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.0458	-0.09	46.6	6.13	0.05	13.5	13.49	1.00
Edge 1 OFDM Antenna 2 08-11-16	55.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.391	-0.01	46.6	6.13	0.41	13.5	13.42	1.02
Edge 1 OFDM Antenna 1 08-11-16	56.	OFDM 5 GHz HT0 (80 MHz)	155	5775	1.15	-0.12	46.6	6.13	<b>1.20</b>	13.5	13.49	1.00
Edge 1 OFDM Antenna 1 Variability 08-11-16	57.	OFDM 5 GHz HT0 (80 MHz)	155	5775	1.11	-0.14	46.6	6.13	1.16	13.5	13.49	1.00
Edge 2 OFDM Antenna 2 08-11-16	58.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.0954	-0.19	46.6	6.13	0.10	13.5	13.42	1.02
Edge 4 OFDM Antenna 1 08-11-16	59.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.261	-0.11	46.6	6.13	0.27	13.5	13.49	1.00
System Performance Check with D5GHzV2 Dipole 08-11-16	60.	System Check	2	5800	8.08	-0.13	46.6	6.17	-	-	-	-

NOTE: The measurement uncertainty of 25.41% for 5GHz testing is not added to the result.

**Table 19 Target Body Simulating Liquid Dielectric Values for 5800MHz range**

Frequency Band	$\epsilon_r$ (target)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
5775 MHz Body	48.2 ±5% (45.79 to 50.61)	6.0 ±5% (5.7 to 6.3)	1000



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 12.0 COMPLIANCE STATEMENT

The Fujitsu P Series LIFEBOOK Convertible PC, Model: P727 with INTEL Wireless LAN Module (Windstorm Peak 802.11a/b/g/n/ac), Model: 8265NGW was found to comply with the FCC and RSS-102 SAR requirements.

The highest Measured SAR level was 1.15 mW/g for a 1g cube. The manufacturer's duty cycle is 99%. Scaling the SAR value, the maximum reported SAR value is **1.20 mW/g**. This value was measured at 5775 MHz (channel 155) in the "Edge 1" position in OFDM (80MHz) modulation mode at the antenna 1. This was below the limit of 1.6 mW/g for uncontrolled exposure, but was within the band of measurement uncertainty around the limit.

The SAR test variability checks were conducted and the repeated results are included in the SAR results tables.



---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 13.0 MULTIBAND EVALUATION CONSIDERATIONS

Fujitsu **P SERIES LIFEBOOK** PC, Model: **P727** has two transmitting antennas that are able to transmit simultaneously.

According to the FCC SAR evaluation procedures mentioned in KDB447498, when the sum of SAR results (simultaneously transmitting antennas WLAN Antenna 1 and WLAN Antenna 2) is  $> 1.6\text{mW/g}$ , the ratio of above sum raised to the power of 1.5, to the distance between peak SAR locations must be  $\leq 0.04$ ,  $(\text{SAR1} + \text{SAR2})^{1.5}/R_i$  (rounded to two decimal digits), or simultaneous (multiband) transmission SAR evaluation is required.

Multiband evaluation was not conducted for WLAN Antenna 1 and WLAN Antenna 2 because the ratio of the sum of highest SAR results raised to the power of 1.5 for the WLAN Antenna 1 and WLAN Antenna 2, to the distance between peak SAR locations of both WLAN antennas was found to be below 0.04.

Summary of the highest SAR results considered for multiband evaluation 5.6 GHz:



---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Find distance of maxima	
Max. 1 - Max. 5	Distance [mm]: 262.65 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 6	Distance [mm]: 242.85 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 7	Distance [mm]: 240.84 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 8	Distance [mm]: 257.24 / Separation ratio [W/kg/mm]: 0.07
Max. 1 - Max. 9	Distance [mm]: 255.45 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 10	Distance [mm]: 254.67 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 11	Distance [mm]: 253.04 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 5	Distance [mm]: 262.62 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 6	Distance [mm]: 242.83 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 7	Distance [mm]: 240.81 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 8	Distance [mm]: 257.21 / Separation ratio [W/kg/mm]: 0.07
Max. 2 - Max. 9	Distance [mm]: 255.42 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 10	Distance [mm]: 254.64 / Separation ratio [W/kg/mm]: 0.01
Max. 2 - Max. 11	Distance [mm]: 253.02 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 5	Distance [mm]: 262.65 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 6	Distance [mm]: 242.85 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 7	Distance [mm]: 240.84 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 8	Distance [mm]: 257.24 / Separation ratio [W/kg/mm]: 0.07
Max. 3 - Max. 9	Distance [mm]: 255.45 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 10	Distance [mm]: 254.67 / Separation ratio [W/kg/mm]: 0.01
Max. 3 - Max. 11	Distance [mm]: 253.05 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 5	Distance [mm]: 262.63 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 6	Distance [mm]: 242.83 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 7	Distance [mm]: 240.82 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 8	Distance [mm]: 257.22 / Separation ratio [W/kg/mm]: 0.07
Max. 4 - Max. 9	Distance [mm]: 255.43 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 10	Distance [mm]: 254.65 / Separation ratio [W/kg/mm]: 0.01
Max. 4 - Max. 11	Distance [mm]: 253.02 / Separation ratio [W/kg/mm]: 0.01

Find distance of maxima	
Maxima and position w.r.t. Grid Reference Point   associated 1g averages	
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 1 07-11-16.da5:0\Channel 102 Variability)	
Max. 1 at (11.82, -132.20, -2.90) mm	1.19 W/kg (Power Scale Factor: 1.05)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 1 07-11-16.da5:0\Channel 110 Test)	
Max. 2 at (11.82, -132.17, -2.94) mm	1.13 W/kg (Power Scale Factor: 1.02)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 1 07-11-16.da5:0\Channel 122 Test)	
Max. 3 at (11.85, -132.20, -3.05) mm	1.19 W/kg (Power Scale Factor: 1.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 1 07-11-16.da5:0\Channel 138 Variability)	
Max. 4 at (11.82, -132.18, -3.07) mm	1.18 W/kg (Power Scale Factor: 1.07)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5800 MHz\Edge 1 OFDM Antenna 2 08-11-16.da5:0\Channel 155 Test)	
Max. 5 at (9.21, 130.44, -3.11) mm	0.41 W/kg (Power Scale Factor: 1.06)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 2 04-11-16.da5:0\Channel 122 Test)	
Max. 6 at (8.80, 110.64, -3.39) mm	0.46 W/kg (Power Scale Factor: 1.08)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 2 04-11-16.da5:0\Channel 138 Test)	
Max. 7 at (11.00, 108.64, -3.49) mm	0.42 W/kg (Power Scale Factor: 1.07)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0\Channel 38 Test)	
Max. 8 at (8.98, 125.03, -3.05) mm	5.97 W/kg (Power Scale Factor: 11.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0\Channel 46 Test)	
Max. 9 at (8.99, 123.24, -3.06) mm	0.65 W/kg (Power Scale Factor: 1.05)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0\Channel 54 Test)	
Max. 10 at (9.01, 122.46, -3.07) mm	0.62 W/kg (Power Scale Factor: 1.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0\Channel 62 Test)	
Max. 11 at (9.00, 120.83, -3.15) mm	0.60 W/kg (Power Scale Factor: 1.04)
Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [mm]: 0.05 / Separation ratio [W/kg/mm]: 70.67



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Summary of the highest SAR results considered for multiband evaluation 5.8 GHz:

Find distance of maxima	
Maxima and position w.r.t. Grid Reference Point   associated 1g averages	
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5800 MHz\Edge 1 OFDM Antenna 1 08-11-16.da5:0/Channel 155 Test)	
Max. 1 at (12.81, -130.18, -3.14) mm	1.20 W/kg (Power Scale Factor: 1.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5800 MHz\Edge 1 OFDM Antenna 2 08-11-16.da5:0/Channel 155 Test)	
Max. 2 at (9.21, 130.44, -3.11) mm	0.41 W/kg (Power Scale Factor: 1.06)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 2 04-11-16.da5:0/Channel 122 Test)	
Max. 3 at (8.80, 110.64, -3.39) mm	0.46 W/kg (Power Scale Factor: 1.08)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5600 MHz\Edge 1 OFDM Antenna 2 04-11-16.da5:0/Channel 138 Test)	
Max. 4 at (11.00, 108.64, -3.49) mm	0.42 W/kg (Power Scale Factor: 1.07)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0/Channel 38 Test)	
Max. 5 at (8.98, 125.03, -3.05) mm	0.56 W/kg (Power Scale Factor: 1.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0/Channel 46 Test)	
Max. 6 at (8.99, 123.24, -3.06) mm	0.65 W/kg (Power Scale Factor: 1.05)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0/Channel 54 Test)	
Max. 7 at (9.01, 122.46, -3.07) mm	0.62 W/kg (Power Scale Factor: 1.04)
Zoom Scan (C:\SAR Results\SAR Results 2016\October\M161026 Fujitsu Progress with WLAN & BLTH\5200 MHz\Edge 1 OFDM Antenna 2 03-11-16.da5:0/Channel 62 Test)	
Max. 8 at (9.00, 120.83, -3.15) mm	0.60 W/kg (Power Scale Factor: 1.04)
<b>Distances and Separation Ratios</b>	
Max. 1 - Max. 2	Distance [mm]: 260.65 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 3	Distance [mm]: 240.85 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 4	Distance [mm]: 238.83 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 5	Distance [mm]: 255.24 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 6	Distance [mm]: 253.45 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 7	Distance [mm]: 252.67 / Separation ratio [W/kg/mm]: 0.01
Max. 1 - Max. 8	Distance [mm]: 251.04 / Separation ratio [W/kg/mm]: 0.01

