



# FCC RADIO TEST REPORT

**FCC ID** : EJE-WB0109  
**Equipment** : STYLISTIC Q739  
**Brand Name** : FUJITSU  
**Model Name** : PQ13B  
**Applicant** : FUJITSU CLIENT COMPUTING LIMITED  
1-1, Kamikodanaka 4-chome,  
Nakahara-ku, Kawasaki, 211-8588 Japan  
**Manufacturer** : FUJITSU CLIENT COMPUTING LIMITED  
1-1, Kamikodanaka 4-chome,  
Nakahara-ku, Kawasaki, 211-8588 Japan  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Dec. 17, 2018 and testing was started from Dec. 19, 2018 and completed on Jan. 27, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	5
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency and Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	9
<b>3 Test Result .....</b>	<b>10</b>
3.1 Output Power Measurement.....	10
3.2 Radiated Band Edges and Spurious Emission Measurement .....	11
3.3 AC Conducted Emission Measurement.....	15
3.4 Antenna Requirements .....	17
<b>4 List of Measuring Equipment.....</b>	<b>18</b>
<b>5 Uncertainty of Evaluation .....</b>	<b>20</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(b)	Power Output Measurement	Pass	-
3.2	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 1.88 dB at 2389.940 MHz
3.3	15.207	AC Conducted Emission	Pass	Under limit 8.79 dB at 0.191 MHz
3.4	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Nancy Yang**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and Wi-Fi 5GHz 802.11a/n/ac

Product Specification subjective to this standard	
<b>Integrated WLAN Module</b>	Brand Name: Intel Model Name: 9560NGW
<b>Antenna Type</b>	WLAN: <Ant. 1> PIFA Antenna <Ant. 2> PIFA Antenna Bluetooth: PIFA Antenna

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.3 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH16-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No. TW1190 and TW0007



## 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

### Single Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


### MIMO Antenna

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + Adapter



### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m

### 2.5 EUT Operation Test Setup

The RF test items, utility “DRTU” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

### 3 Test Result

#### 3.1 Output Power Measurement

##### 3.1.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.3 PKPM1
2. For Average Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.2.3.1 Method AVGPM.
3. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.
6. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Peak Output Power

Please refer to Appendix A.

##### 3.1.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



### 3.2 Radiated Band Edges and Spurious Emission Measurement

#### 3.2.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.




### 3.2.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.2.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.2.7 Duty Cycle

Please refer to Appendix E.

### 3.2.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix C and D.



### 3.3 AC Conducted Emission Measurement

#### 3.3.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

### 3.3.4 Test Setup



### 3.3.5 Test Result of AC Conducted Emission

Please refer to Appendix B.





### 3.4 Antenna Requirements

#### 3.4.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

#### 3.4.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

#### 3.4.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain =  $G_{ANT}$  + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain =  $10 \log(N_{ANT}/N_{SS}=1)$  dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ .

Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain  $G_{ANT}$  is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>				
	Ant. 1 (dBi)	Ant. 2 (dBi)	DG for Power (dBi)	Power Limit Reduction (dB)
2.4 GHz	1.18	-0.73	1.18	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1218006	N/A	Oct. 08, 2018	Dec. 19, 2018~ Jan. 21, 2019	Oct. 07, 2019	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207363	300MHz~40GHz	Oct. 08, 2018	Dec. 19, 2018~ Jan. 21, 2019	Oct. 07, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Dec. 19, 2018~ Jan. 21, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Mar. 01, 2018	Dec. 19, 2018~ Jan. 21, 2019	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 27, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Jan. 27, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jan. 27, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jan. 27, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 27, 2019	N/A	Conduction (CO05-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Sep. 14, 2018	Jan. 27, 2019	Sep. 13, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 27, 2019	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 08, 2018	Jan. 27, 2019	Nov. 07, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 23, 2017	Jan. 03, 2019~ Jan. 11, 2019	Nov. 22, 2019	Radiation (03CH16-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Jan. 03, 2019~ Jan. 11, 2019	Jul. 15, 2019	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 576	18GHz ~ 40GHz	May 08, 2018	Jan. 03, 2019~ Jan. 11, 2019	May 07, 2019	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Jan. 03, 2019~ Jan. 11, 2019	N/A	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0054001	1GHz~18GHz	Apr. 16, 2018	Jan. 03, 2019~ Jan. 11, 2019	Apr. 15, 2019	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY572901 11	3Hz~26.5GHz	Nov. 29, 2018	Jan. 03, 2019~ Jan. 11, 2019	Nov. 28, 2019	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-152 2	1G~18GHz	Sep. 07, 2018	Jan. 03, 2019~ Jan. 11, 2019	Sep. 06, 2019	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532701 47	1GHz~26.5GHz	Feb. 02, 2018	Jan. 03, 2019~ Jan. 11, 2019	Feb. 01, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Jan. 22, 2018	Jan. 03, 2019~ Jan. 11, 2019	Jan. 21, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	335041/4	30M-18G	Jan. 22, 2018	Jan. 03, 2019~ Jan. 11, 2019	Jan. 21, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/ 4	30M~18GHz	Jan. 22, 2018	Jan. 03, 2019~ Jan. 11, 2019	Jan. 21, 2019	Radiation (03CH16-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2018	Jan. 03, 2019~ Jan. 11, 2019	Apr. 16, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/ 4	30M~18GHz	Jan. 22, 2018	Jan. 03, 2019~ Jan. 11, 2019	Jan. 21, 2019	Radiation (03CH16-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL6111D&0 0802N1D01N- 06	47020&06	30MHz to 1GHz	Oct. 13, 2018	Jan. 03, 2019~ Jan. 11, 2019	Oct. 12, 2019	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1000MHz	Oct. 02, 2018	Jan. 03, 2019~ Jan. 11, 2019	Oct. 01, 2019	Radiation (03CH16-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.2
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.9
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.8
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.9
---	-----

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Derek Hsu	Temperature:	21~25	°C
Test Date:	2018/12/19~2018/12/21	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**Peak Output Power**

2.4GHz Band							
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)		
					Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	16.51	16.48	-
11b	1Mbps	1	6	2437	16.50	16.49	-
11b	1Mbps	1	11	2462	16.48	16.47	-
11b	1Mbps	1	12	2467	16.56	16.55	-
11b	1Mbps	1	13	2472	16.30	16.29	-
11g	6Mbps	1	1	2412	19.90	19.73	-
11g	6Mbps	1	6	2437	19.82	19.81	-
11g	6Mbps	1	11	2462	20.06	20.04	-
11g	6Mbps	1	12	2467	18.22	18.21	-
11g	6Mbps	1	13	2472	-1.04	-1.74	-
HT20	MCS0	1	1	2412	20.10	19.87	-
HT20	MCS0	1	6	2437	20.13	20.12	-
HT20	MCS0	1	11	2462	20.18	20.17	-
HT20	MCS0	1	12	2467	18.22	17.53	-
HT20	MCS0	1	13	2472	-1.05	-1.58	-
HT40	MCS0	1	3	2422	19.81	19.54	-
HT40	MCS0	1	6	2437	20.28	20.20	-
HT40	MCS0	1	9	2452	19.55	19.36	-
HT40	MCS0	1	10	2457	16.55	16.52	-
HT40	MCS0	1	11	2462	10.29	11.17	-
HT20	MCS0	2	1	2412	19.61	19.50	22.57
HT20	MCS0	2	6	2437	19.97	19.78	22.89
HT20	MCS0	2	11	2462	19.46	19.66	22.57
HT20	MCS0	2	12	2467	15.84	15.91	18.89
HT20	MCS0	2	13	2472	-2.52	-2.91	0.30
HT40	MCS0	2	3	2422	18.17	18.25	21.22
HT40	MCS0	2	6	2437	19.35	19.28	22.33
HT40	MCS0	2	9	2452	18.11	18.29	21.21
HT40	MCS0	2	10	2457	16.42	16.62	19.53
HT40	MCS0	2	11	2462	9.84	10.08	12.97

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Average Output Power**

2.4GHz Band									
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.04	0.05	14.77	14.65	
11b	1Mbps	1	6	2437	0.04	0.05	14.71	14.70	
11b	1Mbps	1	11	2462	0.04	0.05	14.75	14.74	
11b	1Mbps	1	12	2467	0.04	0.05	14.79	14.75	
11b	1Mbps	1	13	2472	0.04	0.05	14.65	14.64	
11g	6Mbps	1	1	2412	0.08	0.08	14.73	14.58	
11g	6Mbps	1	6	2437	0.08	0.08	14.64	14.63	
11g	6Mbps	1	11	2462	0.08	0.08	14.86	14.83	
11g	6Mbps	1	12	2467	0.08	0.08	13.24	12.91	
11g	6Mbps	1	13	2472	0.08	0.08	-6.12	-6.87	
HT20	MCS0	1	1	2412	0.09	0.09	14.75	14.74	
HT20	MCS0	1	6	2437	0.09	0.09	14.78	14.77	
HT20	MCS0	1	11	2462	0.09	0.09	14.83	14.82	
HT20	MCS0	1	12	2467	0.09	0.09	13.31	12.51	
HT20	MCS0	1	13	2472	0.09	0.09	-6.19	-6.63	
HT40	MCS0	1	3	2422	0.18	0.18	14.66	14.11	
HT40	MCS0	1	6	2437	0.18	0.18	14.70	14.68	
HT40	MCS0	1	9	2452	0.18	0.18	14.18	13.70	
HT40	MCS0	1	10	2457	0.18	0.18	10.64	10.22	
HT40	MCS0	1	11	2462	0.18	0.18	2.81	3.44	
HT20	MCS0	2	1	2412	0.11	0.12	14.15	14.21	17.19
HT20	MCS0	2	6	2437	0.11	0.12	14.63	14.57	17.61
HT20	MCS0	2	11	2462	0.11	0.12	14.04	14.32	17.19
HT20	MCS0	2	12	2467	0.11	0.12	10.73	10.68	13.72
HT20	MCS0	2	13	2472	0.11	0.12	-8.02	-8.08	-5.04
HT40	MCS0	2	3	2422	0.23	0.20	12.63	12.60	15.63
HT40	MCS0	2	6	2437	0.23	0.20	13.64	13.55	16.61
HT40	MCS0	2	9	2452	0.23	0.20	12.60	12.62	15.62
HT40	MCS0	2	10	2457	0.23	0.20	10.09	10.06	13.09
HT40	MCS0	2	11	2462	0.23	0.20	2.15	2.46	5.32

Note: Measured power (dBm) has offset with cable loss.



## Appendix B. AC Conducted Emission Test Results


Test Engineer :	Eric Jeng	Temperature :	22~25°C
		Relative Humidity :	52~55%



# EUT Information

Report NO : 8D1723  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	24.03	55.88	31.85	L1	OFF	19.5
0.152250	45.56	---	65.88	20.32	L1	OFF	19.5
0.190500	---	36.54	54.02	17.48	L1	OFF	19.5
0.190500	55.23	---	64.02	8.79	L1	OFF	19.5
0.208500	---	34.76	53.27	18.51	L1	OFF	19.5
0.208500	53.07	---	63.27	10.20	L1	OFF	19.5
0.255750	---	30.10	51.57	21.47	L1	OFF	19.5
0.255750	47.95	---	61.57	13.62	L1	OFF	19.5
0.316500	---	22.82	49.80	26.98	L1	OFF	19.5
0.316500	42.64	---	59.80	17.16	L1	OFF	19.5
3.770250	---	15.97	46.00	30.03	L1	OFF	19.6
3.770250	24.95	---	56.00	31.05	L1	OFF	19.6
12.147000	---	29.26	50.00	20.74	L1	OFF	19.7
12.147000	35.15	---	60.00	24.85	L1	OFF	19.7

## EUT Information

Report NO : 8D1723  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	23.20	55.88	32.68	N	OFF	19.5
0.152250	45.16	---	65.88	20.72	N	OFF	19.5
0.190500	---	35.73	54.02	18.29	N	OFF	19.5
0.190500	54.27	---	64.02	9.75	N	OFF	19.5
0.208500	---	33.55	53.27	19.72	N	OFF	19.5
0.208500	52.04	---	63.27	11.23	N	OFF	19.5
0.255750	---	29.28	51.57	22.29	N	OFF	19.5
0.255750	46.86	---	61.57	14.71	N	OFF	19.5
0.321000	---	25.25	49.68	24.43	N	OFF	19.5
0.321000	41.92	---	59.68	17.76	N	OFF	19.5
11.940000	---	31.44	50.00	18.56	N	OFF	19.7
11.940000	38.17	---	60.00	21.83	N	OFF	19.7



### Appendix C. Radiated Spurious Emission

Test Engineer :	Jacky Hung, CR Liao, and Andy Yang	Temperature :	23~25°C
		Relative Humidity :	55~57%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 06 2437MHz		2367.54	57.25	-16.75	74	41.78	27.18	18.28	29.99	100	71	P	H
		2388.4	44.76	-9.24	54	29.21	27.23	18.31	29.99	100	71	A	H
	*	2437	107.77	-	-	92.05	27.35	18.35	29.98	100	71	P	H
	*	2437	103.37	-	-	87.65	27.35	18.35	29.98	100	71	A	H
		2494.61	58.18	-15.82	74	42.26	27.49	18.39	29.96	100	71	P	H
		2484.95	45.56	-8.44	54	29.69	27.46	18.38	29.97	100	71	A	H
		2369.36	57.29	-16.71	74	41.8	27.19	18.29	29.99	325	105	P	V
		2388.54	44.61	-9.39	54	29.06	27.23	18.31	29.99	325	105	A	V
	*	2437	107.09	-	-	91.37	27.35	18.35	29.98	325	105	P	V
	*	2437	103.07	-	-	87.35	27.35	18.35	29.98	325	105	A	V
		2484.67	57.77	-16.23	74	41.9	27.46	18.38	29.97	325	105	P	V
		2484.81	45.38	-8.62	54	29.51	27.46	18.38	29.97	325	105	A	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11b CH 06 2437MHz		4874	41.7	-32.3	74	55.04	31.35	13.84	58.53	100	0	P	H	
		7311	43.08	-30.92	74	50.76	36.07	15.22	58.97	100	0	P	H	
													H	
													H	
			4874	41.74	-32.26	74	55.08	31.35	13.84	58.53	100	0	P	V
			7311	44.36	-29.64	74	52.04	36.07	15.22	58.97	100	0	P	V
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		2386.3	62.03	-11.97	74	46.48	27.23	18.31	29.99	100	71	P	H
		2389.94	52.12	-1.88	54	36.55	27.24	18.32	29.99	100	71	A	H
	*	2422	105.16	31.16	74	89.49	27.31	18.34	29.98	100	71	P	H
	*	2422	97.37	43.37	54	81.7	27.31	18.34	29.98	100	71	A	H
		2491.53	57.7	-16.3	74	41.81	27.48	18.38	29.97	100	71	P	H
		2483.9	47.65	-6.35	54	31.78	27.46	18.38	29.97	100	71	A	H
		2388.26	60.94	-13.06	74	45.39	27.23	18.31	29.99	344	105	P	V
		2389.94	51.61	-2.39	54	36.04	27.24	18.32	29.99	344	105	A	V
	*	2422	104.36	30.36	74	88.69	27.31	18.34	29.98	344	105	P	V
	*	2422	96.79	42.79	54	81.12	27.31	18.34	29.98	344	105	A	V
		2495.31	57.55	-16.45	74	41.63	27.49	18.39	29.96	344	105	P	V
	2489.57	47.8	-6.2	54	31.92	27.47	18.38	29.97	344	105	A	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		4844	41.41	-32.59	74	54.86	31.29	13.79	58.53	100	0	P	H
		7266	43.54	-30.46	74	51.35	35.94	15.26	59.01	100	0	P	H
													H
													H
		4844	40.39	-33.61	74	53.84	31.29	13.79	58.53	100	0	P	V
		7266	42.88	-31.12	74	50.69	35.94	15.26	59.01	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz  
2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz 802.11n HT40 LF		79.95	22.33	-17.67	40	40	13.78	0.94	32.39	-	-	P	H	
		148.53	36.32	-7.18	43.5	49.35	17.85	1.48	32.36	100	0	P	H	
		241.95	34.6	-11.4	46	46.64	18.15	2.19	32.38	-	-	P	H	
		361.6	35.7	-10.3	46	43.75	21.51	2.91	32.47	-	-	P	H	
		576.5	26.01	-19.99	46	29.74	25.22	3.71	32.66	-	-	P	H	
		867.7	31.56	-14.44	46	30.07	28.81	4.65	31.97	-	-	P	H	
														H
														H
														H
														H
														H
														H
			57.81	26.16	-13.84	40	44.93	12.62	1.013	32.42	-	-	P	V
			147.72	30.27	-13.23	43.5	43.27	17.88	1.48	32.36	-	-	P	V
			234.39	29.22	-16.78	46	42.03	17.45	2.12	32.38	-	-	P	V
			350.4	36.66	-9.34	46	45.11	21.2	2.82	32.47	100	0	P	V
			579.3	26.48	-19.52	46	30.16	25.26	3.72	32.66	-	-	P	V
			787.2	30.29	-15.71	46	30.28	28	4.39	32.38	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11g (Band Edge @ 3m)**

WIFI Ant. 2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11g CH 01 2412MHz		2322.705	56.41	-17.59	74	41.13	27.07	18.22	30.01	100	296	P	H	
		2390	44.52	-9.48	54	28.95	27.24	18.32	29.99	100	296	A	H	
	*	2412	104.71	-	-	89.07	27.29	18.34	29.99	100	296	P	H	
	*	2412	96.46	-	-	80.82	27.29	18.34	29.99	100	296	A	H	
													H	
														H
			2365.545	55.85	-18.15	74	40.38	27.18	18.28	29.99	332	169	P	V
			2390	44.24	-9.76	54	28.67	27.24	18.32	29.99	332	169	A	V
	*		2412	101.37	-	-	85.73	27.29	18.34	29.99	332	169	P	V
	*		2412	93.18	-	-	77.54	27.29	18.34	29.99	332	169	A	V
														V
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.													

**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11g CH 01 2412MHz		4824	38.44	-35.56	74	51.97	31.25	13.76	58.54	100	0	P	H	
													H	
													H	
													H	
			4824	39.22	-34.78	74	52.75	31.25	13.76	58.54	100	0	P	V
														V
														V
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.													



**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 06 2437MHz		2389.1	55.95	-18.05	74	40.4	27.23	18.31	29.99	115	301	P	H
		2378.74	45.36	-8.64	54	29.84	27.21	18.3	29.99	115	301	A	H
	*	2437	105.06	-	-	89.34	27.35	18.35	29.98	115	301	P	H
	*	2437	97.34	-	-	81.62	27.35	18.35	29.98	115	301	A	H
		2485.79	56.65	-17.35	74	40.77	27.47	18.38	29.97	115	301	P	H
		2492.23	45.95	-8.05	54	30.04	27.48	18.39	29.96	115	301	A	H
		2376.36	56.07	-17.93	74	40.56	27.2	18.3	29.99	368	169	P	V
		2389.8	45.28	-8.72	54	29.71	27.24	18.32	29.99	368	169	A	V
	*	2437	102.32	-	-	86.6	27.35	18.35	29.98	368	169	P	V
	*	2437	94.33	-	-	78.61	27.35	18.35	29.98	368	169	A	V
		2484.81	56.54	-17.46	74	40.67	27.46	18.38	29.97	368	169	P	V
		2489.78	45.71	-8.29	54	29.82	27.48	18.38	29.97	368	169	A	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 06 2437MHz		4874	38.53	-35.47	74	51.87	31.35	13.84	58.53	100	0	P	H	
		7311	43.07	-30.93	74	50.75	36.07	15.22	58.97	100	0	P	H	
													H	
													H	
			4874	38.97	-35.03	74	52.31	31.35	13.84	58.53	100	0	P	V
			7311	42.66	-31.34	74	50.34	36.07	15.22	58.97	100	0	P	V
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against limit line.													





2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 06 2437MHz		2339.26	56.56	-17.44	74	41.21	27.11	18.24	30	118	318	P	H
		2388.26	45.17	-8.83	54	29.62	27.23	18.31	29.99	118	318	A	H
	*	2437	110.41	-	-	94.69	27.35	18.35	29.98	118	318	P	H
	*	2437	102.92	-	-	87.2	27.35	18.35	29.98	118	318	A	H
		2488.59	56.8	-17.2	74	40.92	27.47	18.38	29.97	118	318	P	H
		2496.22	46.16	-7.84	54	30.24	27.49	18.39	29.96	118	318	A	H
		2362.64	56.67	-17.33	74	41.22	27.17	18.28	30	355	88	P	V
		2381.12	44.97	-9.03	54	29.45	27.21	18.3	29.99	355	88	A	V
	*	2437	108.34	-	-	92.62	27.35	18.35	29.98	355	88	P	V
	*	2437	100.7	-	-	84.98	27.35	18.35	29.98	355	88	A	V
		2488.03	56.93	-17.07	74	41.05	27.47	18.38	29.97	355	88	P	V
		2487.68	45.8	-8.2	54	29.92	27.47	18.38	29.97	355	88	A	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 06 2437MHz		4874	38.83	-35.17	74	52.17	31.35	13.84	58.53	100	0	P	H	
		7311	42.63	-31.37	74	50.31	36.07	15.22	58.97	100	0	P	H	
													H	
													H	
		4874	38.86	-35.14	74	52.2	31.35	13.84	58.53	100	0	P	V	
		7311	42.83	-31.17	74	50.51	36.07	15.22	58.97	100	0	P	V	
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		2389.94	58.7	-15.3	74	43.13	27.24	18.32	29.99	100	297	P	H
		2389.94	48.67	-5.33	54	33.1	27.24	18.32	29.99	100	297	A	H
	*	2422	105.59	-	-	89.92	27.31	18.34	29.98	100	297	P	H
	*	2422	97.62	-	-	81.95	27.31	18.34	29.98	100	297	A	H
		2489.64	57.08	-16.92	74	41.19	27.48	18.38	29.97	100	297	P	H
		2489.01	46.72	-7.28	54	30.84	27.47	18.38	29.97	100	297	A	H
		2389.1	56.92	-17.08	74	41.37	27.23	18.31	29.99	354	90	P	V
		2389.52	47.07	-6.93	54	31.52	27.23	18.31	29.99	354	90	A	V
	*	2422	103.45	-	-	87.78	27.31	18.34	29.98	354	90	P	V
	*	2422	95.71	-	-	80.04	27.31	18.34	29.98	354	90	A	V
		2494.75	57.44	-16.56	74	41.52	27.49	18.39	29.96	354	90	P	V
		2493.91	46.96	-7.04	54	31.04	27.49	18.39	29.96	354	90	A	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT40 CH 03 2422MHz		4844	39.78	-34.22	74	53.23	31.29	13.79	58.53	100	0	P	H	
		7266	42.55	-31.45	74	50.36	35.94	15.26	59.01	100	0	P	H	
													H	
													H	
		4844	39.49	-34.51	74	52.94	31.29	13.79	58.53	100	0	P	V	
		7266	42.55	-31.45	74	50.36	35.94	15.26	59.01	100	0	P	V	
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
A		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix D. Radiated Spurious Emission Plots





Test Engineer :	Jacky Hung, CR Liao, and Andy Yang	Temperature :	23~25°C
		Relative Humidity :	55~57%

**Note symbol**



-L	Low channel location
-R	High channel location







**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11b (Band Edge @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>
<b>Avg.</b>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	Left blank
Avg.	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 8D1723</p>











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY  Condition : PEAK_BE_74 3m 91200_1522 VERTICAL  RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 8D1723</p>	Left blank
Avg.	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY  Condition : AVG_BE_54 3m 91200_1522 VERTICAL  RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 8D1723</p>	Left blank



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
<b>Avg.</b>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>	<p>Left Blank</p>
<p><b>Avg.</b></p>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 8D1723</p>	<p>Left Blank</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	<p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Vertical	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>
<p><b>Avg.</b></p>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11b (Harmonic @ 3m)**

<b>WIFI</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11b CH06 2437MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-HY          Condition : PEAK_74 3m 9120D_1522 HORIZONTAL          Detector : Peak          Project : 8D1723</p>	<p>Site : 03CH16-HY          Condition : PEAK_74 3m 9120D_1522 VERTICAL          Detector : Peak          Project : 8D1723</p>



**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)**

<b>WIFI</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11n HT40 CH03 2422MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 8D1723</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 9120D_1522 VERTICAL Detector : Peak Project : 8D1723</p>







Emission below 1GHz  
2.4GHz WIFI 802.11n HT40 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT40 LF	
1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-HY Condition : QP 3m B1LOG_47020406 HORIZONTAL Detector : Peak Project : 801723</p>	<p>Site : 03CH16-HY Condition : QP 3m B1LOG_47020406 VERTICAL Detector : Peak Project : 801723</p>









**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11g (Band Edge @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
2	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
<b>Avg.</b>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:0.010KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:0.010KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
2	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>





2.4GHz 2400~2483.5MHz





WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
2	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	<p>Site : 03CH16-HY            Condition : AV6_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Site : 03CH16-HY            Condition : AV6_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
2	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>
<p><b>Avg.</b></p>	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
2	Vertical	Fundamental
Peak	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-05</p> <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
2	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	Left Blank
Avg.	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	Left Blank



2.4GHz 2400~2483.5MHz  
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-11Y Condition : PEAK_74 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 8D1723</p>	<p>Site : 03CH16-11Y Condition : PEAK_74 3m 9120D_1522 VERTICAL Detector : Peak Project : 8D1723</p>







**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

<b>WIFI</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11n HT20 CH06 2437MHz</b>	
<b>2</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-HY          Condition : PEAK_74 3m 9120D_1522 HORIZONTAL          Detector : Peak          Project : 8D1723</p>	<p>Site : 03CH16-HY          Condition : PEAK_74 3m 9120D_1522 VERTICAL          Detector : Peak          Project : 8D1723</p>











**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
<b>Avg.</b>	 <p>Site : 03CH16-HY            Condition : AV6_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AV6_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>
<p><b>Avg.</b></p>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Vertical	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            Detector : Peak            Project : 8D1723</p>	<p>Left Blank</p>
<p><b>Avg.</b></p>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            Detector : Peak            Project : 8D1723</p>	<p>Left Blank</p>







**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
<b>Avg.</b>	 <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 8D1723</p>	Left Blank
Avg.	<p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 8D1723</p>	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>
Avg.	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : AVG_BE_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>	 <p>Date: 2019-01-07</p> <p>Site : 03CH16-HY            Condition : AVG_54 3m 91200_1522 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 8D1723</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL Detector : Peak Project : 8D1723</p>	Left blank
Avg.	<p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL Detector : Peak Project : 8D1723</p>	Left blank





2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 8D1723</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 8D1723</p>



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

Table with 2 columns: Horizontal and Vertical. Each column contains a graph of Level (dBuV/m) vs Frequency (MHz) with Peak and Avg. markers. Includes metadata like Site, Condition, Detector, and Project.




### Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor (dB)
1	802.11b	99.00	12330.00	0.08	10Hz	0.04
2	802.11g	98.09	2050.00	0.49	10Hz	0.08
2	2.4GHz 802.11n HT20	97.95	1910.00	0.52	1kHz	0.09
1+2	2.4GHz 802.11n HT20 for Ant. 1	97.44	1905.00	0.52	1kHz	0.11
1+2	2.4GHz 802.11n HT20 for Ant. 2	97.19	1905.00	0.52	1kHz	0.12
1	2.4GHz 802.11n HT40	95.90	935.00	1.07	3kHz	0.18
1+2	2.4GHz 802.11n HT40 for Ant. 1	94.92	935.00	1.07	3kHz	0.23
1+2	2.4GHz 802.11n HT40 for Ant. 2	95.43	940.00	1.06	3kHz	0.20




<Ant. 1>

802.11b



Date: 18.DEC.2018 15:12:31

802.11n HT40




Date: 19.DEC.2018 10:39:27




<Ant. 2>

802.11g



Date: 18.DEC.2018 15:46:54

802.11n HT20




Date: 18.DEC.2018 16:09:03




MIMO <Ant. 1>

802.11n HT20



Date: 19.DEC.2018 10:15:57

802.11n HT40




Date: 19.DEC.2018 11:16:31




MIMO <Ant. 2>

802.11n HT20



Date: 19.DEC.2018 10:16:49

802.11n HT40



Date: 19.DEC.2018 11:16:54