



MIMO-B, 802.11n20, HT8

Channel 11 - BE High Freq Section (restricted)




Channel 12 - BE High Freq Section (restricted)




Test Report N° 170919-03.TR04

Channel 13 - BE High Freq Section (restricted)




Channel 11 - BE High Freq Section RMS within 2MHz (restricted)




Test Report N° 170919-03.TR04

Channel 12 - BE High Freq Section RMS within 2MHz (restricted)




Channel 13 - BE High Freq Section RMS within 2MHz (restricted)




MIMO-A, 802.11n40, HT8

Channel 9F - BE High Freq Section (restricted)




Channel 10F - BE High Freq Section (restricted)




Test Report N° 170919-03.TR04

Channel 11F - BE High Freq Section (restricted)




Channel 9F - BE High Freq Section RMS within 2MHz (restricted)




Test Report N° 170919-03.TR04

Channel 10F - BE High Freq Section RMS within 2MHz (restricted)




Channel 11F - BE High Freq Section RMS within 2MHz (restricted)




MIMO-B, 802.11n40, HT8

Channel 9F - BE High Freq Section (restricted)




Channel 10F - BE High Freq Section (restricted)




Test Report N° 170919-03.TR04

Channel 11F - BE High Freq Section (restricted)




Channel 9F - BE High Freq Section RMS within 2MHz (restricted)




Test Report N° 170919-03.TR04

Channel 10F - BE High Freq Section RMS within 2MHz (restricted)




Channel 11F - BE High Freq Section RMS within 2MHz (restricted)




B.3.7 Out of band emissions - spurious

SISO-A, 802.11b, 1Mbps


Channel 7 - Spurious 1 Delta Marker Measurement



Channel 7 - Spurious 2 Delta Marker Measurement




Channel 7 - Spurious 3 Delta Marker Measurement




Date: 6 OCT 2017 11:11:05

SISO-B, 802.11b, 1Mbps

Channel 7 - Spurious 1 Delta Marker Measurement




Channel 7 - Spurious 2 Delta Marker Measurement



Test Report N° 170919-03.TR04


Channel 7 - Spurious 3 Delta Marker Measurement




Date: 9 OCT 2017 16:03:08

SISO-A, 802.11g, 6Mbps

Channel 7 - Spurious 1 Delta Marker Measurement




Channel 7 - Spurious 2 Delta Marker Measurement




Test Report N° 170919-03.TR04

Channel 7 - Spurious 3 Delta Marker Measurement




SISO-B, 802.11g, 6Mbps


Channel 7 - Spurious 1 Delta Marker Measurement



Channel 7 - Spurious 2 Delta Marker Measurement




Channel 7 - Spurious 3 Delta Marker Measurement




Date: 9 OCT 2017 17:20:45

SISO-A, 802.11n20, HT0


Channel 7 - Spurious 1 Delta Marker Measurement



Channel 7 - Spurious 2 Delta Marker Measurement




Channel 7 - Spurious 3 Delta Marker Measurement




Date: 6 OCT 2017 17:04:46

SISO-B, 802.11n20, HT0


Channel 7 - Spurious 1 Delta Marker Measurement



Channel 7 - Spurious 2 Delta Marker Measurement




Channel 7 - Spurious 3 Delta Marker Measurement




SISO-A, 802.11n40, HT0


Channel 7F - Spurious 1 Delta Marker Measurement



Channel 7F - Spurious 2 Delta Marker Measurement




Channel 7F - Spurious 3 Delta Marker Measurement




Date: 6 OCT 2017 17:47:46

SISO-B, 802.11n40, HT0

Channel 7F - Spurious 1 Delta Marker Measurement




Channel 7F - Spurious 2 Delta Marker Measurement




Test Report N° 170919-03.TR04

Channel 7F - Spurious 3 Delta Marker Measurement




MIMO-A, 802.11n20, HT8


Channel 7 - Spurious 1 Delta Marker Measurement



Channel 7 - Spurious 2 Delta Marker Measurement




Channel 7 - Spurious 3 Delta Marker Measurement




Date: 9.OCT.2017 11:00:39

MIMO-B, 802.11n20, HT8

Channel 7 - Spurious 1 Delta Marker Measurement




Channel 7 - Spurious 2 Delta Marker Measurement



Test Report N° 170919-03.TR04


Channel 7 - Spurious 3 Delta Marker Measurement




Date: 15 NOV 2017 17:21:19

MIMO-A, 802.11n40, HT8


Channel 7F - Spurious 1 Delta Marker Measurement



Channel 7F - Spurious 2 Delta Marker Measurement




Channel 7F - Spurious 3 Delta Marker Measurement




MIMO-B, 802.11n40, HT8

Channel 7F - Spurious 1 Delta Marker Measurement




Channel 7F - Spurious 2 Delta Marker Measurement



Test Report N° 170919-03.TR04

Channel 7F - Spurious 3 Delta Marker Measurement



Annex C. Test Results BLE

C.1 Test Results BLE


C.1.1 6dB & 99% Bandwidth

Test limits

FCC part	RSS part	Limits
15.247 (a) (2)	RSS-247 Clause 5.2 (a)	Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test procedure

The setup below was used to measure the 6dB & 99% Bandwidth. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.




Results tables

Mode	Channel	Frequency [MHz]	6dB BW [MHz]	99% BW [MHz]
BLE	0	2402	0.64	1.15
	19	2440	0.64	1.15
	39	2480	0.65	1.15


Results screenshot



BLE



6dB BW – CH0



99% BW – CH0







C.1.2 Maximum Output Power and antenna gain

Test limits

	Limits
FCC Part 15.247 (b) (3)	<p>(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:</p> <p>(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level.</p> <p>(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.</p>
RSS-247 Clause 5.4 (d)	<p>For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).</p> <p>As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode</p>


Test procedure:

The Maximum peak conducted output power was measured using the *RBW ≥ DTS bandwidth* method defined in paragraph 9.1.1 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The Maximum conducted average output power was measured using the channel integration method according to Method AVGSA-2, defined in paragraph 9.2.2.4 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power. The declared maximum antenna gain is 3.24dBi.

The setup below was used to measure the maximum conducted output power. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.



Results tables

Mode	Meas. Duty Cycle [%]	CH	Frequency [MHz]	Peak Power [dBm]		
				Measured Conducted Output Power	EIRP	Peak Output Power [mW]
BLE	63.2	0	2402	8.30	11.54	6.76
		19	2440	8.26	11.50	6.70
		39	2480	8.74	11.98	7.48

Max Value

Min Value


Mode	Meas. Duty Cycle [%]	CH	Frequency [MHz]	Average Output Power* [dBm]			
				Maximum Conducted Output Power	Maximum Conducted Output Power Duty cycle Compensated	EIRP	Average Output Power [mW]
BLE	63.2	0	2402	6.09	8.17	11.41	6.55
		19	2440	6.07	8.15	11.39	6.52
		39	2480	6.54	8.62	11.86	7.27

* Output Power RMS values are shown for indicative purpose only


Results screenshot

BLE

Max Power Peak – CH0




Max Power RMS – CH0




BLE

Max Power Peak – CH19



Date: 10 OCT 2017 16:20:09


Max Power RMS – CH19



Date: 10 OCT 2017 16:19:53


BLE

Max Power Peak – CH39



Date: 10/OCT/2017 16:25:23

Max Power RMS – CH39



Date: 10/OCT/2017 16:25:08

C.1.3 Power Spectral Density

Test limits


FCC part	RSS part	Limits
15.247 (e)	RSS-247 Clause 5.2 (b)	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test procedure

The maximum peak power spectral density level of the fundamental emission was measured using the method PKPSD, defined in paragraph 10.2 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The setup below was used to measure the power spectral density. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

The declared maximum antenna gain is 3.24dBi.




Results tables


Mode	CH	Frequency [MHz]	PSD Peak [dBm]
BLE	0	2402	-6.85
	19	2440	-6.60
	39	2480	-6.36


BLE

PSD Peak – CH0



PSD Peak – CH19





C.1.4 Out-of-band emission (Conducted)

Test Limits

FCC part	RSS part	Limits																				
15.247 (d)	RSS-247 Clause 5.5	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.																				
15.209	RSS-Gen Clause 8.9	<p>Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):</p> <table border="1"> <thead> <tr> <th>Freq Range (MHz)</th> <th>Field Strength (μV/m)</th> <th>Field Strength (dBμV/m)</th> <th>Meas. Distance (m)</th> </tr> </thead> <tbody> <tr> <td>30-88</td> <td>100</td> <td>40</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>43.5</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>46</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>54</td> <td>3</td> </tr> </tbody> </table> <p>The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.</p>	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure


The setup below was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

In case of Band Edge measurements falling in restricted bands, the declared Antenna Gain is also compensated in the graph. The declared maximum antenna gain is 3.24dBi.

For Band Edge measurements falling in restricted bands, the following limits in dBm were applied for the average detector after the conversion from the limits detailed above in dBμV/m, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

§15.209(a)			Converted values	
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)
Above 960	3	500	54.0	-41.2

The setup below was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.




Note: these PSD_{Peak} values are shown just as a reference for the compliance of the Out-of-band Measurements. Thus the RBW used for these measurements was 100kHz.


Mode	CH	Frequency [MHz]	PSD Peak [dBm]
BLE	0	2402	8.17
	19	2440	8.11
	39	2480	8.55

BLE


BE Low Freq Section – CH0



BE Low (Non Restricted) – CH0




BE High Freq Section (Restricted) – CH39




BLE, CH0

Cond Spur, 30MHz – 9GHz




Date: 10.OCT.2017 16:05:44

Cond Spur, 9GHz – 18GHz




Date: 10.OCT.2017 16:05:07




BLE, CH19

Cond Spur, 30MHz – 9GHz




Date: 10.OCT.2017 16:21:35

Cond Spur, 9GHz – 18GHz




Date: 10.OCT.2017 16:21:58





BLE, CH39

Cond Spur, 30MHz – 9GHz



Cond Spur, 9GHz – 18GHz





C.1.5 Radiated spurious emission


Standards references

FCC part	RSS part	Limits																					
<p>15.247 (d) 15.209</p>	<p>RSS-247 Clause 5.5 RSS-Gen Clause 8.9</p>	<p>Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):</p>																					
		<table border="1"> <thead> <tr> <th data-bbox="630 472 794 535">Freq Range (MHz)</th> <th data-bbox="831 472 986 535">Field Strength (μV/m)</th> <th data-bbox="1023 472 1177 535">Field Strength (dBμV/m)</th> <th data-bbox="1214 472 1417 535">Meas. Distance (m)</th> </tr> </thead> <tbody> <tr> <td data-bbox="630 542 794 573">30-88</td> <td data-bbox="831 542 986 573">100</td> <td data-bbox="1023 542 1177 573">40</td> <td data-bbox="1214 542 1417 573">3</td> </tr> <tr> <td data-bbox="630 580 794 611">88-216</td> <td data-bbox="831 580 986 611">150</td> <td data-bbox="1023 580 1177 611">43.5</td> <td data-bbox="1214 580 1417 611">3</td> </tr> <tr> <td data-bbox="630 618 794 649">216-960</td> <td data-bbox="831 618 986 649">200</td> <td data-bbox="1023 618 1177 649">46</td> <td data-bbox="1214 618 1417 649">3</td> </tr> <tr> <td data-bbox="630 656 794 687">Above 960</td> <td data-bbox="831 656 986 687">500</td> <td data-bbox="1023 656 1177 687">54</td> <td data-bbox="1214 656 1417 687">3</td> </tr> </tbody> </table>	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3	
Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																				
30-88	100	40	3																				
88-216	150	43.5	3																				
216-960	200	46	3																				
Above 960	500	54	3																				
<p>The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.</p>																							


Test procedure

The setups below were used to measure the radiated spurious emissions. Depending of the frequency range and bands being tested, different antennas and filters were used. The final measurement is done by varying the antenna height from 1 to 4 meters, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations. The radiated spurious emissions were measured on the lowest, middle and highest channels.


Radiated Setup < 1GHz



Radiated Setup 1 GHz - 18 GHz



Radiated Setup > 18 GHz



Sample Calculation

The field strength is deduced from the radiated measurement using the following equation:

$$E = 126.8 - 20\log(\lambda) + P - G$$

where

E is the field strength of the emission at the measurement distance, in dB μ V/m

P is the power measured at the output of the test antenna, in dBm

λ is the wavelength of the emission under investigation [$300/f_{MHz}$], in m

G is the gain of the test antenna, in dBi

NOTE – The measured power P includes all applicable instrument correction factors up to the connection to the test Antenna e.g. cable losses, amplifier gains.

For field strength measurements made at other than the distance at which the applicable limit is specified, the field strength of the emission at the distance specified by the limit is deduced as follows:

$$E_{SpecLimit} = E_{Meas} + 20\log(D_{Meas}/D_{SpecLimit})$$

where

E_{SpecLimit} is the field strength of the emission at the distance specified by the limit, in dB μ V/m

E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m

D_{Meas} is the measurement distance, in m

D_{SpecLimit} is the distance specified by the limit, in m

Test Results

30 MHz – 26.5 GHz, BLE

Radiated Spurious – CH0

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.6	30.0	---	40.0	10.0
115.1	26.9	---	43.5	16.7
216.0	28.7	---	43.5	14.9
288.0	31.5	---	46.0	14.6
375.1	33.6	---	46.0	12.4
576.0	35.0	---	46.0	11.0
1190.3	---	42.5	54.0	11.5
2325.3	---	43.7	54.0	10.3
3492.5	60.6	---	74.0	13.4
6042.2	61.3	---	74.0	12.7
17026.6	---	44.2	54.0	9.8
17032.9	56.6	---	74.0	17.4
17484.3	57.9	---	74.0	16.1
17496.4	---	45.3	54.0	8.7
25236.3	48.8	---	74.0	25.3
25259.5	---	36.5	54.0	17.5
25924.4	50.0	---	74.0	24.0
26027.1	---	37.4	54.0	16.6

Radiated Spurious – CH19

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
115.1	25.7	---	43.5	17.9
216.0	28.7	---	46.0	17.3
220.4	27.9	---	46.0	18.2
500.0	35.6	---	46.0	10.4
576.1	33.6	---	46.0	12.4
720.0	39.1	---	46.0	6.9
2363.1	---	44.6	54.0	9.4
2516.9	---	44.2	54.0	9.8
3392.2	60.5	---	74.0	13.5
6399.3	61.2	---	74.0	12.8
17030.0	56.7	---	74.0	17.3
17030.0	---	44.3	54.0	9.7
17485.3	---	45.6	54.0	8.4
17499.8	57.4	---	74.0	16.6
25237.8	48.8	---	74.0	25.3
25267.4	---	36.4	54.0	17.6
25927.0	---	37.2	54.0	16.9
26041.8	50.1	---	74.0	23.9

Radiated Spurious – CH39

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
72.0	25.2	---	40.0	14.8
115.2	26.1	---	43.5	17.5
187.5	25.3	---	43.5	18.3
360.0	31.5	---	46.0	14.5
375.0	33.7	---	46.0	12.3
585.9	38.0	---	46.0	8.0
1113.4	---	41.8	54.0	12.2
1190.3	---	42.6	54.0	11.4
3445.3	60.4	---	74.0	13.7
6095.1	61.3	---	74.0	12.7
17005.8	---	44.3	54.0	9.7
17052.7	56.5	---	74.0	17.5
17475.6	58.0	---	74.0	16.0
17484.8	---	45.6	54.0	8.4
25231.4	48.4	---	74.0	25.6
25250.9	---	36.4	54.0	17.6
25902.3	50.0	---	74.0	24.0
25932.6	---	37.2	54.0	16.8