

## WLL4030 Specifications ( Draft )

**General Specification**

REV.0.0 2003/07/01

Host Interface	Mini-PCI spec V1.0
Form Factor	Mini-PCI type IIIB
Chipset	ATHEROS AR5212 , AR5112
Network Standard	IEEE802.11a, 802.11b, 802.11g
Security	Encryption AES, TKIP , WEP Authentication 802.1x
Network Architectures	Ad hoc , Infrastructure
Modulation Techniques	BPSK, QPSK, 16QAM, 64QAM
Modulation Technology	OFDM, CCK, DSSS
Media Access Technique	CSMA/CA
Supported Data Rates	IEEE 802.11a/g/b Standard Mode : 1 – 54Mbps Turbo Mode : 12 – 108Mbps
Antenna type	Internal diversity with connectors
OS Compatibility	Windows 95/98, 2000, ME, XP

**Electronic Specification**

Symbol	Parameter	Min	Typical	Max	Unit	Note
Ts	Storage Temperature	-40		+85		
Tw	Working Temperature	+0	+25	+70		
It	Transmit Mode Current					Note1
	11a		560		mA	@17dBm ART TX99 mode
	11b		470		mA	@18dBm ART TX99 mode
	11g		520		mA	@18dBm ART TX99 mode
	Turbo Mode		590		mA	@16dBm ART TX99 mode
Ir	Receive Mode Current					Note1
	11a		340		mA	
	11b		280		mA	
	11g		350		mA	
	Turbo Mode		400		mA	
Is	Sleep Mode Current		40		mA	
Vcc	Supplied Voltage	3.0	3.3	3.6	V	

Note1 : Condition at 3.3V , 25

**Radio Specification**
**Condition : VCC=3.3V, Temp=25**

Parameter	Min	Typical	Max	Unit	Note
<b>Transmitter</b>					
<b>11a</b>					
TX Power		+17		dBm	
Tx Spectrum Mask					
Transmitted spectrum at 11Mhz frequency offset			-20	dBr	<b>Note1</b>
Transmitted spectrum at 20Mhz frequency offset			-28	dBr	
Transmitted spectrum at 30Mhz frequency offset			-40	dBr	
Frequency Range	5150		5850	Mhz	
<b>Turbo Mode</b>					
TX Power		+16		dBm	
Channel					<b>Note2</b>
<b>11b</b>					
11b TX Power		+18		dBm	
11b Tx Spectrum Mask					
Transmitted spectral for frequency at $fc \pm 11\text{Mhz}$ to $fc \pm 22\text{Mhz}$			-30	dBr	<b>Note3</b>
Transmitted spectral for frequency at $fc \pm 22\text{Mhz}$ to $fc \pm 33\text{Mhz}$			-50	dBr	
Frequency Range	2412		2484	Mhz	
<b>11g</b>					
TX Power		+18		dBm	
Tx Spectrum Mask					
Transmitted spectrum at 11Mhz frequency offset			-20	dBr	<b>Note1</b>
Transmitted spectrum at 20Mhz frequency offset			-28	dBr	
Transmitted spectrum at 30Mhz frequency offset			-40	dBr	
Frequency Range	2412		2472	Mhz	
<b>Turbo Mode</b>					
TX Power		+16		dBm	
Channel					<b>Note4</b>
<b>Receiver</b>					
RX Sensitivity @ 11a 54Mbps PER<10%	-65			dBm	<b>Note5</b>
RX Sensitivity @ Turbo Mode 108Mbps PER<10%	-62			dBm	
RX Sensitivity @ 11b 11Mbps PER<8%	-82			dBm	
RX Sensitivity @ 11g 54Mbps PER<10%	-65			dBm	
<b>Antenna Port Impedance</b>		50		ohm	

Note 1 dBr (dB relative to the maximum spectral density of the signal)

Note 2 Turbo mode channel list :

Ch42, Ch50, Ch58, Ch152, Ch160, total 5 channels

Note 3 dBr (dB relative to the  $\sin(x)/x$  peak)

Note 4 Turbo mode channel list : Ch6 only

Note 5 PER : Packet Error Rate