

**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
176 Harrick Road  
Keilor Park  
Victoria Australia 3042

Ph: + 613 9365 1000  
Fax: + 613 9331 7455  
email: melb@emctech.com.au

## SAR Test Report

Report Number: M080425\_CERT\_AR5BHB92\_SAR\_2.4-1  
Replacement for  
M080425\_CERT\_AR5BHB92\_SAR\_2.4

Test Sample: Portable Tablet Computer  
Radio Modules: WLAN AR5BHB92 &  
Bluetooth EYSMJCS  
Host PC Model Number: T5010  
Tested For: Fujitsu Australia Pty Ltd  
Host PC FCC ID: EJE-WB0059(with Bluetooth variant)  
EJE-WL0020 (with No Bluetooth variant)  
Host PC IC: 337J-WB0059(with Bluetooth variant)  
337J-WL0020 (with No Bluetooth variant)  
Date of Issue: 24<sup>th</sup> June 2010

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



## CONTENTS

<b>1.0 GENERAL INFORMATION .....</b>	<b>3</b>
<b>2.0 INTRODUCTION .....</b>	<b>4</b>
<b>3.0 SAMPLE TECHNICAL INFORMATION.....</b>	<b>4</b>
3.1 EUT (WLAN) Details.....	4
3.2 EUT (Bluetooth) Details .....	6
3.3 EUT (Notebook PC) Details.....	6
3.4 Test sample Accessories.....	7
3.4.1 Battery Types.....	7
<b>4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER .....</b>	<b>7</b>
4.1 Battery Status .....	8
<b>5.0 DETAILS OF TEST LABORATORY .....</b>	<b>8</b>
5.1 Location .....	8
5.2 Accreditations .....	8
5.3 Environmental Factors.....	8
<b>6.0 DESCRIPTION OF SAR MEASUREMENT SYSTEM.....</b>	<b>9</b>
6.1 Probe Positioning System.....	9
6.2 E-Field Probe Type and Performance .....	9
6.3 Data Acquisition Electronics .....	9
6.4 Validation .....	9
6.4.1 Validation Results @ 2450MHz.....	9
6.4.2 Deviation from reference validation values.....	10
6.4.3 Liquid Depth 15cm.....	10
6.5 Phantom Properties (Size, Shape, Shell Thickness).....	11
6.6 Tissue Material Properties.....	12
6.6.1 Liquid Temperature and Humidity.....	12
6.7 Simulated Tissue Composition Used for SAR Test.....	12
6.8 Device Holder for Laptops and P 10.1 Phantom .....	13
<b>7.0 SAR MEASUREMENT PROCEDURE USING DASY4.....</b>	<b>13</b>
<b>8.0 MEASUREMENT UNCERTAINTY .....</b>	<b>14</b>
<b>9.0 EQUIPMENT LIST AND CALIBRATION DETAILS.....</b>	<b>16</b>
<b>10.0 OET BULLETIN 65 – SUPPLEMENT C TEST METHOD.....</b>	<b>17</b>
10.1 Positions .....	17
10.1.1 “Tablet” Position Definition (0mm spacing).....	17
10.1.2 “Edge On” Position.....	17
10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes).....	17
10.3 FCC RF Exposure Limits for Occupational/ Controlled Exposure.....	18
10.4 FCC RF Exposure Limits for Un-controlled/Non-occupational .....	18
<b>11.0 SAR MEASUREMENT RESULTS .....</b>	<b>18</b>
11.1 2450MHz SAR Results .....	18
<b>12.0 COMPLIANCE STATEMENT.....</b>	<b>19</b>
<b>APPENDIX A1 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>20</b>
<b>APPENDIX A2 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>21</b>
<b>APPENDIX A3 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>22</b>
<b>APPENDIX A4 TEST SETUP PHOTOGRAPHS .....</b>	<b>23</b>
<b>APPENDIX A5 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>24</b>
<b>APPENDIX B PLOTS OF THE SAR MEASUREMENTS .....</b>	<b>26</b>
<b>APPENDIX C CALIBRATION DOCUMENTS.....</b>	<b>46</b>



**SAR TEST REPORT****Report Number: M080425\_CERT\_AR5BHB92\_SAR\_2.4-1****Host PC FCC ID:** EJE-WB0059 (with Bluetooth variant) EJE-WL0020 (with No Bluetooth variant)**Host PC IC:** 337J-WB0059 (with Bluetooth variant) 337J-WL0020 (with No Bluetooth variant)**1.0 GENERAL INFORMATION**

**Test Sample:** Portable Tablet Computer  
**Model Name:** T5010  
**Radio Modules:** WLAN AR5BHB92 & Bluetooth EYSMJCS  
**Interface Type:** Half Mini-Card Wireless LAN Module  
**Device Category:** Portable Transmitter  
**Test Device:** Pre-Production Unit  
**Host PC FCC ID:** EJE-WB0059 (with Bluetooth variant)  
EJE-WL0020 (with No Bluetooth variant)  
**Host PC IC:** 337J-WB0059 (with Bluetooth variant)  
337J-WL0020 (with No Bluetooth variant)  
**RF exposure Category:** General Population/Uncontrolled  
  
**Manufacturer:** Fujitsu Limited  
  
**Test Standard/s:**

1. Evaluating Compliance with FCC Guidelines For Human Exposure to Radiofrequency Electromagnetic Fields Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01)
2. Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) RSS-102

  
**Statement Of Compliance:** The Fujitsu Tablet Computer T5010 with Wireless LAN model AR5BHB92 and Bluetooth module EYSMJCS complied\* with the FCC General public/uncontrolled RF exposure limits of 1.6mW/g per requirements of 47CFR2.1093(d). It also complied with IC RSS-102 requirements.  
\*Refer to compliance statement section 12.

**Test Dates:** 30<sup>th</sup> April 2008  
  
**Tested for:** Fujitsu Australia Pty Ltd  
**Address:** 1230 Nepean Highway, Cheltenham VIC 3192  
**Contact:** Praveen Rao  
**Phone:** +61 3 9265 0210  
**Fax:** +61 3 9265 0656  
**E-mail:** Praveen.rao@au.fujitsu.com

**Test Officer:**

**Peter Jakubiec****Authorised Signature:**

**Peter Jakubiec**

**SAR TEST REPORT**  
**Portable Tablet Computer**  
**Model: T5010**  
**Report Number: M080425\_CERT\_AR5BHB92\_SAR\_2.4-1**

## 2.0 INTRODUCTION

This is a re-issued report. The purpose of additional testing is to apply for a Class II permissive change. The Secondary Landscape edge of this tablet PC was disabled for the previous submission and Grant. The Secondary Landscape edge is now enabled for operation, and hence SAR tests in Secondary Landscape configuration were conducted and included in this report.

The measurement test results mentioned hereon only apply to the 2450MHz frequency band; Additional reports titled "M080425\_CERT\_AR5BHB92\_SAR\_5.6-1" and "M1005100\_FCC\_AR5BHB92\_SAR\_5.6" apply to the 5GHz range.

Testing was performed on the Fujitsu Tablet PC, Model: T5010 with ATHEROS Half Mini-Card Wireless LAN Module (HB92 802.11a/b/g/n), Model: AR5BHB92 & TAIYO YUDEN Bluetooth Module, Model: EYSMJCS. The HB92 module is an OEM product. The Half Mini-Card Wireless LAN (WLAN) was tested in the dedicated host – Lifebook T Series, Model T5010.

There are two variants of the Fujitsu Tablet PC, Model: T5010 one that is equipped with the Bluetooth transmitter and Bluetooth antenna FCC ID: EJE-WB0059 IC: 337J-WB0059, and one variant that does not contain Bluetooth transmitter or Bluetooth antenna FCC ID: EJE-WL0020 IC: 337J-WL0020.

SAR testing was conducted on the sample that is equipped with the Bluetooth transmitter and Bluetooth antenna.

According to the manufacturer specifications the Bluetooth is a low power transmitter (4dBm), also Bluetooth Antenna is located >5cms from any other antenna in the system. The Antenna location is shown on page 24 of the report

## 3.0 SAMPLE TECHNICAL INFORMATION

(Information supplied by the client)

### 3.1 EUT (WLAN) Details

<b>Transmitter:</b>	Mini-Card Wireless LAN Module
<b>Wireless Module:</b>	HB92 (802.11a/b/g/n)
<b>Model Number:</b>	AR5BHB92
<b>Manufacturer:</b>	Atheros Corporation
<b>Modulation Type:</b>	DSSS for 802.11b OFDM for 802.11g OFDM for 802.11a OFDM for 802.11n
<b>2.4 GHz (802.11b/g/n):</b>	CCK, DQPSK, DBPSK, 16QAM, 64QAM
<b>5 GHz (802.11a/n):</b>	BPSK, QPSK, 16QAM, 64QAM
<b>Maximum Data Rate:</b>	802.11b = 11 Mbps, 802.11g and 802.11a = 54 Mbps 802.11n = 300 Mbps
<b>Frequency Ranges:</b>	2.412–2.462 GHz for 11b/g/n 5.18-5.32 GHz, 5.500-5.700 GHz and 5.745-5.825 GHz for 11a/n
<b>Number of Channels:</b>	11 channels for 11b/g/n with 20MHz Bandwidth 24 channels for 11a/n with 20MHz Bandwidth 18 channels for 11n with 40MHz Bandwidth
<b>Antenna Types:</b>	Nissei Electric Inverted F Antenna Location: Top edge of LCD screen
<b>Power Supply:</b>	3.3 VDC from PCI Express bus



**Channels and Output power setting:**

Channel and Mode	Frequency MHz	Average Output Power dBm
<b>802.11b/g mode</b>		
Channels 1, 6 and 11	2412, 2437 and 2462	14.0
<b>802.11a mode</b>		
Channels 36	5180	8.5
Channels 48	5240	13.0
Channels 64	5320	13.0
Channels 100	5500	14.0
Channels 120	5600	14.0
Channels 140	5700	14.0
Channels 149	5745	14.0
Channels 157	5785	14.0
Channels 165	5825	14.0
<b>802.11n mode with 20MHz Bandwidth</b>		
Channels 1 & 6	2412 & 2437	14.0
Channels 11	2462	12.5
Channels 36	5180	10.0
Channels 48	5240	13.5
Channels 64	5320	13.5
Channels 100	5500	14.0
Channels 120	5600	14.0
Channels 140	5700	14.0
Channels 149	5745	14.0
Channels 157	5785	14.0
Channels 165	5825	14.0
<b>802.11n mode with 40MHz Bandwidth</b>		
Channels 3	2412	12.0
Channels 6	2437	14.0
Channels 9	2462	10.5
Channels 38	5190	12.5
Channels 54	5270	14.0
Channels 62	5310	14.0
Channels 102	5510	14.0
Channels 118	5590	14.0
Channels 134	5670	14.0
Channels 151	5755	14.0
Channels 159	5795	14.0

NOTE: For 5GHz SAR results refer to reports titled "M080425\_CERT\_AR5BHB92\_SAR\_5.6-1" and "M1005100\_FCC\_AR5BHB92\_SAR\_5.6".



### 3.2 EUT (Bluetooth) Details

**Transmitter:** Bluetooth  
**FCC ID:** RYYEYSMJCS  
**IC:** 4389B-EYSMJCS  
**Model Number:** EYSMJCS  
**Manufacturer:** TAIYO YUDEN  
**Network Standard:** Bluetooth™ RF Test Specification  
**Modulation Type:** Frequency Hopping Spread Spectrum (FHSS)  
**Frequency Range:** 2402 MHz to 2480 MHz  
**Number of Channels:** 79  
**Carrier Spacing:** 1.0 MHz  
**Antenna Types:** Included BT module  
 Location: left side of hinge  
**Max. Output Power:** 4 dBm  
**Reference Oscillator:** 16 MHz (Built-in)  
**Power Supply:** 3.3 VDC from host.

#### Frequency allocation:

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
1	2402	Power (Ext, Int) = 0, 96
2	2403	
-	-	
39	2440	
40	2441	
41	2442	
-	-	
78	2479	
79	2480	

### 3.3 EUT (Notebook PC) Details

**EUT:** LIFEBOOK T SERIES  
**Host PC FCC ID:** EJE-WB0059 (with Bluetooth variant)  
EJE-WL0020 (with No Bluetooth variant)  
**Host PC IC:** 337J-WB0059 (with Bluetooth variant)  
337J-WL0020 (with No Bluetooth variant)  
**Model Name:** T5010  
**Serial Number:** Pre-production Sample  
**Manufacturer:** FUJITSU LIMITED

**CPU Type and Speed:** Core2 Duo T9600 2.8GHz  
**LCD:** 13.3" WXGA (LED)  
**Wired LAN:** Intel 82567LM : 10 Base-T/100 Base-TX/1000Base-T  
**Modem:** Agere MDC1.5 modem Model: D40  
**Port Replicator Model:** FPCPR85

**AC Adapter Model:** SEC100P2-19.0(Sanken) / SEC100P3-19.0(Sanken, 3pin) /  
 ADP-80NB A(Delta) / SED100P2-19.0(Sanken)  
**Voltage:** 19 V  
**Current Specs:** 4.22A  
**Watts:** 80W

### 3.4 Test sample Accessories

#### 3.4.1 Battery Types

One type of Fujitsu Lithium Ion Battery is used to power the Portable Tablet Computer Wireless LAN Model: AR5BHB92. SAR measurements were performed with the battery as shown below.

##### Standard Battery

Model	FPCBP155	FPCBP155
V/mAh	10.8V 5200mAh	10.8V 5200mAh
Part No.:	CP293420-01	CP293420-01
Lot No.:	X01A-6412	X01A-6607

## 4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER

ATHEROS's CRTU test tool was used to configure the WLAN for testing. The Portable Tablet Computer Wireless LAN had a total of 11 channels (USA model) within the 2412 to 2462 MHz frequency band and 24 channels (20 MHz Bandwidth) within the frequency range 5180 – 5825 MHz. In The frequency range 2412 MHz to 2462 MHz the device operates in 2 modes, OFDM and DSSS. Within the 5180 – 5825 MHz frequency range the device operates in OFDM mode only. For the SAR measurements the device was operating in continuous transmit mode using programming codes supplied by Fujitsu. The fixed frequency channels used in the testing are shown in Table Below.

The Bluetooth module operates over 79 channels within the frequency range 2402 to 2480 MHz. It is possible for the Bluetooth module to operate simultaneously with the WLAN module (co-transmission). The fixed frequency channels used in the testing are shown in the table below. The Bluetooth interface utilizes dedicated antenna, for the purpose of this report labelled antenna "D".

The test results mentioned in this report only apply to the 2450MHz frequency range. Reports titled "M080425\_CERT\_AR5BHB92 \_SAR\_5.6-1" and "M1005100\_FCC\_AR5BHB92\_SAR\_5.6" are specific to the 5GHz range.

The WLAN modules can be configured in a number of different data rates. It was found that the highest source based time averaged power was measured when using the lowest data rates available in each mode. This lowest data rate corresponds to 6Mbps in OFDM mode and 1Mbps in DSSS mode. It was found that OFDM with corresponding data rate of 6Mbps produced the highest SAR level.

The frequency span of the 2450 MHz band was more than 10MHz consequently; the SAR levels of the test sample were measured for lowest, centre and highest channels in the applicable modes. The EUT is capable of using two antennas transmitting simultaneously (HT8 DATA mode) the power level is 3dB lower (50%) than if a single antenna was transmitting. There were no wires or other connections to the Portable Tablet Computer during the SAR measurements.

At the beginning and at the completion of the SAR tests, the conducted power of the device was measured after temporary modification of antenna connector inside the device's TX RX compartment. Measurements were performed with a calibrated Power Meter.



#### 4.1 Battery Status

The device battery was fully charged prior to commencement of measurement. Each SAR test was completed within 30 minutes. The battery condition was monitored by measuring the RF field at a defined position inside the phantom before the commencement of each test and again after the completion of the test. It was not possible to perform conducted power measurements at the output of the device, at the beginning and end of each scan due to lack of a suitable antenna port. The uncertainty associated with the power drift was less than 12% and was assessed in the uncertainty budget.

### 5.0 DETAILS OF TEST LABORATORY

#### 5.1 Location

EMC Technologies Pty Ltd  
176 Harrick Road  
Keilor Park, (Melbourne) Victoria  
Australia 3042

**Telephone:** +61 3 9365 1000  
**Facsimile:** +61 3 9331 7455  
**email:** [melb@emctech.com.au](mailto:melb@emctech.com.au)  
**website:** [www.emctech.com.au](http://www.emctech.com.au)

#### 5.2 Accreditations

EMC Technologies Pty. Ltd. is accredited by the National Association of Testing Authorities, Australia (NATA).  
**NATA Accredited Laboratory Number: 5292**

EMC Technologies Pty Ltd is NATA accredited for the following standards:

<b>AS/NZS 2772.1:</b>	RF and microwave radiation hazard measurement
<b>ACA:</b>	Radio communications (Electromagnetic Radiation - Human Exposure) Standard 2003
<b>FCC:</b>	Guidelines for Human Exposure to RF Electromagnetic Field OET65C 01/01
<b>EN 50360: 2001</b>	Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
<b>EN 50361: 2001</b>	Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300MHz – 3GHz)
<b>IEEE 1528: 2003</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

Refer to NATA website [www.nata.asn.au](http://www.nata.asn.au) for the full scope of accreditation.

#### 5.3 Environmental Factors

The measurements were performed in a shielded room with no background RF signals. The temperature in the laboratory was controlled to within  $21 \pm 1^\circ\text{C}$ , the humidity was in the range 35%. The liquid parameters are measured daily prior to the commencement of each test. Tests were performed to check that reflections within the environment did not influence the SAR measurements. The noise floor of the DASY4 SAR measurement system using the SN1377 probe was less than  $5\mu\text{V}$  in both air and liquid mediums.





## 6.0 DESCRIPTION OF SAR MEASUREMENT SYSTEM

Applicable Head Configurations	: None
Applicable Body Configurations	: Tablet Position : Edge On Position

### 6.1 Probe Positioning System

The measurements were performed with the state-of-the-art automated near-field scanning system **DASY4 V4.7 Build 53** from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision 6-axis robot (working range greater than 1.1m), which positions the SAR measurement probes with a positional repeatability of better than  $\pm 0.02$  mm. The DASY4 fully complies with the OET65 C (01-01), IEEE 1528 and EN50361 SAR measurement requirements.

### 6.2 E-Field Probe Type and Performance

The SAR measurements were conducted with SPEAG dosimetric probe ET3DV6 Serial: 1377 (2.45 GHz) designed in the classical triangular configuration and optimised for dosimetric evaluation. The probes have been calibrated and found to be accurate to better than  $\pm 0.25$  dB. The probe is suitable for measurements close to material discontinuity at the surface of the phantom. The sensors of the probe are directly loaded with Schottky diodes and connected via highly resistive lines (length = 300 mm) to the data acquisition unit.

### 6.3 Data Acquisition Electronics

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. The input impedance of the DAE3 box is 200 M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80dB. Transmission to the PC-card is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The mechanical probe-mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

## 6.4 Validation

### 6.4.1 Validation Results @ 2450MHz

The following tables lists the dielectric properties of the tissue simulating liquid measured prior to SAR validation. The results of the validation are listed in columns 4 and 5. The forward power into the reference dipole for SAR validation was adjusted to 250 mW.

**Table: Validation Results (Dipole: SPEAG D2450V2 SN: 724)**

1. Validation Date	2. $\epsilon_r$ (measured)	3. $\sigma$ (mho/m) (measured)	4. Measured SAR 1g (mW/g)	5. Measured SAR 10g (mW/g)
30 <sup>th</sup> April 08	39.5	1.74	13.7	6.47

### 6.4.2 Deviation from reference validation values

The reference SAR values are derived using a reference dipole and flat section of the SAM phantom suitable for a centre frequency of 2450MHz. These reference SAR values are obtained from the IEEE Std 1528-2003 and are normalized to 1W.

The SPEAG calibration reference SAR value is the SAR validation result obtained in a specific dielectric liquid using the validation dipole (D2450V2) during calibration. The measured one-gram SAR should be within 10% of the expected target reference values shown in table below (2450MHz) below.

**Table: Deviation from reference validation values @ 2450MHz**

Frequency and Date	Measured SAR 1g (mW/g)	Measured SAR 1g (Normalized to 1W)	SPEAG Calibration reference SAR Value 1g (mW/g)	Deviation From SPEAG Reference (1g)	IEEE Std 1528 reference SAR value 1g (mW/g)	Deviation From IEEE (1g)
2450MHz	13.7	54.8	53.3	2.81	52.4	4.58

NOTE: All reference validation values are referenced to 1W input power.

### 6.4.3 Liquid Depth 15cm

During the SAR measurement process the liquid level was maintained to a level of 15cm with a tolerance of 0.5cm.




Photo of liquid Depth in Flat Phantom

### 6.5 Phantom Properties (Size, Shape, Shell Thickness)

The phantom used during the validations was the SAM Phantom model: TP - 1260 from SPEAG. It is a phantom with a single thickness of 2 mm and was filled with the required tissue simulating liquid. The SAM phantom support structures were all non-metallic and spaced more than one device width away in transverse directions.

For SAR testing in the body worn positions an AndreT Flat phantom P 10.1 was used. The phantom thickness is 2.0mm+/-0.2 mm and was filled with the required tissue simulating liquid. Below table provides a summary of the measured phantom properties.

**Table: Phantom Properties (300MHz-2500MHz)**


Phantom Properties	Required	Measured
Thickness of flat section	2.0mm $\pm$ 0.2mm (bottom section)	2.12-2.20mm
Dielectric Constant	<5.0	4.603 @ 300MHz (worst-case frequency)
Loss Tangent	<0.05	0.0379 @ 2500MHz (worst-case frequency)

Depth of Phantom	200mm
Length of Flat Section	620mm
Width of Flat Section	540mm

P 10.1 Flat Phantom



P 10.1 Flat Phantom



## 6.6 Tissue Material Properties

The dielectric parameters of the brain simulating liquid were measured prior to SAR assessment using the HP85070A dielectric probe kit and HP8753ES Network Analyser. The actual dielectric parameters are shown in the following table.

**Table: Measured Brain Simulating Liquid Dielectric Values for Validations**

Frequency Band	$\epsilon_r$ (measured range)	$\epsilon_r$ (target)	$\sigma$ (mho/m) (measured range)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
2450 MHz Brain	39.5	39.2 $\pm$ 5% (37.2 to 41.2)	1.74	1.80 $\pm$ 5% (1.71 to 1.89)	1000

NOTE: The brain liquid parameters were within the required tolerances of  $\pm$ 5%.

**Table: Measured Body Simulating Liquid Dielectric Values**

Frequency Band	$\epsilon_r$ (measured range)	$\epsilon_r$ (target)	$\sigma$ (mho/m) (measured range)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
2412 MHz Muscle	52.5	52.7 $\pm$ 5% (50.1 to 55.3)	1.86	1.95 $\pm$ 5% (1.85 to 2.05)	1000
2437 MHz Muscle	52.4	52.7 $\pm$ 5% (50.1 to 55.3)	1.90	1.95 $\pm$ 5% (1.85 to 2.05)	1000
2462 MHz Muscle	52.2	52.7 $\pm$ 5% (50.1 to 55.3)	1.94	1.95 $\pm$ 5% (1.85 to 2.05)	1000

NOTE: The brain and muscle liquid parameters were within the required tolerances of  $\pm$ 5%.

### 6.6.1 Liquid Temperature and Humidity

The humidity and dielectric/ambient temperatures were recorded during the assessment of the tissue material dielectric parameters. The difference between the ambient temperature of the liquid during the dielectric measurement and the temperature during tests was less than  $|2|^\circ\text{C}$ .

**Table: Temperature and Humidity recorded for each day**

Date	Ambient Temperature ( $^\circ\text{C}$ )	Liquid Temperature ( $^\circ\text{C}$ )	Humidity (%)
30th April 2008	21.5	21.2	35.0

## 6.7 Simulated Tissue Composition Used for SAR Test

The tissue simulating liquids are created prior to the SAR evaluation and often require slight modification each day to obtain the correct dielectric parameters.

**Table: Tissue Type: Brain @ 2450MHz**

Volume of Liquid: 30 Litres

Approximate Composition	% By Weight
Distilled Water	62.7
Salt	0.5
Triton X-100	36.8

**Table: Tissue Type: Muscle @ 2450MHz**

Volume of Liquid: 60 Litres

Approximate Composition	% By Weight
Distilled Water	73.2
Salt	0.04
DGBE	26.7

\*Refer "OET Bulletin 65 97/01 P38"

## 6.8 Device Holder for Laptops and P 10.1 Phantom

A low loss clamp was used to position the Tablet underneath the phantom surface. Small pieces of foam were then used to press the Tablet flush against the phantom surface.

*Refer to Appendix A for photographs of device positioning*

## 7.0 SAR MEASUREMENT PROCEDURE USING DASY4

The SAR evaluation was performed with the SPEAG DASY4 system. A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the EUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 3.9 mm from the inner surface of the shell. The area covers the entire dimension of the EUT and the horizontal grid spacing is 15 mm x 15 mm. The actual Area Scan has dimensions of 150mm x 210 mm surrounding the test device. Based on this data, the area of the maximum absorption is determined by Spline interpolation.
- c) Around this point, a volume of 30 mm x 30 mm x 30 mm is assessed by measuring 7 x 7 x 7 points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:
  - (i) The data at the surface are extrapolated, since the centre of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axes. This polynomial is then used to evaluate the points between the surface and the probe tip.
  - (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
  - (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
  - (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.

## 8.0 MEASUREMENT UNCERTAINTY

The uncertainty analysis is based on the template listed in the IEEE Std 1528-2003 for both Handset SAR tests and Validation uncertainty. The measurement uncertainty of a specific device is evaluated independently and the total uncertainty for both evaluations (95% confidence level) must be less than 30%.

**Table: Uncertainty Budget for DASY4 V4.7 Build 53 – EUT SAR test 2450MHz**

a	b	c	d	e= f(d,k)	f	g	h=cxf/e	i=cxg/e	k
Uncertainty Component	Sec.	Tol. (%)	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub> (%)	10g u <sub>i</sub> (%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration (k=1) (numerical calibration)	7.2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	7.2.1	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	7.2.1	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	7.2.1	1	R	1.73	1	1	0.6	0.6	∞
Linearity	7.2.1	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	7.2.1	1	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	7.2.1	1	N	1	1	1	1.0	1.0	∞
Response Time	7.2.1	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	7.2.1	2.6	R	1.73	1	1	1.5	1.5	∞
RF Ambient Conditions	7.2.3	0.05	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	7.2.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	7.2.2	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	7.2.4	1	R	1.73	1	1	0.6	0.6	∞
<b>Test Sample Related</b>									
Test Sample Positioning	7.2.2	1.61	N	1	1	1	1.6	1.6	11
Device Holder Uncertainty									
Output Power Variation – SAR Drift Measurement	7.2.3	11.7	R	1.73	1	1	6.8	6.8	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	7.2.2	4	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity – Deviation from target values	7.2.3	5	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity – Measurement uncertainty	7.2.3	4.3	N	1	0.64	0.43	2.8	1.8	5
Liquid Permittivity – Deviation from target values	7.2.3	5	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity – Measurement uncertainty	7.2.3	4.3	N	1	0.6	0.49	2.6	2.1	5
Combined standard Uncertainty			RSS				11.4	11.0	154
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				22.9	22.07	

Estimated total measurement uncertainty for the DASY4 measurement system was ±11.4%. The extended uncertainty (K = 2) was assessed to be ±22.9% based on 95% confidence level. The uncertainty is not added to the measurement result.

**Table: Uncertainty Budget for DASY4 V4.7 Build 53 – Validation 2450MHz**

a	b	c	D	e= f(d,k)	f	g	h=cx <sub>f</sub> /e	i=cx <sub>g</sub> /e	k
Uncertainty Component	Sec.	Tol. (6%)	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub> (6%)	10g u <sub>i</sub> (6%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration (k=1) (standard calibration)	E.2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Hemispherical Isotropy	E.2.2	0	R	1.73	1	1	0.0	0.0	∞
Boundary Effect	E.2.3	1	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0	R	1.73	1	1	0.0	0.0	∞
Integration Time	E.2.8	0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions	E.6.1	0.05	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	1	R	1.73	1	1	0.6	0.6	∞
<b>Test Sample Related</b>									
Dipole Axis to Liquid Surface		2	R	1.73	1	1	1.2	1.2	∞
Power Drift		4.7	R	1.73	1	1	2.7	2.7	∞
				□					□
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity – Deviation from target values	E.3.2	5	R	1.73	0.6	0.43	1.7	1.2	∞
Liquid Conductivity – Measurement uncertainty	E.3.3	2.5	N	1.73	0.6	0.43	0.9	0.6	5
Liquid Permittivity – Deviation from target values	E.3.2	5	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity – Measurement uncertainty	E.3.3	2.5	N	1.73	0.6	0.49	0.9	0.7	5
Combined standard Uncertainty			RSS				<b>8.0</b>	<b>7.8</b>	154
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				16.0	15.63	

Estimated total measurement uncertainty for the DASY4 measurement system was  $\pm 8.0\%$ . The extended uncertainty ( $K = 2$ ) was assessed to be  $\pm 16.0\%$  based on 95% confidence level. The uncertainty is not added to the Validation measurement result.

## 9.0 EQUIPMENT LIST AND CALIBRATION DETAILS

Table: SPEAG DASY4 Version V4.7 Build 53

Equipment Type	Manufacturer	Model Number	Serial Number	Calibration Due	Used For this Test?
Robot - Six Axes	Staubli	RX90BL	N/A	Not applicable	✓
Robot Remote Control	SPEAG	CS7MB	RX90B	Not applicable	✓
SAM Phantom	SPEAG	N/A	1260	Not applicable	✓
SAM Phantom	SPEAG	N/A	1060	Not applicable	
Flat Phantom	AndreT	10.1	P 10.1	Not applicable	✓
Flat Phantom	AndreT	9.1	P 9.1	Not applicable	
Flat Phantom	SPEAG	PO1A 6mm	1003	Not applicable	
Data Acquisition Electronics	SPEAG	DAE3 V1	359	03-July-2008	
Data Acquisition Electronics	SPEAG	DAE3 V1	442	26-Feb-09	✓
Probe E-Field - Dummy	SPEAG	DP1	N/A	Not applicable	
Probe E-Field	SPEAG	ET3DV6	1380	18-Dec-2008	
Probe E-Field	SPEAG	ET3DV6	1377	09-July-2008	✓
Probe E-Field	SPEAG	ES3DV6	3029	Not Used	
Probe E-Field	SPEAG	EX3DV4	3563	13-July-2008	
Antenna Dipole 300 MHz	SPEAG	D300V2	1005	14-Dec-2009	
Antenna Dipole 450 MHz	SPEAG	D450V2	1009	14-Dec-2008	
Antenna Dipole 900 MHz	SPEAG	D900V2	047	6-July-2008	
Antenna Dipole 1640 MHz	SPEAG	D1640V2	314	30-June-2008	
Antenna Dipole 1800 MHz	SPEAG	D1800V2	242	3-July-2008	
Antenna Dipole 1950 MHz	SPEAG	D1950V3	1113	5-March-2009	
Antenna Dipole 3500 MHz	SPEAG	D3500V2	1002	06-July-2008	
Antenna Dipole 2450 MHz	SPEAG	D2450V2	724	13-Dec-2008	✓
Antenna Dipole 5600 MHz	SPEAG	D5GHzV2	1008	07-Dec-2009	
RF Amplifier	EIN	603L	N/A	Not applicable	
RF Amplifier	Mini-Circuits	ZHL-42	N/A	Not applicable	✓
RF Amplifier	Mini-Circuits	ZVE-8G	N/A	Not applicable	
Synthesized signal generator	Hewlett Packard	ESG-D3000A	GB37420238	*In test	✓
RF Power Meter Dual	Hewlett Packard	437B	3125012786	30-May-2008	✓
RF Power Sensor 0.01 - 18 GHz	Hewlett Packard	8481H	1545A01634	30-May-2008	✓
RF Power Meter Dual	Gigatronics	8542B	1830125	11-May-2008	✓
RF Power Sensor	Gigatronics	80301A	1828805	11-May-2008	✓
RF Power Meter Dual	Hewlett Packard	435A	1733A05847	*In test	✓
RF Power Sensor	Hewlett Packard	8482A	2349A10114	*In test	✓
Network Analyser	Hewlett Packard	8714B	GB3510035	06-Sept-2008	
Network Analyser	Hewlett Packard	8753ES	JP39240130	02 Oct-2008	✓
Dual Directional Coupler	Hewlett Packard	778D	1144 04700	*In test	
Dual Directional Coupler	NARDA	3022	75453	*In test	✓

\* Calibrated during the test for the relevant parameters.





## 10.0 OET BULLETIN 65 – SUPPLEMENT C TEST METHOD

Notebooks should be evaluated in normal use positions, typical for lap-held bottom-face only. However the number of positions will depend on the number of configurations the laptop can be operated in. The “LifeBook T series” can be used in either a conventional laptop position (see Appendix A1) or a Tablet configuration. The antenna location in the “LifeBook T series” is closest to the top of the screen when used in a conventional laptop configuration and due to the separation distances involved between the phantom and the laptop antenna, testing is not required in this position.

### 10.1 Positions

#### 10.1.1 “Tablet” Position Definition (0mm spacing)

The device was tested in the 2.00 mm flat section of the AndreT Flat phantom P 10.1 for the “Tablet” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of the device was touching the phantom. This device orientation simulates the PC’s normal use – being held on the lap of the user. A spacing of 0mm ensures that the SAR results are conservative and represent a worst-case position.

#### 10.1.2 “Edge On” Position

The device was tested in the (2.00 mm) flat section of the AndreT phantom for the “Edge On” position. The Antenna edge of the Transceiver was placed underneath the flat section of the phantom and suspended until the edge touched the phantom. *Refer to Appendix A for photos of measurement positions.*


### 10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes)

The device has a fixed antenna. Depending on the measured SAR level up to three test channels with the test sample operating at maximum power, as specified in section 4.0 were recorded. The following table represents the matrix used to determine what testing was required.


**Table: Testing configurations**

Phantom Configuration	*Device Mode	Antenna	Test Configurations		
			Channel (Low)	Channel (Middle)	Channel (High)
Tablet	OFDM 2.4GHz	Aux		X	
		Main		X	
	DSSS 2.4GHz	Aux		X	
		Main		X	
Edge On	OFDM 2.4GHz	Aux		X	
		Main		X	
	DSSS 2.4GHz	Aux		X	
		Main		X	

**Legend**



Testing Required in this configuration



Testing required in this configuration only if SAR of middle channel is more than 3dB below the SAR limit or it is the worst case.



### 10.3 FCC RF Exposure Limits for Occupational/ Controlled Exposure

Spatial Peak SAR Limits For:	
Partial-Body:	8.0 mW/g (averaged over any 1g cube of tissue)
Hands, Wrists, Feet and Ankles:	20.0 mW/g (averaged over 10g cube of tissue)

### 10.4 FCC RF Exposure Limits for Un-controlled/Non-occupational

Spatial Peak SAR Limits For:	
Partial-Body:	1.6 mW/g (averaged over any 1g cube of tissue)
Hands, Wrists, Feet and Ankles:	4.0 mW/g (averaged over 10g cube of tissue)

## 11.0 SAR MEASUREMENT RESULTS

The SAR values averaged over 1g tissue masses were determined for the sample device for all test configurations listed in section 7.2.

### 11.1 2450MHz SAR Results

There are two modes of operation within the 2450MHz band, they include OFDM and DSSS modulations. Refer to section 7.2 for selection of all device test configurations. Table below displays the SAR results.

**Table: SAR MEASUREMENT RESULTS**

Test Position	Plot No.	Mode	Ant	Bit rate Mode (Mbps)	Channel Bandwidth (MHz)	Test Channel	Test Freq (MHz)	Measured 1g SAR Results (mW/g)	Measured Drift (dB)
Tablet	1	OFDM	Aux	6	-	06	2437	0.025	0.481
Tablet	2	OFDM	Main	6	-	06	2437	0.026	0.134
Edge On Side (Primary Portrait)	3	OFDM	Aux	6	-	01	2412	0.225	-0.301
	4	OFDM	Aux	6	-	06	2437	0.120	-0.035
	5	OFDM	Aux	6	-	11	2462	0.117	-0.475
Edge on Secondary Landscape	6	DSSS	Main	1	-	06	2437	0.202	-0.470
	7	OFDM	Main	6	-	06	2437	0.232	-0.212
	8	OFDM	Aux	6	-	06	2437	0.127	-0.026
	9	OFDM	Main	HT0	20	06	2437	0.204	0.175
	10	OFDM	Main	HT0	40	06	2437	0.194	-0.160

NOTE: The measurement uncertainty of 22.9% for 2.45GHz was not added to the result.

The highest SAR level recorded in the 2450MHz band was 0.232 mW/g as evaluated in a 1g cube of averaging mass. This value was obtained in Edge On Secondary Landscape position in OFDM mode, utilizing channel 06 (2437 MHz) and antenna Main.

## 12.0 COMPLIANCE STATEMENT

The Fujitsu Tablet PC, Model: T5010 with ATHEROS Half Mini-Card Wireless LAN Module (HB92 802.11a/b/g/n), Model: AR5BHB92 & TAIYO YUDEN Bluetooth Module, Model: EYSMJCS was found to comply with the FCC and RSS-102 SAR requirements.

The highest SAR level recorded was 0.232 mW/g for a 1g cube. This value was measured at 2437 MHz (channel 06) in the "Edge On Secondary Landscape" position in OFDM modulation mode at the antenna Main. The Bluetooth was OFF Frequency 2441 MHz. This was below the limit of 1.6 mW/g for uncontrolled exposure, even taking into account the measurement uncertainty of 22.9 %.

