



EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WL0024
Industry Canada ID: 337J-WL0024

Test Sample: Portable PC LifeBook T Series
Model: T901

Radio Module: Intel Centrino 6205 Taylor Peak 62205ANHMMW WLAN

Report Number: M101140_FCC_62205ANHMMW_DTS

Issue Date: 14th February 2011

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
EMC Technologies Report No. M101140_FCC_62205ANHMW_DTS
Issue Date: 14th February 2011

CONTENTS

1.0	INTRODUCTION
2.0	GENERAL INFORMATION
FCC 15.247 (DTS) RESULTS	
3.0	CONDUCTED EMI MEASUREMENTS
4.0	RADIATED SPURIOUS EMI MEASUREMENTS
5.0	PEAK OUTPUT POWER
6.0	CHANNEL BANDWIDTH
7.0	PEAK POWER SPECTRAL DENSITY
8.0	RADIO FREQUENCY EXPOSURE
9.0	ANTENNA REQUIREMENT
10.0	COMPLIANCE STATEMENT
11.0	MEASUREMENT UNCERTAINTIES
12.0	TEST REPORT APPENDICES
APPENDIX A: MEASUREMENT INSTRUMENT DETAILS	
APPENDIX B: PHOTOGRAPHS	
APPENDIX C: OPERATIONAL DESCRIPTION	
APPENDIX D: BLOCK DIAGRAM	
APPENDIX E: ANTENNA INFORMATION	
APPENDIX F: SCHEMATIC	
APPENDIX G: FCC LABELLING DETAILS	
APPENDIX H: USER MANUAL	
Attachment 1: RF Exposure Information	
Attachment 2: FCC DOC for LifeBook T Series	
Attachment 3: FCC Part 15B Test Report	
Attachment 4: Intel FCC Part 15.247 Test Report	

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210

Report No. M101140_FCC_62205ANHMMW_DTS

Test Sample: Portable PC LifeBook T Series
Model: T901
Radio Module: Intel Centrino Advanced-N 6205 Taylor Peak 62205ANHMMW WLAN

FCC ID: EJE-WL0024
Industry Canada ID: 337J-WL0024
Equipment Type: Intentional Radiator (Transceiver)

Manufacturer (LifeBook): Fujitsu Ltd
Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan
Contact: Mr. Tsuyoshi Uchihara, Mobile Computing Division

Test Standards: FCC Part 15 – Radio Frequency Devices (October 2009)
FCC Part 15 Subpart C - Intentional Radiators
Section 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Bands
ANSI C63.4 – 2003

RSS-210 Issue 7 Low Power Licence-Exempt RadioCommunication
Devices Annex 8: 2400–2483.5 MHz & 5725–5850 MHz Operation Bands

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and
Portable Radio Transmitters with respect to Health Canada's Safety Code 6
for Exposure of Humans to Radio Frequency Fields

Test Dates: 9th to 12th February 2011

Test Engineer: Chieu Huynh - B.Eng (Hons) Electronics

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*



Authorised Signatory: Chieu Huynh
Senior EMC Engineer
EMC Technologies Pty Ltd

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210

1.0 INTRODUCTION

EMI testing was performed on the Portable PC, Fujitsu LifeBook T Series, Model: T901 with Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHMMW.

The Taylor Peak 2x2 WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH).

The other transmitter installed in the T901 LifeBook is Broadcom Bluetooth Module, Model: BCM92070MD_REF6. The Bluetooth module was originally certified by Broadcom as a modular approval under FCC ID: QDS-BRCM1043 (Canada ID: 4324A-BRCM1043).

There are two variants of the Portable PC, Fujitsu LifeBook T Series, Model: T901 covered in this report. One that is equipped with the modular certified low power Bluetooth transmitter with built-in antenna, and one variant that does not contain Bluetooth transmitter or Bluetooth antenna FCC ID: EJE-WL0024 (IC: 337J-WL0024). Testing was conducted on the sample that is equipped with the Bluetooth transmitter and Bluetooth antenna.

The intention of this application is to FCC certify Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHMMW installed in Portable PC Fujitsu LifeBook T Series, Model: T901. The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The 62205ANHMMW 2x2 WLAN supports IEEE 802.11b, IEEE 802.11g, IEEE 802.11a and IEEE 802.11n (DTS & U-NII) configurations.

DTS results for configurations IEEE 802.11b, IEEE 802.11g, IEEE 802.11a and IEEE 802.11n are reported in this test report.

The NII (WLAN) is submitted separately under NII submission.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 8 and the RF exposure requirements of RSS-102.

The measurement procedure used was in accordance with ANSI C63.4-2003. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.1 Summary of Results

FCC Subpart C, Section 15.247

FCC Part 15 Subpart C Clauses	Industry Canada RSS-210 Issue 7 and RSS-Gen Clauses	Test Performed	Results
15.203	RSS-Gen (7.1.4)	Antenna Requirement	Complies
15.205	2.2 (Table 1)	Operation in Restricted Band	Complies
15.207	RSS-Gen (7.2.2)	Conducted Emissions	Note 1
15.209	RSS-Gen (6)	Radiated Emissions	Complies
15.247 (a)(2)	A8.1 (b) (d)	Channel Bandwidth	Note 2
15.247 (b)(3)	A8.4	Peak Output Power	Note 2
15.247 (c)	RSS-Gen (7.1.4)	Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	A8.5	Out of Band Emissions	Complies
15.247 (e)	A8.2 (b)	Peak Power Spectral Density	Note 2
15.247 (f)	A8.3	Hybrid Systems (Note 3)	Not Applicable. EUT does not employ a hybrid system
15.247 (g)	A8.1	Frequency Hopping	Not Applicable. EUT does not employ frequency hopping
15.247 (h)	A8.1	Frequency Hopping	Not Applicable. EUT does not employ frequency hopping
15.247 (i)	RSS-Gen (5.5)	Radio Frequency Hazard	Complies

Note 1: Refer to Attachment 3, FCC Part 15B Test Report

Note 2: Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH)

Note 3: Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

1.2 Modifications by EMC Technologies

No modifications were required.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (WLAN) Details

Transmitter: Half Mini-Card Wireless LAN Module
Wireless Module: Intel Centrino Advanced-N 6205 Taylor Peak 2x2 (11a/b/g/n)
Model Number: 62205ANHMMW
Manufacturer: Intel Corporation
Frequency Ranges: 2.412 – 2.462 GHz
5.18 - 5.32 GHz, 5.5 – 5.7 GHz and 5.745 - 5.825 GHz
Maximum Data Rates: 802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps
802.11n = 450 Mbps
Antenna Types: Nissei Inverted F (1st, 2nd)
Antenna gain: Max antenna gain is less than 6 dBi.
Refer antenna data provided separately

Channels and Output Power Settings:

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		
					Tx A		Tx B
802.11a	36	5180	6	-	15		15
	40	5200					
	44	5220					
	48	5240					
	52	5260					
	56	5280					
	60	5300					
	64	5320					
	100	5500					
	104	5520					
	108	5540					
	112	5560					
	116	5580					
	120	5600					
	124	5620					
	128	5640					
	132	5660					
	136	5680					
	140	5700					
	149	5745					
	153	5765					
157	5785						
161	5805						
165	5825						
802.11b	1	2412	1	-	15.5		15.5
	6	2437					
	11	2462					
802.11g	1	2412	6	-	14		14
	2	2417			16		16.5
	6	2437					
	10	2457					
	11	2462			14		14

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		
					Tx A		Tx B
802.11n	1	2412	HT0	20	13		13
	2	2417			16		16.5
	6	2437					
	10	2457			12.5		13
	11	2462					
	36	5180			14.5		14.5
	40	5200					
	44	5220			15		15
	48	5240					
	52	5260					
	56	5280					
	60	5300					
	64	5320					
	100	5500					
	104	5520					
	108	5540					
	112	5560					
	116	5580					
	120	5600					
	124	5620					
	128	5640					
	132	5660					
	136	5680					
	140	5700					
	149	5745					
	153	5765					
	157	5785					
	161	5805					
	165	5825					
	3F	2422			40 Wide	9	
	4F	2427		10.5			11
	5F	2432		12.5			13
	6F	2437		16			16
	7F	2442		12.5			13
	8F	2447		10.5			11.5
	9F	2452		9.5			10
	38	5190		10			10
	46	5230		15			15
	54	5270					
	62	5310		10			10
	102	5510		12.5			12.5
	110	5550		15			15
	118	5590					
	126	5630					
	134	5670					
	151	5755					
	159	5795					


The 62205ANHWMW is capable of using multiple antennas transmitting simultaneously (two antennas). In any two antennas transmitting, the power level is 3 dB lower (50%) for each antenna port than if a single antenna was transmitting.

2.2 EUT (Notebook PC) Details


NoteBook PC:	Portable PC LifeBook T series
*Model Name:	T901
Serial Number:	Pre-production Sample
Manufacturer:	FUJITSU LIMITED
CPU Type and Speed:	Core i7-2620M 2.7GHz
LCD:	13.3" WXGA (1280x800 : HV133WX1
Wired LAN:	Intel 82579LM : 10 Base-T/100 Base-TX/1000Base-T
Modem:	Agere MDC1.5 modem Model: D40
Port Replicator Model:	FPCPR105
AC Adapter Model:	80W: ADP-80NB A (Delta), SEE100P2-19.0 (Sanken), PJW1942N (Tamura), PJW1942NA (Tamura)
Voltage:	19 V
Current Specs:	4.22A
Watts:	80W




Primary
Landscape Orientation



Primary Portrait
Orientation



Secondary
Landscape Orientation



Secondary Portrait
Orientation

2.3 Test Configuration

The Intel WLAN test software "DRTU" was used to transmit continuously during the tests.

Conducted tests were performed at the WLAN Antenna ports.

Radiated harmonics and spurious emissions were performed while the transmitter transmits continuously.

Power is provided via an AC adaptor. Testing was performed at a voltage of 110VAC at 50Hz.

2.4 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT.

2.5 Test Facility

2.5.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (DoC) and Certification under Parts 15 & 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001.**

EMC Technologies has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional) - **Industry Canada number 3569B.**

Measurements were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

2.5.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.6 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by EMC Technologies. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

FCC 15.247 (DTS) RESULTS

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

4.0 RADIATED SPURIOUS EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209 and 15.247. All measurements above 1 GHz were made over a distance of 3 and 1 metres.

Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

E = Radiated Field Strength in dBμV/m.

V = EMI Receiver Voltage in dBμV. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dBμV is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

4.3 Radiated Emissions (Spurious and Harmonics)

This transmitter module was originally tested and certified by the manufacturer as a stand-alone module outside a laptop (host) with higher gain antennas. Refer to manufacturer's original test report (Attachment 4) for full results showing compliance with the spurious and harmonics limits. However, to ensure the transmitter module install in T901 LifeBook is still in compliance, verification tests were performed at the worst case (frequencies with higher average output power) or selected frequencies for harmonics and spurious emissions.

Initial investigations were performed with all data rates. Final testing was performed while the transmitter continuously operated in the worst case condition.

All orientations were investigated and tested. Worst results were reported below.

4.3.1 Frequency Band: 1 – 40 GHz

The 74 dB μ V/m @ 3m and 54 dB μ V/m @ 3m limits are applied for emissions fall in the restricted bands. The limits for emission outside the restricted band are 20 dB below the fundamental field strength. The limits are adjusted by 10.5 dB when measurements perform at a distance of 1m.

Testing was performed while the WLAN transmitter continuously operated. Harmonics related to the WLAN transmitter operated in the frequency bands 2.4 – 2.4835 GHz and 5.725 – 5.850 GHz are reported below. Harmonics in the frequency bands 5.15 – 5.35 GHz and 5.47 – 5.725 GHz, refer to M101140_FCC_62205ANHWMW_NII.

Measurements were performed with the EUT operating in the worst case mode of single antenna transmitting. For multiple antennas transmitting like two antennas transmitting, the power level is 3 dB lower (50%) with respect to single antenna mode.

Harmonics were measured for channels where the average output power was highest.

4.3.1.1 Configuration 802.11b

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2412	Transmit Frequency				
4824	52.7	48.2	74.0	54.0	Complied

Result: Harmonic was recorded up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of 5.8 dB.

4.3.1.2 Configuration 802.11g

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2437	Transmit Frequency				
4874	52.1	38.8	74.0	54.0	Complied

Result: Harmonic was recorded up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of 15.2 dB.

4.3.1.3 Configuration 802.11a

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5825	Transmit Frequency				
Harmonics	Low				Complied

Result: Harmonics were low. Emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of greater than 20dB.

4.3.1.4 Configuration 802.11n – Tx BW = 20 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2437	Transmit Frequency				
4874	51.6	38.3	74.0	54.0	Complied

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5745	Transmit Frequency				
Harmonics	Low				Complied

Result: Harmonic was recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of 15.7 dB.

4.3.1.5 Configuration 802.11n – Tx BW = 40 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
2437	Transmit Frequency				
4874	50.3	36.9	74.0	54.0	Complied

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5795	Transmit Frequency				
Harmonics	Low				Complied

Result: Harmonic was recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.247 by a margin of 17.1 dB.

4.3.2 Frequency Band: 30 - 1000 MHz

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

4.3.3 RF Conducted Measurements at the Antenna Terminal (including Band Edge)

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

5.0 PEAK OUTPUT POWER - Section 15.247 (b)(3)

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

6.0 CHANNEL BANDWIDTH

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

7.0 PEAK POWER SPECTRAL DENSITY

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

8.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M101142_FCC_62205ANHMW_SAR_2.4 (2.4 GHz) and M101142_FCC_62205ANHMW_SAR_5.6 (5.18 – 5.825 GHz). SAR values of 1.53 mW/g (5GHz) and 0.404 mW/g (2.4GHz) were measured which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

9.0 ANTENNA REQUIREMENT

This intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.0 COMPLIANCE STATEMENT

The Portable PC Fujitsu LifeBook T Series, Model: T901 with Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHmw, **complied** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 8 and the RF exposure requirements of RSS-102.

Results were as follows:

FCC Subpart C, Section 15.247

FCC Part 15 Subpart C Clauses	Industry Canada RSS-210 Issue 7 and RSS-Gen Clauses	Test Performed	Results
15.203	RSS-Gen (7.1.4)	Antenna Requirement	Complies
15.205	2.2 (Table 1)	Operation in Restricted Band	Complies
15.207	RSS-Gen (7.2.2)	Conducted Emissions	Note 1
15.209	RSS-Gen (6)	Radiated Emissions	Complies
15.247 (a)(2)	A8.1 (b) (d)	Channel Bandwidth	Note 2
15.247 (b)(3)	A8.4	Peak Output Power	Note 2
15.247 (c)	RSS-Gen (7.1.4)	Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	A8.5	Out of Band Emissions	Complies
15.247 (e)	A8.2 (b)	Peak Power Spectral Density	Note 2
15.247 (f)	A8.3	Hybrid Systems (Note 3)	Not Applicable. EUT does not employ a hybrid system
15.247 (g)	A8.1	Frequency Hopping	Not Applicable. EUT does not employ frequency hopping
15.247 (h)	A8.1	Frequency Hopping	Not Applicable. EUT does not employ frequency hopping
15.247 (i)	RSS-Gen (5.5)	Radio Frequency Hazard	Complies

Note 1: Refer to Attachment 3, FCC Part 15B Test Report

Note 2: Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH)

Note 3: Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

11.0 MEASUREMENT UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions:	9 kHz to 30 MHz	±3.2 dB
Radiated Emissions:	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB
	1 GHz to 18 GHz	±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

12.0 TEST REPORT APPENDICES

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: PHOTOGRAPHS

APPENDIX C: OPERATIONAL DESCRIPTION

APPENDIX D: BLOCK DIAGRAM

APPENDIX E: ANTENNA INFORMATION

APPENDIX F: SCHEMATIC

APPENDIX G: FCC LABELLING DETAILS

APPENDIX H: USER MANUAL

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook T Series

Attachment 3: FCC Part 15B Test Report

Attachment 4: Intel FCC Part 15.247 Test Report