



Global Product Certification
EMC-EMF Safety Approvals

EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

FCC ID: EJE-WL0028
Industry Canada ID: 337J-WL0028

Test Sample: STYLISTIC Q Series
Model: Q702

Radio Module: Intel Centrino 6205 Taylor Peak 62205ANHMW WLAN

Report Number: M120811_FCC_62205ANHMW_NII

Issue Date: 15th August 2012

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.

This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

EMC Technologies Report No. M120811_FCC_62205ANHMW_NII

Issue Date: 15th August 2012

CONTENTS

**1.0 INTRODUCTION
2.0 GENERAL INFORMATION**

FCC 15.407 (U-NII) RESULTS

**3.0 CONDUCTED EMI MEASUREMENTS
4.0 RADIATED EMI MEASUREMENTS
5.0 PEAK OUTPUT POWER
6.0 CHANNEL BANDWIDTH
7.0 PEAK POWER SPECTRAL DENSITY
8.0 PEAK EXCURSION
9.0 FREQUENCY STABILITY
10.0 DYNAMIC FREQUENCY SELECTION
11.0 DISCONTINUE TRANSMISSION
12.0 RADIO FREQUENCY EXPOSURE
13.0 ANTENNA REQUIREMENT
14.0 COMPLIANCE STATEMENT
15.0 MEASUREMENT UNCERTAINTIES**

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

**APPENDIX B: PHOTOGRAPHS
APPENDIX C: OPERATIONAL DESCRIPTION
APPENDIX D: BLOCK DIAGRAM
APPENDIX E: SCHEMATIC
APPENDIX F: ANTENNA INFORMATION
APPENDIX G: FCC LABELLING DETAILS
APPENDIX H: USER MANUAL**

**Attachment – RF Exposure Information
Attachment – FCC DOC for STYLISTIC Q Series
Attachment – Intel FCC Part 15E Test Report
Attachment – Intel FCC Part 15E DFS Test Report**

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

Report No. M120811_FCC_62205ANHMW_NII

Test Sample: STYLISTIC Q Series
Model: Q702
Radio Module: Intel Centrino Advanced-N 6205 Taylor Peak 62205ANHMW WLAN

FCC ID: EJE-WL0028
Industry Canada ID: 337J-WL0028
Equipment Type: Intentional Radiator (Transceiver)

Manufacturer (LifeBook): Fujitsu Ltd
Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan
Contact: Mr. Tsuyoshi Uchihara, Mobile Computing Division

Test Standards: FCC Part 15 – Radio Frequency Devices (October 2009)
FCC Part 15, Subpart E – Unlicensed National Information, Infrastructure
Devices
FCC Part 15.407, General Technical Requirements

ANSI C63.4 – 2009

RSS-210 Issue 8 Low Power Licence-Exempt RadioCommunication Devices
Annex 9: Local Area Network Devices

RSS-GEN Issue 3 General Requirements and Information for the Certification
of Radiocommunication Equipment

Test Date: 13th August 2012

Test Engineer: Chieu Huynh - B.Eng (Hons) Electronics

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*



Authorised Signatory: Chieu Huynh
Senior EMC Engineer
EMC Technologies Pty Ltd

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210

1.0 INTRODUCTION

EMI testing was performed on the STYLISTIC Q Series, Model: Q702 with Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHMW.

The Taylor Peak 2x2 WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH).

The intention of this application is to FCC certify Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHMW **installed in** STYLISTIC Q Series, Model: Q702. The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The other transmitter that may be installed in the STYLISTIC Q Series, Model: Q702 is Broadcom Bluetooth Module, Model: BCM92070MD_REF6. The Bluetooth module was originally certified by Broadcom as a modular approval under FCC ID: QDS-BRCM1043 (Canada ID: 4324A-BRCM1043).

This Bluetooth pre-approved module, is not co-located as the WLAN and Bluetooth antennas are >5cms apart. The maximum power output of the Bluetooth module is 4dBm (2.5mW).

RF exposure and labeling will be addressed by Fujitsu according to FCC multi-transmitter and modular procedures.

There are two variants of the STYLISTIC Q Series, Model: Q702 covered in this report. One that is equipped with the modular certified low power Bluetooth transmitter with built-in antenna and one variant that does not contain Bluetooth transmitter or Bluetooth antenna. Testing was conducted on the sample that is equipped with the Bluetooth transmitter and Bluetooth antenna.

This certification is for the STYLISTIC Q Series, Model: Q702 with Intel 62205ANHMW WLAN module.

Appendix G shows the FCC label details.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart E:	Unlicensed National Information Infrastructure Devices (U-NII) operating in the 5.15-5.35 GHz, 5.47-5.725 GHz and 5.725-5.825 GHz frequency bands
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.407:	General Technical Requirements

The results and technical details of the test sample are detailed in this report. The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart E - Section 15.407.

The test sample also complied with the Industry Canada RSS-210 issue 8 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 and RSS-Gen.

The measurement procedure used was in accordance with ANSI C63.4-2009. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.1 Summary of Results

FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	IC RSS-210 and RSS-Gen Clauses	Test Performed	Result
15.203	RSS-Gen (7.1.2)	Antenna Requirement	Complies
15.205	RSS-Gen (7.2.2)	Operation in Restricted Band	Complies
15.207	RSS-Gen (7.2.4)	Conducted Emissions	Note 1
15.209	RSS-Gen (7.2.5)	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	Annex A9.2	Peak Transmit Power	Note 2
15.407 (a)(5)	Annex A9.2	Peak Power Spectral Density	Note 2
15.407 (a)(6)		Peak Excursion	Note 2
15.407 (b)	Annex A9.2	Undesirable Emission	Complies
15.407 (c)	Annex A9.4	Discontinue Transmission	Complies
15.407 (d)		Reserved	-
15.407 (e)	Annex A9.4	Restricted to Indoor Operations	Complies
15.407 (f)	RSS-Gen (5.6)	Radio Frequency Hazard	Complies
15.407 (g)	RSS-Gen (4.7)	Frequency Stability	Note 2
15.407 (h)		Transmit Power Control	Not Applicable E.I.R.P < 500 mW
15.407 (h)	Annex A9.3	Dynamic Frequency Selection	Note 2

Note 1: Refer to attached FCC Part 15B DoC

Note 2: Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH)

1.2 Modifications by EMC Technologies

No modifications were required.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (WLAN) Details


Transmitter:	Half Mini-Card Wireless LAN Module
Wireless Module:	Intel Centrino Advanced-N 6205 Taylor Peak 2x2 (11a/b/g/n)
Model Number:	62205ANHMW
Manufacturer:	Intel Corporation
Frequency Ranges:	2.412 – 2.462 GHz 5.18 - 5.32 GHz, 5.5 – 5.7 GHz and 5.745 - 5.825 GHz
Maximum Data Rates:	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps 802.11n = 450 Mbps
Antenna Types:	Nissei Inverted F (1 st , 2 nd)
Antenna gain:	Max antenna gain is less than 6 dBi. Refer antenna data provided separately

2.2 EUT (Notebook PC) Details

NoteBook PC:	STYLISTIC Q series
Model Name:	Q702
Serial Number:	Pre-production Sample
Manufacturer:	FUJITSU LIMITED

CPU Type and Speed:	Core i5 1.8GHz
LCD	11.7"WXGA(1280x800 : LP116WH4
Graphics chip	None
Wired LAN:	None
Modem:	None
Optional Docking Unit:	FPCPR199

AC Adapter Model:	60W: PXW1931N
Voltage:	19 V
Current Specs:	3.16A
Watts:	60W



2.3 Test Configuration

The Intel WLAN test software "DRTU" was used during the tests.

Power is provided via an AC adaptor. Testing was performed at a voltage of 120VAC at 50Hz.

2.4 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2009. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT.

2.5 Test Facility

2.5.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (Doc) and Certification under Parts 15 & 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001**.

EMC Technologies has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional) - **Industry Canada number 3569B**.

Measurements were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

2.5.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.6 Test Equipment Calibration

Measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by EMC Technologies. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

FCC 15.407 (U-NII) RESULTS

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

4.0 RADIATED EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.407(b).

Radiated emission measurements were performed to the limits as per section 15.209 and 15.407. Measurements above 1 GHz were made over a distance of 3 and 1 metres.

Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

E = Radiated Field Strength in dB μ V/m.

V = EMI Receiver Voltage in dB μ V. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB μ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

4.3 Results - Out of Band Emissions (Spurious and Harmonics)

This transmitter module was originally tested and certified by the manufacturer as a stand-alone module outside a laptop (host) with higher gain antennas. Refer to manufacturer's original test report (FCC Part 15E) for full results showing compliance with the spurious and harmonics limits. However, to ensure the transmitter module install in STYLISTIC Q Series, Model: Q702 is still in compliance, verification tests were performed at the worst case (frequencies with higher average output power) or selected frequencies for harmonics and spurious emissions.

Initial investigations were performed with all data rates. Final testing was performed while the transmitter continuously operated in the worst case condition.

All orientations were investigated and tested. Worst results were reported below.

4.3.1 Frequency Band: 1 – 40 GHz

The peak limits for undesirable emission outside of the restricted bands are –27 dBm (68.3 dB_uV/m @ 3m). The 74 dB_uV/m @ 3m and 54 dB_uV/m @ 3m limits are applied for emissions fall in the restricted bands. The limits are adjusted by 10.5 dB when measurements perform at a distance of 1m.

Testing was performed while the WLAN transmitter continuously operated. Harmonics related to the WLAN transmitter operated in the frequency bands 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are reported below. Harmonics in the frequency bands 2.4 – 2.4835 GHz and 5.725 – 5.850 GHz, refer to M120811_FCC_62205ANHMW_DTS.

Measurements were performed with the EUT operating in the worst case mode of single antenna transmitting. For multiple antennas transmitting like two antennas transmitting, the power level is 3 dB lower (50%) with respect to single antenna mode.

Harmonics were measured for channels where the RF output power was highest.

4.3.1.1 Configuration 802.11a

Frequency MHz	Peak Detector dB _u V/m	Average Detector dB _u V/m	Peak Limit dB _u V/m	Average Limit dB _u V/m	Result
5180	Transmit Frequency				
10360	57.4	44.1	68.3	-	Complied

Frequency MHz	Peak Detector dB _u V/m	Average Detector dB _u V/m	Peak Limit dB _u V/m	Average Limit dB _u V/m	Result
5320	Transmit Frequency				
10640	56.2	42.9	74.0	54.0	Complied

Frequency MHz	Peak Detector dB _u V/m	Average Detector dB _u V/m	Peak Limit dB _u V/m	Average Limit dB _u V/m	Result
5580	Transmit Frequency				
11160	55.0	40.3	74.0	54.0	Complied
16740	54.8	40.6	68.3	-	Complied

Result: Harmonic was recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.407 by a margin of 10.9 dB.

4.3.1.2 Configuration 802.11n – Tx BW = 20 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5240	Transmit Frequency				
10480	58.7	44.5	68.3	-	Complied

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5500	Transmit Frequency				
11000	55.7	42.3	74.0	54.0	Complied
16500	53.8	38.9	68.3	-	Complied

Result: Harmonic was recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.407 by a margin of 9.6 dB.

4.3.1.3 Configuration 802.11n – Tx BW = 40 MHz

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5270	Transmit Frequency				
10540	58.1	43.7	68.3	-	Complied

Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5670	Transmit Frequency				
11340	52.8	36.2	74.0	54.0	Complied

Result: Harmonic was recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions complied with the FCC limits of sections 15.209 and 15.407 by a margin of 10.2 dB.

4.3.2 Frequency Band: 30 - 1000 MHz

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

4.3.3 RF Conducted Measurements at the antenna terminal (including Band Edge)

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

5.0 PEAK OUTPUT POWER - Section 15.407(a)

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

6.0 CHANNEL BANDWIDTH

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

7.0 PEAK POWER SPECTRAL DENSITY

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

8.0 PEAK EXCURSION

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

9.0 FREQUENCY STABILITY

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

10.0 DYNAMIC FREQUENCY SELECTION

The EUT is a Client Device without Radar Interference Detection Function.

Ad-hoc operation (not under control of a Master Device) is supported in the 2.4 GHz & 5.15 - 5.25 GHz bands only. This Ad-hoc capability is limited in hardware via factory programmed EEPROM settings that cannot be accessed or changed by end users. The Ad-hoc supported channels of operation cannot be modified – regardless of which client utility or operating system control is used.

Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH) certified by INTEL.

Testing was performed by Elliott Laboratories CA, USA accredited by A2LA (Certificate Number: 2016.01)

11.0 DISCONTINUE TRANSMISSION

Data Transmission is always initiated by software, which is then passed down through the MAC, through the digital and analog baseband, finally to the RF chip. Several special packets (ACKs, CTS, PSPoll, etc) are initiated by the MAC. These are the only ways the digital baseband portion will turn on the RF transmitter, which then turns off at the end of the packet. Therefore, the transmitter will be ON only while one of the four mentioned packets is being transmitted.

12.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M120808_FCC_62205ANHMW_SAR_2.4 (2.4 GHz) and M120808_FCC_62205ANHMW_SAR_5.6 (5.18 – 5.825 GHz). SAR values of 1.20 mW/g (5GHz) and 1.16 mW/g (2.4GHz) were measured which complied with the FCC human exposure requirements of 47 CFR 2.1093 (d).

13.0 ANTENNA REQUIREMENT

This intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.0 COMPLIANCE STATEMENT

The STYLISTIC Q Series, Model: Q702 with Intel Centrino Advanced-N 6205 (Taylor Peak 802.11a/b/g/n 2x2), Model: 62205ANHMW, **complied** with the requirements of 47 CFR, Part 15 Subpart E -Section 15.407 (5.15-5.35 GHz and 5.47 – 5.725 GHz bands).

The test sample also complied with the Industry Canada RSS-210 issue 8 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 and RSS-Gen.

Results were as follows:

FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	IC RSS-210 and RSS-Gen Clauses	Test Performed	Result
15.203	RSS-Gen (7.1.2)	Antenna Requirement	Complies
15.205	RSS-Gen (7.2.2)	Operation in Restricted Band	Complies
15.207	RSS-Gen (7.2.4)	Conducted Emissions	Note 1
15.209	RSS-Gen (7.2.5)	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	Annex A9.2	Peak Transmit Power	Note 2
15.407 (a)(5)	Annex A9.2	Peak Power Spectral Density	Note 2
15.407 (a)(6)		Peak Excursion	Note 2
15.407 (b)	Annex A9.2	Undesirable Emission	Complies
15.407 (c)	Annex A9.4	Discontinue Transmission	Complies
15.407 (d)		Reserved	-
15.407 (e)	Annex A9.4	Restricted to Indoor Operations	Complies
15.407 (f)	RSS-Gen (5.6)	Radio Frequency Hazard	Complies
15.407 (g)	RSS-Gen (4.7)	Frequency Stability	Note 2
15.407 (h)		Transmit Power Control	Not Applicable E.I.R.P < 500 mW
15.407 (h)	Annex A9.3	Dynamic Frequency Selection	Note 2

Note 1: Refer to attached FCC Part 15B DoC

Note 2: Refer to original approval under FCC ID: PD962205ANH (Canada ID: 1000M-62205ANH)

15.0 MEASUREMENT UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions:	9 kHz to 30 MHz	±3.2 dB
Radiated Emissions:	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB
	1 GHz to 18 GHz	±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.