

CFR 47 FCC Part 15.247

TEST REPORT

Product : Transmitter

Trade Name : N/A

Model Number : 145SPR

FCC ID : ELVATNE

Prepared for

Nutek Corporation

NO. 167, Lane 235, Bauchiau Rd., Xindian District,
New Taipei City 23145, Taiwan

TEL. : +886 2 2918 9478

FAX. : +886 2 2917 9069

Prepared by

Interocean EMC Technology Corp.

No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,
Taiwan 244, R.O.C.

TEL.: +886 2 2600 6861

FAX.: +886 2 2600 6859

Remark :

The test report consists of **44** pages in total. It shall not be reproduced except in full, without the written approval of IETC. This document may be altered or revised by IETC only, and shall be noted in the revision section of the document.

The test result in the report is only subjected to the test sample.

Table of Contents

| | | |
|----------|--|-----------|
| 1 | General Information | 5 |
| 1.1 | Description of Equipment Under Test | 5 |
| 1.2 | Table for Carrier Frequencies | 6 |
| 1.3 | Hopping Sequence | 6 |
| 1.4 | Details of Tested Supporting System | 7 |
| 1.5 | Test Facility | 8 |
| 1.6 | Test Equipment | 9 |
| 1.7 | Summary of Measurement | 10 |
| 1.8 | Justification | 11 |
| 2 | Test specifications | 12 |
| 2.1 | Test standard | 12 |
| 2.2 | Operation mode | 12 |
| 2.3 | Test Step of EUT | 12 |
| 3 | 20dB Bandwidth test | 13 |
| 3.1 | Limit | 13 |
| 3.2 | Configuration of Measurement | 13 |
| 3.3 | Test Procedure | 13 |
| 3.4 | Test Result | 13 |
| 4 | Carrier Frequency Separation test | 17 |
| 4.1 | Limit | 17 |
| 4.2 | Configuration of Measurement | 17 |
| 4.3 | Test Procedure | 17 |
| 4.4 | Test Result | 17 |
| 5 | Number of hopping frequencies test | 21 |
| 5.1 | Configuration of Measurement | 21 |
| 5.2 | Test Procedure | 21 |
| 5.3 | Test Result | 21 |
| 6 | Time of Occupancy (dwell time) test | 23 |
| 6.1 | Limit | 23 |
| 6.2 | Configuration of Measurement | 23 |
| 6.3 | Test Procedure | 23 |
| 6.4 | Test Result | 23 |

| | | |
|-----------|---|-----------|
| 7 | Maximum Output Power test | 25 |
| 7.1 | Limit | 25 |
| 7.2 | Configuration of Measurement | 25 |
| 7.3 | Test Procedure | 25 |
| 7.4 | Test Result | 25 |
| 8 | RF Conducted spurious emission | 28 |
| 8.1 | Limit | 28 |
| 8.2 | Configuration of Measurement | 28 |
| 8.3 | Test Procedure | 28 |
| 8.4 | Test Result | 28 |
| 9 | RF Radiated spurious emission test | 32 |
| 9.1 | Limit | 32 |
| 9.2 | Configuration of Measurement | 32 |
| 9.3 | Test Procedure | 33 |
| 9.4 | Test Result | 33 |
| 10 | Photographs of Test | 38 |
| 10.1 | Radiated Emission Measurement | 38 |
| 11 | Photographs of EUT | 40 |

Statement of Compliance

Applicant: Nutek Corporation

Manufacturer: Nutek Corporation

Product: Transmitter

Model No.: 145SPR

Tested Power Supply: 3Vdc battery

Date of Final Test: Jul. 25, 2014

Revision of Report: Rev. 00

Configuration of Measurements and Standards Used :

FCC Rules and Regulations Part 15 Subpart C


I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of IETC

Report Issued: 2014/08/01

Project Engineer: 
Elli Chang

Approved: 
Jerry Liu

1 General Information

1.1 Description of Equipment Under Test

| | |
|-------------------------------|---|
| Product | : Transmitter |
| Model Number | : 145SPR |
| Applicant | : Nutek Corporation NO. 167, Lane 235, Bauchiau Rd., Xindian District, New Taipei City 23145, Taiwan |
| Manufacturer | : Nutek Corporation NO. 167, Lane 235, Bauchiau Rd., Xindian District, New Taipei City 23145, Taiwan |
| Power Supply | : 3Vdc battery |
| Operating Frequency | : 909.6MHz ~ 918MHz |
| Channel Number | : 25 channels |
| Type of Modulation | : FSK |
| Antenna Description | : This device uses PCB Printed antenna. Antenna gain 0dBi. The antenna is integral to the device, thereby meeting the requirement of FCC 15.203. |
| Date of Test | : Jul. 01 ~ 25, 2014 |
| Additional Description | : 1) The Model Number " 145SPR " is representative selected in the test and included in this report. 2) For more detail specification about EUT, please refer to the user's manual. |

1.2 Table for Carrier Frequencies

| | FC (MHz) | | FC (MHz) | | FC (MHz) |
|------------|-----------------|-------------|-----------------|-------------|-----------------|
| CH0 | 909.6000 | CH9 | 912.7500 | CH18 | 915.9000 |
| CH1 | 909.9500 | CH10 | 913.1000 | CH19 | 916.2500 |
| CH2 | 910.3000 | CH11 | 913.4500 | CH20 | 916.6000 |
| CH3 | 910.6500 | CH12 | 913.8000 | CH21 | 916.9500 |
| CH4 | 911.0000 | CH13 | 914.1500 | CH22 | 917.3000 |
| CH5 | 911.3500 | CH14 | 914.5000 | CH23 | 917.6500 |
| CH6 | 911.7000 | CH15 | 914.8500 | CH24 | 918.0000 |
| CH7 | 912.0500 | CH16 | 915.2000 | | |
| CH8 | 912.4000 | CH17 | 915.5500 | | |

1.3 Hopping Sequence

12, 8, 6, 2, 0, 5, 1, 7, 3, 9, 4, 10, 15, 19, 13, 11, 16, 18, 14, 20, 22, 21, 24, 23, 17

1.4 Details of Tested Supporting System

N/A

1.5 Test Facility

- Site Description** : ☒OATS 1 ☒RF Test Room
- Name of Firm** : Interocean EMC Technology Corp.
- Company web** : <http://www.ietc.com.tw>
- Location** : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City, Taiwan 244, R.O.C.
- Site Filing** :
- Federal Communication Commissions – USA
Registration No.: 96399 (OATS 1, 2, 3 & Chamber 3)
Designation No.: TW1020
 - Industry Canada (IC)
OUR FILE: 46405-4437
Registration No. (OATS 1): Site# 4437A-1
Registration No. (OATS 3): Site# 4437A-3
Registration No. (Chamber 3): Site# 4437A-5
Registration No. (OATS 5): Site# 4437A-6
 - Voluntary Control Council for Interference by Information Technology Equipment (VCCI) – Japan
Member No.: 1349
Registration No. (Conducted Room): C-1094
Registration No. (Conducted Room): T-1562
Registration No. (OATS 1): R-1040; G-274
Registration No. (OATS 2): R-1041
- Site Accreditation** :
- Bureau of Standards and Metrology and Inspection (BSMI) – Taiwan, R.O.C.
Accreditation No.:
SL2-IN-E-0026 for CNS13438 / CISPR 22
SL2-IN-E-0026 for CNS14757-2 / IEC 62040-2
SL2-R1-E-0026 for CNS13439 / CISPR 13
SL2-R2-E-0026 for CNS13439 / CISPR 13
SL2-A1-E-0026 for CNS13783-1 / CISPR 14-1
SL2-L1-E-0026 for CNS 14115 / CISPR 15
 - Taiwan Accreditation Foundation (TAF)
Accreditation No.: 1113
 - Vehicle Safety Certification Center (VSCC)
Approval No.: TW16-11-0
 - TÜV NORD
Certificate No: TNTW0801R-04
 - Nemko
Authorisation No: AeLA 011
Authorisation No: ELA 181

1.6 Test Equipment

| Instrument | Manufacturer | Model | Serial No. | Next Cal. Date |
|-------------------|-----------------|-------------------|---------------|----------------|
| Spectrum Analyzer | R&S | FSP40 | 100478 | 2015/06/02 |
| Preamplifier | Agilent | 8449B | 3008A01434 | 2015/05/07 |
| Preamplifier | Agilent | 83050A | 3950A00225 | 2014/09/08 |
| Horn Antenna | Schwarzbeck | BBHA 9120 | 9120D-583 | 2015/05/13 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | 213 | 2015/07/24 |
| Cable | HARBOUR | 27478LL142 | CBL22 | 2015/01/01 |
| EMI Test Receiver | Rohde & Schwarz | ESVS10 | 826148/011 | 2014/11/04 |
| Biconical Antenna | Schwarzbeck | BBA 9106 | VHA 9103-2418 | 2015/01/18 |
| Log Antenna | Schwarzbeck | UHALP 9108 A | 0738 | 2015/01/18 |
| Pre-Amplifier | Agilent | 8447D | 2944A09703 | 2015/04/29 |
| RF Cable | EMCI | EMC8D-NM-NM-25000 | 140105 | 2015/02/16 |
| RF Cable | Mini-Circuits | CBL-3FL-NMNM | CBL56 | 2014/08/30 |
| RF Cable | Insulated Wire | CBL59 | CBL59 | 2015/01/22 |

Note: The above equipments are within the valid calibration period.

1.7 Summary of Measurement

| Report Clause | Test Parameter | Reference Document CFR47 Part15 | Results |
|---------------|---------------------------------------|---------------------------------|----------------|
| 3 | 20dB Bandwidth test | §15.247(a)(1) | Pass |
| 4 | Carrier Frequency Separation test | §15.247(a)(1) | Pass |
| 5 | Number of hopping frequencies test | §15.247(a)(1) | Pass |
| 6 | Time of Occupancy (dwell time) test | §15.247(a)(1) | Pass |
| 7 | Maximum Peak output power test | §15.247(b) | Pass |
| 8 | RF Conducted spurious emission | §15.247(c) | Pass |
| 9 | RF Radiated spurious emission test | §15.205, 15.209 | Pass |
| | Emission on the Band Edge test | §15.247(d) | Not Applicable |
| | AC Power Line Conducted Emission test | §15.207 | Not Applicable |

1.8 Justification

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of the frequency band were all arrive limit requirement, thus we evaluate the EUT pass the specified test.

2 Test specifications

2.1 Test standard

The EUT was performed according to FCC Part 15 Subpart C Section 15.247 procedure and setup followed by ANSI C63.4, 2003 requirements.

2.2 Operation mode

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report

The EUT was operated in continuous transmission mode during all of the tests.



X axis mode



Y axis mode



Z axis mode

2.3 Test Step of EUT


- 2.3.1 Setup the fixture to EUT for power supplying.
- 2.3.2 Turn on the power of all equipment.
- 2.3.3 Let the EUT continuous transmission. Executed the test.

3 20dB Bandwidth test

3.1 Limit

For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

3.2 Configuration of Measurement



3.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

The 20dB bandwidth per FCC §15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 10 kHz, the video bandwidth \geq RBW, and the SPAN may equal to approximately 2 to 3 time the 20dB bandwidth.

3.4 Test Result


PASS.

The final test data is shown as following pages.

20dB bandwidth

| Test CH | | 20dB Bandwidth (kHz) | Limit (kHz) | Result |
|---------|-------------|----------------------|-------------|--------|
| CH No. | Freq. (MHz) | | | |
| 0 | 909.6 | 300.00 | 250 - 500 | PASS |
| 12 | 913.8 | 290.00 | 250 - 500 | PASS |
| 24 | 918.0 | 296.00 | 250 - 500 | PASS |


CH0 909.6MHz



CH12 913.8MHz




Ref 11 dBm *Att 10 dB *RBW 10 kHz Marker 2 [T1] 0.78 dBm
*VBW 30 kHz 913.918000000 MHz
SWT 10 ms



CH24 918.0MHz



Ref 11 dBm *Att 10 dB *RBW 10 kHz Marker 2 [T1] 1.21 dBm
*VBW 30 kHz 918.12800000 MHz
SWT 10 ms




4 Carrier Frequency Separation test

4.1 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

4.2 Configuration of Measurement



4.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

The carrier frequency separation per FCC Part15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at $\geq 1\%$ of the span, the video bandwidth \geq RBW, and the SPAN was wide enough to capture the peaks of two adjacent channels.

4.4 Test Result


PASS.

The final test data is shown as following pages.

Carrier Frequency Separation test

| Modulation type | Frequency (MHz) | Separation (kHz) | Result |
|-----------------|-----------------|------------------|--------|
| FSK | 909.60-909.95 | 346.00 | PASS |
| FSK | 913.80-914.15 | 388.00 | PASS |
| FSK | 917.65-918.00 | 372.00 | PASS |

Channel Separation (909.6MHz)



Channel Separation (913.8MHz)




*RBW 10 kHz Delta 1 [T1]
*VBW 30 kHz -0.57 dB
SWT 10 ms 388.00000000 kHz

Ref 11 dBm

*Att 10 dB

1. PK
VIEW



Channel Separation (918MHz)




*RBW 10 kHz Delta 1 [T1]
*VBW 30 kHz 0.07 dB
SWT 10 ms 372.00000000 kHz

Ref 11 dBm

*Att 10 dB

1. PK
VIEW




Center 917.888 MHz

100 kHz/

Span 1 MHz

5 Number of hopping frequencies test

5.1 Configuration of Measurement



5.2 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

The number of hopping frequencies per FCC Part15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at $\geq 1\%$ of the span, the video bandwidth \geq RBW, and the SPAN was the frequency band of operation.

5.3 Test Result


PASS.

The final test data is shown as following pages.

Number of hopping frequencies test

| Modulation | No. of Hopping CH. |
|------------|--------------------|
| FSK | 25 |

Channel Number




6 Time of Occupancy (dwell time) test

6.1 Limit

For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

6.2 Configuration of Measurement



6.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

According to FCC Part15.247(a)(1) the time of occupancy (dwell time) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 1MHz, the video bandwidth \geq RBW and the zero span function of spectrum analyzer was enable. The EUT has its hopping function enable.

6.4 Test Result


PASS.

The final test data is shown as following pages.


Time of Occupancy (dwell time) test

3 occurrences in 10 seconds x 132.78 ms = 398.34 ms which is less than 400 ms.

Dwell time-1



Dwell time-2




7 Maximum Output Power test

7.1 Limit

For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

7.2 Configuration of Measurement



7.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

For FCC Part 15.247(b) the power output per was measured on the EUT using a 50 ohm SMA cable connected to peak Spectrum Analyzer. Peak output power was read directly from Spectrum Analyzer. The test was performed at 3 channels (lowest, middle and highest).

7.4 Test Result


PASS.

The final test data is shown as following pages.


Maximum output power

| Channel | Frequency (MHz) | Maximum transmit power (dBm) | Watts | Limit (dBm) | Margin (dB) |
|---------|-----------------|------------------------------|---------|-------------|-------------|
| 0 | 909.6 | 1.90 | 0.00155 | 24 | -22.10 |
| 12 | 913.8 | 2.06 | 0.00161 | 24 | -21.94 |
| 24 | 918.0 | 2.31 | 0.00170 | 24 | -21.69 |


CH0 909.6MHz



CH12 913.8MHz



CH24 918.0 MHz




8 RF Conducted spurious emission

8.1 Limit

According to FCC Part 15.247(d) requirement :

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

8.2 Configuration of Measurement



8.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

RF antenna conducted spurious emissions was measured from the EUT antenna port using a 50ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 100 kHz.

The measurements were performed from 30MHz to 10GHz.

8.4 Test Result

PASS.

The final test data is shown as following pages.

Conducted spurious emission

909.6MHz (30MHz ~ 1GHz)




*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz 0.74 dBm
SWT 100 ms 910.76000000 MHz

Ref 11 dBm

*Att 10 dB

1 PK
MAXH



909.6MHz (1~10GHz)




*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -40.72 dBm
SWT 900 ms 1.810000000 GHz

Ref 11 dBm

*Att 10 dB


1 PK
MAXH



913.8MHz (30MHz ~ 1GHz)




Ref 11 dBm *Att 10 dB SWT 100 ms 914.64000000 MHz
*RBW 100 kHz Marker 1 [T1] 0.93 dBm
*VBW 100 kHz




913.8MHz (1~10GHz)




Ref 11 dBm *Att 10 dB SWT 900 ms 1.828000000 GHz
*RBW 100 kHz Marker 1 [T1] -41.43 dBm
*VBW 100 kHz



918MHz (30MHz ~ 1GHz)



918MHz (1~10GHz)



9 RF Radiated spurious emission test

9.1 Limit


For intentional radiator, the radiated emission shall comply with FCC Part 15.209(a).

For intentional radiators, according to FCC Part 15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with FCC Part 15.247 (c)


| Frequency (MHz) | Field strength dB(μ V/m) | Measurement distance (meters) |
|-----------------|-------------------------------|-------------------------------|
| 1.705~30.0 | 29.5 | 30 |
| 30 ~ 88 | 40 | 3 |
| 88~216 | 43.5 | 3 |
| 216~960 | 46 | 3 |
| Above 960 | 54 | 3 |

9.2 Configuration of Measurement

Measurement Frequency under 1GHz



Measurement Frequency above 1GHz



9.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

Radiated emission measurements were performed from 30MHz to 10GHz. Spectrum Analyzer set as below: For frequency range from 30MHz to 1GHz: RBW=100kHz or greater. For frequencies above 1GHz: set RBW=VBW=1MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and whole system. During the test, all cables were arranged to present worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meter and down to 1 meter.

9.4 Test Result

PASS.

The final test data is shown as following pages.

Radiated spurious emission

Test Environment

Ambient temperature : 25.9°C

Relative humidity : 43%

Radiated Emission below 1GHz

After verifying low, middle and high channel,
 The worse case was found at High channel X Axis.

| Frequency | Antenna | Reading | Preamp | Correction Factor | Corrected Level | Limits | Margin | Det |
|-----------|--------------|---------|--------|-------------------|-----------------|----------|--------|------|
| (MHz) | Polarization | (dBuV) | (dB) | (dB/m) | (dBuV/m) | (dBuV/m) | (dB) | Mode |
| 153.680 | H | 41.20 | 30.27 | 17.05 | 27.98 | 43.52 | -15.54 | PK |
| 197.530 | H | 41.35 | 30.00 | 19.52 | 30.87 | 43.52 | -12.65 | PK |
| 289.710 | H | 39.55 | 29.46 | 23.43 | 33.52 | 46.02 | -12.50 | PK |
| 347.850 | H | 42.57 | 29.42 | 18.71 | 31.86 | 46.02 | -14.16 | PK |
| 468.200 | H | 39.08 | 30.39 | 22.26 | 30.95 | 46.02 | -15.07 | PK |
| 657.230 | H | 36.98 | 30.03 | 25.73 | 32.68 | 46.02 | -13.34 | PK |
| 72.300 | V | 48.95 | 30.63 | 7.69 | 26.01 | 40.00 | -13.99 | PK |
| 166.000 | V | 41.00 | 29.72 | 18.54 | 29.82 | 43.52 | -13.70 | PK |
| 234.700 | V | 39.76 | 29.55 | 21.19 | 31.40 | 46.02 | -14.62 | PK |
| 394.500 | V | 38.99 | 29.96 | 20.51 | 29.54 | 46.02 | -16.48 | PK |
| 510.400 | V | 38.70 | 29.42 | 22.58 | 31.86 | 46.02 | -14.16 | PK |
| 655.000 | V | 36.50 | 30.00 | 25.43 | 31.93 | 46.02 | -14.09 | PK |

Remark : Corrected Level = Reading + Correction Factor – Preamp

Correction Factor = Antenna Factor + Cable Loss

The present spurious only show those points are above noise level and the frequency range test from 30MHz to 1GHz.

Radiated spurious emission

Radiated Emission above 1GHz

Channel 0 (909.6MHz)

| Frequency | Antenna | Reading | Preamp | Correction Factor | Corrected Level | Limits | Margin | Det |
|-----------|--------------|---------|--------|-------------------|-----------------|----------|--------|------|
| (MHz) | Polarization | (dBuV) | (dB) | (dB/m) | (dBuV/m) | (dBuV/m) | (dB) | Mode |
| 1819.20 | H | 50.06 | 27.71 | 29.50 | 51.85 | 74.00 | -22.15 | PK |
| 1819.20 | H | 48.40 | 27.71 | 29.50 | 50.19 | 54.00 | -3.81 | AV |
| 2728.80 | H | 45.66 | 27.88 | 32.51 | 50.29 | 74.00 | -23.71 | PK |
| 2728.80 | H | 41.82 | 27.88 | 32.51 | 46.45 | 54.00 | -7.55 | AV |
| 3638.40 | H | 44.89 | 27.81 | 34.45 | 51.53 | 74.00 | -22.47 | PK |
| 3638.40 | H | 39.12 | 27.81 | 34.45 | 45.76 | 54.00 | -8.24 | AV |
| 4548.00 | H | 43.10 | 27.50 | 36.76 | 52.36 | 74.00 | -21.64 | PK |
| 4548.00 | H | 35.33 | 27.50 | 36.76 | 44.59 | 54.00 | -9.41 | AV |
| 5457.60 | H | 35.89 | 27.77 | 38.96 | 47.08 | 54.00 | -6.92 | PK |
| 6367.20 | H | 34.85 | 27.48 | 41.54 | 48.91 | 54.00 | -5.09 | PK |
| *7276.8 | H | 34.20 | 27.26 | 44.81 | 51.75 | 54.00 | -2.25 | PK |
| 1819.20 | V | 55.40 | 27.71 | 29.50 | 57.19 | 74.00 | -16.81 | PK |
| 1819.20 | V | 51.66 | 27.71 | 29.50 | 53.45 | 54.00 | -0.55 | AV |
| 2728.80 | V | 44.11 | 27.88 | 32.51 | 48.74 | 74.00 | -25.26 | PK |
| 2728.80 | V | 35.77 | 27.88 | 32.51 | 40.40 | 54.00 | -13.60 | AV |
| 3638.40 | V | 41.96 | 27.81 | 34.45 | 48.60 | 74.00 | -25.40 | PK |
| 3638.40 | V | 35.77 | 27.81 | 34.45 | 42.41 | 54.00 | -11.59 | AV |
| 4548.00 | V | 41.40 | 27.50 | 36.76 | 50.66 | 74.00 | -23.34 | PK |
| 4548.00 | V | 32.83 | 27.50 | 36.76 | 42.09 | 54.00 | -11.91 | AV |
| 5457.60 | V | 37.50 | 27.77 | 38.96 | 48.69 | 54.00 | -5.31 | PK |
| 6367.20 | V | 35.26 | 27.48 | 41.54 | 49.32 | 54.00 | -4.68 | PK |
| *7276.8 | V | 34.82 | 27.26 | 44.81 | 52.37 | 54.00 | -1.63 | PK |

Remark : Corrected Level = Reading + Correction Factor – Preamp

Correction Factor = Antenna Factor + Cable Loss

* Mark indicated background noise level.

Channel 12 (913.8MHz)

| Frequency | Antenna | Reading | Preamp | Correction Factor | Corrected Level | Limits | Margin | Det |
|-----------|--------------|---------|--------|-------------------|-----------------|----------|--------|------|
| (MHz) | Polarization | (dBuV) | (dB) | (dB/m) | (dBuV/m) | (dBuV/m) | (dB) | Mode |
| 1827.60 | H | 49.62 | 27.72 | 29.52 | 51.42 | 74.00 | -22.58 | PK |
| 1827.60 | H | 47.36 | 27.72 | 29.52 | 49.16 | 54.00 | -4.84 | AV |
| 2741.40 | H | 44.75 | 27.88 | 32.54 | 49.41 | 74.00 | -24.59 | PK |
| 2741.40 | H | 41.85 | 27.88 | 32.54 | 46.51 | 54.00 | -7.49 | AV |
| 3655.20 | H | 44.45 | 27.81 | 34.53 | 51.17 | 74.00 | -22.83 | PK |
| 3655.20 | H | 39.12 | 27.81 | 34.53 | 45.84 | 54.00 | -8.16 | AV |
| 4569.00 | H | 44.45 | 27.51 | 36.82 | 53.76 | 74.00 | -20.24 | PK |
| 4569.00 | H | 37.93 | 27.51 | 36.82 | 47.24 | 54.00 | -6.76 | AV |
| 5482.80 | H | 36.90 | 27.78 | 39.00 | 48.12 | 54.00 | -5.88 | PK |
| 6396.60 | H | 35.38 | 27.47 | 41.66 | 49.57 | 54.00 | -4.43 | PK |
| *7310.4 | H | 34.76 | 27.25 | 44.94 | 52.45 | 54.00 | -1.55 | PK |
| 1827.60 | V | 54.80 | 27.72 | 29.52 | 56.60 | 74.00 | -17.40 | PK |
| 1827.60 | V | 51.42 | 27.72 | 29.52 | 53.22 | 54.00 | -0.78 | AV |
| 2741.40 | V | 43.28 | 27.88 | 32.54 | 47.94 | 74.00 | -26.06 | PK |
| 2741.40 | V | 38.42 | 27.88 | 32.54 | 43.08 | 54.00 | -10.92 | AV |
| 3655.20 | V | 43.00 | 27.81 | 34.53 | 49.72 | 74.00 | -24.28 | PK |
| 3655.20 | V | 36.35 | 27.81 | 34.53 | 43.07 | 54.00 | -10.93 | AV |
| 4569.00 | V | 41.05 | 27.51 | 36.82 | 50.36 | 54.00 | -3.64 | PK |
| 5482.80 | V | 36.58 | 27.78 | 39.00 | 47.80 | 54.00 | -6.20 | PK |
| 6396.60 | V | 35.71 | 27.47 | 41.66 | 49.90 | 54.00 | -4.10 | PK |
| *7310.4 | V | 34.85 | 27.25 | 44.94 | 52.54 | 54.00 | -1.46 | PK |

Remark : Corrected Level = Reading + Correction Factor – Preamp

Correction Factor = Antenna Factor + Cable Loss

* Mark indicated background noise level.

Channel 24 (918MHz)

| Frequency | Antenna | Reading | Preamp | Correction Factor | Corrected Level | Limits | Margin | Det |
|-----------|--------------|---------|--------|-------------------|-----------------|----------|--------|------|
| (MHz) | Polarization | (dBUV) | (dB) | (dB/m) | (dBUV/m) | (dBUV/m) | (dB) | Mode |
| 1836.00 | H | 48.78 | 27.72 | 29.54 | 50.60 | 74.00 | -23.40 | PK |
| 1836.00 | H | 47.00 | 27.72 | 29.54 | 48.82 | 54.00 | -5.18 | AV |
| 2754.00 | H | 46.23 | 27.89 | 32.59 | 50.93 | 74.00 | -23.07 | PK |
| 2754.00 | H | 42.62 | 27.89 | 32.59 | 47.32 | 54.00 | -6.68 | AV |
| 3672.00 | H | 46.33 | 27.81 | 34.62 | 53.14 | 74.00 | -20.86 | PK |
| 3672.00 | H | 41.50 | 27.81 | 34.62 | 48.31 | 54.00 | -5.69 | AV |
| 4590.00 | H | 44.20 | 27.52 | 36.89 | 53.57 | 74.00 | -20.43 | PK |
| 4590.00 | H | 37.00 | 27.52 | 36.89 | 46.37 | 54.00 | -7.63 | AV |
| 5508.00 | H | 35.86 | 27.78 | 39.03 | 47.11 | 54.00 | -6.89 | PK |
| 6426.00 | H | 35.57 | 27.47 | 41.77 | 49.87 | 54.00 | -4.13 | PK |
| *7344.0 | H | 34.69 | 27.23 | 45.07 | 52.53 | 54.00 | -1.47 | PK |
| 1836.00 | V | 53.71 | 27.72 | 29.54 | 55.53 | 74.00 | -18.47 | PK |
| 1836.00 | V | 51.48 | 27.72 | 29.54 | 53.30 | 54.00 | -0.70 | AV |
| 2754.00 | V | 43.66 | 27.89 | 32.59 | 48.36 | 74.00 | -25.64 | PK |
| 2754.00 | V | 38.52 | 27.89 | 32.59 | 43.22 | 54.00 | -10.78 | AV |
| 3672.00 | V | 42.70 | 27.81 | 34.62 | 49.51 | 74.00 | -24.49 | PK |
| 3672.00 | V | 36.60 | 27.81 | 34.62 | 43.41 | 54.00 | -10.59 | AV |
| 4590.00 | V | 41.12 | 27.52 | 36.89 | 50.49 | 54.00 | -3.51 | PK |
| 5508.00 | V | 35.94 | 27.78 | 39.03 | 47.19 | 54.00 | -6.81 | PK |
| 6426.00 | V | 35.42 | 27.47 | 41.77 | 49.72 | 54.00 | -4.28 | PK |
| *7344.0 | V | 35.10 | 27.23 | 45.07 | 52.94 | 54.00 | -1.06 | PK |

Remark : Corrected Level = Reading + Correction Factor – Preamp

Correction Factor = Antenna Factor + Cable Loss

* Mark indicated background noise level.