

# RF Exposure Evaluation

E.U.T. : Transmitter

Model Number : 145SPR


Applicant : **Nutek Corporation**


Address : NO. 167, Lane 235, Bauchiau Rd., Xindian District,  
New Taipei City 23145, Taiwan

Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,  
Taiwan 244, R.O.C.

Report Issued : 2014/08/01

Project Engineer :   
Elli Chang

Approved :   
Jerry Liu

### Portable Device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498\_D01\_V05 4.3.1(1)

SAR exclusion thresholds by:

$[\text{max. power of channel, including tune-up tolerance, mW}]/(\text{min, test separation distances, mm}) * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

and  $\leq 7.5$  for 10-g extremity SAR.

### Maximum measured transmitter power

Frequency Range (MHz)	Maximum peak power (dBm)	Maximum peak power (mW)
909.6	1.90	1.5488
913.8	2.06	1.6069
918.0	2.31	1.7022

$$(1.7022/5) * (\sqrt{0.918}) = 0.32618 \leq 3.$$

**Conclusion:** No SAR is required.

### SIMULTANEOUS TRANSMISSION EVALUATION

N/A