

RF Exposure Evaluation

E.U.T. : Transmitter

Model Number : 175XPR

Applicant : Nutek Corporation


Address : No.167, Lane 235, Bauchiau Rd., Xindian District,
New Taipei City 23145, Taiwan

Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,
Taiwan 244, R.O.C.

Report Issued : 2017/07/11

Project Engineer : _____



Elli Chang

Approved: _____



Jerry Liu

1 RF Exposure Evaluation

Portable Device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB 447498_D01_V06 4.3.1(a) SAR exclusion thresholds by:
 [max. power of channel, including tune-up tolerance, mW]/(min, test separation distances, mm)]* $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Maximum measured transmitter power

Frequency Range (MHz)	Maximum measured transmitter power (dBm)	Tune-up power tolerance (dB)	Total Maximum power (dBm)	Total Maximum power (mW)
909.6	-1.46	(±)2	0.54	1.132
913.8	-2.00	(±)2	0.00	1.00
918.0	-2.46	(±)2	-0.46	0.899

$$(1.132/5)*(\sqrt{0.9096})=0.216 \leq 7.5$$

Conclusion:

No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A