

# RF Exposure Evaluation

E.U.T. : Transceiver

Model Number : TRX15SS


Applicant : **Nutek Corporation**


Address : NO. 167, Lane 235, Bauchiau Rd., Xindian District,  
New Taipei City 23145, Taiwan

Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,  
Taiwan 244, R.O.C.

Report Issued : 2015/09/22

Project Engineer :   
Elli Chang

Approved :   
Jerry Liu

## RF Exposure Evaluation

### Portable Device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio

frequency energy level in excess of the Commission's guidelines.

According to KDB 447498\_D01\_V05 4.3.1(1)

SAR exclusion thresholds by:

$[\text{max. power of channel, including tune-up tolerance, mW}]/(\text{min, test separation distances, mm}) \times [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

and  $\leq 7.5$  for 10-g extremity SAR.

### Maximum measured transmitter power

Frequency Range (MHz)	Maximum measured transmitter power (dBm)	Tune-up power tolerance (dB)	Total Maximum power (dBm)	Total Maximum power (mW)
909.6	12.70	(±)2	14.70	29.5121
913.8	12.69	(±)2	14.69	29.4442
918.0	12.69	(±)2	14.69	29.4442

$$(29.5121/5) \times (\sqrt{0.9096}) = 5.62931 \leq 7.5$$

**Conclusion:** No SAR is required.

### SIMULTANEOUS TRANSMISSION EVALUATION

N/A