

Description of components of RF Mouse

RO07001001X01-C DESCRIPTION:IBM 27MHZ RF USB Mouse

CODE	ITEM NO.	DESCRIPTION	PRICE	Q'TY	Location
1	EXTL021200(-C)	RESONATOR 6.0Mhz		1	Y1
2	EOTH0H9600(-C)	GLOBAL LINK RF MODULE		1	JP5
3	ASYM139450(-C)	SMD ASS'Y			
4	MP830N0000(-C)	BATTERY CONTACT (+)		1	BT1+
5	MP840N0000(-C)	BATTERY CONTACT (-)		1	BT1-
6	ESWC041800(-C)	DICGU TS-02P-130		1	S1
7	ESNS009300(-C)	IR-M00A1(JIN)		2	K1,2
8	ESNS010500(-C)	Digital OC-M00B1/LV(R)		2	U4,5
9	EPCB0S8300(-C)	PCB'M (IBM 27MHZ RF) (-1)	2.5HKD	1	
10	ECAPB00100(-C)	CAP SMD CER 0.1UF 50V	0.044HKD	9	C1,2,3,8,9,10,11,12,19
11	541031506500	CAP 15PF NPO 5% 50V 0805		2	C20,23
12	541031217500	CAP 120PF NPO 10%50V 0805		1	C21
13	ECAPB03700(-C)	CAP CER 33pF 25V +80/-20%	0.039HKD	2	C5,6,
14	ERES000F02(-C)	RES SMD 0 OHM 1/10W 5%	0.0105HKD	1	R18
15	ERES101F02(-C)	RES SMD 100 OHM 1/10W 5%	0.0105HKD	1	R8
16	ERES102F02(-C)	RES SMD 1K OHM 1/10W 5%	0.0105HKD	2	R2,9
17	ERES104F02(-C)	RES SMD 100K OHM 1/10W 5%	0.0175HKD	1	R1
18	ERES151F02(-C)	RES SMD 150 OHM 1/10W 5%	0.0105HKD	2	R20,21
19	ERES333F02(-C)	RES SMD 33K OHM 1/10W 5%	0.0105HKD	1	R6
20	ERES473F02(-C)	RES SMD 47K OHM 1/10W 5%	0.0105HKD	4	R10,11,12,13
21	ETRS004400(-C)	TRANSISTOR SMT 2N3906	0.145HKD	2	Q1,2
22	542034736500	CAP CER 0.047uF 50V	0.044HKD	1	C7
23	EIC1161600(-C)	VOLTAGE DETECTOR 2.4V	20JPY	1	U6
24	EPMA014250(-C)	IBM RF 4D 27MHZ MOUSE F/W		1	
25	EPCB0S5100(-C)	SUB PCB'M (3 KEY + FSR DIP) (-1)	0.2HKD	1	
26	EOTH0H19700(-C)	FLAT CABLE 20mm 5P pitch2.0mm	0.1HKD	1	JP6
27	ECAB122300(-C)	FLAT CABLE 20mm 6P pitch 2.0mm		1	JP3
28	EOTH0F5200(-C)	2.54MM PITCH,3PIN HEAD	0.035HKD	2	P1,2
29	ESWC048100(-C)	TACT Switch (E-Switch)	0.19HKD	3	SW1,2,3