



**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT  
INTENTIONAL RADIATOR CERTIFICATION TO  
FCC PART 15 SUBPART C REQUIREMENT**

*OF*

FCC ID: EMJ202R70

**RF WIRELESS MOUSE**

**MODEL NO: RO07**

**REPORT NO: RF00002**

**DEC. 11, 2000**

*Prepared for*

**PRIMAX ELECTRONICS LTD.**

**No. 669, Ruen Kuang Road,**

**Neihu Taipei, Taiwan R.O.C.**

*Prepared by*

**C&C LABORATORY CO., LTD.**

**#B1, 1<sup>st</sup> FL., UNIVERSAL CENTER, NO.183,  
SEC.1, TATUNG RD., HSI CHIN, TAIPEI HSIEN,  
TAIWAN, R.O.C.**

**TEL: (03) 324-0332**

**FAX: (03) 324-5235**

---

TABEL OF CONTENTS

PAGE

---


1. VERIFICATION OF COMPLIANCE.....	3
2. DESCRIPTION OF EQUIPMENT UNDER MEASUREMENT (EUT).....	4
3. ANTENNA CONNECTION.....	4
4. CHANNEL USAGE.....	5
5. THEORY OF OPERATION.....	5
6. EUT SETUP FOR MEASUREMENT PURPOSE.....	5
7. MEASUREMENT LOCATION.....	5
8. SUPPORT EQUIPMENT.....	5
9. MEASUREMENT CONFIGURATION(SIGNAL PATH ONLY).....	6
10. MEASUREMENT PROCEDURES AND MEASUREMENT RESULTS.....	6
RADIATED EMISSIONS (GENERAL REQUIREMENTS).....	6
AC LINE CONDUCTED EMISSIONS.....	10
THE EMISSION LEVEL IN OPERATING BAND.....	13
11. RADIATED EMISSION MEASUREMENT SETUP PHOTO.....	17
12. AC LINE CONDUCTED EMISSION MEASUREMENT SETUP PHOTO.....	18

**1. VERIFICATION OF COMPLIANCE**

COMPANY NAME : PRIMAX ELECTRONICS LTD.  
 No. 669, Ruen Kuang Road, Neihu Taipei, Taiwan R.O.C.  
 CONTACT PERSON : Raymond Liang  
 TELEPHONE NO : 02-22993279 ext 377  
 EUT DESCRIPTION : RF WIRELESS MOUSE  
 MODEM NAME : RO07  
 DATE OF MEASUREMENT: Dec. 05, 2000

LIMITES APPLY TO: FCC PART 15 SECTION 15.227	
TECHNICAL LIMITS	MEASUREMENT RESULT
Radiated Emission/ 15.205 & 15.209	PASS
AC Line Conducted Emission/15.207	PASS
Emission in operating band/15.227	PASS

The above equipment was tested by C&C Laboratory Co. Ltd. for compliance with the requirements set forth in CFR 47 PART 15, SUBPART C. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requires.




---

Charles Wang/ Technical Director  
 C&C Laboratory Co. Ltd.

**2. DESCRIPTION OF EQUIPMENT UNDER MEASUREMENT (EUT)**

RO07 is a wireless mouse product which allow its users to connect it to the USB port of PC through its receiver unit and wireless controlled by host mouse unit (Transmitter) to form a typical application as a traditional mouse

Transmitter Technical Data	
Actual Operating Frequency	26.985 MHz to 27.26 MHz
Transmit Power	0.75dBm
Modulation scheme	FSK
Power consumption	Maximum -----25mA Standby -----0.80mA Sleep -----0.02mA (wake-up by clicking mouse key only)
Channel	6 channel with 4 bit security ID for mouse
Antenna type	Antenna match at 27 MHz, integrated inside housing
Operation range	1.5m (minimum)
DC voltage	3V(2*AAA Alkaline battery for mouse)

Receiver Technical Data	
PC interface type	From USB interface
DC voltage	From PC
Antenna type	Wired-loop antenna integrated inside housing
Receiver power consumption	60 mA
Receiver dynamic range	0 dBm ~ 90 dBm

**3. ANTENNA CONNECTION**

The RF wireless mouse equipped with an integrated antenna fixed permanently in transmitting unit, user can't changeable.

#### 4. CHANNEL USAGE

The operating frequency used is 27.05908 MHz, it is subject to the requirement of FCC CFR 47 ; 15.227.

#### 5. THEORY OF OPERATION

The unit is working at 27.05908 MHz as a carrier to send communication signal to PC through a receiver which is sold together with the transmitter (Mouse host unit).

#### 6. EUT SETUP FOR MEASUREMENT PURPOSE

The EUT (transmitter) was setup as a minimum test configuration as like testing to regular ITE product as per requirement described in ANSI C63.4-1992. The function of EUT was checked and stay in working status under the tests.

#### 7. MEASUREMENT LOCATION

All emissions tests were performed at:

C&C Laboratory Co. Ltd.

No.15, 14 Lin, Chin Twu Chi, Lu Chu Hsiang, Taoyuan, Taiwan R.O.C.

C&C has site descriptions on file with the FCC for 10 and 3 meter site configurations. C&C is a A2LA accredited facility.


Radiated emissions from the EUT were performed at site 4, one of our 3/10 meters sites.

Conducted emissions – NA (Because the EUT was powered with Battery)

#### 8. SUPPORT EQUIPMENT

No.	Equipment	Model #	Serial #	FCC ID	Trade Name	Data Cable	Power Cord
1.	PC	D84XX	SG93000552	FCC DoC	HP	Shielded, 1.8m	Unshielded, 1.8m
2.	Modem	2400	94-364-176276	DK467GSM24	Computer Peripherals	Shielded, 1.8m	Unshielded, 1.8m
3.	Monitor	D2835	KR74011499	A3LCGE750	HP	Shielded, 1.8m	Unshielded, 1.8m
4.	Printer	2225C	3137S01428	DSI6XU2225	HP	Shielded, 1.8m	Unshielded, 1.8m
5.	Keyboard	2225C	3137S01428	DSI6XU2225	HP	Shielded, 1.8m	N/A
6.	Mouse	M-S34	LZC81065474	DZL211029	HP	Shielded, 1.8m	N/A
7.	Keyboard	SK-8808	N/A	GYUR93SK	IBM	N/A	N/A

**9. MEASUREMENT CONFIGURATION(SIGNAL PATH ONLY)**



**10. MEASUREMENT PROCEDURES AND MEASUREMENT RESULTS**

➤ *Radiated Emissions (General Requirements)*

**Measurement Requirement: 15.205, 15.209**

**Measurement facility used for Radiated Emissions**

Open Area Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3132	91700456	02/15/2000	02/14/2001
EMI Test Receiver	R&S	ESCS30	847793/012	11/10/2000	11/09/2001
Precision Dipole	R&S	HZ-12	846932/0004	07/14/2000	07/13/2001
Precision Dipole	R&S	HZ-13	846556/0008	07/14/2000	07/13/2001
Bilog Antenna	CHASE	CBL 6112B	2462	01/16/2001	01/15/2002
Turn Table	Chance most	N/A	N/A	N.C.R	N.C.R
Antenna Tower	Chance most	N/A	N/A	N.C.R	N.C.R
Controller	Chance most	N/A	N/A	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M51067	N.C.R	N.C.R
Site NSA	C&C Lab.	N/A	N/A	11/24/2000	11/23/2001

**Measurement Results (1/2):**

Measured by: Eric Lin

Polar: Vertical – 3 m

Detector Function: Quasi-Peak

Measurement Results: Passed

Temperature: 22 °C

Humidity: 68 % RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level ( dBuV/m )	Limits ( )	Margin (dB)
168.03	25.5	10.9	36.4	43.5	-7.1
216.04	25.4	11.0	36.4	46.0	-9.6
336.08	24.8	16.0	40.8	46.0	-5.2
360.04	20.8	16.9	37.7	46.0	-8.3
384.06	24.9	18.5	43.4	46.0	-2.6
408.08	20.6	19.6	40.2	46.0	-5.8

**Measurement Results (2/2):**

Measured by: Eric Lin

Detector Function: Quasi-Peak

Temperature: 26 °C

(The chart below shows the highest readings taken from the final data)

Polar: Horizontal – 3 m

Measurement Results: Passed


Humidity: 68 % RH

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level ( dBuV/m )	Limits ( )	Margin (dB)
168.03	26.1	10.9	37.0	43.5	-6.5
288.05	19.0	15.0	34.0	46.0	-12.0
360.06	24.8	16.9	41.7	46.0	-4.3
396.06	18.9	19.3	38.2	46.0	-7.8
470.30	22.2	19.6	41.8	46.0	-4.2
480.05	17.9	19.7	37.6	46.0	-8.4



### Measurement Procedures

1. The EUT was placed on a metal free table on the outdoor ground plane. The search antenna was placed 3 meter from the EUT. Measurement distance is chosen so that the noise floor of the measurement system is at least 6dB below the specification limits.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205.
3. Once maximum direction was determined, the searching antenna was raised and lowered in both vertical and horizontal polarization. The maximum readings so obtained are recorded in the data listed below.
4. General measurement set up drawing.




➤ *AC Line Conducted Emissions*

**Measurement facility used for Conducted Emissions**

<b>Conducted Emission Test Site # 4</b>					
<b>EQUIPMENT TYPE</b>	<b>MFR</b>	<b>MODEL NUMBER</b>	<b>SERIAL NUMBER</b>	<b>LAST CAL.</b>	<b>CAL. DUE</b>
EMI Test Receiver	R&S	ESHS10	843743/015	12/10/1999	12/09/2000
LISN	EMCO	3825/2	9003/1382	01/10/2000	01/09/2001
LISN	EMCO	3825/2	9003-1628	07/12/2000	07/11/2001

### Measurement Procedure

1. The EUT was placed on a wooden table 40 cm from a vertical ground plane and approximately 80 cm above the horizontal ground plane on the floor, The EUT was set to transmit in a normal hopping mode.
2. Line conducted data was recorded for both NEUTRAL and HOT lines.
3. General measurement set up drawing.



**Measurement Results:** N/A (Since the EUT is Powered with battery Test to 15.207 is not required.)

**THE EMISSION LEVEL IN OPERATING BAND**

As per the requirement of FCC;  $\pm 5.227$ , any emission within this band shall not exceed (100uV/m, 80dBuV/m) at 3 meters.

The measurement procedure and setup are same as radiated emission measurement. The test result as listed at next page.

**Measurement facility used for the emission level in operating band**

<b>OATS #4</b>					
<b>EQUIPMENT TYPE</b>	<b>* MFR</b>	<b>MODEL NUMBER</b>	<b>SERIAL NUMBER</b>	<b>LAST CAL.</b>	<b>CAL. DUE</b>
EMI Test Receiver	R&S	ESHS10	843743/015	12/10/1999	12/09/2000
Loop Antenna	EMCO	6502	2356	04/20/2000	04/19/2001

**Measurement Results:**

Measured by: Bob Lin

Polar: Vertical – 3 m

Detector Function: Average/Peak

Measurement Results: Passed

Temperature: 26 °C

Humidity: 70 % RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level ( dBuV/m )	Limits	Margin (dB)
27.05908	38.3	10.1	48.4	80.0	-11.6 (Av)
27.05908	41.7	10.1	51.8	100.0	-28.2 (Pk)

**Measurement Results:**

Measured by: Bob Lin

Polar: Horizontal – 3 m

Detector Function: Average/Peak

Measurement Results: Passed

Temperature: 26 °C


Humidity: 70 % RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level ( dBuV/m )	Limits	Margin (dB)
27.058	38.3	10.1	48.4	80.0	47.0 (Av)
27.058	41.7	10.1	51.8	100.0	50.1 (Pk)

➤ **OPERATING RANGE VERIFICATION**

The stipulated operating range of FCC §15.227 is 26.96 to 27.28 MHz. The band edge requirement meets the requirement from the spectrum plot shown below.





### 11. RADIATED EMISSION MEASUREMENT SETUP PHOTO



## **12. AC LINE CONDUCTED EMISSION MEASUREMENT SETUP PHOTO**


N/A

(This page is left blank)

**INTERNAL**







**EXTERNAL**

