REV.	DESCRIPTION	ENG.	APPROVAL

NOTE:

1. Printin:white words on black backgroud.
2. TOL: +0/-0.5MM
3. The dimensions marked with"*"are important.
4. Glue: T=0.022~0.025MM
5. Stickiness: 3.0kg/cm^2.
6. Requirement of PRIMAX Green Part:
   1. Comply with PRIMAX QW-5Q002 " Green Product Chemical Substances Specification"
   2. Follow customer's specification as required.
   3. Follow Halogen- Free requirement : Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm if required.
7. 驗收大貨時,請拿下蓋現合ok後,才可收貨.

DO NOT SCALE DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PRIMAX ELECTRONICS LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF PRIMAX ELECTRONICS LTD.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
ANGULAR TOLERANCE: ±1.0°

DIMENSIONS	TOLERANCE
0.00 TO 30.00mm	±0.10mm
30.01 TO 80.00mm	±0.13mm
80.01 TO 150.00mm	±0.15mm
150.01 ↑	±0.20mm

MATERIAL
80P合成紙
黑底白字

PRIMAX 致伸資訊電子有限公司
PRIMAX ELECTRONICS LTD.

USED	28-236F9A7XX	APPD.	Ruby.Ai
FINISH		CHKD.	Ruby.Ai
SCALE /	UNIT mm	DR.	Violet.Hu 2010/08/27
TITLE	KB FCC LABEL		
DWG NO .		SIZE	A4
FILE NAME	SHEET 1/1	REV.	1