


REV.	DESCRIPTION	ENG.	APPROVAL



S/N: CN P Y WW XXXX

流水碼(0001~ZZZZ, 其中A,E,I,O,U不能使用),31進制
WEEK(01,02,.....)
YEAR(2010=0,2011=1....)
P代表Primax
固定碼

流水碼具體如下:

0001,0002,...0009,000B,000C,000D,000F,...000Z
0010,0011,.....0019,001B,001C,001D,001F...001Z
0020...009Z,00B0,00B1...00BB..00ZY,00ZZ,...
1000,1001,...1009,100B...100Z,1010,1011...9999,
999B,999C,....999Y,999Z,99B0,99B1...99ZZ...9ZZZ,
B000.....ZZZZ

NOTE:

- 印刷: 黑底, 字體顏色:877C
- TOL:-0.2/0mm.
- THE DIMENSIONS MARKED WITH"*" ARE IMPORTANT.
- GLUE : T=0.022~0.025mm.
- STICKINESS: 3.0kg/cm.²
- Requirement of PRIMAX Green Part:
 - Comply with PRIMAX QW-5Q002 " Green Product Chemical Substances Specification"
 - Follow customer's specification as required.
 - Follow Halogen- Free requirement : Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm if required.
- 驗收大貨時,請拿下蓋現合ok後,才可收貨.

DO NOT SCALE DRAWING		PRIMAX 致伸資訊電子有限公司 PRIMAX ELECTRONICS LTD.											
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE:±1.0 °		USED 20-2EY02H101	APPD. Ruby.Ai										
FINISH		CHKD. Ruby.Ai											
<table border="1"> <thead> <tr> <th>DIMENSIONS</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>0.00 TO 30.00mm</td> <td>±0.10mm</td> </tr> <tr> <td>30.01 TO 80.00mm</td> <td>±0.13mm</td> </tr> <tr> <td>80.01 TO 150.00mm</td> <td>±0.15mm</td> </tr> <tr> <td>150.01↑</td> <td>±0.20mm</td> </tr> </tbody> </table>		DIMENSIONS	TOLERANCE	0.00 TO 30.00mm	±0.10mm	30.01 TO 80.00mm	±0.13mm	80.01 TO 150.00mm	±0.15mm	150.01↑	±0.20mm	SCALE /	UNIT mm
DIMENSIONS	TOLERANCE												
0.00 TO 30.00mm	±0.10mm												
30.01 TO 80.00mm	±0.13mm												
80.01 TO 150.00mm	±0.15mm												
150.01↑	±0.20mm												
MATERIAL		DR. Susan.Lee 2010/07/03											
80P合成紙+霧膜		TITLE BOTTOM LABEL											
DWG NO. 304007506000		SIZE A4											
FILE NAME 304007506000	SHEET	1/1	REV. 1										