

REV.	DESCRIPTION	ENG.	APPROVAL



廠商UL代碼
被貼底蓋材質: ABS

1:1

S/N: DC11211001 Y WW XXXXX K7 01

- ▶ Engr.Ver
- ▶ Site Code
- ▶ Series No. 16 CODE (0~9,A,B,C,D,E,F)
- ▶ WEEK(01,02,03.....)
- ▶ YEAR(2010=0,2011=1,2012=2.....)
- ▶ 固定碼

NOTE:

1. Printing: White words on black background.
2. TOL: +0/-0.5mm
3. The dimensions marked with "*" are important.
4. Glue T=0.025~0.03mm
5. Stickiness: 3.0kg/cm
6. Requirement of PRIMAX Green Part:
 1. Comply with PRIMAX QW-5Q002 "Green Product Chemical Substances Specifion."
 2. Follow customer's specification as required.
 3. Follow Halogen- Free requirement : Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm if required.
7. Product must be halogen free
8. 注: 30400757406X 與 91000022225X / 91000022810X
流水號要求一一對應,且同一周內流水號要求順流!

DO NOT SCALE DRAWING		致伸資訊電子有限公司 PRIMAX ELECTRONICS LTD.											
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PRIMAX ELECTRONICS LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF PRIMAX ELECTRONICS LTD.</small>													
<small>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°</small>		USED 28-265G3A701	APPD. Ruby.Ai										
<table border="1"> <thead> <tr> <th>DIMENSIONS</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>0.00 TO 30.00mm</td> <td>±0.10mm</td> </tr> <tr> <td>30.01 TO 80.00mm</td> <td>±0.13mm</td> </tr> <tr> <td>80.01 TO 150.00mm</td> <td>±0.15mm</td> </tr> <tr> <td>150.01 ↑</td> <td>±0.20mm</td> </tr> </tbody> </table>		DIMENSIONS	TOLERANCE	0.00 TO 30.00mm	±0.10mm	30.01 TO 80.00mm	±0.13mm	80.01 TO 150.00mm	±0.15mm	150.01 ↑	±0.20mm	FINISH	CHKD. Ruby.Ai
DIMENSIONS	TOLERANCE												
0.00 TO 30.00mm	±0.10mm												
30.01 TO 80.00mm	±0.13mm												
80.01 TO 150.00mm	±0.15mm												
150.01 ↑	±0.20mm												
MATERIAL		SCALE / UNIT mm	DR. Cheery.Qiao 12-02-17										
80P合成紙+霧P 黑底白字		TITLE MS FCC LABEL											
DWG NO.		SIZE A4											
FILE NAME		SHEET	1/1										
		REV.	1										