



Label Location

REV.	DESCRIPTION	ENG.	APPROVAL

***55mm**



***39mm**

供應商UL代碼
 被貼底盖材质: ABS

DC1121101540400001K700

Engr. Ver
 Site Code
 Series No. (0~9,A,B,C,D,E,F 16 Code)
 Week Code (1st week=01, 2rd week=02...)
 Year Code (EX:2013=3,2014=4...)
 ACER P/N

- NOTE:**
1. Printing: White words on black background.
 2. TOL: +0/-0.5mm
 3. The dimensions marked with "*" are important.
 4. Glue T=0.025~0.03mm
 5. Stickiness: 3.0kg/cm
 6. Requirement of PRIMAX Green Part:
 1. Comply with PRIMAX QW-5Q002 "Green Product Chemical Substances Specifion."
 2. Follow customer's specification as required.
 3. Follow Halogen-Free requirement: Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm if required.
 7. Product must be halogen free
 8. 具體請參考樣品。

DO NOT SCALE DRAWING <small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PRIMAX ELECTRONICS LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF PRIMAX ELECTRONICS LTD.</small>	PRIMAX 致伸資訊電子有限公司 PRIMAX ELECTRONICS LTD.											
	USED 28-296*	APPD. Sarah.Le										
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°	FINISH	CHKD. Apple.Zhao										
<table border="1"> <thead> <tr> <th>DIMENSIONS</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>0.00 TO 30.00mm</td> <td>±0.10mm</td> </tr> <tr> <td>30.01 TO 80.00mm</td> <td>±0.13mm</td> </tr> <tr> <td>80.01 TO 150.00mm</td> <td>±0.15mm</td> </tr> <tr> <td>150.01 ↑</td> <td>±0.20mm</td> </tr> </tbody> </table>	DIMENSIONS	TOLERANCE	0.00 TO 30.00mm	±0.10mm	30.01 TO 80.00mm	±0.13mm	80.01 TO 150.00mm	±0.15mm	150.01 ↑	±0.20mm	SCALE / UNIT mm	DR. Wing.Liang 2014/2/20
DIMENSIONS	TOLERANCE											
0.00 TO 30.00mm	±0.10mm											
30.01 TO 80.00mm	±0.13mm											
80.01 TO 150.00mm	±0.15mm											
150.01 ↑	±0.20mm											
MATERIAL 100P合成紙+霧P 黑底白字	TITLE MS FCC LABEL	SIZE A4										
	DWG NO. 304009713000	FILE NAME 304009713000										
	SHEET 1/1	REV. 1										