

RF EXPOSURE REPORT

REPORT NO.: SA980821A01

MODEL NO.: MOBTDZUL, 44062

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: PRIMAX ELECTRONICS LTD.

ADDRESS: No. 669, Ruey Kuang Road, Neihu, Taipei, Taiwan,

R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,

Taipei Hsien, 244 Taiwan

Report No: SA980821A01 1 Report Format Version 3.0.0



Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW	
Low	2.402	24.58	
High	2.480	24.50	

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	-8.04	0.157
EIRP Power	-8.60	0.138

^{*}Note: The antenna is F Type Antenna with -0.56dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 0.157mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---