

# TEST REPORT

**Product Name** : Bluetooth Storyteller with Sleep Therapy  
**Model Number** : Di-465, M1 – 465 M2M3M4M5M6M7M8M9M10  
(M1 – M10, please refer to model no. table)  
**FCC ID** : EMO465A

**Prepared for** : SDI Technologies Inc.  
**Address** : 1299, Main Street, Rahway, NJ 07065, U.S.A.

**Prepared by** : EMTEK (DONGGUAN) CO., LTD.  
**Address** : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology  
Research and Development Base, No.9, Xincheng Avenue,  
Songshanhu High-technology Industrial Development Zone,  
Dongguan, Guangdong, China

TEL: +86-0769-22807078  
FAX: +86-0769-22807079

**Report Number** : EDG2210090018E00403R  
**Date(s) of Tests** : October 09, 2022 to November 25, 2022  
**Date of issue** : November 25, 2022

## Table of Contents

1. TEST RESULT CERTIFICATION .....	3
2. EUT SPECIFICATION .....	5
3. TEST REQUIREMENT .....	7
4. MEASUREMENT RESULT .....	8



## 1. TEST RESULT CERTIFICATION

Applicant : SDI Technologies Inc.  
 Address : 1299, Main Street, Rahway, NJ 07065, U.S.A.  
 Manufacturer : eKids, LLC. / KIDDESIGNS INC.  
 Address : 1299, Main Street, Rahway, NJ 07065, U.S.A.  
 Factory : DongGuan Synst Electronics Co., Ltd.  
 Address : No. 20, Fudong Road, Houjie Town, Dong-Guang City, Guangdong Province, China  
 EUT : Bluetooth Storyteller with Sleep Therapy  
 Model Name : Di-465, M1-465 M2M3M4M5M6M7M8M9M10 (M1-M10, please refer to model no. table)  
 Trademark : eKids / iHome

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : October 09, 2022 to November 25, 2022

Prepared by : 

Xia Yang /Editor

Reviewer : 

Tim Dong/ Supervisor

Approve & Authorized Signer :  

Sam Lv / Manager

## Modified History

Version	Report No.	Revision Date	Summary
	EDG2210090018E00403R	/	Original Report



## 2. EUT Specification

Characteristics	Description
<b>Product:</b>	Bluetooth Storyteller with Sleep Therapy
<b>Model Number:</b>	Di-465, M1-465 M2M3M4M5M6M7M8M9M10 (M1-M10, please refer to model no. table) All products are the same, only the model number and color of appearance are different Here we selected Di-465DG.EEv23 for all the test
<b>Sample:</b>	1#
<b>Device Type:</b>	Bluetooth V5.1
<b>Data Rate:</b>	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
<b>Modulation:</b>	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK
<b>Operating Frequency Range(s) :</b>	2402-2480MHz
<b>Number of Channels:</b>	BT: 79 channels BLE: 40 Channels
<b>Transmit Power Max:</b>	BT: -1.88 dBm(0.000649W) BLE: -2.90 dBm(0.000513W)
<b>Antenna Gain:</b>	-6.04 dBi
<b>Power supply:</b>	DC 5V from USB, DC 3.7V from battery
<b>Evaluation applied:</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

Model:  $M_1-465 M_2M_3M_4M_5M_6M_7M_8M_9M_{10}$  ( $M_1 - M_{10}$ , please refer to model no. table)

Model no. table

Part of model #	$M_1$	$M_2$	$M_3$	$M_4$	$M_5$	$M_6$	$M_7$	$M_8$	$M_9$	$M_{10}$
Number of digit(s)	2 to 3	2	1	1	1 to 2	1	1 to 3	1 to 4	2	1
Description	2 to 3 digits alphabets combination by "a" - "Z" for brand	1 to 2 digits alphabets combination by "a" - "Z" special character version <i>Or</i> <i>blank</i>	"," <i>Or</i> <i>blank</i>	"U" for Europe version <i>Or</i> <i>blank</i>	"E" for English content <i>Or</i> "F" for English & French <i>Or</i> "3" for 3 language version <i>Or</i> "5" for 5 languages version <i>Or</i> "11" for Europe version with 11 languages	"X" for having no sound effect <i>Or</i> "E" for having speech or sound effect <i>Or</i> "M" for having Music effect	"0"- "9" for year version <i>Or</i> "V0" - "V99" for year version	"M" for Movie version brand <i>Or</i> <i>blank</i>	"AK" for Walmart exclusive <i>Or</i> "AP" for Apple exclusive <i>Or</i> "KS" for Kohl's exclusive <i>Or</i> "TG" for Target exclusive <i>blank</i>	"I" for inner carton required <i>Or</i> "z" for direct to consumer on-line packaging <i>Or</i> "OL" for Amazon packaging <i>Or</i> <i>blank</i>

### 3. Test Requirement

## RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>24</sup> where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

## 4. Measurement Result

Antenna gain:-6.04 dBi  
BT

Transmit Frequency(MHz)	Mode	Measured Power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2402	GFSK	-3.81	-4±1	-3	0.1553519	3
2441	GFSK	-3.05	-4±1	-3	0.1566080	3
2480	GFSK	-2.80	-3±1	-2	0.1987265	3
2402	Π/4-DQPSK	-3.31	-4±1	-3	0.1553519	3
2441	Π/4-DQPSK	-2.51	-3±1	-2	0.1971578	3
2480	Π/4-DQPSK	-2.12	-3±1	-2	0.1987265	3
2402	8DPSK	-2.91	-3±1	-2	0.1955764	3
2441	8DPSK	-2.11	-2±1	-2	0.1971578	3
2480	8DPSK	-1.88	-2±1	-1	0.2501819	3

BLE\_1M

Transmit Frequency(MHz)	Mode	Measured Power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2402	GFSK	-3.85	-4±1	-3	0.1553519	3
2441	GFSK	-3.01	-4±1	-3	0.1565759	3
2480	GFSK	-2.90	-3±1	-2	0.1987265	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

\*\*\* End of Report \*\*\*