

# Testing Report

Customer Name: Dongguan synst Electronics Co., LTD


Product Name: Bluetooth Party Mixer

Sample Model: TR-625

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-1979*

Issue Date: 2022.11.2

Engineer: <i>Jeremy</i>	Date: <i>2022.11.1</i>
Auditor: <i>Eason</i>	Date: <i>2022.11.2</i>
Approver: <i>Aaron</i>	Date: <i>2022.11.2</i>



### Version

Version No.	Date	Description	Formulate	Approval
A0	2022.11.2	For the first time, formulate	Jeremy	Eason

### Contents

- 1.General Information ..... 3
  - 1.1 General information of testing institutions ..... 3
  - 1.2 Testing principle ..... 3
  - 1.3 Test equipment ..... 4
  - 1.4 Test environment ..... 4
  - 1.5 Statement ..... 4
- 2.Sample Information ..... 5
  - 2.1 Client information ..... 5
  - 2.2 Description of EUT(S) ..... 5
  - 2.3 EUT appearance ..... 6
- 3.Test Results ..... 6
  - 3.1 Test standard ..... 6
  - 3.2 Test uncertainty ..... 6
  - 3.3 Test data ..... 7
    - 3.3.1 Typical free space efficiency and gain ..... 7
    - 3.3.2 Typical free space radiation pattern ..... 7
  - (The following is blank) ..... 8

# 1. General Information


## 1.1 General information of testing institutions

<b>Name</b>	Shenzhen RFI-LAB Communication Technology Co., Ltd.
<b>Address</b>	10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ
<b>Tel</b>	13682621346
<b>E-mail</b>	rfi-lab@tech-now.com
<b>Equipment</b>	All the equipment used in the report is fixed in 10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ

## 1.2 Testing principle



### Multi-Probe OTA Measurement System



### 1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
16 probe microwave chamber	3*3*2.5	RFI-LAB-RF-A00	SUNYIELD	2021.3.15	2023.3.14
Network Analyzer	E5071C	RFI-LAB-RF-A02	Agilent	2022.5.13	2023.5.12

### 1.4 Test environment

Temperature	23.8°C
Humidity	59%RH
Pressure	100.03kPa

### 1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

## 2. Sample Information


### 2.1 Client information

<b>Name</b>	Dongguan synst Electronics Co., LTD
<b>Address</b>	20 Fudong Road, Houjie Town, Dongguan City, Guangdong Province
<b>Contacts</b>	Yabo.Cui
<b>Tel</b>	13537066595
<b>E-mail</b>	YB.Cui@synst.com

### 2.2 Description of EUT(S)

<b>Product Name</b>	Bluetooth Party Mixer
<b>Sample Model</b>	TR-625
<b>Antenna Size</b>	14.3*4.3mm
<b>Antenna Type</b>	PCB antenna
<b>Serial No.</b>	/
<b>Test Item</b>	Antenna gain; Efficiency; Radiation pattern
<b>Frequency Range</b>	2402MHz-2480MHz
<b>Received Date</b>	2022.11.1
<b>Test Date</b>	2022.11.1
<b>Remark</b>	The length of the RF cable is 90mm

## 2.3 EUT appearance



## 3. Test Results

### 3.1 Test standard

Name	Parameter	Method	Standard no.
Mobile communication antenna	Antenna gain	Generic specification for antennas used in the mobile communications	GB/T 9410-2008
	Radiation pattern		
Antenna	Radiation efficiency	IEEE Standard Test Procedures for Antennas	ANSI/IEEE Std 149-1979
	Gain and directivity		

### 3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of  $K=2$  and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
Antenna gain	$\pm 1\text{dB}$
Radiation efficiency	$\pm 10\%$

### 3.3 Test data


#### 3.3.1 Typical free space efficiency and gain

Frequency/MHz	2402	2410	2420	2430	2440	2450	2460	2470	2480
Peak Gain/dBi	-6.04	-6.1	-6.39	-6.3	-6.49	-6.51	-6.59	-6.37	-6.27
Efficiency/%	8.29	8.15	7.91	7.92	7.91	7.83	7.80	8.03	8.03

#### 3.3.2 Typical free space radiation pattern


(1) X-Z Plane:

V Phi=0




(2) Y-Z Plane:

V Phi=90




(3) X-Y Plane:

**H Theta=90**



(4) Typical Free Space 3D Radiation Pattern at 2.44GMHz:



**End**

(The following is blank)