



**MET Laboratories, Inc.** *Safety Certification - EMI - Telecom Environmental Simulation*  
3162 BELICK STREET • SANTA CLARA, CALIFORNIA 95054 • PHONE (510) 489-6300 • FAX (510) 489-6372

## **Electromagnetic Compatibility Criteria Test Report**

for the

**Electronic Systems Technology,  
Model 195Ed**

**Tested under**  
the FCC Certification Rules  
contained in  
Title 47 of the CFR, Parts 15 Subpart B & ICES-003  
for Class B Digital Devices  
&  
15.247 Subpart C & RSS-210, Issue 7, June 2007  
for Intentional Radiators

**MET Report: EMC80990-FCC247**

July 31, 2008

**Prepared For:**

**Electronic Systems Technology,  
415 North Quay St. Bldg B-1  
Kennewick, WA 99336**




## Electromagnetic Compatibility Criteria Test Report

for the


### Electronic Systems Technology, Model 195Ed

**Tested under**  
the FCC Certification Rules  
contained in  
Title 47 of the CFR, Parts 15 Subpart B & ICES-003  
for Class B Digital Devices  
&  
15.247 Subpart C & RSS-210, Issue 7, June 2007  
for Intentional Radiators

  
Anderson Soungpanya, Project Engineer  
Electromagnetic Compatibility Lab

  
Jennifer Sanchez  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Parts 15B, 15.247 and Industry Canada standards ICES-003, Issue 4 February 2004, RSS-210, Issue 7, June 2007 under normal use and maintenance.

  
Shawn McMillen, Manager  
Electromagnetic Compatibility Lab



## Report Status Sheet

Revision	Report Date	Reason for Revision
∅	August 6, 2008	Initial Issue.
1	August 8, 2008	Final Issue
2	August 12, 2008	Correct Antenna Information, Configuration, 15.207 section



## Table of Contents

<b>I.</b>	<b>Executive Summary .....</b>	<b>1</b>
	A. Purpose of Test .....	2
	B. Executive Summary .....	2
<b>II.</b>	<b>Equipment Configuration .....</b>	<b>3</b>
	A. Overview .....	4
	B. References .....	5
	C. Test Site .....	6
	D. Description of Test Sample .....	6
	E. Equipment Configuration .....	9
	F. Support Equipment .....	9
	G. Ports and Cabling Information .....	9
	H. Mode of Operation .....	10
	I. Method of Monitoring EUT Operation .....	10
	J. Modifications .....	10
	a) Modifications to EUT .....	10
	b) Modifications to Test Standard .....	10
	K. Disposition of EUT .....	10
<b>III.</b>	<b>Electromagnetic Compatibility Criteria for Unintentional Radiators .....</b>	<b>11</b>
	§ 15.107(a) Conducted Emissions Limits .....	12
	§ 15.109(a) Radiated Emission Limits .....	19
	§ 15.09(a) Radiated Emissions Limits .....	19
<b>IV.</b>	<b>Electromagnetic Compatibility Criteria for Intentional Radiators .....</b>	<b>24</b>
	§ 15.203 Antenna Requirement .....	25
	§ 15.207(a) Conducted Emissions Limits .....	26
	§ 15.247(a) 6 dB and 99% Bandwidth .....	33
	§ 15.247(b) Peak Power Output and RF Exposure .....	34
	§ 15.247(d) Spurious Emissions Requirements – Radiated and RF Conducted .....	36
	§ 15.247(d) Peak Power Spectral Density .....	63
<b>V.</b>	<b>Test Equipment .....</b>	<b>64</b>
<b>VI.</b>	<b>Certification &amp; User’s Manual Information .....</b>	<b>66</b>
	A. Certification Information .....	67
	B. Label and User’s Manual Information .....	71
<b>VII.</b>	<b>ICES-003 Procedural &amp; Labeling Requirements .....</b>	<b>73</b>



## List of Tables

Table 1 Executive Summary of EMC Part 15.247 Compliance Testing .....	2
<b>Table 2. EUT Summary Table .....</b>	<b>4</b>
Table 3. References .....	5
Table 4. Equipment Configuration .....	9
Table 5. Support Equipment .....	9
Table 6. Ports and Cabling Information .....	9
Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a) .....	12
Table 8. Conducted Emissions - Voltage, AC Power, Phase Line (110 VAC, 60 Hz).....	13
Table 9. Conducted Emissions - Voltage, AC Power, Neutral Line (110 VAC, 60 Hz).....	13
Table 10. Conducted Emissions - Voltage, POE Power, Phase Line (110 VAC, 60 Hz).....	15
Table 11. Conducted Emissions - Voltage, POE Power, Neutral Line (110 VAC, 60 Hz).....	15
Table 12. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b) .....	19
Table 13. Radiated Emissions Limits Test Results, 30 MHz – 1GHz, Yagi Antenna.....	20
Table 14. Radiated Emissions Limits Test Results, 30 MHz – 1GHz, Omni Antenna .....	20
Table 15. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a) .....	26
Table 16. Conducted Emissions - Voltage, AC Power, Phase Line .....	27
Table 17. Conducted Emissions - Voltage, AC Power, Neutral Line.....	27
Table 18. Conducted Emissions - Voltage, POE Power, Phase Line .....	29
Table 19. Conducted Emissions - Voltage, POE Power, Neutral Line.....	29
Table 20. Output Power Requirements from §15.247 .....	34
Table 21. Restricted Bands of Operation.....	36
Table 22. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11b Mode, 20MHz .....	38
Table 23. Radiated Harmonics Emissions Test Results – High Channel 917MHz, 802.11b Mode, 20MHz.....	38
Table 24. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 5MHz.....	39
Table 25. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 10MHz.....	39
Table 26. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 5MHz .....	40
Table 27. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 10MHz .....	40
Table 28. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 20MHz .....	40
Table 29. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 5MHz .....	41
Table 30. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 10MHz .....	41
Table 31. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 20MHz .....	41
Table 32. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 5MHz.....	42
Table 33. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 10MHz.....	42
Table 34. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11b Mode, 20MHz .....	49
Table 35. Radiated Harmonics Emissions Test Results – High Channel 917MHz, 802.11b Mode, 20MHz.....	49
Table 36. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 5MHz.....	50
Table 37. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 10MHz.....	50
Table 38. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 5MHz .....	51
Table 39. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 10MHz .....	51
Table 40. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 20MHz .....	51
Table 41. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 5MHz .....	52
Table 42. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 10MHz .....	52
Table 43. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 20MHz .....	52
Table 44. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 5MHz.....	53
Table 45. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 10MHz.....	53
Table 46. Test Equipment List .....	65



## List of Figures

Figure 1. Block Diagram of Test Configuration (AC/DC Power).....	7
Figure 2. Block Diagram of Test Configuration (POE Power) .....	8

## List of Photographs

Photograph 1. Electronic Systems Technology, 195Ed.....	6
Photograph 2. Conducted Emissions Test Setup, AC/DC Power.....	17
Photograph 3. Conducted Emissions Test Setup, POE Power .....	18
Photograph 4. Radiated Emission Test Setup 30 MHz - 1 GHz, Yagi Antenna.....	22
Photograph 5. Radiated Emission Test Setup 30 MHz - 1 GHz, Omni Antenna .....	23
Photograph 6. Conducted Emissions Test Setup, AC/DC Power.....	31
Photograph 7. Conducted Emissions Test Setup, POE Power .....	32
Photograph 8. Test Equipment and setup for various Radiated Measurements (Yagi Antenna).....	60
Photograph 9. Test Equipment and setup for various Radiated Measurements (Omni Antenna) .....	61



## List of Terms and Abbreviations

<b>AC</b>	<b>Alternating Current</b>
<b>ACF</b>	<b>Antenna Correction Factor</b>
<b>Cal</b>	<b>Calibration</b>
<b><i>d</i></b>	<b>Measurement Distance</b>
<b>dB</b>	<b>Decibels</b>
<b>dB<math>\mu</math>A</b>	<b>Decibels above one microamp</b>
<b>dB<math>\mu</math>V</b>	<b>Decibels above one microvolt</b>
<b>dB<math>\mu</math>A/m</b>	<b>Decibels above one microamp per meter</b>
<b>dB<math>\mu</math>V/m</b>	<b>Decibels above one microvolt per meter</b>
<b>DC</b>	<b>Direct Current <math>\mu</math></b>
<b>E</b>	<b>Electric Field</b>
<b>DSL</b>	<b>Digital Subscriber Line</b>
<b>ESD</b>	<b>Electrostatic Discharge</b>
<b>EUT</b>	<b>Equipment Under Test</b>
<b><i>f</i></b>	<b>Frequency</b>
<b>FCC</b>	<b>Federal Communications Commission</b>
<b>GR-1089-CORE</b>	<b>(GR) General Requirement(s) imposed by the NEBS standard, (CORE) Central Office Recovery Express (AT&amp;T), (1089) specifies various parts of the General Requirements under Bellcore Technical Standard, Requirements for Electromagnetic Compatibility and Electrical Safety - Generic Criteria for Network Telecommunications Equipment</b>
<b>GRP</b>	<b>Ground Reference Plane</b>
<b>H</b>	<b>Magnetic Field</b>
<b>HCP</b>	<b>Horizontal Coupling Plane</b>
<b>Hz</b>	<b>Hertz</b>
<b>IEC</b>	<b>International Electrotechnical Commission</b>
<b>kHz</b>	<b>kilohertz</b>
<b>kPa</b>	<b>kilopascal</b>
<b>kV</b>	<b>kilovolt</b>
<b>LISN</b>	<b>Line Impedance Stabilization Network</b>
<b>MHz</b>	<b>Megahertz</b>
<b><math>\mu</math>H</b>	<b>microhenry</b>
<b><math>\mu</math></b>	<b>microfarad</b>
<b><math>\mu</math>s</b>	<b>microseconds</b>
<b>NEBS</b>	<b>Network Equipment-Building System</b>
<b>PRF</b>	<b>Pulse Repetition Frequency</b>
<b>RF</b>	<b>Radio Frequency</b>
<b>RMS</b>	<b>Root-Mean-Square</b>
<b>TWT</b>	<b>Traveling Wave Tube</b>
<b>V/m</b>	<b>Volts per meter</b>
<b>VCP</b>	<b>Vertical Coupling Plane</b>



# **I. Executive Summary**





**A. Purpose of Test**

An EMC evaluation was performed to determine compliance of the Electronic Systems Technology, 195Ed, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the 195Ed. Electronic Systems Technology, should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the 195Ed, has been **permanently** discontinued

**B. Executive Summary**

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Electronic Systems Technology,, purchase order number 1389. All tests were conducted using measurement procedure ANSI C63.4-2003.

FCC Reference	IC Reference	Description	Compliance
47 CFR Part 15.247:2005	RSS-210 Issue 7: 2007	Applicable Standard	
Title 47 of the CFR, Part 15 §15.203	N/A	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.205	RSS-210(A8.5)	Emissions at Restricted Band	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	RSS-210(7.2.2)	Conducted Emission Voltage	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	RSS-210(A8.1)	Occupied Bandwidth	Refer to FCC ID: SWX-XR9
Title 47 of the CFR, Part 15 §15.247(b)	RSS-210(A8.4)	RF Output Power	Refer to FCC ID: SWX-XR9
Title 47 of the CFR, Part 15 §15.209, §15.247(d)	RSS-210(A8.5)	Radiated and Conducted Spurious Emissions	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	RSS-210(A8.3)	Power Spectral Density	Refer to FCC ID: SWX-XR9
Title 47 of the CFR, Part 15 §15.247(i)	RSSGen(5.5)	Maximum Permissible Exposure	Compliant
N/A	RSSGen(4.8)	Receiver Spurious Emissions	Compliant

**Table 1 Executive Summary of EMC Part 15.247 Compliance Testing**



## **II. Equipment Configuration**



## A. Overview

MET Laboratories, Inc. was contracted by Electronic Systems Technology, to perform testing on the 195Ed, under Electronic Systems Technology's purchase order number 1389.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Electronic Systems Technology, 195Ed.

The results obtained relate only to the item(s) tested.

<b>Model(s) Tested:</b>	195Ed	
<b>Model(s) Covered:</b>	195Ed	
<b>EUT Specifications:</b>	Primary Power: 12VDC or 46VDC POE	
	FCC ID: ENPESTEEM195ED IC: 2163A-195ED	
	Type of Modulations:	DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency Division multiplexing)
	Equipment Code:	DTS
	RF Output Power:	<b>802.11b:</b> 28.8dBm (0.758W)
		<b>802.11g:</b> 29.0dBm (0.794W)
	EUT Frequency Ranges:	907 – 922MHz
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
<b>Evaluated by:</b>	Anderson Soungpanya	
<b>Date(s):</b>	July 31, 2008	

**Table 2. EUT Summary Table**



## B. References

<b>CFR 47, Part 15, Subpart C</b>	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
<b>RSS-210, Issue 7, June 2007</b>	Low-power Licence-exempt Radiocommunications Devices (All Frequency Bands): Category I Equipment
<b>CFR 47, Part 15, Subpart B</b>	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
<b>ICES-003, Issue 4 February 2004</b>	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
<b>ANSI C63.4:2003</b>	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>ANSI/NCSL Z540-1-1994</b>	Calibration Laboratories and Measuring and Test Equipment - General Requirements
<b>ANSI/ISO/IEC 17025:2000</b>	General Requirements for the Competence of Testing and Calibration Laboratories

Table 3. References



### C. Test Site

All testing was performed at MET Laboratories, Inc., 3162 Belick Street, Santa Clara, California 95054. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

### D. Description of Test Sample

The Electronic Systems Technology, 195Ed, is a fully functional wireless LAN transceiver operating in the 902-928MHz band. The unit is typically used in law enforcement or industrial applications.



Photograph 1. Electronic Systems Technology, 195Ed




Figure 1. Block Diagram of Test Configuration (AC/DC Power)




Figure 2. Block Diagram of Test Configuration (POE Power)



### E. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Serial Number
A	ESTeem 900MHz Modem	195Ed	12345701
B	7dBi Omni Antenna (MAXRAD)	MFB9155RPC	427989
C	7dBi Yagi Antenna (ASTRON)	918-3	NA
E	Power Over Ethernet (I.T.E)	PW183RB4800F01	0813A

Table 4. Equipment Configuration

### F. Support Equipment

Electronic Systems Technology, supplied support equipment necessary for the operation and testing of the 195Ed. All support equipment supplied is listed in the following Support Equipment List.

Ref. ID	Name / Description	Manufacturer	Model Number	*Customer Supplied Calibration Data
D	Laptop	Dell	Inspiron 1600	

Table 5. Support Equipment

\* The 'Customer Supplied Calibration Data' column will be marked as either not applicable, not available, or will contain the calibration date supplied by the customer.  
 \*\* The AC/DC Adapter was use to power the EUT for testing purpose only, will not be sold with radio.

### G. Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty.	Length (m)	Shielded (Yes/No)	Termination Box ID & Port ID
<b>POE Configuration</b>						
1	A, Ant Port 1	Coaxial	1	.5	Yes	B or C
2	E, Lan In	Ethernet	1	3	No	D, Ethernet
3	A Pwr Lan Out	Ethernet	1	3	No	A, Ethernet 1
4	E, Power	AC Cord	1	1.5	No	120VAC Power Supply
5	A, Program Port	Ethernet to Serial to USB	1	3	Yes	D, USB
<b>AC-DC Configuration</b>						
1	A, Ant Port 1	Coaxial	1	.5	Yes	B or C
2	A Pwr	10 Gauge Cable	1	3	No	F
3	A, Program Port	Ethernet to Serial to USB	1	3	Yes	D, USB
4	F, Power	AC Cord	1	1.5	No	120VAC Power Supply

Table 6. Ports and Cabling Information





## **H. Mode of Operation**

The modem has two RF antenna ports. Port 1 is receive only and Port 2 is transmit and receive. Both ports are reverse gender TNC connections to restrict the use of antennas to those provided by the manufacturer as a listed in section 15.203 of this report.

## **I. Method of Monitoring EUT Operation**

A Spectrum Analyzer and a Power Meter was use to monitor the EUT's transmitter channel and power output.

## **J. Modifications**

- a) **Modifications to EUT**  
No modifications were made to the EUT.
- b) **Modifications to Test Standard**  
No modifications were made to the test standard.

## **K. Disposition of EUT**

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Electronic Systems Technology, upon completion of testing.



### **III. Electromagnetic Compatibility Criteria for Unintentional Radiators**



## Electromagnetic Compatibility Criteria

### § 15.107 Conducted Emissions Limits

**Test Requirement(s):** **15.107 (a)** Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

**15.107 (b)** For a Class A digital device that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals. The lower limit applies at the band edges.

**15.207(a)**, Except as shown in paragraphs (b) and (c) of this section\*, charging, AC adapters or battery eliminators the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the Table 7, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency range (MHz)	Class A Conducted Limits (dBµV)		*Class B Conducted Limits (dBµV)	
	Quasi-Peak	Average	Quasi-Peak	Average
* 0.15- 0.45	79	66	66 - 56	56 - 46
0.45 - 0.5	79	66	56	46
0.5 - 30	73	60	60	50

Note 1 — The lower limit shall apply at the transition frequencies.

Note 2 — The limit decreases linearly with the logarithm if the frequency in the range 0.15 MHz to 0.5 MHz.

\* -- Limits per Subsection 15.207(a).

**Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a)**

**Test Results:** The EUT was found compliant with the Class A requirement(s) of this section. Measured emissions were below applicable limits.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** June 30, 2008



## AC-DC Adapter SETUP

### Conducted Emissions - Voltage, AC Power, Phase Line (110 VAC, 60 Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.174	51.82	79	-27.18	35.1	66	-30.9
.314	32.89	79	-46.11	22.55	66	-43.45
18.5	39.3	73	-33.7	31.63	60	-28.37

Table 8. Conducted Emissions - Voltage, AC Power, Phase Line (110 VAC, 60 Hz)


### Conducted Emissions - Voltage, AC Power, Neutral Line (110 VAC, 60 Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.169	49.88	79	-29.12	30.25	66	-35.75
6.36	33.78	73	-39.22	26.55	60	-33.45
18.5	39.71	73	-33.29	31.56	60	-28.44


Table 9. Conducted Emissions - Voltage, AC Power, Neutral Line (110 VAC, 60 Hz)



### Conducted Emissions - Voltage, Worst Case Emissions, AC Power, (110 VAC, 60 Hz)



Conducted Emission, Phase Line Plots



Conducted Emission, Neutral Line Plots



## POE SETUP

### Conducted Emissions - Voltage, POE Power, Phase Line (110 VAC, 60 Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
28.97	48.03	73	-24.97	45	60	-15
.203	54.12	79	-24.88	45.78	66	-20.22
6.04	40.44	73	-32.56	38.48	60	-21.52

Table 10. Conducted Emissions - Voltage, POE Power, Phase Line (110 VAC, 60 Hz)


### Conducted Emissions - Voltage, POE Power, Neutral Line (110 VAC, 60 Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
28.97	48.18	73	-24.82	43.1	60	-16.9
.204	54.11	79	-24.89	41.69	66	-24.31
.475	44.71	79	-34.29	40.93	66	-25.07


Table 11. Conducted Emissions - Voltage, POE Power, Neutral Line (110 VAC, 60 Hz)



### Conducted Emissions - Voltage, Worst Case Emissions, POE Power, (110 VAC, 60 Hz)




Conducted Emission, Phase Line Plots



Conducted Emission, Neutral Line Plots


## Conducted Emission Limits Test Setup



Photograph 2. Conducted Emissions Test Setup, AC/DC Power



### Conducted Emission Limits Test Setup



Photograph 3. Conducted Emissions Test Setup, POE Power



## Radiated Emission Limits

### § 15.109 Radiated Emissions Limits

**Test Requirement(s):** **15.109 (a)** Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the Class B limits expressed in Table 12.

**15.109 (b)** The field strength of radiated emissions from a Class A digital device, as determined at a distance of 10 meters, shall not exceed the Class A limits expressed in Table 12.

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	
	§15.109 (b), Class A Limit (dB $\mu$ V) @ 10m	§15.109 (a), Class B Limit (dB $\mu$ V) @ 3m
30 - 88	39.00	40.00
88 - 216	43.50	43.50
216 - 960	46.40	46.00
Above 960	49.50	54.00

**Table 12. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)**

**Test Procedures:** The EUT was placed on a 0.8m-high wooden table inside a semi-anechoic chamber. The method of testing and test conditions of ANSI C63.4 were used. An antenna was located 10 m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a quasi-peak detector with a 120 kHz bandwidth.

**Test Results:** The EUT was found to comply with the Class A requirement(s) of this section. Measured emissions were below applicable limits. EUT was tested from 1-2GHz, no peaks were found.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** June 30 & July 3, 2008



**Radiated Emissions Limits Test Results, Class A**

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBuV)	ACF (dB/m)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBuV)	Limit (dBuV)	Margin (dB)
38.93	V	19	100	26.55	12.628	0.771	-10.46	29.489	39	-9.511
98.46	V	177	100	28.5	12.161	1.283	-10.46	31.484	43.5	-12.016
250	H	100	125	22.26	12.9	2.308	-10.46	27.008	46.4	-19.392
374.99	V	20	138	23.74	15.699	2.915	-10.46	31.894	46.4	-14.506
499.98	V	160	100	17.89	17.6	3.508	-10.46	28.538	46.4	-17.862
749.99	H	212	100	16.18	20.6	4.503	-10.46	30.823	46.4	-15.577

**Table 13. Radiated Emissions Limits Test Results, 30 MHz – 1GHz, Yagi Antenna**


Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBuV)	ACF (dB/m)	CBL (dB)	Corrected Amplitude (dBuV)	Limit (dBuV)	Margin (dB)
56	V	32	100	19.95	6.8	1.174	27.924	39	-11.076
100.09	V	127	103	13.24	10.616	1.599	25.455	43.5	-18.045
249.99	V	0	100	11.45	12.099	2.607	26.156	46.4	-20.244
374.99	V	348	100	5.65	15.099	3.198	23.947	46.4	-22.453
374.99	H	107	264	9.23	15	3.198	27.428	46.4	-18.972
656.22	H	113	147	2.63	18.749	4.288	25.667	46.4	-20.733

**Table 14. Radiated Emissions Limits Test Results, 30 MHz – 1GHz, Omni Antenna**


Note: EUT was tested from 1-2GHz, no peaks were found.



### Radiated Emissions Limits Test Results, Class A



Plot 1. Radiated Emissions Limits Test Results, 30 MHz – 1 GHz, Yagi Antenna




Plot 2. Radiated Emissions Limits Test Results, 30 MHz – 1 GHz, Omni Antenna

## Radiated Emission Limits Test Setup



**Photograph 4. Radiated Emission Test Setup 30 MHz - 1 GHz, Yagi Antenna**

## Radiated Emission Limits Test Setup



**Photograph 5. Radiated Emission Test Setup 30 MHz - 1 GHz, Omni Antenna**



## **IV. Electromagnetic Compatibility Criteria for Intentional Radiators**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.203 Antenna Requirement

**Test Requirement:** § 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Results:** The EUT as tested meets the criteria of this rule by use of unique type connector to attach to the EUT. The EUT is therefore compliant with §15.203.

Gain	Model	Type	Manufacturer
7dBi	AA191Es	Omni-Directional	Esteem
7dBi	AA203Es900	Yagi	Esteem
2dBi	AA20DMEs	Omni-Directional	Esteem
7dBi	AA20Es900	Omni-Directional	Esteem

Note: The antennas listed above are the antennas intended to be sold/marketed with the 195Ed. The only antennas tested in the report are models AA203Es900 and AA20Es900.

**Test Engineer(s):** Anderson Soungpanya





## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.207 Conducted Emissions Limits

**Test Requirement(s):** § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50  $\Sigma$  line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

**Table 15. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)**

**Test Procedure:** The EUT was placed on a 0.8 m-high wooden table inside a semi-anechoic chamber. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50  $\Omega$ /50  $\mu$ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-1992 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50  $\Omega$ /50  $\mu$ H LISN as the input transducer to an EMC/field intensity meter. The tests were conducted in a RF-shielded enclosure.

**Test Results:** The EUT was found compliant with the requirement(s) of this section. Measured emissions were below applicable limits.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** June 30, 2008



## AC\_DC SETUP

### Conducted Emissions - Voltage, AC Power, Phase Line

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.150	54.25	79	-24.75	36.92	66	-29.08
.176	52.35	79	-26.65	34.73	66	-31.27
17.56	36.69	73	-36.31	30.86	60	-29.14

Table 16. Conducted Emissions - Voltage, AC Power, Phase Line


### Conducted Emissions - Voltage, AC Power, Neutral Line

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.150	55.33	79	-23.67	36.42	66	-29.58
.178	51.91	79	-27.09	34.39	66	-31.61
17.39	36.04	73	-36.96	32.02	60	-27.98


Table 17. Conducted Emissions - Voltage, AC Power, Neutral Line



### Conducted Emissions - Voltage, Worst Case Emissions, AC Power



Conducted Emission, Phase Line Plots



Conducted Emission, Neutral Line Plots



## POE SETUP

### Conducted Emissions - Voltage, POE Power, Phase Line

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.203	54.21	79	-24.79	45.52	66	-20.48
.746	39.33	73	-33.67	35.75	60	-24.25
28.97	48.1	73	-24.9	44.5	60	-15.5

Table 18. Conducted Emissions - Voltage, POE Power, Phase Line


### Conducted Emissions - Voltage, POE Power, Neutral Line

Freq (MHz)	QP Amplitude	QP Limit	Delta	Average Amplitude	Average Limit	Delta
.203	54.93	79	-24.07	42.63	66	-23.37
6.58	42.01	73	-30.99	40.85	60	-19.15
28.96	48.67	73	-24.33	45.83	60	-14.17


Table 19. Conducted Emissions - Voltage, POE Power, Neutral Line



### Conducted Emissions - Voltage, Worst Case Emissions, POE Power, (110 VAC, 60 Hz)




Conducted Emission, Phase Line Plots




Conducted Emission, Neutral Line Plots

## Conducted Emission Limits Test Setup



Photograph 6. Conducted Emissions Test Setup, AC/DC Power

## Conducted Emission Limits Test Setup



**Photograph 7. Conducted Emissions Test Setup, POE Power**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(a) 6 dB and 99% Bandwidth

**Test Requirements:** § 15.247(a): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

**Test Procedure:** The transmitter was set to the mid channel at the highest output power and connected to the spectrum analyzer through an attenuator and a directional coupler. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth, VBW > RBW. The 6 dB Bandwidth was measured and recorded. The measurements were repeated at the low and high channels.

**Test Results** Equipment complies with § 15.247 (a). Please refer to FCC ID: SWX-XR9 for results.





## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) Peak Power Output and RF Exposure

**Test Requirements:** §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

**Table 20. Output Power Requirements from §15.247**

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in the Table 20, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400 – 2483.5 MHz band may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Fixed, point-to-point operation excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

**Test Procedure:** The transmitter was connected to a calibrated Power Meter. The EUT was measured at the low, mid and high channels of each band at a data rate which gave the maximum power level.

**Test Results:** Equipment complies with the Peak Power Output limits of § 15.247(b). Please refer to FCC ID: SWX-XR9 for results.



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) Peak Power Output and RF Exposure

**RF Exposure Requirements:** §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

**RF Radiation Exposure Limit:** §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 907 – 922MHz MHz; highest conducted power = 29.0dBm (peak) therefore, **Limit for Uncontrolled exposure: .6 mW/cm<sup>2</sup> or 6 W/m<sup>2</sup>**

EUT maximum antenna gain = 7 dBi

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density ( mW/cm<sup>2</sup>)  
P = Power Input to antenna (794.3mW)  
G = Antenna Gain (5.0numeric)

$R = (794.3 * 5.0 / 4 * 3.14 * 0.6)^{1/2} = (3971.5 / 7.536)^{1/2} = 22.95\text{cm}$  (separation distance required to meet the .6mW/cm<sup>2</sup> limit at 900MHz)

$S = (794.3 * 5.0 / 4 * 3.14 * 20.0^2) = (3971.5 / 5024) = 0.790\text{mW/cm}^2$



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Harmonic Emissions – Radiated and Conducted

**Test Requirements:** §15.247(d); §15.205, §15.209: Emissions outside the frequency band.

**§15.247(d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

**§15.205(a):** Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
<sup>1</sup> 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	( <sup>2</sup> )

**Table 21. Restricted Bands of Operation**

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

<sup>2</sup> Above 38.6



**Test Procedure:** The EUT was installed placed on a 0.8m-high wooden table inside a semi-anechoic chamber. The harmonic frequencies the carriers were recorded for reference for final measurements. A receiving horn antenna was placed 3m away from the EUT. Unless otherwise specified, measurements were made using a with a 1MHz RBW & 1MHz VBW for peak measurements and 1MHz RBW & 10Hz VBW for average measurements on a spectrum analyzer.

For each harmonic of the carrier frequency, the turntable was rotated, the positions of the interface cables were varied, and the antenna height was varied between 1 m and 4 m, in order to find the maximum radiated emissions.

**Test Results:** The EUT was found compliant with the requirement(s) of this section. Measured emissions were below applicable limits.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** July 1, 2008



**Electromagnetic Compatibility Criteria for Intentional Radiators**

**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11b) – Yagi Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	H	76.87	34.86	26.51	2.80	71.31	Peak	74	-2.69
2.736	H	46.54	35.00	29.27	4.20	45.02	Peak	74	-28.98
2.736	H	34.84	35.00	29.27	4.20	33.32	Avg	54	-20.68
3.648	H	44.41	34.72	31.58	4.59	45.86	Peak	74	-28.14
3.648	H	33.42	34.72	31.58	4.59	34.87	Avg	54	-19.13
4.56	H	43.71	34.76	32.79	7.65	49.38	Peak	74	-24.62
4.56	H	32.87	34.76	32.79	7.65	38.54	Avg	54	-15.46

**Table 22. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11b Mode, 20MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	H	75.65	34.86	26.55	2.80	70.14	Peak	74	-3.86
2.751	H	46.79	35.01	29.32	4.23	45.33	Peak	74	-28.67
2.751	H	36.33	35.01	29.32	4.23	34.87	Avg	54	-19.13
3.668	H	45.37	34.71	31.64	4.69	46.98	Peak	74	-27.02
3.668	H	33.56	34.71	31.64	4.69	35.17	Avg	54	-18.83
4.585	H	43.32	34.77	32.83	7.67	49.05	Peak	74	-24.95
4.585	H	32.78	34.77	32.83	7.67	38.51	Avg	54	-15.49

**Table 23. Radiated Harmonics Emissions Test Results – High Channel 917MHz, 802.11b Mode, 20MHz**

**Note: All other emissions were measured at the noise floor of the spectrum analyzer**



**Electromagnetic Compatibility Criteria for Intentional Radiators**

**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Yagi Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.814	H	64.52	34.86	26.47	2.79	58.92	Peak	74	-15.08
2.721	H	44.38	34.99	29.23	4.17	42.79	Peak	74	-31.21
2.721	H	33.58	34.99	29.23	4.17	31.99	Avg	54	-22.01
3.628	H	44.56	34.73	31.53	4.49	45.85	Peak	74	-28.15
3.628	H	33.32	34.73	31.53	4.49	34.61	Avg	54	-19.39
4.535	H	43.93	34.76	32.75	7.62	49.54	Peak	74	-24.46
4.535	H	32.87	34.76	32.75	7.62	38.48	Avg	54	-15.52

**Table 24. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.814	H	61.96	34.86	26.47	2.79	56.36	Peak	74	-17.64
2.721	H	45.96	34.99	29.23	4.17	44.37	Peak	74	-29.63
2.721	H	33.51	34.99	29.23	4.17	31.92	Avg	54	-22.08
3.628	H	44.32	34.73	31.53	4.49	45.61	Peak	74	-28.39
3.628	H	33.25	34.73	31.53	4.49	34.54	Avg	54	-19.46
4.535	H	45.33	34.76	32.75	7.62	50.94	Peak	74	-23.06
4.535	H	32.81	34.76	32.75	7.62	38.42	Avg	54	-15.58

**Table 25. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 10MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer



**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Yagi Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	H	61.88	34.86	26.51	2.80	56.32	Peak	74	-17.68
2.736	H	45.27	35.00	29.27	4.20	43.75	Peak	74	-30.25
2.736	H	33.54	35.00	29.27	4.20	32.02	Avg	54	-21.98
3.648	H	44.32	34.72	31.58	4.59	45.77	Peak	74	-28.23
3.648	H	33.31	34.72	31.58	4.59	34.76	Avg	54	-19.24
4.56	H	44.28	34.76	32.79	7.65	49.95	Peak	74	-24.05
4.56	H	32.88	34.76	32.79	7.65	38.55	Avg	54	-15.45

**Table 26. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	H	60.54	34.86	26.51	2.80	54.98	Peak	74	-19.02
2.736	H	44.96	35.00	29.27	4.20	43.44	Peak	74	-30.56
2.736	H	33.46	35.00	29.27	4.20	31.94	Avg	54	-22.06
3.648	H	44.49	34.72	31.58	4.59	45.94	Peak	74	-28.06
3.648	H	33.32	34.72	31.58	4.59	34.77	Avg	54	-19.23
4.56	H	43.4	34.76	32.79	7.65	49.07	Peak	74	-24.93
4.56	H	32.81	34.76	32.79	7.65	38.48	Avg	54	-15.52

**Table 27. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 10MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	H	61.77	34.86	26.51	2.80	56.21	Peak	74	-17.79
2.736	H	45.09	35.00	29.27	4.20	43.57	Peak	74	-30.43
2.736	H	33.39	35.00	29.27	4.20	31.87	Avg	54	-22.13
3.648	H	44.69	34.72	31.58	4.59	46.14	Peak	74	-27.86
3.648	H	32.25	34.72	31.58	4.59	33.70	Avg	54	-20.30
4.56	H	44.08	34.76	32.79	7.65	49.75	Peak	74	-24.25
4.56	H	32.72	34.76	32.79	7.65	38.39	Avg	54	-15.61

**Table 28. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 20MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer



**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Yagi Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	H	62.18	34.86	26.55	2.80	56.67	Peak	74	-17.33
2.751	H	45.82	35.01	29.32	4.23	44.36	Peak	74	-29.64
2.751	H	33.42	35.01	29.32	4.23	31.96	Avg	54	-22.04
3.668	H	44.45	34.71	31.64	4.69	46.06	Peak	74	-27.94
3.668	H	33.39	34.71	31.64	4.69	35.00	Avg	54	-19.00
4.585	H	44.18	34.77	32.83	7.67	49.91	Peak	74	-24.09
4.585	H	32.63	34.77	32.83	7.67	38.36	Avg	54	-15.64

**Table 29. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	H	60.83	34.86	26.55	2.80	55.32	Peak	74	-18.68
2.751	H	45.57	35.01	29.32	4.23	44.11	Peak	74	-29.89
2.751	H	33.38	35.01	29.32	4.23	31.92	Avg	54	-22.08
3.668	H	44.15	34.71	31.64	4.69	45.76	Peak	74	-28.24
3.668	H	33.44	34.71	31.64	4.69	35.05	Avg	54	-18.95
4.585	H	43.53	34.77	32.83	7.67	49.26	Peak	74	-24.74
4.585	H	32.61	34.77	32.83	7.67	38.34	Avg	54	-15.66

**Table 30. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 10MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	H	61.44	34.86	26.55	2.80	55.93	Peak	74	-18.07
2.751	H	45.94	35.01	29.32	4.23	44.48	Peak	74	-29.52
2.751	H	33.75	35.01	29.32	4.23	32.29	Avg	54	-21.71
3.668	H	44.23	34.71	31.64	4.69	45.84	Peak	74	-28.16
3.668	H	32.98	34.71	31.64	4.69	34.59	Avg	54	-19.41
4.585	H	43.22	34.77	32.83	7.67	48.95	Peak	74	-25.05
4.585	H	32.65	34.77	32.83	7.67	38.38	Avg	54	-15.62

**Table 31. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 20MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer





**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Yagi Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.844	H	61.97	34.86	26.59	2.81	56.51	Peak	74	-17.49
2.766	H	51.36	35.01	29.36	4.26	49.97	Peak	74	-24.03
2.766	H	33.91	35.01	29.36	4.26	32.52	Avg	54	-21.48
3.688	H	44.16	34.70	31.69	4.79	45.94	Peak	74	-28.06
3.688	H	33.15	34.70	31.69	4.79	34.93	Avg	54	-19.07
4.61	H	44.02	34.77	32.88	7.69	49.82	Peak	74	-24.18
4.61	H	32.54	34.77	32.88	7.69	38.34	Avg	54	-15.66

**Table 32. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.844	H	59.65	34.86	26.59	2.81	54.19	Peak	74	-19.81
2.766	H	48.65	35.01	29.36	4.26	47.26	Peak	74	-26.74
2.766	H	34.88	35.01	29.36	4.26	33.49	Avg	54	-20.51
3.688	H	44.77	34.70	31.69	4.79	46.55	Peak	74	-27.45
3.688	H	33.09	34.70	31.69	4.79	34.87	Avg	54	-19.13
4.61	H	43.58	34.77	32.88	7.69	49.38	Peak	74	-24.62
4.61	H	32.56	34.77	32.88	7.69	38.36	Avg	54	-15.64


**Table 33. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 10MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer




## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Restricted Band Requirements – Yagi Antenna




Plot 3. Restricted Band 907MHz, 5MHz




Plot 4. Restricted Band 907MHz, 10MHz



### § 15.247(d) Restricted Band Requirements – Yagi Antenna




Plot 5. Restricted Band 912MHz, 5MHz




Plot 6. Restricted Band 912MHz, 10MHz



### § 15.247(d) Restricted Band Requirements – Yagi Antenna




Plot 7. Restricted Band 912MHz, 20MHz




Plot 8. Restricted Band 912MHz, 20MHz



### § 15.247(d) Restricted Band Requirements – Yagi Antenna




Plot 9. Restricted Band 917MHz, 5MHz




Plot 10. Restricted Band 917MHz, 10MHz



### § 15.247(d) Restricted Band Requirements – Yagi Antenna




Plot 11. Restricted Band 917MHz, 20MHz




Plot 12. Restricted Band 917MHz, 20MHz



### § 15.247(d) Restricted Band Requirements – Yagi Antenna



Plot 13. Restricted Band 922MHz, 5MHz



Plot 14. Restricted Band 922MHz, 10MHz



**Electromagnetic Compatibility Criteria for Intentional Radiators**

**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11b) – Omni Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	V	63.6	34.86	26.53	2.80	58.07	Peak	74	-15.93
2.736	V	51.65	35.00	29.15	4.20	50.00	Peak	74	-24.00
2.736	V	40.3	35.00	29.15	4.20	38.65	Avg	54	-15.35
3.648	V	43.73	34.72	31.72	4.59	45.32	Peak	74	-28.68
3.648	V	31.74	34.72	31.72	4.59	33.33	Avg	54	-20.67
4.56	V	43.96	34.76	32.68	7.65	49.52	Peak	74	-24.48
4.56	V	31.54	34.76	32.68	7.65	37.10	Avg	54	-16.90

**Table 34. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11b Mode, 20MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	V	58.4	34.86	26.57	2.80	52.91	Peak	74	-21.09
2.751	V	53.4	35.01	29.20	4.23	51.82	Peak	74	-22.18
2.751	V	40.3	35.01	29.20	4.23	38.72	Avg	54	-15.28
3.668	V	44.37	34.71	31.79	4.69	46.13	Peak	74	-27.87
3.668	V	32.1	34.71	31.79	4.69	33.86	Avg	54	-20.14
4.585	V	44.02	34.77	32.73	7.67	49.65	Peak	74	-24.35
4.585	V	31.33	34.77	32.73	7.67	36.96	Avg	54	-17.04

**Table 35. Radiated Harmonics Emissions Test Results – High Channel 917MHz, 802.11b Mode, 20MHz**

**Note: All other emissions were measured at the noise floor of the spectrum analyzer**





**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Omni Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.814	V	52.16	34.86	26.49	2.79	46.58	Peak	74	-27.42
2.721	V	46.44	34.99	29.10	4.17	44.72	Peak	74	-29.28
2.721	V	32.36	34.99	29.10	4.17	30.64	Avg	54	-23.36
3.628	V	44.49	34.73	31.66	4.49	45.92	Peak	74	-28.08
3.628	V	32.28	34.73	31.66	4.49	33.71	Avg	54	-20.29
4.535	V	42.95	34.76	32.64	7.62	48.45	Peak	74	-25.55
4.535	V	31.4	34.76	32.64	7.62	36.90	Avg	54	-17.10

**Table 36. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.814	V	49.54	34.86	26.49	2.79	43.96	Peak	74	-30.04
2.721	V	44.5	34.99	29.10	4.17	42.78	Peak	74	-31.22
2.721	V	32.4	34.99	29.10	4.17	30.68	Avg	54	-23.32
3.628	V	43.65	34.73	31.66	4.49	45.08	Peak	74	-28.92
3.628	V	31.6	34.73	31.66	4.49	33.03	Avg	54	-20.97
4.535	V	43.92	34.76	32.64	7.62	49.42	Peak	74	-24.58
4.535	V	31.7	34.76	32.64	7.62	37.20	Avg	54	-16.80

**Table 37. Radiated Harmonics Emissions Test Results – Low Channel 907MHz, 802.11g Mode, 10MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer



**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Omni Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	V	47.65	34.86	26.53	2.80	42.12	Peak	74	-31.88
2.736	V	49	35.00	29.15	4.20	47.35	Peak	74	-26.65
2.736	V	32.5	35.00	29.15	4.20	30.85	Avg	54	-23.15
3.648	V	43.91	34.72	31.72	4.59	45.50	Peak	74	-28.50
3.648	V	31.7	34.72	31.72	4.59	33.29	Avg	54	-20.71
4.56	V	41.74	34.76	32.68	7.65	47.30	Peak	74	-26.70
4.56	V	31.9	34.76	32.68	7.65	37.46	Avg	54	-16.54

**Table 38. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	V	48.27	34.86	26.53	2.80	42.74	Peak	74	-31.26
2.736	V	46.93	35.00	29.15	4.20	45.28	Peak	74	-28.72
2.736	V	32.7	35.00	29.15	4.20	31.05	Avg	54	-22.95
3.648	V	43.84	34.72	31.72	4.59	45.43	Peak	74	-28.57
3.648	V	31.8	34.72	31.72	4.59	33.39	Avg	54	-20.61
4.56	V	43.7	34.76	32.68	7.65	49.26	Peak	74	-24.74
4.56	V	31.8	34.76	32.68	7.65	37.36	Avg	54	-16.64

**Table 39. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 10MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.824	V	48.72	34.86	26.53	2.80	43.19	Peak	74	-30.81
2.736	V	44.9	35.00	29.15	4.20	43.25	Peak	74	-30.75
2.736	V	32.5	35.00	29.15	4.20	30.85	Avg	54	-23.15
3.648	V	44.44	34.72	31.72	4.59	46.03	Peak	74	-27.97
3.648	V	31.8	34.72	31.72	4.59	33.39	Avg	54	-20.61
4.56	V	43.98	34.76	32.68	7.65	49.54	Peak	74	-24.46
4.56	V	31.9	34.76	32.68	7.65	37.46	Avg	54	-16.54

**Table 40. Radiated Harmonics Emissions Test Results – Mid Channel 912MHz, 802.11g Mode, 20MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer



**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Omni Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	V	45.9	34.86	26.57	2.80	40.41	Peak	74	-33.59
2.751	V	53.54	35.01	29.20	4.23	51.96	Peak	74	-22.04
2.751	V	32.8	35.01	29.20	4.23	31.22	Avg	54	-22.78
3.668	V	44.7	34.71	31.79	4.69	46.46	Peak	74	-27.54
3.668	V	31.95	34.71	31.79	4.69	33.71	Avg	54	-20.29
4.585	V	44.77	34.77	32.73	7.67	50.40	Peak	74	-23.60
4.585	V	31.7	34.77	32.73	7.67	37.33	Avg	54	-16.67

**Table 41. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	V	48.1	34.86	26.57	2.80	42.61	Peak	74	-31.39
2.751	V	51.5	35.01	29.20	4.23	49.92	Peak	74	-24.08
2.751	V	32.7	35.01	29.20	4.23	31.12	Avg	54	-22.88
3.668	V	45.1	34.71	31.79	4.69	46.86	Peak	74	-27.14
3.668	V	32.04	34.71	31.79	4.69	33.80	Avg	54	-20.20
4.585	V	43.83	34.77	32.73	7.67	49.46	Peak	74	-24.54
4.585	V	31.7	34.77	32.73	7.67	37.33	Avg	54	-16.67

**Table 42. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 10MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.834	V	48.26	34.86	26.57	2.80	42.77	Peak	74	-31.23
2.751	V	46.2	35.01	29.20	4.23	44.62	Peak	74	-29.38
2.751	V	32.54	35.01	29.20	4.23	30.96	Avg	54	-23.04
3.668	V	44.6	34.71	31.79	4.69	46.36	Peak	74	-27.64
3.668	V	32.1	34.71	31.79	4.69	33.86	Avg	54	-20.14
4.585	V	44.22	34.77	32.73	7.67	49.85	Peak	74	-24.15
4.585	V	31.6	34.77	32.73	7.67	37.23	Avg	54	-16.77

**Table 43. Radiated Harmonics Emissions Test Results – Mid Channel 917MHz, 802.11g Mode, 20MHz**

**Note:** All other emissions were measured at the noise floor of the spectrum analyzer



**§ 15.247(d) Harmonic Emissions Requirements – Radiated (802.11g) – Omni Antenna**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.844	V	47.04	34.86	26.61	2.81	41.60	Peak	74	-32.40
2.766	V	50.8	35.01	29.25	4.26	49.30	Peak	74	-24.70
2.766	V	32.7	35.01	29.25	4.26	31.20	Avg	54	-22.80
3.688	V	43.7	34.70	31.85	4.79	45.63	Peak	74	-28.37
3.688	V	31.7	34.70	31.85	4.79	33.63	Avg	54	-20.37
4.61	V	44.23	34.77	32.78	7.69	49.92	Peak	74	-24.08
4.61	V	31.7	34.77	32.78	7.69	37.39	Avg	54	-16.61

**Table 44. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 5MHz**

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg)	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg (Peak) / (Avg)	Limit @ 3 m (dBuV/m)	Delta (dB)
1.844	V	46.8	34.86	26.61	2.81	41.36	Peak	74	-32.64
2.766	V	47.03	35.01	29.25	4.26	45.53	Peak	74	-28.47
2.766	V	32.7	35.01	29.25	4.26	31.20	Avg	54	-22.80
3.688	V	45.5	34.70	31.85	4.79	47.43	Peak	74	-26.57
3.688	V	31.93	34.70	31.85	4.79	33.86	Avg	54	-20.14
4.61	V	42.96	34.77	32.78	7.69	48.65	Peak	74	-25.35
4.61	V	31.6	34.77	32.78	7.69	37.29	Avg	54	-16.71


**Table 45. Radiated Harmonics Emissions Test Results – High Channel 922MHz, 802.11g Mode, 10MHz**

**Note: All other emissions were measured at the noise floor of the spectrum analyzer**




## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Restricted Band Requirements – Omni Antenna




Plot 15. Restricted Band 907MHz, 5MHz




Plot 16. Restricted Band 907MHz, 10MHz



### § 15.247(d) Restricted Band Requirements – Omni Antenna




Plot 17. Restricted Band 912MHz, 5MHz




Plot 18. Restricted Band 912MHz, 10MHz



### § 15.247(d) Restricted Band Requirements – Omni Antenna




Plot 19. Restricted Band 912MHz, 20MHz




Plot 20. Restricted Band 912MHz, 20MHz



§ 15.247(d) Restricted Band Requirements – Omni Antenna



Plot 21. Restricted Band 917MHz, 5MHz




Plot 22. Restricted Band 917MHz, 10MHz






### § 15.247(d) Restricted Band Requirements – Omni Antenna




Plot 23. Restricted Band 917MHz, 20MHz




Plot 24. Restricted Band 917MHz, 20MHz



### § 15.247(d) Restricted Band Requirements – Omni Antenna



Plot 25. Restricted Band 922MHz, 5MHz



Plot 26. Restricted Band 922MHz, 10MHz

## Electromagnetic Compatibility Criteria for Intentional Radiators



**Photograph 8. Test Equipment and setup for various Radiated Measurements (Yagi Antenna)**

## Electromagnetic Compatibility Criteria for Intentional Radiators



**Photograph 9. Test Equipment and setup for various Radiated Measurements (Omni Antenna)**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Spurious Emissions Requirements –RF Conducted

**Test Procedure:** For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10<sup>th</sup> harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

For frequencies 1-18GHz, measurements were made at coupler port of a 20dB directional coupler. The output of the coupler was terminated by a 50Ω load. For frequencies 18-40GHz a HP11970A and HP11970K harmonic mixer was used. Each harmonic mixer was fed with a SMA to wave guide adapter.

**Test Results:** Equipment complies with the Spurious Emissions Requirements – Radiated and RF Conducted limits of § 15.247 (d). Please refer to FCC ID: SWX-XR9 for results.



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(e) Peak Power Spectral Density

**Test Requirements:** §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

**Test Procedure:** The transmitter was connected directly to a Spectrum Analyzer through a directional coupler. The power was monitored at the coupler port with a Peak Power Meter. The power level was set to the maximum level. The RBW was set to 3 kHz with a VRB at 3\*RBW. The spectrum analyzer was set to sweep over a 100 second interval. Measurements were carried out at the low, mid and high channels.

**Test Results:** Equipment complies with the peak power spectral density limits of § 15.247 (e). Please refer to FCC ID: SWX-XR9 for results.



## **IV. Test Equipment**



## Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

TEST EQUIPMENT USED					
MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1S2484	Bilog Antenna	Teseq	CBL-6112D	1/21/08	1/21/09
1S2481	10m Chamber	ETS-Lindgren	DKE 8X8 DBL	12/26/2007	12/26/2008
1S2421	EMI Test Receiver	Rohde & Schwarz	ESIB7	4/18/2008	4/18/2009
1S2508	AC LISN	Solar Electronics	Type 9252-50-R-24-BNC	4/22/08	4/22/09
1S2438	Transient Limiter	Agilent	11947A	10/25/07	10/25/08
1S2460	Spectrum Analyzer	Agilent	E4407B	3/24/08	3/24/09
1S2198	Horn Antenna	EMCO	3115	8/31/07	8/31/08
1S2121	Preamplifier	HP	8449B	10/26/08	10/26/09
1S2460	Spectrum Analyzer	Agilent	E4407B	3/23/08	3/23/09
1S2501	EMI Test Receiver	Rohde & Schwarz	ESU 40	4/8/08	4/8/09
1S2485	Bilog Antenna	Teseq	CBL-6112D	1/21/08	1/21/09
1S2482	5m Semi-Anechoic Chamber	Panashield	N/A	11/18/07	11/18/08

**Table 46. Test Equipment List**

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.





## **V. Certification & User's Manual Information**



---

## Certification & User's Manual Information

### A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

#### § 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

#### § 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
  - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
  - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.



- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing;*
  - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
  - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.



---

## Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

### § 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.<sup>1</sup> *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

### § 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

---

<sup>1</sup> In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.



---

## Certification & User's Manual Information

### § 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
  - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
    - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
    - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
  - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.



---

## Certification & User's Manual Information

### Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

#### § 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

#### § 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



## Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

### § 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



## ICES-003 Procedural & Labeling Requirements

From the Industry Canada Electromagnetic Compatibility Advisory Bulletin entitled, "Implementation and Interpretation of the Interference-Causing Equipment Standard for Digital Apparatus, ICES-003" (EMCAB-3, Issue 2, July 1995):

"At present, CISPR 22: 2002 and ICES technical requirements are essentially equivalent. Therefore, if you have CISPR 22: 2002 approval by meeting CISPR Publication 22, the only additional requirements are: to attach a note to the report of the test results for compliance, indicating that these results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations; to maintain these records on file for the requisite five year period; and to provide the device with a notice of compliance in accordance with ICES-003."

### Procedural Requirements:

According to Industry Canada's Interference Causing Equipment Standard for Digital Apparatus ICES-003 Issue 4, February 2004:

- Section 6.1: A record of the measurements and results, showing the date that the measurements were completed, shall be retained by the manufacturer or importer for a period of at least five years from the date shown in the record and made available for examination on the request of the Minister.
- Section 6.2: A written notice indicating compliance must accompany each unit of digital apparatus to the end user. The notice shall be in the form of a label that is affixed to the apparatus. Where because of insufficient space or other constraints it is not feasible to affix a label to the apparatus, the notice may be in the form of a statement in the user's manual.

### Labeling Requirements:

The suggested text for the notice, in English and in French, is provided below, from the Annex of ICES-003:

This Class [<sup>2</sup>] digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [<sup>1</sup>] est conforme à la norme NMB-003 du Canada.

<sup>2</sup> Insert either A or B but not both as appropriate for the equipment requirements.





# End of Report