



## **TEST REPORT**

### **Equipment Tested:**

**Utility Meter Transmitter  
Model 50ESS  
Serial Number 4577**

**Itron Test Facility  
2401 North State Street  
Waseca, Minnesota 56093**



# TABLE OF CONTENTS

1. TEST SUMMARY .....3

2. PRODUCT DESCRIPTION AND TEST OBJECTIVE .....4

3. TEST FACILITY .....4

4. EUT SUPPORT EQUIPMENT USED.....4

5. EUT SYSTEM DESCRIPTION.....4

6. OPERATING MODE OF EUT, SOFTWARE/FIRMWARE ETC.....5

7. BLOCK DIAGRAM.....6

8. TEST AND MEASUREMENT EQUIPMENT DETAIL .....7

9. AMBIENT CONDITIONS DURING TEST .....7

10. DISTRIBUTION LIST .....7

11. REFERENCES.....7

12. DESCRIPTION OF TEST PROCEDURE .....8

    RADIATED EMISSIONS.....8

13 RESULTS.....8

    BANDWIDTH OF EMISSION .....10

ATTACHMENT A .....11

    RADIATED EMISSIONS - TRANSMITTER .....11

    RADIATED EMISSIONS - 30 MHZ TO 1000MHZ .....12,13

ATTACHMENT B.....14

    CONVERSION FROM INSTANTANEOUS PEAK POWER TO AVERAGE POWER.....14

ATTACHMENT C.....15

    PART 15.231 (C) BANDWIDTH PLOT .....15

ATTACHMENT D.....16

    MEASUREMENT OF RELATIVE FIELD INTENSITY.....16

ATTACHMENT E.....17

    TRANSMITTER AC WIRELINE CONDUCTED EMISSIONS .....17

ATTACHMENT F .....18

    PHOTOGRAPHS (TEST SETUP).....18



## 1. TEST SUMMARY

**Test Report No.:** W020125

**Company:** Itron, Inc.

**Test Date(s):** November 20, 21, 26, 27, 29, & December 7, 2001  
January 4, 11, 16, 2002

**Equipment Under Test:** Utility Meter Transmitter

**General Test Summary:** The 50ESS transmitter was tested for compliance to FCC Part 15.249 requirements for an intentional radiator.

**Original Grant or Permissive Change:** Original Grant

**Certification Status:** The 50ESS transmitter has been verified as being compliant with FCC Part 15.249 requirements for an intentional radiator.

**Modifications Necessary for Compliance:** None. See Section 2. For EUT description.

The tests were performed by me or under my supervision.  
Robert A. Sleen

**Tested By:** Mark J. Kvamme  
Robert A. Sleen

**Report Written By:** Robert A. Sleen



## 2. PRODUCT DESCRIPTION AND TEST OBJECTIVE

The EUT is a utility meter transmitter and is used in conjunction with a host meter to measure electrical consumption. The EUT transmits consumption data. See Sections 6 and 7 for test set-up description. The 50ESS has a frequency-hopping transmitter that operates over a maximum 4 MHz. bandwidth in the 910 - 920 MHz band (the actual fundamental frequency is set at the time of manufacture). The objective of this test is to determine if the EUT transmitter meets the radiated emission levels established by FCC Part 15.249 for intentional radiators. The EUT was tested at an antenna to EUT distance of 3 meters according to ANSI C63.4-1992.

## 3. TEST FACILITY

The tests were performed at the test facility of Itron, Inc. located at 2401 North State Street, Waseca, Minnesota 56093. This site is fully described in a document submitted to the FCC accepted per letter dated June 4, 1999 (Ref.: Registration Number: 90716).

## 4. EUT SUPPORT EQUIPMENT USED:

Test Equipment	Model	Manufacturer	Serial. No.	Cal. Due
Spectrum Analyzer Display Section	141T	Hewlett Packard	1337A06309	N/A
RF Section	8555A	Hewlett Packard	1724A07744	N/A
IF Section	8552B	Hewlett Packard	1952A17996	N/A
Dipole Antenna	Roberts	Compliance Design	7341	N/A

## 5. EUT SYSTEM DESCRIPTION:

The EUT was physically configured similar to a typical user configuration. The 50ESS was placed in an A3 ALPHA Meter housing and interfaced to the A3 ALPHA Meter. The assembly was placed in the center of the test table 80 cm above the ground plane. There were no other associated components or accessories on the table during the radiated emissions tests.



#### **6. OPERATING MODE OF EUT, SOFTWARE/FIRMWARE ETC. :**

During testing, the EUT was operationally configured to a special test mode. This special test mode causes the 50ESS to transmit more messages consecutively, thus allowing peaks of transmitter radiation to be more easily found as antenna height and turntable azimuth are varied.



The hopping bandwidth of the transmitter is around 2.5 to 3.5 MHz including manufacturing and component variability.

See Attachment B for message detail.

See the test set-up diagram in Section 7 and the photo in Attachment F.



7. TEST SET-UP DIAGRAM:





## 8. TEST AND MEASUREMENT EQUIPMENT DETAIL:

Test Equipment	Model	Manufacturer	Serial Number	Cal Due
Spectrum Analyzer Display Section	141T	Hewlett-Packard	1337A06309	05/02
RF Section	8555A	Hewlett-Packard	1724A07744	05/02
IF Section	8552B	Hewlett-Packard	1952A17996	05/02
Spectrum Analyzer	8593E	Hewlett-Packard	3543A02032	07/02
Synthesized Signal Generator	8673D	Hewlett-Packard	3123A01161	09/02
Power Meter	437B	Hewlett-Packard	3125U11553	10/02
Power Meter Sensor	8481D	Hewlett-Packard	331BA08626	10/02
Amplifier < 5 GHz	ZHL - 1042J	Mini-Circuits	H110894-008	N/A
Amplifier > 5 GHz	JCA010-415	JCA	103	N/A
Power Supply	6201B	Hewlett-Packard	1145A03611	12/02
LISN	3825-2	EMCO	9508-2436	01/11/02
Antenna - Dipole	Roberts	Compliance Design	4106	08/02
Antenna - Double Ridged Guide	3115	EMCO	9508-4550	04/02
Antenna - Log periodic	3148	EMCO	9901-1044	07/02
Antenna - Bi-conical	3108	EMCO	9203-2455	09/02

## 9. AMBIENT CONDITIONS DURING TEST:

Date	Temp ( °F )	Humidity ( % RH )
11/20/01	54	33
11/21/01	63	36
11/26/01	54	48
11/27/01	54	47
11/29/01	54	36
12/04/01	55	32
12/07/01	56	36
01/04/02	54	30
01/11/02	54	26
01/16/02	55	41

## 10. DISTRIBUTION LIST:

Archive

## 11. REFERENCES:

ANSI C63.4-1992



## 12. DESCRIPTION OF TEST PROCEDURE

### 12.1 Radiated Emissions (Transmitter)

These tests measure the transmitter radiated emissions using a spectrum analyzer and receiving antenna. During testing the EUT was placed on a non-conducting support, 80 cm above the ground plane. The RF spectrum was scanned from 30 MHz to 1000 MHz using the Bi-conical, Log Periodic and Dipole antennae. A Double Ridged Guide antenna was used from 1 GHz to the transmitter's 10<sup>th</sup> harmonic at 9170. Levels below 1 GHz were measured with the spectrum analyzer resolution bandwidth at 120 kHz and levels at or above 1 GHz were measured with the spectrum analyzer resolution bandwidth at 1 MHz. The emissions were measured in vertical and horizontal antenna polarizations. The antenna height was varied from 1-4 meters and the EUT was rotated from 0-360°. Maximum emissions were recorded. The antenna to EUT test distance was 3 meters horizontally. An analog spectrum analyzer was used as an aid in locating the maximum radiation emission as the EUT orientation and antenna position were varied. The level was determined on the HP8593E by means of signal substitution. Testing was performed according to the procedures in ANSI C63.4-1992.

See Attachment F; Test Setup Photographs.

### 12.2 CONDUCTED EMISSIONS

This test determines the power line conducted emission using a LISN (Line Impedance Stabilization Network) and a spectrum analyzer. The EUT was placed on a non-conducting tabletop 80 cm above the conductive ground plane of the test site. The LISN was grounded to the conductive ground plane by means of a copper strap. A 9 kHz resolution bandwidth was used during the conducted emissions testing. The response due to the ambient electromagnetic conditions (without the EUT being energized) was plotted and the frequencies involved were determined. This was done in order to differentiate between the responses caused by ambient electromagnetic signals and the true EUT generated conducted emissions. The outputs of both ports of the LISN were plotted.

## 13. RESULTS

### 13.1 Radiated Emissions (Transmitter)

Final emission levels are expressed in dB $\mu$ V/m. This level is determined by converting the reading from the spectrum analyzer or power meter to dB $\mu$ V and adding the antenna correction factor (dB) and cable loss (dB) to it. The amplifier gain is accounted for when the spectrum analyzer display is calibrated. Antenna and cable loss factors are included in the tabular results contained in Attachment A. All levels below 1 GHz are peak. The transmitter fundamental is expressed in peak level as it is hopping in frequency and can not be measured quasi-peak. Transmitter harmonic final levels above 1 GHz are peak average with a 13 dB relaxation allowed for duty cycle.

Refer to Attachment B for duty cycle calculation.





**13.1.1 Transmitter Radiated Emissions**

**RULE:** Part 15.249: Emission of RF Energy - Transmitter

**STANDARD:** Part 15.249

The field strengths shall not exceed the following:

Fundamental (MHz)	Fundamental		Harmonic	
	( $\mu$ V/m)	(dB $\mu$ V/m)	( $\mu$ V/m)	(dB $\mu$ V/m)
902 - 928	50,000	94	500	54

**Part 15.249 (c): Field Strength of Spurious Radiation**

The emissions radiated outside the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the limits in Part 15.209, whichever is the lesser attenuation.

**Part 15.209**

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of Emission (MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)
30 – 88	100	40
88 – 216	150	43.5
216 – 960	200	46
Above 960	500	54

**TEST RESULTS:**

The EUT transmitter radiated emissions met the requirements established by Part 15.249 for intentional radiators. The EUT was tested from 30 MHz to the transmitter’s 10<sup>th</sup> harmonic (9.17 GHz). Emissions in the 30 MHz to 1 GHz that had less than 20 dB margin in respect to the limit were recorded.

The transmitter fundamental (916.5 MHz) was measured to be 93.7 dB $\mu$ V/m peak. This is 0.3 dB below the quasi-peak limits established by Part 15.249. The worst case harmonic radiated emission was determined to be 64.3 dB $\mu$ V/m peak. The limit established by Part 15.249 is 54 dB $\mu$ V/m with a relaxation of 13 dB (67 dB $\mu$ V/m).

In compliance with Part 15.35 (b) - Pulsed Operation, conversion of instantaneous peak power to average power is addressed in Attachment B.

**TEST DATA:**

Refer to Attachment A for detailed test results



### 13.1.2 Bandwidth of Emission

**RULE:** Part 15.231 (c) Bandwidth of Emission

**STANDARD:** Part 15.231 (c), Part 15.31 (m)

The 20 dB bandwidth of devices operating above 900 MHz shall be no wider than 0.5% of the center frequency.

$$916.5 \text{ MHz} * 0.005 = 4.58 \text{ MHz}$$

**TEST RESULTS:** Meets standard. The occupied bandwidth of the transmitted signal was determined to be 222 kHz. Refer to Attachment C for Part 15.231 (c); Bandwidth Plot.

**TEST DATA:** Refer to Attachment D for Part 15.31 (m); Measurement of Relative Field Intensity at the High and Low Frequencies of the EUT.

### 13.2 Conducted Emissions

**RULE:** Part 15.107 (a), Part 15.207 (a)

**STANDARD:** Part 15.107 (a), Part 15.207 (a)

For equipment that is connected to the public utility power line, the frequencies in the band 450 kHz to 30 MHz as measured between each power line and ground at the power terminal shall not exceed 250 microvolts (48 dB $\mu$ V).

**TEST RESULTS:** All conducted emissions were less than the 48 dB $\mu$ V limit.

**TEST DATA:** Refer to Attachment E for FCC Part 15.107; Power line Conducted Emissions Plots

**Results contained in this report apply to test sample only**



### ATTACHMENT A

EUT: Encoder/Transmitter  
 Model : 50ESS  
 Serial No.: 4577

FCC Part 15.249  
 Radiated Emissions-Transmitter  
 Test Dates: November 20, 21, 26, 27 & 29, 2001

Freq. MHz	Ant. Pos.	Level dBm	[1]	Level dBuV	Ant. Factor dB	Cable Loss dB	[2] [3] Corrected Level dBuV/m	Limit dBuV/m	Duty Cycle Factor dB	[4] Final Limit dBuV/m	Margin dB
916.5	V	<b>-43.4</b>	P	<b>63.6</b>	28.6	1.6	<b>93.7</b>	94.0		94.0	0.3
916.5	H	<b>-53.2</b>	P	<b>53.8</b>	28.6	1.6	<b>84.0</b>	94.0		94.0	10.1
1833.0	V	<b>-73.6</b>	P	<b>33.4</b>	28.5	2.4	<b>64.3</b>	54.0	-13.0	67.0	2.7
1833.0	H	<b>-74.3</b>	P	<b>32.7</b>	28.5	2.4	<b>63.6</b>	54.0	-13.0	67.0	3.4
2749.5	V	<b>-89.5</b>	P	<b>17.6</b>	31.2	3.0	<b>51.8</b>	54.0	-13.0	67.0	15.2
2749.5	H	<b>-90.6</b>	P	<b>16.4</b>	31.2	3.0	<b>50.7</b>	54.0	-13.0	67.0	16.3
3666.0	V	<b>-85.2</b>	P	<b>21.8</b>	33.7	3.5	<b>59.0</b>	54.0	-13.0	67.0	8.0
3666.0	H	<b>-84.2</b>	P	<b>22.8</b>	33.7	3.5	<b>60.0</b>	54.0	-13.0	67.0	7.0
4582.6	V	<b>-94.4</b>	P	<b>12.7</b>	34.9	4.2	<b>51.7</b>	54.0	-13.0	67.0	15.3
4582.6	H	<b>-93.4</b>	P	<b>13.6</b>	34.9	4.2	<b>52.7</b>	54.0	-13.0	67.0	14.4
5499.1	V	<b>-97.3</b>	P	<b>9.7</b>	36.6	4.5	<b>50.8</b>	54.0	-13.0	67.0	16.2
5499.1	H	<b>-99.3</b>	P	<b>7.7</b>	36.6	4.5	<b>48.7</b>	54.0	-13.0	67.0	18.3
6415.6	V	-98.2	NF	8.8	37.3	4.5	<i>50.6</i>	54.0	-13.0	67.0	
6415.6	H	-98.2	NF	8.8	37.3	4.5	<i>50.6</i>	54.0	-13.0	67.0	
7332.1	V	-96.6	NF	10.4	38.8	6.3	<i>55.5</i>	54.0	-13.0	67.0	
7332.1	H	-96.6	NF	10.4	38.8	6.3	<i>55.5</i>	54.0	-13.0	67.0	
8248.6	V	-95.5	NF	11.5	39.2	6.7	<i>57.4</i>	54.0	-13.0	67.0	
8248.6	H	-95.5	NF	11.5	39.2	6.7	<i>57.4</i>	54.0	-13.0	67.0	
9165.1	V	-95.3	NF	11.7	40.4	7.3	<i>59.4</i>	54.0	-13.0	67.0	
9165.1	H	-95.3	NF	11.7	40.4	7.3	<i>59.4</i>	54.0	-13.0	67.0	

- Notes:
- [1] QP = Quasi-peak, P = Peak, NF = Noise Floor of the Spectrum Analyzer
  - [2] The Spectrum Analyzer settings are as follows:  
 Fundamental - Resolution Bandwidth = 120 kHz; Video Bandwidth = 300 kHz; Span = 10 MHz.  
 Harmonics - Resolution Bandwidth = 1 MHz; Video Bandwidth = 1 MHz; Span = 50 MHz.
  - [3] "Corrected Level" numbers in bold are RF signal levels.  
 "Corrected Level" numbers in italics are noise floor and as such indicate that there is no RF signal at that level.  
 The "Antenna Correction Factor" and the "Cable Loss" have been factored in with the noise floor levels in order to demonstrate what the "Corrected Level" of an RF signal at the noise floor level would have been equal to.
  - [4] The "Final Limit", in the case of the harmonics, represents 13 dB above the average limit in FCC part 15.249. Refer to Attachment B; Pulsed Operation (Part 15.35 (b)).



ATTACHMENT A cont.

EUT: Encoder/Transmitter **FCC Part 15.249**  
 Model : 50ESS **Radiated Emissions-Transmitter**  
 Serial Number: 4577 **Test Dates:** Dec. 7, 01 & Jan. 4, 02  
**Engineer:** Mark J. Kvamme

Freq. MHz	Ant. Pos.	Level dBm	[1]	Level dBuV	[4] Ant. Factor dB	Cable Loss dB	[2] [3] Corrected Level dBuV/m	Limit dBuV/m	Duty Cycle dB	Final Limit dBuV/m	Margin dB
325.60		<b>-99.8</b>	P	7.2	15.6	0.87	<b>23.7</b>	46		46	22.3
337.89		<b>-97.3</b>	P	9.7	15.6	0.87	<b>26.2</b>	46		46	19.8
350.17		<b>-100.5</b>	P	6.5	15.4	0.90	<b>22.8</b>	46		46	23.2
411.61		<b>-98.1</b>	P	8.9	16.5	0.96	<b>26.3</b>	46		46	19.7
423.89		<b>-97.8</b>	P	9.2	16.5	0.97	<b>26.7</b>	46		46	19.3
460.74		<b>-93.3</b>	P	13.7	17.3	1.08	<b>32.1</b>	46		46	13.9
466.88		<b>-98.5</b>	P	8.6	17.4	1.08	<b>27.0</b>	46		46	19.0
473.04		<b>-87.0</b>	P	20.0	17.4	1.09	<b>38.5</b>	46		46	7.5
479.16		<b>-98.2</b>	P	8.8	18.4	1.14	<b>28.3</b>	46		46	17.7
485.30		<b>-88.1</b>	P	18.9	18.4	1.14	<b>38.4</b>	46		46	7.6
485.33		<b>-88.7</b>	P	18.3	18.4	1.14	<b>37.8</b>	46		46	8.2
491.45		<b>-97.0</b>	P	10.0	18.4	1.14	<b>29.5</b>	46		46	16.5
497.62		<b>-87.6</b>	P	19.4	18.4	1.15	<b>38.9</b>	46		46	7.1
503.75		<b>-95.3</b>	P	11.7	18.3	1.20	<b>31.2</b>	46		46	14.8
509.89		<b>-88.1</b>	P	19.0	18.3	1.20	<b>38.5</b>	46		46	7.5
522.18		<b>-88.1</b>	P	18.9	18.4	1.20	<b>38.4</b>	46		46	7.6
534.47		<b>-89.3</b>	P	17.7	18.9	1.21	<b>37.8</b>	46		46	8.2
546.76		<b>-89.5</b>	P	17.5	18.9	1.21	<b>37.7</b>	46		46	8.3
559.04		<b>-90.2</b>	P	16.8	19.2	1.22	<b>37.2</b>	46		46	8.8
571.32		<b>-92.1</b>	P	14.9	19.2	1.22	<b>35.3</b>	46		46	10.7
583.61		<b>-89.1</b>	P	17.9	19.3	1.23	<b>38.4</b>	46		46	7.6
589.74		<b>-95.6</b>	P	11.4	19.3	1.23	<b>32.0</b>	46		46	14.0
595.89		<b>-89.9</b>	P	17.1	19.3	1.23	<b>37.7</b>	46		46	8.3
602.04		<b>-94.7</b>	P	12.3	19.6	1.24	<b>33.1</b>	46		46	12.9
608.18		<b>-89.2</b>	P	17.8	19.6	1.24	<b>38.6</b>	46		46	7.4
614.31		<b>-96.9</b>	P	10.1	19.7	1.24	<b>31.0</b>	46		46	15.0
620.47		<b>-88.0</b>	P	19.0	19.7	1.24	<b>39.9</b>	46		46	6.1
626.61		<b>-92.6</b>	P	14.4	20.5	1.28	<b>36.1</b>	46		46	9.9

Notes:

- [1] QP = Quasi-peak, P = Peak, NF = Noise Floor of the Spectrum Analyzer
- [2] The Spectrum Analyzer settings are as follows:  
 30 to 1000 MHz - Resolution Bandwidth = 120 kHz; Video Bandwidth = 300 kHz; Span = 10 MHz.  
 Above 1000 MHz - Resolution Bandwidth = 1 MHz; Video Bandwidth = 1 MHz; Span = 50 MHz.
- [3] "Corrected Level" numbers in bold are RF signal levels.  
 "Corrected Level" numbers in italics are noise floor and as such indicate that there is no RF signal at that level.  
 The "Antenna Correction Factor" and the "Cable Loss" have been factored in with the noise floor levels in order to demonstrate what the "Corrected Level" of an RF signal at the noise floor level would have been equal to.
- [4] The Antennas used were as follows:  
 30 to below 300 MHz. - Biconical: AN 16230  
 200 to 1000 MHz. - Log Periodic: AN 12005



ATTACHMENT A cont.

EUT: Encoder/Transmitter **FCC Part 15.249**  
 Model : 50ESS **Radiated Emissions-Transmitter**  
 Serial Number: 4577 **Test Dates:** Dec. 7, 01 & Jan. 4, 02  
**Engineer:** Mark J. Kvamme

Freq. MHz	Ant. Pos.	Level dBm	[1]	Level dBuV	[4] Ant. Factor dB	Cable Loss dB	[2] [3] Corrected Level dBuV/m	Limit dBuV/m	Duty Cycle Factor dB	Final Limit dBuV/m	Margin dB
632.76		<b>-88.2</b>	P	18.8	20.5	1.28	<b>40.6</b>	46		46	5.4
638.89		<b>-95.3</b>	P	11.7	20.5	1.28	<b>33.5</b>	46		46	12.5
645.05		<b>-89.3</b>	P	17.7	20.5	1.28	<b>39.5</b>	46		46	6.5
651.17		<b>-93.4</b>	P	13.6	21.0	1.31	<b>35.9</b>	46		46	10.1
657.33		<b>-88.0</b>	P	19.0	21.0	1.31	<b>41.3</b>	46		46	4.7
663.47		<b>-97.3</b>	P	9.7	21.1	1.31	<b>32.0</b>	46		46	14.0
669.62		<b>-91.2</b>	P	15.8	21.1	1.31	<b>38.2</b>	46		46	7.8
675.74		<b>-97.0</b>	P	10.0	22.0	1.35	<b>33.3</b>	46		46	12.7
681.91		<b>-90.0</b>	P	17.0	22.0	1.35	<b>40.3</b>	46		46	5.7
688.02		<b>-98.3</b>	P	8.7	22.0	1.35	<b>32.1</b>	46		46	13.9
694.19		<b>-91.2</b>	P	15.8	22.0	1.35	<b>39.2</b>	46		46	6.8
700.34		<b>-98.5</b>	P	8.5	22.6	1.38	<b>32.5</b>	46		46	13.5
706.47		<b>-92.7</b>	P	14.3	22.6	1.38	<b>38.2</b>	46		46	7.8
712.62		<b>-100.0</b>	P	7.0	22.6	1.38	<b>31.0</b>	46		46	15.0
718.75		<b>-95.4</b>	P	11.7	22.6	1.38	<b>35.6</b>	46		46	10.4
731.05		<b>-99.0</b>	P	8.0	22.5	1.41	<b>31.9</b>	46		46	14.1
743.32		<b>-100.7</b>	P	6.3	22.5	1.41	<b>30.2</b>	46		46	15.8
780.18		<b>-98.1</b>	P	8.9	22.5	1.46	<b>32.9</b>	46		46	13.1
786.31		<b>-101.0</b>	P	6.1	22.5	1.46	<b>30.0</b>	46		46	16.0
792.47		<b>-100.4</b>	P	6.6	22.5	1.46	<b>30.5</b>	46		46	15.5
804.77		<b>-99.3</b>	P	7.7	22.9	1.49	<b>32.1</b>	46		46	13.9
810.91		<b>-101.1</b>	P	5.9	22.9	1.49	<b>30.3</b>	46		46	15.7
903.06		<b>-102.0</b>	P	5.0	24.3	1.55	<b>30.8</b>	46		46	15.2
933.75		<b>-100.3</b>	P	6.7	24.2	1.60	<b>32.5</b>	46		46	13.5
939.89		<b>-103.1</b>	P	3.9	24.2	1.60	<b>29.7</b>	46		46	16.3
958.35		<b>-98.9</b>	P	8.1	24.0	1.62	<b>33.7</b>	46		46	12.3
964.49		<b>-102.8</b>	P	4.2	24.0	1.62	<b>29.8</b>	46		46	16.2

Notes:

- [1] QP = Quasi-peak, P = Peak, NF = Noise Floor of the Spectrum Analyzer
- [2] The Spectrum Analyzer settings are as follows:  
 30 to 1000 MHz - Resolution Bandwidth = 120 kHz; Video Bandwidth = 300 kHz; Span = 10 MHz.  
 Above 1000 MHz - Resolution Bandwidth = 1 MHz; Video Bandwidth = 1 MHz; Span = 50 MHz.
- [3] "Corrected Level" numbers in bold are RF signal levels.  
 "Corrected Level" numbers in italics are noise floor and as such indicate that there is no RF signal at that level.  
 The "Antenna Correction Factor" and the "Cable Loss" have been factored in with the noise floor levels in order to demonstrate what the "Corrected Level" of an RF signal at the noise floor level would have been equal to.
- [4] The Antennas used were as follows:  
 30 to below 300 MHz. - Biconical: AN 16230  
 200 to 1000 MHz. - Log Periodic: AN 12005



**ATTACHMENT B**  
**Part 15.35 (b) - Pulsed Operation**  
**Conversion from Instantaneous Peak Power to Average Power**  
**50ESS**

The Unit Transmits Manchester Encoded Messages separated by a two to six second period of time. Each of the messages is 92 bytes (736 bits) long. Each message is broadcast on a different frequency within the Transmit Band.

Zooming in on a message length:



Bit rate is: 16.384 Kbits/Second.  
 Message Period is: 736/16.384 Kbits / sec = 44.92 msec

During the transmission of messages, the Transmit Duty Cycle can be computed.

$$\% \text{ Duty Cycle Transmit} = (736 \text{ bits}) (1/16.384 \text{ Kbits/Sec}) (.5) (100\%) / (100 \text{ msec})$$

$$\% \text{ Duty Cycle Transmit} = 22.46 \%$$

Note: The .5 factor is a result of Manchester Encoded Data.

Expressing the correction factor for Duty Cycle in dB:

$$\text{dB Duty Cycle Transmit} = 20 \text{ Log (Duty Cycle)}$$

$$\text{dB Duty Cycle Transmit} = 20 \text{ Log} (.2246)$$

$$\text{dB Duty Cycle Transmit} = -12.97 \text{ dB}$$

The maximum relaxation allowed per Part 15.35 (b) is 20 dB.




### ATTACHMENT C

#### Part 15.231 (c) Bandwidth of Emission Bandwidth Plot

12:23:33 JAN 16, 2002

REF .0 dBm AT 10 dB MKR  $\Delta$  140 kHz  
-20.74 dB

PEAK  
LOG  
10  
dB/



Marker	Trace	Type	Freq / Time	Amplitude
1:	(A)	$\Delta$ Freq	-0.082 MHz	-20.43 dB
2:	(A)	$\Delta$ Ref	916.610 MHz	-12.39 dBm
3:	(A)	$\Delta$ Freq	0.140 MHz	-20.74 dB
4:		Inactive		

CENTER 916.625 MHz SPAN 1.000 MHz  
#RES BW 30 kHz #VBW 100 kHz SWP 20.0 msec



### ATTACHMENT D

#### Part 15.31(m)


#### Measurement of Relative Field Intensity at the High and Low Frequencies of the EUT

12:13:18 JAN 16, 2002

MKR 918.000 MHz  
-11.92 dBm

REF .0 dBm AT 10 dB

PEAK  
LOG  
10  
dB/



Marker	Trace	Type	Freq / Time	Amplitude
1:	(A)	Freq	915.263 MHz	-13.19 dBm
2:	(A)	Freq	917.775 MHz	-11.73 dBm
3:	(A)	Freq	918.000 MHz	-11.92 dBm
4:		Inactive		

CENTER 916.625 MHz  
#RES BW 100 kHz

#VBW 30 kHz

SPAN 5.000 MHz  
SWP 20.0 msec







# ATTACHMENT E

## Part 15.107 Power line Conducted Emissions

### Plots



L1



L2



### ATTACHMENT F Photographs (Test Setup)

