Revision: 2

Issue Date: 8/18/2021 Final Test Date: 8/16/2021







An IIA Company

Test Report - FCC PART 1.1310 / MPE Prepared For: CRESTRON ELECTRONICS INC.

Approved for Release By:

Signature: Brune Churer

Name & Title: Bruno Clavier, General Manager

Date of Signature

(YYYY-MM-DD): 2021-08-18

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Table of Contents

1.	CUS	STOMER INFORMATION	.3
2.		CATION OF TESTING	
		Test Laboratory Testing was performed, reviewed by	
3.	TEST	T SAMPLE(S) (EUT/DUT)	.5
	3.1	Description of the EUT	.5
4.	TEST	T METHODS & APPLICABLE REGULATORY LIMITS	.6
	4.1.1	Test methods/Standards/Guidance:	.6
5.	RF E	XPOSURE RESULTS	.8
6.	HIST	TORY OF TEST REPORT CHANGES	.9



1. Customer Information

Applicant: CRESTRON ELECTRONICS INC.

Address: 15 Volvo Drive

Rockleigh, NJ 07647 United States

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

2.2 Testing was performed, reviewed by

Dates of Testing: 7/1/2021 - 7/2/2021



Sr. EMC Engineer EMC-003838-NE

Signature:

Name & Title: Tim Royer, EMC Engineer

Date of Signature

(YYYY-MM-DD): 08/18/2021

3. Test Sample(s) (EUT/DUT)

The test sample was received: 5/28/2021

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification						
FCC ID:	EROCENGW1					
Brief Description	CEN-GW1 Sub GHz Radios					
Model(s) #	M201913001					
Firmware version	V2.4881.22497					
Software version	n/a					
Serial number	Engineering Sample 1					

Technical Characteristics						
Technology	BLE					
Frequency Range	2405-2480 MHz / 903-926.2 MHz					
Modulation	GFSK					
Antenna Type	External Connector					

Antenna Characteristics								
Frequency Range	Mode / BW	Ant Gain 1	Ant Gain 2					
2405 – 2480 MHz	n/a	0 dBi	n/a					
903-926.2 MHz	n/a	0 dBi	n/a					

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging Time (minutes)						
A Limits for Occupational/Controlled Exposure										
0.3-3.0	614	1.63	*(100)	≤6						
3.0-30	1842/f	4.89/f	*(900/f²)	<6						
30-300	61.4	0.163	1.0	<6						
300-1,500			f/300	<6						
1,500-100,000			5	<6						
	B Limits for General Population/Uncontrolled Exposure									
0.3-1.34	614	1.63	*(100)	<30						
1.34-30	824/f	2.19/f	*(180/f²)	<30						
30-300	27.5	0.073	0.2	<30						
300-1,500			f/1500	<30						
1,500-100,000			1.0	<30						

4.2 Equations

POWER DENSITY

E(V/m) = SQRT (30 * P * G) / d $Pd(W/m^2) = E^2 / 377$

 $S = EIRP / (4 * Pi * D^2)$

Where:

S = Power density, in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power, in mW D = Separation distance in cm

Power density is converted from units of <u>mW/cm^2</u> to units of <u>W/m^2</u> by multiplying by 10.

DISTANCE

D = SQRT (EIRP / (4 * Pi * S))

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

Source-based time-average EIRP = (DC / 100) * EIRP

Where:

DC = Duty Cycle in % as applicable. EIRP = Equivalent Isotropic radiated Power, in mW

5. RF Exposure Results

MPE

Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
2405-2480 MHz	20	18.18	0.00	100%	0.07	0.013 mW/cm2	1 mW/cm2	5 mW/cm2	20.00

RESULT: Passes Limit at Distance: 20 cm

MPE

TVII L									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
903-926.2 MHz	20	26.17	0.00	100%	0.41	0.082 mW/cm2	0.602 mW/cm2	3.01 mW/cm2	20.00

RESULT: Passes Limit at Distance: 20 cm

6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_2726-21_FCC_MPE_1	1	Initial release	August 16, 2021
TR_2726-21_FCC_MPE_2	2	Added bands 902-926.2 MHz data	August 18, 2021

END OF TEST REPORT