

TEST REPORT

Reference No..... : WTD21D09101438W005
FCC ID : EROUC-ENGINE-A
Applicant..... : Crestron Electronics Inc
Address..... : 15 Volvo Drive, Rockleigh, NJ 07647, United States of America
Manufacturer : SMART Wireless Computing Inc.
Address..... : 39870 Eureka Dr, Newark,CA 94560, United States of America
Product..... : UC-ENGINE-A
Model(s) : M202138002(SKU: UC-ENGINE-A-T, UC-ENGINE-A-Z)
Brand name : Crestron
Standards..... : FCC Part 2.1091
Date of Receipt sample : 2021-02-19
Date of Test : 2021-02-20 to 2021-04-06
Date of Issue..... : 2021-10-27
Test Result..... : Pass
Remark..... : This report is based on the original report WTD21D01009766W005, Change the manufacturer, product name, model, and EUT some ports and functions have Change, For details, please refer to section 4.3 of the report

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

Approved by:

Levi Xiao

Levi Xiao / Project Engineer



Daniel Liu

Daniel Liu / Designated Reviewer

2 Contents

| | Page |
|--|-------------|
| 1 COVER PAGE | 1 |
| 2 CONTENTS | 2 |
| 3 REVISION HISTORY | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 GENERAL DESCRIPTION OF E.U.T. | 4 |
| 4.2 DETAILS OF E.U.T. | 4 |
| 4.3 PRODUCT INFORMATION | 4 |
| 4.4 TEST FACILITY | 4 |
| 5 TEST SUMMARY | 5 |
| 6 RF EXPOSURE | 6 |
| 6.1 PROCEDURES AND REQUIREMENTS | 6 |
| 6.2 TEST RESULT | 7 |

3 Revision History

| Test report No. | Date of Receipt sample | Date of Test | Date of Issue | Purpose | Comment | Approved |
|------------------------|------------------------|--------------------------------|---------------|----------|---------|----------|
| WTD21D09101 438W005 | 2021-02-19 | 2021-02-20 to 2021-04-06 | 2021-10-27 | Original | - | Valid |

4 General Information

4.1 General Description of E.U.T.

| | |
|----------------------|--|
| Product: | UC-ENGINE-A |
| Model(s): | M202138002(SKU: UC-ENGINE-A-T, UC-ENGINE-A-Z) |
| Wi-Fi Specification: | 2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/n/ac HT20 /n/ac HT40 /ac HT80 |
| Bluetooth Version: | Bluetooth v5.0 with BLE |
| Hardware Version: | CRE6720-XX-P1 |
| Software Version: | Android 10 |

4.2 Details of E.U.T.

| | |
|----------|--------------------|
| Ratings: | DC 12V For Battery |
|----------|--------------------|

4.3 Product information

Removed the below interfaces

1)1*MIPI-CSI Camera connector

2)1*30-pin Expansion connector

3)1*SMA(GPS)

4)1*M.2 SATA SSD slot

5)Micro sd Card removed and added one Type A USB to connect Mouse

Remark: Based on the above information, All the test data, Please refer to the original report
WTD21D01009766W005

4.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

| Test Items | Test Requirement | Result |
|---|------------------|--------|
| Maximum Permissible Exposure (Exposure of Humans to RF Fields) | 2.1091 | PASS |

6 RF Exposure

Test Requirement: FCC Part 2.1091
 Test Mode: The EUT work in test mode(Tx).

6.1 Procedures and Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

FCC Part 1.1307:

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ;

*Plane-wave equivalent power density

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the gain of the used antenna, the RF power density can be obtained

6.2 Test Result

Remark: Refer to Original report WTD21D01009766W005

=====**End of Report**=====