

Cover Page

1

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

Report No.: SHEM201100938403 Page: 1 of 8

i coron ago	
	RF MPE REPORT
Application No.: FCC ID:	SHEM2011009384CR ESVEVOLVE
Applicant: Address of Applicant: Manufacturer: Address of Manufacturer: Factory: Address of Factory:	Bosch Security Systems, LLC 130 Perinton Parkway, Fairport, NY, USA Bosch Security Systems, LLC 130 Perinton Parkway, Fairport, NY, USA Speaker Electronic(Jiashan) Co.,Ltd No. 8 Development Zone Road, Huimin Sub-district, Jiashan County, Zhejiang, 314112, P.R. China
Equipment Under Test (EU	
EUT Name:	EVOLVE Portable Column Loudspeaker
Model No.:	EVOLVE Portable Column Loudspeaker EVOLVE 50M
Add Model No.:	EVOLVE 50M-XX, EVOLVE 50M-XX-XX, Refer to Page 2
Trade mark:	Electro-Voice
Standard(s) :	FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt:	2020-11-06
Date of Test:	2020-11-17 to 2020-11-28
Date of Issue:	2020-11-30
Test Result:	Pass*
* In the configuration tested	the FUT complied with the standards specified above

* In the configuration tested, the EUT complied with the standards specified above.

parlan shar

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch



Report No.: SHEM201100938403 Page: 2 of 8

Naming rules for wildcards:

1. The X range can indicate the regional variances, external colors, accessories, possibly generations, and blank (if we do need to use).

Model Name:	Sales area:	Difference:
EVOLVE 50M-SB-US	US	box volume is larger
EVOLVE 50M-SB-EU	EU AP	box volume is larger
EVOLVE 50M-SW	global	The exterior is white
		box volume is larger

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM201100938403 Page: 3 of 8

Revision Record					
Version Description Date Remark					
00	Original	2020-11-30	/		

Authorized for issue by:		
	Bul wu	
	Bill Wu / Project Engineer	
	parlam zhan	
	Parlam Zhan /Reviewer	

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・ 松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM201100938403 Page: 4 of 8

2 Contents

COV	ER PAGE	1
CON	ITENTS	4
GEN	IERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF E.U.T.	5
3.2	TECHNICAL SPECIFICATIONS	5
3.3		
3.4	TEST FACILITY	6
TES	T STANDARDS AND LIMITS	7
4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	7
MEA	SUREMENT AND CALCULATION	7
5.1	MAXIMUM TRANSMIT POWER	7
5.2	MPE CALCULATION	8
	CON GEN 3.1 3.2 3.3 3.4 TES 4.1 MEA 5.1	 3.1 GENERAL DESCRIPTION OF E.U.T. 3.2 TECHNICAL SPECIFICATIONS 3.3 TEST LOCATION 3.4 TEST FACILITY. TEST STANDARDS AND LIMITS 4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS: MEASUREMENT AND CALCULATION 5.1 MAXIMUM TRANSMIT POWER



Report No.: SHEM201100938403 Page: 5 of 8

3 General Information

3.1 General Description of E.U.T.

Power supply:	AC 100-240V~50-60Hz
---------------	---------------------

3.2 Technical Specifications

ВΤ

DI	
Antenna Gain:	3.3dBi (Provided by client)
Antenna Type:	PCB Antenna
Bluetooth Version:	V5.0 Dual mode
Channel Spacing:	1MHz
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channels:	79
Operation Frequency:	2402MHz to 2480MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
BLE	
Antenna Gain:	2.24D: (Dravidad by alignt)

Antenna Gain:	3.3dBi (Provided by client)
Antenna Type:	PCB Antenna
Bluetooth Version:	V5.0 Dual mode
Channel Spacing:	2MHz
Modulation Type:	GFSK
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz



Report No.: SHEM201100938403 Page: 6 of 8

3.3 Test Location

All tests were performed at: SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch 588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (LAB CODE: 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

• FCC (Designation Number: CN5033)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number: 479755.

• ISED (CAB Identifier: CN0020)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. ISED#: 8617A.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM201100938403 Page: 7 of 8

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to§1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM201100938401 & SHEM201100938402.

BT				
Test Mode	Test Channel	Power[dBm]	Power[mW]	
DH5	2402	3.93	2.47	
DH5	2441	3.39	2.18	
DH5	2480	2.14	1.64	
2DH5	2402	1.87	1.54	
2DH5	2441	1.41	1.38	
2DH5	2480	0.12	1.03	
3DH5	2402	2.32	1.71	
3DH5	2441	1.8	1.51	
3DH5	2480	0.55	1.14	

BLE

Test Mode	Test Channel	Power[dBm]	Power[mW]
BLE	2402	5.88	3.87
BLE	2440	5.06	3.21
BLE	2480	4.07	2.55



Branch

Report No.: SHEM201100938403 Page: 8 of 8

5.2 MPE Calculation

For FCC:

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

The max. antenna gain is 3.3

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
3.87	2.138	20	0.00165	1	Pass

--End of the Report--

dBi