

# INTERTEK TESTING SERVICES

---

## Analysis Report

The equipment under test (EUT) is a Portable Bluetooth Speaker. The EUT can be powered by AC/DC adapter (Input 100-240, 50/60Hz, 1A; Output: 12Vdc, 2.5A). For more detail information pls. refer to the user manual.

Modulation Type: GFSK,  $\pi/4$ DQPSK, 8DPSK

Bluetooth Version: 2.1 with EDR function and disable the AFH mode

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal radiated output power (e.i.r.p) specified: 0dBm ( Tolerance: +/- 4dB)

The nominal conducted output power specified: 0dBm ( Tolerance: +/- 4dB)

According to the KDB 447498:

The worst-case radiated emission for the EUT is 98.5dB $\mu$ V/m at 3m in the frequency 2.480GHz

= [(FS\*D) ^2 / 30] mW

= 3.27dBm which is within the production variation.

The maximum conducted output power specified is 4dBm = 2.5mW

The source- based time-averaging conducted output power

= 2.5 \* Duty cycle mW= 2.1 mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.480) mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

### Transmitter Duty Cycle Calculation

Based on the Bluetooth Specification (BT version: 2.1), transmitter duty cycle is dependent of packet type (DH1, DH3 and DH5). For one period for a pseudo-random hopping through all 79 RF channels, for DH5:

One hopset consists of 5 TX slot and 1 RX slot.

Duty cycle = 5 / 6 = 0.833

This requirement is according to KDB 865664 D02

---

FCC ID: ESX4000437